



# **NAVIGATE**

Use the arrows to turn the page. On mobile devices just swipe left or right



## **SEARCH**

Search the entire catalog by keyword or item number



## **BOOKMARK/NOTES**

Bookmark your favorite pages and leave notes directly in the catalog



# ZOOM

Zoom in and out







**EXAIR's Intelligent** Compressed Air® products vs Your current installation

**EXAIR's FREE Efficiency Lab service determines** how much air and dollar savings you will achieve by installing one of our Intelligent Compressed Air products.

#### How does the Efficiency Lab work?

Our Efficiency Lab service begins with receiving a sample of the product(s) you currently use for your application. One of our qualified Application Engineers will use calibrated testing equipment to compare the performance of your existing product(s) to an EXAIR engineered solution. These tests will determine air consumption, noise levels and force. The test results will then be published in a comprehensive report, which includes a cost savings analysis, and be provided to you. For most applications, EXAIR products can help you improve application efficiency AND typically pay for themselves in a matter of weeks.

#### How can I get a product tested for free?

advantage of our live help at www.exair.com.

To participate in our FREE Efficiency Lab please contact one of our Application Engineers and get the details about sending us your product(s). You may reach an Application Engineer by phone at (800) 903-9247 or (513) 671-3322. You can send an email to lab@exair.com or visit our website and take

#### Unable to send your product to **EXAIR's Efficiency Lab?**

If it is not possible to send us your product, we have a one page Product Efficiency Survey on our website (exair.com/labdoc) where you can provide us the details about a current inefficient compressed air application. Fill in the information and click submit. You will hear from one of our Application Engineers within three business days.

#### Okay, so what is the fine print?

This service is available to all customers in the U.S. and Canada only. Some restrictions may apply.

#### What about confidentiality?

Yes, EXAIR will keep the results of our Efficiency Lab test and report confidential unless given permission to share that information with others.

Products must be shipped to EXAIR prepaid. EXAIR will pay the return shipping via UPS Ground.









# Optimization

# **Optimization**

An INTELLIGENT OMPRESSED AIR Product

#### "Go Green" with Intelligent Compressed Air® Products!

It's a worldwide problem. Compressed air leaks and inefficient blowoffs can waste thousands of dollars of electricity per year, affecting your company's production costs and bottom line. For many plants, the leakage alone accounts for up to 30% of the total compressed air cost.

EXAIR can help your company "go green" with six easy to follow steps. It's as simple as finding the leaks, making the repairs, controlling the air use, and upgrading to efficient blowoffs. EXAIR's Intelligent Compressed Air® products can help you accomplish these steps so your compressed air system becomes more efficient, along with the benefit of drastically lowering your energy costs.



#### Six Steps To Optimizing **Your Compressed Air System**

#### Measure the air consumption to find sources that use a lot of compressed air.

EXAIR's Digital Flowmeter™ and the Digital Flowmeter™ with wireless capability accurately measure compressed air usage and monitor waste. Trends can be monitored to find excessive air use. Detect leaks at compressed air fittings when the machinery is off. Regular monitoring can detect leaks that develop as the machinery ages. Pressure Sensing and Hot Tap models are also available

- · Easy to install No adjustments or calibrations needed.
- Digital readout displays actual airflow through pipe



#### Find and fix the leaks in your compressed air system.

EXAIR's Ultrasonic Leak Detector can help you identify costly leaks in your compressed air system. Leaks can account for 30% of total compressor output! In many cases, finding small leaks can quickly pay for the leak detector.

• Detects leaks up to 20' (6.1m) away Accurate in noisy industrial environments

Page 18

#### Upgrade your blowoff, cooling and drying operations using engineered compressed air products.

EXAIR's Super Air Knives™, Super Air Amplifiers™, and Super Air Nozzles™ dramatically reduce air consumption and noise. EXAIR's Digital Sound Level Meter™ can identify and isolate the source of the noisy blowoffs.

- Low cost-replaces noisy blowers
- · Improves blowoff performance and safety

Pages 17, 20, 46, 55

#### Turn off the compressed air when it isn't in use. EXAIR's EFC™ is an electronic flow control that minimizes compressed air

use by turning off the compressed air when no part is present. For use on blowoff, drying, cooling, conveying and static elimination operations.

- · Easy hook up: 100-240 VAC with eight function timer
- Photoelectric sensor withstands water and dust

Page 7

#### Use intermediate storage of compressed air near the point of use.

An EXAIR 60 gallon Receiver Tank can be installed at the point of high demand so there is an additional supply of compressed air available for a short duration. Meets ASME pressure vessel code.

· Eliminates fluctuations in pressure and volume

· Vertical, space saving design

Page 237

#### Control the air pressure at the point of use to minimize air consumption.

EXAIR Pressure Regulators permit easy selection of an operating pressure that will allow the air product to work properly without using excessive amounts of compressed air. Reducing the air pressure from 100 PSIG to 80 PSIG reduces energy use by almost 20%.

- Modular design
- · Many sizes available
- · Pressure gauge included

Page 232







**EFC**TM

**Electronic Flow Control minimizes** compressed air use for blowoff. drying, cooling, conveying and static elimination operations!

**Dramatically reduces compressed** air costs by turning off the air when no part is present!



An INTELLIGENT

#### What Is The EFC?

EXAIR's EFC is a user-friendly electronic flow control for compressed air that is designed to minimize compressed air use on blowoff. drying, cooling, conveying and static elimination operations. The EFC combines a photoelectric sensor with a timing control that limits compressed air use by turning it off when no part is present. The timing control permits easy tuning to the application requirements while providing flexibility in sensing distance. The EFC also has eight programmable on and off modes.

#### **Applications**

- Auto body blowoff
- Package cleaning
- · Part drying after wash
- Dust removal
- Scrap removal
- Filling operations
- Neutralizing static Cleaning molded parts

EXAM

#### Cooling hot parts

# · Compact sensor for mounting in tight spaces Sensor withstands water and dust for accurate readings

Model #	Description	
9055	EFC Electronic Flow Control, 40 SCFM (1,133 SLPM), solenoid valve, 1/4 NPT	
9056	EFC Electronic Flow Control, 100 SCFM (2,832 SLPM), solenoid valve, 1/2 NPT	
9057	EFC Electronic Flow Control, 200 SCFM (5,664 SLPM), solenoid valve, 3/4 NPT	
9064	EFC Electronic Flow Control, 350 SCFM (9,911 SLPM), solenoid valve, 1 NPT	



and dust.

Photoelectric sensor

withstands water

#### Why The EFC?

For most companies, the air compressor uses more electricity than any other type of equipment. One simple operation that uses compressed air can easily waste thousands of electricity dollars per year if not properly controlled. The EFC has been designed to improve efficiency by minimizing compressed air use and, as a result, reduce compressed air costs. It turns on the air only when a part is present and provides just enough air to complete a specific task or operation.

The EFC has an easy electrical connection for voltages from 100 to 240VAC, 50/60Hz making it suitable for applications throughout the world. The compact photoelectric sensor has a sensitivity adjustment and detects objects up to 3' (1m) away. The sensor has superior immunity to noise and inductive loads that are common to industrial environments and installs easily in tight spaces with the supplied mounting bracket. The control system provides flexibility with numerous valve operating modes and timing delays. The polycarbonate enclosure is suitable for use in a wide range of applications including those located in wet environments.

#### Advantages

- Easy electrical hook-up; 100-240VAC, 50/60Hz
- NEMA 4/IP66 environments
- · Eight function analog timer for on/off, pulsing and delay control
- Timer setting from 0.10 sec. to 120 hrs.
- · Sensor has superior immunity to noise and inductive loads Sensor has long distance sensing up to 3 feet (1m)

# 5.12 On / Off Controller

The timing control unit and the photoelectric sensor are equipped with a 9' (2.74m) power cord. The timing control unit is housed in a polycarbonate NEMA 4 / IP66 water tight enclosure.


There are four models of the EFC. Each includes the timing control unit and photoelectric sensor with a choice of solenoid valve sizes of 40, 100, 200 and 350 SCFM (1,133, 2,832, 5,664 and 9,911 SLPM).

EFC Specifications		
Power Supply Input	100-240VAC, 50/60Hz, 0.25 - 0.45A	
Power Supply Output (To Sensor)	24VDC at 0.65A	
Sensor	12-24VDC input, consumes 30mA	
Sensing Range	Diffuse reflective to 3' (1 meter)	
Enclosure Rating	NEMA 4 / IP66	
Temperature Rating	-13°F to 131°F (-25°C to 55°C)	
RoHS Compliant	Yes	
CE Compliant	Yes	

#### \$2,045.22 Annual Air Savings On A Flat Panel Display Blowoff

**EFC** 

A flat panel display manufacturer runs 3 shifts. It takes a 40 second cycle to produce one fully assembled display. Prior to packaging, they use EXAIR's 12" (305mm) Super Ion Air Knife at 40 PSIG (2.8 BAR) to blow across the display to remove any static electricity, dust, debris and plastic flash from the panel surface. The air ran constantly. The displays are under the airflow only 10 seconds. Thirty seconds pass until the next display is in position. They manufacture 675 displays per shift (7.5 hrs.) for a total of 2,025 displays manufactured per day.



The timer was set to the "interval" setting when detecting the flat panel displays. The sensor was mounted 1" (25mm) prior to the Super Ion Air Knife blowoff station. When it detected the flat panel, it turned the air on immediately and started the 10 second timing sequence for closing the valve (shutting the air off). In the event the conveyor stopped, the air would no longer cycle on again until the next flat panel was detected.

#### **Old Method**

EXAIR's 12" (305mm) Super Ion Air Knife was supplied at 40 PSIG to clean the displays.

strolling two solenoid valves are available. Contact FXAIR for detail-

At 40 PSIG, EXAIR's 12" (305mm) Super Ion Air Knife consumes 20 4 SCFM (577 SLPM)

Non-stop blowing of 1.440 minutes (24 hours) per day x 20.4 SCFM = 29,376 SCF (831,341 SL) air usage per day.

The EFC was installed to shut off the compressed air for 30 seconds of the 40 second cycle. (Turns air off for 75% of the cycle.)

#### **Cost Difference**

Most large plants know their air cost. If the actual cost is unknown, \$0.25 per 1,000 SCF (28,329 SL) is reasonable.

#### Before the EFC installation:

29.376 SCF/1.000 = 29.38 x \$0.25 = \$7.34 air cost per day.


#### With the EFC installed:

The EFC shut the air off during the three 30 minute shift changes. Upon sensing the display, the timer turned on the compressed air for only 10 seconds of each 40 second cycle (25% of the time).

1,440 minutes per day - 90 minutes between shifts = 1,350 minutes of operation per day. 1,350 minutes x 25% = 337.5 minutes of air per day

337.5 minutes x 20.4 SCFM = 6,885 SCF (194,846 SL) air usage per day. 6,885 SCF/1,000 = 6.89 x \$0.25 = \$1.72 air cost per day \$7.34 (old air cost) - \$1.72 (new air cost) =

\$5.62 savings per day x 7 days a week = \$39.33 savings per week x 52 weeks a year = \$2,045.22 savings per year.









#### \$5,012.28 Annual Air Savings For Pre-Paint Bumper Cleaning

A manufacturer of car bumpers installed a 60" (1524mm) Super Ion Air Knife in the down draft cleaning area prior to their paint booth. The bumpers enter that area in the same orientation as they would when mounted to the automobile, moving at 10' (3m) per minute with a 12" (305mm) space between bumpers. The bumpers are under the blow off for 10 seconds, 6 seconds pass with no bumper in the ionized airflow. The operation runs around the clock with three shifts.



The timer was set to "interval" and the sensor mounted next to the Super Ion Air Knives. When it detected a bumper, it immediately turned on the air for 10 seconds. If the conveyor stopped, it would not turn the air on again until it detected the next bumper.

#### \$3,393 Annual Air Savings On A Tank Blowoff Operation

A company that refurbishes large tanks runs the tanks through an oven on a conveyor line to burn off old paint. Only one tank at a time can be processed and each takes 6 minutes to complete the journey. Super Air Knives are used for blowoff at the exit of the oven.

However, the tank travels through the oven for 5 minutes before it reaches the knives for blowoff. At 80 PSIG (5.5 BAR), the four knives consume 348 SCFM (9,854 SLPM). Once the tanks have been blown off, the conveyor stops, the air is shut off, and a new tank is loaded at the other end. The operation runs 30 tanks per day, 5 days a week.



The timer was set to "on/off delay". The sensor was mounted at the oven exit (1 minute away from the blowoff station). When the sensor detected a tank, the timer turned the air on for one minute, just as the next tank reached the blowoff station.

#### **Old Method**

EXAIR's 60" (1524mm) Super Ion Air Knife was supplied at 40 PSIG to clean the bumper.

At 40 PSIG, EXAIR's 60" (1524mm) Super Ion Air Knife consumes

Non-stop blowing of 1.440 minutes (24 hours) per day x 102 SCFM = 146,880 SCF (4,156,704 SL) air usage per day.

#### **EFC Solution**

The EFC was installed to shut off the compressed air for the 6 seconds where no bumper was present - an on cycle reduction of 37.5%. 1,440 minutes x 37.5% = 540 minutes of off time per day

#### **Cost Difference**

Most large plants know their air cost. If the actual cost is unknown, \$0.25 per 1,000 SCF (28,329 SL) is reasonable.

#### Before the EFC installation:

 $146.880 \text{ SCF}/1.000 = 146.88 \times 50.25 = 536.72 \text{ air cost per day.}$ 

With EFC installed: 146.880 SCF x 62.5% on cycle = 91.800 SCF/1.000 =  $91.8 \times $0.25 = $22.95 \text{ air cost per day.}$ \$36.72 (old air cost) - \$22.95 (new air cost) =

\$13.77 savings per day x 7 days per week = \$96.39 savings per week x 52 weeks per year = \$5,012.28 savings per year.

#### **Old Method**

It takes 6 minutes to complete the process.

6 minutes x 348 SCFM=

2,088 SCF (59,090 SL)

2.088 SCF x 30 tanks =

62,640 SCF (1,772,712 SL)

#### **EFC Solution**

The EFC was installed to shut off the compressed air for the 5 minutes where no tank was present (one minute of air on).

1 minute x 348 SCFM = 348 SCF x 30 tanks = 10.440 SCF (295.452 SL)

#### **Cost Difference**

Most large plants know their air cost. If the actual cost is unknown, \$0.25 per 1,000 SCF (28,329 SL) is reasonable.

#### Before the EFC installation:

62,640 SCF/1,000 = 62.64 x \$0.25 = \$15.66 air cost per day.

With the EFC installed: 10,440 SCF/1,000 = 10.44 x \$0.25 = \$2.61 air cost per day. \$15.66 (old air cost) - \$2.61 (new air cost) =

\$13.05 savings per day x 5 days per week = \$65.25 savings per week x 52 weeks per year = \$3,393 savings per year.

# **Digital Flowmeter™**

#### Monitor compressed air usage and waste!

An INTELLIGENT

#### What is the Digital Flowmeter?

Anyone serious about lowering their energy consumption, operating an efficient plant or optimizing their compressed air system knows that measuring compressed air consumption is the first step toward efficiency. EXAIR's Digital Flowmeter is the easy way to monitor compressed air consumption and waste! The digital display shows the exact amount of compressed air being used, making it easy to identify costly leaks or inefficient air products. Many companies install the Digital Flowmeter on each major leg of their air distribution system to constantly monitor and benchmark compressed air usage.

#### Why the Digital Flowmeter?

The Digital Flowmeter has an LED display that directly indicates the SCFM or m<sup>3</sup>/hr volume of airflow through that pipe. Models from 1/2" to 4" iron pipe are in stock. Each Digital Flowmeter is calibrated for the pipe size to which it is mounted. The Digital Flowmeter is designed for permanent or temporary mounting to the pipe. It requires the user to drill two small holes through the pipe using the included drill bit and locating fixture. The two flow sensing probes of the flowmeter are inserted in these holes. The unit seals to the pipe once the clamps are tightened. No cutting, welding, adjustments or calibration are ever required. If the unit needs to be removed, block-off rings are available, NEMA Type 4 (IP66) meters available. Consult the factory for NEMA 4 meters.

#### **How it Works?**

These flowmeters measure flow by maintaining a temperature differential between the two probes inserted into the compressed air pipe. One probe is kept warmer than the other and mass flow rate is determined by the amount of heat required to maintain the temperature differential. The flow rate, in SCFM or m3/hr, is shown on the large four-digit display. A 4-20 mA output and pulse output permit remote display of the flow value and data collection.

#### Advantages

All EXAIR Digital Flowmeters . No moving parts are available in four fundamental versions and offer these advantages over traditional flowmeters.

- Summing Remote Display and Data Logger available
- · Optional RS-485 output serial communication board available
- · Sensitive at low flows
- · No calibration or set up required
- · Includes all components for installation
- · Models from 1/2" to 4" Schedule 40 iron
- · Models are available for sizes 1/2" to 8" in iron pipe

SCAN & WATCH the vid

- · Models are available for sizes 3/4" to 4" in copper pipe
- Models are available for sizes 25mm through 101mm in aluminum pipe
- · Easy to install

CONTROL CONTROL

2020


2021



















Basic kits for EXAIR's Digital Flowmeters include all of the components for installation, which are: a drill

guide to locate the holes for the sensing probes accurately, a drill bit so the holes are the proper size

and a hex wrench for installing the pipe clamp

securely. If you have purchased a Digital Flowmeter

in the past and have these components for the same

sized flowmeter, you can order the flowmeter without a drill guide kit by adding the "-DG" suffix to the

Need an EXAIR Drill Guide?

#### **Flowmeter Versions**

These four versions of digital flowmeter can be used on Schedule 40 iron pipe, Type L copper pipe, or the nominal pipe sizes listed on Page 13.

Standard The original Digital Flowmeter provides accuracy and an easy to read display of current compressed air consumption, daily consumption or cumulative consumption. Digital Flowmeter with optional Data Logger shown at left.



Wireless Transmit the compressed air data wirelessly over a ZigBee mesh network! A radio module within each meter transmits data to an Ethernet connected gateway. Using the ZigBee mesh network protocol, data can be passed from meter to meter to extend the distance over which the wireless system can operate. Each meter has a range of 100' (30 meters). Setup is simple and consists of installing a meter, installing EXAIR's wireless-to-Ethernet gateway and running the no-charge graphing software available from our website. 128 bit encryption is in place for secure wireless transmissions and they are configured to prevent unwanted joining upon the network.



Hot Tap This meter allows for installation under pressure, eliminating the need to isolate and remove pressure from the pipe it is being installed upon. It incorporates two valves that the probes pass through and a muffler that collects chips from the drilling process. It takes an equally short amount of installation time as the standard meters. Available on 2" and 50mm or larger flowmeters.



2020 FINALISTS



Pressure Sensing Digital Flowmeters monitor pressure and flow. A pressure sensor is mounted between the two flow sensing probes. The pressure signal is provided as a second milliamp output. The display can be configured to show pressure or flow. The pressure signal is also available through wired or wireless serial outputs. The pulse output is replaced with a transistor output configured as a low-pressure alarm when the pressure drops below 50 PSIG. Available on 2" and 50mm or larger flowmeters.



2021







# For Technical Assistance, Call An EXAIR Application Engineer 1-800-903-9247



FXAIR's Drill **Guide for Digital** Flowmeter.

#### **Drill Guides**

Model #	Description
900817	Drill Guide Kit Only, 1/2", 3/4", 1", 1-1/4", 1-1/2" Schedule 40 and Type L Copper (double ring mount)
901281	Drill Guide Kit Only, 2" and 2.5" Schedule 40 and Type L Copper (single ring mount)
900939	Drill Guide Kit Only, 3" Schedule 40 and Type L Copper
900871	Drill Guide Kit Only, 4" Schedule 40 and Type L Copper
900872	Drill Guide Kit Only, 5" Schedule 40 and Type L Copper
901151	Drill Guide Kit Only, 6" Schedule 40 and Type L Copper
902098	Drill Guide Kit Only, 8" Schedule 40 and Type L Copper
901994	Drill Guide Kit Only for 2" and Up Aluminum Compressed Air Pipe

#### Page 13). Drill guides can also be ordered separately. What is the Summing Remote Display?

model number. (Model Number Configurator on

EXAIR's Summing Remote Display for the Digital Flowmeter has a four-digit LED display that makes it easy to monitor compressed air consumption from a convenient location. With the push of a button, the display cycles to show the current air consumption, usage for the previous 24 hours, and total cumulative usage. The Summing Remote Display shows that flow measurement, the daily and cumulative usage and is frequently used when the Digital Flowmeter is in an obscure, hard to read location. Regular monitoring of the air usage of a machine, process or department makes it possible to save thousands of dollars per year in compressed air waste by identifying the costly leaks or inefficient air products. The Summing Remote Display is CE and RoHS compliant

#### What is the USB Data Logger?

EXAIR's award-winning Model 9147 USB Data Logger connects directly to your Digital Flowmeter and is simple to use. Download the software to configure the Data Logger to record your flow rate from once a second (about nine hours of data) up to once every 12 hours (over 2 years!).

When the Data Logger is removed from the Digital Flowmeter and plugged into a computer, the data can be viewed in the software or exported directly into Microsoft Excel\*. The Data Logger is available pre-installed on the Digital Flowmeter. Data Loggers can be added to your Digital Flowmeter by adding a suffix to the model number (Model Number Configurator on Page 13). They can also be ordered separately.

#### **Summing Remote Display**

Model #	Description
9150	LED Readout displays SCFM
9150-M3	LED Readout displays m³/hr



**EXAIR's Summing** Remote Display for the Digital Flowmeter.

#### **USB Data Logger**

Model #	Description	
9147	USB Data Logger for Digital Flowmeter	



EXAIR's USB Data Logger for the Digital Flowme

#### What are Block-Off Rings?

Block-Off rings are used to safely cover and seal any holes which were drilled for the Digital Flowmeters They allow for moving a Digital Flowmeter to multiple locations in your piping system.

#### **Block-Off Rings**

	A I Was the Control of the Control o				
Model#	Description	Model #	Des		
901327	Block-Off Rings for 9090 or 9090Z	901332	Bloc		
901328	Block-Off Rings for 9091 or 9091Z	901333	Bloc		
901329		901334	Bloc		
	Block-Off Rings for 9092, 9092-M3 or 9092Z	901335	Bloc		
901331	Block-Off Rings for 9094, 9094-M3 or 9094Z	902099	Bloc		

Model #	Description	
901332	Block-Off Rings for 9095, 9095-M3 or 9095Z	
901333	Block-Off Rings for 9096, 9096-M3 or 9096Z	
901334	Block-Off Rings for 9097, 9097-M3 or 9097Z	
901335	Block-Off Rings for 9098, 9098-M3 or 9098Z	
902099	Block-Off Rings for 90100 or 90100Z	







#### **Digital Flowmeter Model Numbering**

1. Choose the Version of Digital Flowmeter using one of these prefixes:

#### Version

version	
Standard or Wireless	No Prefix
Hot Tap DFM (available on 2" and 50mm or larger)	н
Pressure Sensing DFM (available on 2" and 50mm or larger)	P

2. Choose the Size of your compressed air pipe:

#### Size

Model #	Pipe Size	Model #	Pipe Size
9090	1/2*	9099	5*
9091	3/4"	90100	6*
9092	1"	90101	8*
9093	1-1/4°	91025	for nominal pipe 25mm
9094	1-1/2*	91040	for nominal pipe 40mm
9095	2"	91050	for nominal pipe 50mm
9096	2-1/2"	91063	for nominal pipe 63mm
9097	3"	91076	for nominal pipe 76mm
9098	4"	91101	for nominal pipe 101mm

3. Choose the Configuration you want by picking one suffix below:

#### Configuration

Model #	Configuration	
-DG	removes Drill Guide	
-DAT	includes Data Logger w/ Drill Guide	
-DG-DAT	includes Data Logger, removes Drill Guide	
Z	Wireless w/ Drill Guide	
Z-DG	Wireless, removes Drill Guide	
ZG	Wireless and Gateway w/ Drill Guide	
ZG-DG	Wireless and Gateway, removes Drill Guide	

CU	for Copper Pipe w/ Drill Guide	
CU-DG	for Copper Pipe, removes Drill Guide	
CU-DAT	for Copper Pipe includes Data Logger w/ Drill Guide	
CU-DG-DAT	for Copper Pipe, includes Data Logger, removes Drill Guide	
CUZ	for Copper Pipe, Wireless w/ Drill Guide	
CUZ-DG	for Copper Pipe, Wireless, removes Drill Guide	
CUZG	for Copper Pipe, Wireless and Gateway w/ Drill Guide	
CUZG-DG	for Copper Pipe, Wireless and Gateway, removes Drill Guide	

1	-M3	Metric (displays m³/hr) w/ Drill Guide	
1	-M3-DG	Metric (displays m <sup>8</sup> /hr), removes Drill Guide	
1	-M3-DAT	Metric (displays m³/hr) includes Data Logger w/ Drill Guide	
1	-M3-DG- DAT	Metric (displays m³/hr), includes Data Logger, removes Drill Guide	

#### **Configuration Samples**

Version	Size	Configuration	Summary
	9090	-DG	Model 9090-DG Standard 2" DFM without a Drill Guide
н	9098	CU	Model H9098CU Hot Tap 4" DFM for Copper Pipe w/Drill Guide
P	9095	ZG	Model P909SZG Pressure Sensing 2" DFM, Wireless Gateway w/Drill Guide
	91025	CUZ	Model 91025CUZ 25mm Nominal Pipe DFM for Copper Pipe, Wireless with Drill Guide



EXAIR's Digital Flowmeter is a product designed to monitor compressed air consumption and flow, offering an easy solution for tracking these metrics. Equipped with a digital display, it provides the precise amount of compressed air being used. This feature allows for the identification of costly leaks or inefficient air products. The device is easy to install, sensitive at low flows, requires no calibration or setup, and includes all components necessary for installation.

#### **Digital Flowmeter**

(Add specific Configuration from Page 13)

Model #	Pipe Size	Flow Range*
9090	1/2*	1-90 SCFM (2-153 m³/hr)
9091	3/4*	1-120 SCFM (2-204 m³/hr)
9092	1*	1-160 SCFM (2-272 m <sup>2</sup> /hr)
9093	1-1/4"	2-150 SCFM (3.6-252 m³/hr)
9094	1-1/2"	2-200 SCFM (3-340 m³/hr)
9095	2*	4-400 SCFM (6.6-678 m³/hr
9096	2-1/2"	5-500 SCFM (8.4-846 m³/hr)
9097	3"	12-1200 SCFM (19.8-2040 m³/hr)
9098	4"	20-2000 SCFM (34.2-3396 m³/hr)
9099	5*	20-2500 SCFM (34.2-4248 m³/hr)
90100	6"	50-5000 SCFM (85.2-8496 m³/hr)
90101	8"	100-6000 SCFM (169.8-10194 m³/hr)

#### **Digital Flowmeter Type L Copper Pipe**

(Add specific Configuration from Page 13)

120 SCFM (2-204 m3/hr) 160 SCFM (2-272 m3/hr)
160 SCFM (2-272 m3/hr)
on see in the my will plain?
150 SCFM (3.6-252 m3/hr)
200 SCFM (3-342 m3/hr)
350 SCFM (4.8-594 m3/hr)
00 SCFM (8.4-846 m3/hr)
00 SCFM (12-1188 m3/hr)
1500 SCFM :2-2544 m3/hr)

Calibrated range, Usable range higher. Please consult factory.

Note: Flow ranges for all Digital Flowmeters in top 3 tables except for Hot Tap Digital Flowmeters, shown below.

#### Digital Flowmeter -**Nominal Pipe Size - Millimeters**

(Add specific Configuration from Page 13)

Model #	Pipe Size	Flow Range*
91025	25mm	1-150 SCFM (2-254 m3/hr)
91040	40mm	2-200 SCFM (3.6-342 m3/hr)
91050	50mm	3-350 SCFM (4.8-594 m3/hr)
91063	63mm	5-500 SCFM (8.4-846 m3/hr)
91076	76mm	7-700 SCFM (12-1188 m3/hr)
91101	101mm	15-1500 SCFM (25.2-2544 m3/hr)









**EXAIR's Digital Flowmeter family is** available in many sizes from stock.

#### Hot Tap Digital Flowmeter -Schedule 40 Iron Pipe

(Add specific Configuration from Page 13)

Model #	Pipe Size	Flow Range*	
H9095	2°	4-400 SCFM or 7-680 m3/hr	
H9096	2-1/2"	5-500 SCFM or 8-850 m3/hr	
H9097	3"	12-1200 SCFM or 20-2039 m3/hr	
H9098	4"	20-2000 SCFM or 34-3398 m3/hr	
H90100	6*	50-5000 SCFM or 85-8495 m3/hr	
H90101	8"	100-6000 SCFM or 169-10194 m3/hr	

#### Hot Tap Digital Flowmeter -Type L Copper Pipe

Model #	Pipe Size	Flow Range*	
H9095CU	2*	3-350 SCFM or 5-595 m3/hr	
H9096CU	2-1/2"	5-500 SCFM or 8-850 m3/hr	
H9097CU	3*	7-700 SCFM or 12-1189 m3/hr	
H9098CU	4*	15-1500 SCFM or 25-2548 m3/hr	
H90100CU	6*	50-5000 SCFM or 85-8495 m3/hr	

		Digital Flowmeter Specific	cations	
	Wired	Wireless	Hot Tap	Pressure Sensing
Accuracy	5% of reading plus 1% of range for flows from 10% to 100% of indicated range at air temperatures between 20°F and 120°F.	5% of reading plus 1% of range for flows from 10% to 100% of indicated range at air temperatures between 20°F and 120°F.	5% of reading plus 1% of range for flows from 10% to 100% of indicated range at air temperatures between 20°F and 120°F.	PRESSURE: +/- 2 PSIG maximum. +/- 0.5 PSIG at 68°F.
Operating Pressure	200 PSIG maximum on Sch. 40 iron and on Type L Copper below 3". Consult EXAIR for other materials and higher pressures	200 PSIG maximum on Sch. 40 iron and on Type L Copper below 3". Consult EXAIR for other materials and higher pressures	130 PSIG maximum on Sch. 40 iron. Consult EXAIR for other materials and higher pressures	200 PSIG maximum on Sch. 40 iro and on Type L Copper below 3°. Consult EXAIR for other materials and higher pressures
Input Power	250 mA at 24V DC			
Output resistance	600 Ohms maximum	600 Ohms maximum	600 Ohms maximum	600 Ohms maximum
Wetted Materials	Stainless Steel, Gold, Thermal epoxy, Viton	Stainless Steel, Gold, Thermal epoxy, Viton	Stainless Steel, Gold, Thermal epoxy, Viton, PTFE, Aluminum	Stainless Steel, Gold, Thermal epoxy, Viton
Ring Material	Aluminum	Aluminum	Aluminum	Aluminum
Display	Four digit LED	Four digit LED	Four digit LED	Four digit LED
Response Time	One second to 63% of change in value at flows above 30% of range	One second to 63% of change in value at flows above 30% of range	One second to 63% of change in value at flows above 30% of range	One second to 63% of change in value at flows above 30% of range
Pressure Range	N/A	N/A	N/A	0-145 PSIG operating range 200 PSIG maximum 145 PSIG full sc ale of mA output For best accuracy, avoid pressure above 145 PSIG
Compliance	CE and RoHS	CE and RoHS	CE and RoHS	CE and RoHS











#### Wired, Wireless and Pressure **Sensing Flowmeter Dimensions**



#### Wired, Wireless, Hot Tap, and **Gateway Flowmeter Dimensions**



	Pipe	-	1
Series	Size		mm
9090	1/2"	3.31	84
9091	3/4"	3.49	89
9092	1"	3.87	98
9093	1-1/4"	4.24	108
9094	1-1/2"	4.62	117





Large Digital Flowmeter -	NA.
Schedule 40 Iron Pipe**	3
Pine A	

	Pipe		
Series	Size		mm
9095	2"	5.34	136
9096	2-1/2"	6.09	155
9097	3"	6.71	171
9098	4"	7.71	196
9099	5*	8.84	224
90100	6°	9.84	250
90101	8"	11.84	301





Small Digital Flowmeter -Type L Copper Pipe\*\*








Large Digital Flowmeter -Type L Copper Pipe\*\*

	Pipe		
Series	s Size		
9095CU	2"	5.09	129
9096CU	2-1/2"	5.84	148
9097CU	3*	6.34	161
9098CU	4"	7.34	186







Small Digital Flowmeter -**Nominal Pipe\*\*** 

	Pipe		
Series	Size		mm
91025	25mm	3.49	89
91040	40mm	4.24	108








	Pipe		
Series	Size		mm
91050	50mm	5.1	129
91063	63mm	5.6	142
91076	76mm	6.3	161
91101	101mm	7.3	186































	Pipe	100			
Series	Size		mm		
H9095	2"	6.43	163		
H9096	2-1/2"	7.20	183		
H9097	3"	7.82	199		
H9098	4"	8.82	224		
H90100	6*	10.95	278		
H90101	8"	12.95	329		





**Type L Copper Pipe** 2" 6.18 157 6.95 177 H9096CU 2-1/2" 7.45 189 4" 8.45 215 H9098CU


H90100CU

Hot Tap Digital Flowmeter -

6° 10.45 265












#### **Gateway Dimensions**





bit, ethernet cable and hole locating fixture.







# Digital Sound Level Meter COMPRESSED AIR



#### **Ultrasonic Leak Detector**

# Digital Sound Level Meter™

#### Prevent worker-related hearing loss!

#### What Is The Digital Sound Level Meter?

EXAIR's Model 9104 Digital Sound Level Meter is an easy to use instrument that can measure and monitor the sound level pressure in a wide variety of industrial environments. The source of loud noises can be quickly identified and isolated so corrective measures can be taken to reduce or eliminate the problem.



For compressed air noise, it is often as simple as replacing the existing inefficient blowoffs with EXAIR's engineered compressed air products such as the Super Air Knife, Super Air Amplifier or Super Air Nozzles. In many cases, the EXAIR products can reduce noise levels by 10 dBA which is perceived as cutting the sound volume in half.

#### Why The Digital Sound Level Meter?

Hearing loss induced by high noise in the workplace is a common problem. Exposure to high noise levels for an extended period of time can lead to permanent hearing loss for workers not wearing proper hearing protection. The Digital Sound Level Meter can help employers protect workers by monitoring noise levels so they don't exceed the limits shown in OSHA Standard 29 CFR - 1910.95(a). Failure to comply can result in hefty fines.

OSHA Maximum	Allowa	ble	Nois	e Exp	osur	е	
Hours per day (constant noise)	8	7	4	3	2	1	0.5
Sound level dBA	90	91	95	97	100	105	110

Accurate and responsive, the Digital Sound Level Meter measures the decibels of the sound and displays the reading on the large LCD display that has a backlight button for easier viewing. An "F/S" response time button provides a choice of slow response measurements for comparatively stable noise measurement or fast for varying noise. The "Max Hold" setting will measure the maximum noise level of sounds and updates continuously if a louder sound is detected. Certification of accuracy and calibration traceable to NIST (National Institute of Standards and Technology) is included.

The Sound Level Meter identifies a potential source of hearing loss.



Model 9104 Digital Sound Level Meter comes complete with removable wind screen, battery and a protective case.

#### **Advantages**

- Measures sound level range from 35 dB 130 dB (Low: 35 to 100; High: 65 to 130 dB)
- Frequency range 31.5Hz 8kHz
- A and C weightings (check compliance with safety regulations and acoustic analysis)
- Slow (1 sec) and fast (125ms) response settings to check peak and average noise levels
- Maximum hold feature to measure peak sound levels
- Accuracy is ± 1.5 dB
- NIST Certification included

- · Four digit LCD display in 0.1 dB steps with backlight
- · Battery life is 50 hours (typical) with low battery alert
- · Automatic power off after 15 minutes of non-use
- · Meets CE, ANSI and IEC Type 2 SLM standards
- · Tripod mounting ideal for taking long term measurements (tripod not included)
- · Removable windscreen for use in windy conditions
- · Includes protective carrying case, 9V battery, instruction manual and removable windscreen

## **Ultrasonic Leak Detector**

#### Locate costly leaks in your compressed air system!

#### What Is The Ultrasonic Leak Detector?

The Ultrasonic Leak Detector (ULD) is a hand-held, high quality instrument that can locate costly leaks in a compressed air system.



A person using the ULD need only aim it in the direction of a suspected leak. When a leak is present, an audible tone can be heard with the use of the headphones, and the LED display will light. Testing the various unions, pipes, valves and fittings of a complete installation can be done quickly and effectively at distances up to 20' (6.1m) away!

#### Why The Ultrasonic Leak Detector?

Plants that aren't maintained can easily waste up to 30% of the compressor output through leaks that go undetected. Compressing air is an expensive operation. Saving the wasted compressed air reduces overall operating costs. In large plants, the cost of a small air leak may be insignificant, but many small leaks when located and repaired can amount to huge energy savings.

#### What is Ultrasound?




Ultrasonic sound is a range of sound that is above human hearing capacity. Most people can hear frequencies from 20 Hz to 20 kHz. Sound from 20 kHz to 100 kHz cannot be heard and is called "ultrasonic". The Model 9207 Ultrasonic Leak Detector converts ultrasonic sound emissions to a range that is audible to people. (The sound generated by the ULD is 32 times lower in frequency than the sound that is received.)

#### Advantages

- Detects any pressurized air leak up to 20 feet (6.1m) away
- Converts ultrasound to an audible frequency
- · LED display confirms the leak location
- Detects leaks in noisy industrial environments
- Sensitivity controls provide accurate detection
- Not affected by contaminants or windy conditions
- Includes accessories to detect leaks in hard to reach areas
- Rugged carrying case
- Complies with the International Electrotechnical Commission (IEC) 61325-1

#### **Applications**

- · Locates leaks in air, steam and non-flammable gas systems including pipes, fittings, valves, cylinders and pressure vessels
- Finds the source of bearing and gear wear
- · Locates arcing in an electrical system
- · Detects refrigeration and air conditioning system leaks
- · Locates leaks in brake systems, tubes, tires and radiators
- · Senses cracks in moving rubber v-belts · Detects leaks in vacuum systems
- Checks condition of engine seals



CE

m

EXAIR con

25





























Tubular

Earbuds

Ultrasonic sound is directional in transmission and is loudest at the source. Turbulence created by the air forced through a small orifice generates ultrasonic sound. This emitted sound is called "white noise" and occurs when the air moves from a high pressure area such as a pipe or vessel and escapes to a low pressure area such as the room. The Ultrasonic Leak Detector converts the turbulent flow to a frequency that can be heard using the earbuds. As the ULD moves closer to the leak, more LEDs on the display light to confirm the source of the leak.

In some cases, the suspected leak is in a hot area and/or close to moving parts. The tubular extension and parabola make it possible to probe these difficult locations from a distance to isolate the leak.



The Model 9207 Ultrasonic Leak Detector comes complete with a hard-shell plastic case, earbuds, parabola, tubular adaptor, tubular extension and 4 AA batteries.



The Model 9207 Ultrasonic Leak Detector with tubular extension quickly pinpoints a costly leak in a noisy industrial environment.

#### Find Leaks -

#### Pay For Your Ultrasonic Leak Detector

Consider one small leak that is equivalent to a 1/16" (1.6mm) diameter hole. At 80 PSIG (5.5 BAR), it consumes 3.8 SCFM or 108 SLPM.

Most large plants know their air cost.

If you don't know your actual cost per 1,000 SCF, a reasonable average is \$0.25 per 1,000 SCF (28,329 SL).

Dollars consumed per hour = SCFM consumed x 60 minutes x cost/1,000 SCF

- $= 3.8 \times 60 \times \$0.25/1,000$
- = \$0.06 per hour
- = \$1.44 per 24 hour period
- = \$10.08 per week
- = \$524.16 per year









#### Super Air Knife










# **Super Air Knife™**

Quiet, hard-hitting curtain of air for blowoff, cleaning, drying, and cooling.

















#### What Is The Super Air Knife?

EXAIR's Super Air Knife is the latest generation of our engineered air knife that dramatically reduces compressed air usage and noise when compared to other blowoffs. The Super Air Knife offers a more efficient way to clean, dry or cool parts, webs or conveyors. It delivers a uniform sheet of laminar airflow across the entire length with hard-hitting force.

Noisy blowoffs become a whisper when replaced with the compact Super Air Knife. Even at high pressures of 80 PSIG (5.5 BAR), the sound level is surprisingly quiet at 69 dBA for most applications! Air amplification ratios (entrained air to compressed air) of 40:1 are produced. Meets OSHA maximum dead-end pressure and noise requirements.







#### **Applications**

- · Part drying after wash
- · Sheet cleaning in strip mills
- · Conveyor cleaning
- Part or component cooling
- · Web drying or cleaning · Environmental separation
- · Pre-paint blowoff
- · Bag opening/filling operations
- · Scrap removal on converting operations

#### **Advantages**

- Quiet 69 dBA for most applications
- · Minimal air consumption
- · 40:1 air amplification
- · Uniform airflow across entire length
- · Variable force and flow
- . No moving parts maintenance free
- · Easy mounting compressed air inlets on each end and bottom
- Compact, rugged, easy to install

- Recessed hardware
- · Stock lengths to 108" (2743mm) in aluminum, 303 stainless steel, and 316 stainless steel (ss - for temperatures up to 800°F (427°C), food processing or or corrosive environments), and PVDF up to 54" (1372mm) for superior corrosion resistance.
- · Special lengths available
- · Unlimited system lengths of uninterrupted airflow available













#### Dry

The laminar airflow of the Super Air Knife is perfect for removing moisture prior to packaging, painting, labeling, bar coding and assembly. Common applications include drying parts, rolled steel, circuit boards, webs, bottles, cans and more. Velocity is easily adjusted from a "blast" to a "breeze" with a pressure regulator.



Fast moving bottles are blown dry by (2) Model 110012 12" (305mm) Super Air Knives prior to labeling.



Model 110006 6" (152mm) Super Air Knife removes residual water from can bottoms after a rinse process. eliminating water damage to packaging and shipping materials.



Model 110054 54" (1372mm) Super Air Knife dries stamped parts that exit a washer.

EXAIR

#### Blowoff

The Super Air Knife is ideal for blowing off chips, dirt or water from parts, webs or conveyors. It delivers a uniform sheet of air that has the same force across the entire length. There are no interruptions or "dead spots", which means all surfaces are dried or cleaned. The Super Air Knife is available in aluminum, stainless steel, or PVDF for corrosive and high temperature applications.



A Model 110048PKI 48" (1219mm) Super Air Knife with Plumbing Kit installed uses **EXAIR's Universal Air Knife Mounting** System to maintain proper position for removing dust on a conveyor belt and eliminate carryover accumulation.



(3) Model 110012 12" (305mm) Super Air Knives blow excess honing oil off machined engine sleeves.

#### Cool

Large volumes of airflow can be generated in very tight spaces due to the compact size of the Super Air Knife. Flow and force are easily controlled with a pressure regulator, allowing fast or gradual cooling. Shims can be installed if additional hard-hitting velocity is required.



A Model 110018 18" (457mm) Super Air Knife cools molded plastic following dip molding.

Open, Float, Separate

The uniform airflow exits the Super


Air Knife in a perfectly straight line (does not deflect). It is ideal for

opening bags and pouches, floating

webs, and keeping environments

# With a 40:1 air amplification ratio, a

high volume of airflow is the result from minimal air input to keep linear induction motors from overheating.




A Model 110006 6" (152mm) Super Air Knife opens pouches on a form-fill-seal-bagger.

#### FAX (513) 671-3363 \* E-mail: techelp@exair.com \* www.exair.com



#### **Super Air Knife**

#### **How The Super Air Knife Works**



Compressed air flows through an inlet (1) into the plenum chamber of the Super Air Knife. The flow is directed to a precise, slotted orifice. As the primary airflow exits the thin slotted nozzle (2), it follows a flat surface that directs the airflow in a perfectly straight line. This creates a uniform sheet of air across the entire length of the Super Air Knife. Velocity loss is minimized and force is maximized as the room air (3) is entrained into the primary airstream at a ratio of 40:1. The result is a well defined sheet of laminar airflow with hard-hitting force and minimal wind shear.

#### Intelligent Use Of Compressed Air

Almost every industrial facility has at least one compressor that is used for hundreds of different tools, equipment and operations. While most applications for compressed air present no real problems, some do. Improper use can translate into unnecessary energy costs, high noise levels and dangerous exposure of personnel to high pressure air.

#### **Reduce Energy Costs**

The best way to cut energy costs is through proper maintenance and use of the compressed air system. Leaks and dirty filters require maintenance on a regular basis. Energy savings can also be realized when replacing outdated motors and controls with high efficiency models that often pay for themselves in a short period of time. The most important factor to dramatically boost efficiency is to use proper compressed air products. The Super Air Knife uses only 1/3 of the compressed air of typical blowoffs.

#### **Reduce Noise Levels**

High noise levels are a common problem for many plants. Compressed air noise often exceeds OSHA (Occupational Safety and Health Administration) noise level exposure requirements, resulting in hearing loss to those working in close proximity. The sound level of the Super Air Knife is quiet at 69 dBA, even at high pressures of 80 PSIG (5.5 BAR). Using the Super Air Knife, it is possible to obtain hard-hitting force without the high noise.

OSHA Maximum A	llowa	nie is	oise	Expu	sure		
Hours per day (constant noise)	8	7	4	3	2	1	0.5
Sound level dBA	90	91	95	97	100	105	110

#### **Eliminate Harmful Dead End Pressures**

Air can be dangerous when the outlet pressure of a hole, hose or copper tube is higher than 30 PSIG (2 BAR). In the event the opening is blocked by a hand or other body part, air may enter the bloodstream through the skin, resulting in a serious injury. The Super Air Knife has been engineered for safety and cannot be dead-ended. It is safe to operate at higher pressures and complies with OSHA standard 1910.242(b).

#### Replacement For Expensive, Noisy Blowers

Energy conscious plants might think a blower to be a better choice due to its slightly lower electrical consumption compared to a compressor. In reality, a blower is an expensive capital expenditure that requires frequent downtime and costly maintenance of filters, belts and bearings.

#### Here are some important facts:

- · Filters must be replaced every one to three months.
- · Belts must be replaced every three to six months.
- Blower bearings wear out quickly due to the motor that must turn at 17,000-20,000 RPM in order to generate effective airflows.
- · Poorly designed seals that allow dirt and moisture infiltration along with environments above 125°F (52°C) decrease the one year bearing life.
- · Typical bearing replacement is at least once a year at
- · Many bearings can't be replaced in the field, resulting in wntime to send the assembly back to the manufacturer.
- · Many blowers generate heat, making conditions uncomfortable and difficult to use for cooling applications.

Blowers take up a lot of space and often produce sound levels that exceed OSHA noise level exposure requirements. Air volume and velocity are often difficult to control since mechanical adjustments are required.









#### **Compare These Blowoffs**

There are a variety of ways to blow the water from the bottles shown in the photo below, but which method is best? The following comparison of drilled pipe, flat air nozzles, a blower and the Super Air Knife proves that EXAIR has the best choice for your blowoff, cooling or drying application.

Our goal for each of the blowoff choices was to use the least amount of air possible to get the job done (lowest

energy and noise level). Compressed air pressure required for each was 60 PSIG (4.1 BAR) which provided adequate velocity to blow the water off. The blower used had a ten horsepower electric motor and was a centrifugal type blower at 18,000 RPM. The table at the bottom of the page summarizes the overall performance. Since your actual part may have an odd configuration, holes or sharp edges, we took sound level measurements in free air (no impinging surface).

#### **Drilled Pipe**

This common blowoff is very inexpensive and easy to make. For this test, we used (2) drilled pipes, each with (25) 1/16" (1.6mm) diameter holes on 1/2" (13mm) centers. As shown in the test results below, the drilled pipe performed poorly. The initial cost of the drilled pipe is overshadowed by its high energy use. The holes are easily blocked and the noise level is excessive - both of which violate OSHA requirements. Velocity across the entire length was very inconsistent with spikes of air and numerous dead spots.

As shown below, this inexpensive air nozzle was the worst performer. It is available in plastic, aluminum and stainless steel from several manufacturers. The flat air nozzle provides some entrainment, but suffers from many of the same problems as the drilled pipe. Operating cost and noise level are both high. Some manufacturers offer flat air nozzles where the holes can be blocked - an OSHA violation. Velocity was inconsistent with spikes of air.

The blower proved to be an expensive, noisy option. As noted below, the purchase price is high. Operating cost was considerably lower than the drilled pipe and flat air nozzle, but was comparable to the EXAIR Super Air Knife. The large blower with its two 3" (76mm) diameter hoses requires significant mounting space compared to the others. Noise level was high at 90 dBA. There was no option for cycling it on and off to conserve energy like the other blowoffs. Costly bearing and filter maintenance along with downtime were also negative factors.

#### **EXAIR Super Air Knife**

The Super Air Knife pair did an exceptional job of removing the moisture on one pass due to the uniformity of the laminar airflow. The sound level was extremely low at 69 dBA. For this application, energy use was slightly higher than the blower but can be less than the blower if cycling on and off is possible. Safe operation is not an issue since the Super Air Knife cannot be dead-ended. Maintenance costs are low since there are no moving parts to wear out.



#### EXAIR

11510 Goldcoast Drive • Cincinnati, OH 45249-1621 • Phone (513) 671-3322 FAX (513) 671-3363 \* E-mail: techelp@exair.com \* www.exair.com

## For Technical Assistance, Call An EXAIR Application Engineer 1-800-903-9247

#### **Super Air Knife**

#### Super Air Knife Performance with .002" (0.05mm) thick shim installed

Press Sup		Air Consun Inch (2		Velocity ⊕ 6 from t		Sound Level @ 3' (914mm)	Force per Inch (152mm) fr	
PSIG	BAR	SCFM	SLPM	FPM	M/S	dBA	OUNCES	GRAMS
20	1.4	1.1	31	5,000	25.4	57	0.6	17
40	2.8	1.7	48	7,000	35.6	61	1.1	31
60	4.1	2.3	65	9,600	48.8	65	1.8	51
80	5.5	2.9	82	11,800	59.9	69	2.5	71
100	6.9	3.5	99	13,500	68.5	72	3.2	91

# **Airflow Pattern**

#### **Holes Drilled In Pipe**

Press Sup		Air Consum (1.59mm)		Air Consum (2.38mm)		Air Consum (3.18mm)		Air Consum (4.76mm)			on 1/4" (6.35mm) . hole
PSIG	BAR	SCFM	SLPM	SCFM	SLPM	SCFM	SLPM	SCFM	SLPM	SCFM	SLPM
20	1.4	1.4	40	3.5	99	6.4	181	14.5	410	25	710
40	2.8	2.2	62	5.4	153	10.2	289	22.9	648	40	1,132
60	4.1	3.0	85	7.4	209	14	396	31	877	54	1,528
80	5.5	3.8	108	9.4	266	17.5	495	39.5	1,118	69	1,953
100	6.9	4.6	130	11.5	326	21.5	609	47.5	1,344	84	2,363

#### **Super Air Knife Specifications**

The Super Air Knife is available in standard lengths of 3", 6", 9" 12", 18", 24", 30", 36", 42", 48", 54", 60", 72", 84", 96" and 108". Special lengths and unlimited system lengths are available. Any number of Super Air Knives may be installed across a given area.

Compressed Air Inlets: A Super Air Knife has compressed air inlets on each end and the bottom. Knives 24"-47" should use the 2 inlets at opposite ends of the knife. Knives 48"-59" use 2 inlets at opposite ends plus 1 near the middle on the bottom of the knife. Knives 60"-83" use 2 inlets at opposite ends plus 2 inlets equally spaced on the bottom of the knife. Knives 84" and longer use 2 inlets at opposite ends plus 3 inlets equally spaced on the bottom of the knife.

Filtration: The use of clean air is essential. Kits include an automatic drain filter with a 5 micron filter element that is sized properly for flow.

Materials of Construction: The Super Air Knife is available from stock in aluminum, Type 303 stainless steel, Type 316 stainless steel and PVDF. Other materials are available on special order.

Mounting: The Universal Air Knife Mounting System is shown on page 29. The Super Air Knife can be supported by the compressed air pipe. Tapped holes (1/4-20) on the bottom are also provided.

Regulation: A pressure regulator on the compressed air supply provides infinite control of flow, force and air consumption. Kits include a pressure regulator that is sized properly for flow.

Shim Sets: The compressed air exhausts through a gap which is set with a shim. Force and flow may be increased by adding shims. Shim sets for aluminum Super Air Knives include a .001" (0.03mm) Amber color .003" (0.08mm), Green color , and .004" (0.10mm) thick Tan color plastic shims. A Red color [ 0.05mm] thick shim comes installed in the Super Air Knife. Shim sets for stainless steel Super Air Knives include (3) .002" (0.05mm) stainless steel shims. PVDF Super Air Knife shim sets include (3) .002" (0.05mm) PTFE shims.

#### **How To Calculate Air Savings:**

The chart at the top of the page shows the air consumption of a Super Air Knife per inch of length (25mm) at various pressures. Comparable data is given for holes drilled in pipe.

#### To Determine Air Consumption for the Drilled Pipe

- 1. Determine the size of existing holes and supply pressure. From the chart, find air consumption per hole.
- 2. Multiply air consumption per hole times the number of holes to obtain total air consumption.

#### To Determine Air Consumption for the Super Air Knife

1. From the chart, find the air consumption per inch (25mm) at supply pressure and multiply by number of inches required.

- 1. Existing blowoff is 18" long pipe with 1/16" diameter holes on 1/2" spacing (37 holes), 80 PSIG supply. Air consumption from chart is 3.8 SCFM per hole. Total air consumption is 37 x 3.8 = 140.6 SCFM (3,981 SLPM).
- 2. Use 18" (457mm) Super Air Knife with standard .002" gap and 80 PSIG supply. Air consumption from chart is 2.9 SCFM per inch. Total air consumption is  $18 \times 2.9 = 52.2$  SCFM (1,478 SLPM).
- 3. Compressed air saved = 140.6 SCFM 52.2 SCFM = 88.4 SCFM
- 4. Most large plants know their air cost. If you don't know your actual cost, a reasonable average to use is \$0.25 per 1,000 SCF
- 5. Dollars saved per hour = SCFM saved x 60 minutes x cost/1,000  $SCF = 88.4 \times 60 \times 50.25/1.000$ 
  - = \$1.33/hour
  - = \$53,20 per 40 hour week
  - = \$2,766.40 per year savings







#### **Changing Performance By Adding Shims**

The Super Air Knife is shipped with a Red color 1 .002" (0.05mm) thick shim installed, which works best for most applications. There are, however, some situations that require more force and flow. Thicker shims will increase the gap opening which offers higher velocity and harder hitting force. Air consumption and noise will be slightly higher. Shim sets are included with all kits or can be purchased separately.



Kits include a Super Air Knife, shim set, filter separator and pressure regulator (with coupler).

#### **Special Super Air Knives**

EXAIR

EXAIR manufactures special Super Air Knives suited to specific application requirements. The shape, dimensions and materials of construction can be modified to fit existing machines and environments.

The curved stainless steel Super Air Knife (shown top right) was manufactured for a laboratory that uses the force of the airflow to hold test tubes in place on a rotating index table. They were able to eliminate the mechanical clips and latches that slowed the test tube removal. This holding method minimized risk of tube breakage and eliminated any chance of puncturing the technician's rubber gloves.


EXAIR manufactures special Super Air Knives made of plastic. These products are engineered to work under normal operating pressures, providing the same performance as their aluminum and stainless steel counterparts.

The PVC Super Air Knife (shown 2nd from top right) was manufactured for a picture tube plant. The softer material was less likely to scratch the picture tube surface and was chemically resistant to the phosphorus which coated the inside.

The flat Super Air Knife (shown 3rd from top right) is used in a molding machine for integrated circuit chips. Prior to molding the black plastic shells around the silicon wafers, they blow the mold cavity clean of any fine plastic fibers left by the previous cycle. The flat design constructed of corrosion resistant stainless steel was made to fit the tight space of the molding machine.

The double-sided Super Air Knife (shown 2nd from bottom right) provides two uniform sheets of air in opposite directions. It is ideal for blowing water from two or more columns of stacked parts (like printed circuit boards) as they are lifted out of a bath or the open halves of a mold. Each side operates independently.

The Super Air Knife (shown bottom right) can be modified to include extra mounting holes to suit your application.





A special curved stainless steel Super Air Knife holds test tubes in place on a rotating index table.



A PVC Super Air Knife designed to withstand a phosphorus environment.



A flat Super Air Knife, only 11/16" thick, blows plastic fibers from a mold used to make integrated circuit chips.



The double-sided Super Air Knife provides two uniform sheets of laminar airflow.



Stainless steel Super Air Knife modified to include extra mounting holes.

#### **Super Air Knife**

#### Many Lengths Available From Stock in Four Materials

EXAIR's Super Air Knives are available from stock in many lengths and your choice of four materials. The force, flow and air pattern stay the same for each construction.

The aluminum Super Air Knife is suited to a wide variety of environments where corrosion or contamination is not a factor. The aircraft grade aluminum construction with plastic shim is very durable for general purpose applications. Stainless steel screws are used to eliminate corrosion in damp locations. It can withstand temperatures up to 180°F (82°C).

#### Type 303 Stainless Steel

This is the most common grade of stainless steel. It offers good strength and is best suited to mildly corrosive environments. It can withstand temperatures up to 800°F (427°C).

#### **Type 316 Stainless Steel**

Some applications require better corrosion resistance than offered by Type 303 stainless steel. Type 316 stainless steel offers excellent corrosion resistance, better strength properties and resists pitting. These factors are important to manufacturers of food, pharmaceutical and surgical products that need to minimize contamination by the metal. It can withstand temperatures up to 800°F (427°C).

#### PVDF (Polyvinylidene Fluoride)

EXAIR's Super Air Knife is also available from stock in PVDF (Polyvinylidene Fluoride). PVDF offers superior strength and is resistant to UV light, inorganic chemicals. solvents, ozone, weather, fungi, chlorinated hydrocarbons, highly corrosive acids, weak bases and salts. The PVDF Super Air Knife uses PTFE shims, Type 316 Stainless Steel pipe plugs, and Hastelloy® C-276 alloy screws to withstand harsh environments. The PVDF Super Air Knife is suitable for manufacturing processes that involve electroplating, solar cells, lithium ion batteries, transfer of acids and caustic chemicals, brine, solvent recovery, semiconductors,

and medical devices. It can withstand temperatures up to 275°F (135°C).

HASTELLOY is a registered trademark of Havnes International, Inc.




**PVDF Super Air Knives provide** superior corrosion resistance.

#### Super Air Knife Replaces Fan Cooling

The Problem: A manufacturer of automotive electronics had a problem cooling computers as they exited a wave solder machine. In order to be handled and tested, the computers had to first be cooled to 81°F (27°C). Initially, they had tried banks of 6" (152mm) diameter axial fans across the 8' (2.5m) length of the cooling conveyor. It consisted of 16 fans blowing down from the top and 16 fans blowing up from the bottom at 7" (178mm) away from the surface. After traveling the full length of the conveyor with the fans running at full force (a five minute duration), the computers were still 108°F (42°C). Quality control personnel sat with an unacceptable backlog of computers waiting to be tested.

The Solution: The company removed the top and bottom fan banks and replaced them with (3) Model 110012 12" (305mm) Super Air Knives that were evenly spaced across the cooling section. Each Super Air Knife was angled so the computer and heat sink received the constant rush of airflow. With the conveyor at the same speed 1.6 FPM (0.5m/min), and Super Air Knives at only 40 PSIG (2.8 BAR), the computers were cooled to 81°F (27°C) in 90 seconds!



Comment: The laminar airflow of the Super Air Knives was the key to success in this application. Fan cooling could only provide random spikes of air at moderate velocities. The uniform sheet of air from the Super Air Knife quietly swept the heat away within the first 2' (610mm) of the conveyor. Low air consumption and the compact size of the Super Air Knife were an added bonus.












The Problem: A dirty lens can affect the quality of cameras, sensors and lasers. Today's visual inspection systems are highly accurate tools used to monitor dimensions, temperature, finish quality, labeling and much more. These products require clean lenses in order to provide the proper

feedback to operators or other machinery within the process. The laser lens to the left is integral to a laser cleaning operation where a laser is used to clear away debris and provide a fresh surface. The laser cleaning operation in this case was creating debris which flew up and deposited onto the laser lens. Debris on the lens could affect the laser's cleaning quality or become burned upon the lens and create the need for a replacement lens.

The Solution: A Model 110006 6" (152mm) Super Air Knife was installed just above the laser lens to blow air down and across the lens. The sheet of air created an invisible barrier the contaminants could not penetrate and kept them from depositing onto the lens. The quality of the laser cleaning has been consistently good and the need for replacement lenses due to debris deposition has been eliminated.

Comment: An air barrier is a common application for a Super Air Knife and can create a non-contact wiper with little or no obstruction. They have been used in similar applications to prevent debris from getting to many different sensors or cameras, to retain heat within an oven, or to deflect mist from a machine tool.

#### **Bakery Creates Clean Break In Icing**




The Problem: A bakery had a problem applying the icing to their snack cakes. As the baked sponge cakes moved down the conveyor, a continuous ribbon of icing was applied to the individual cakes. Trying to make a clean

break in the icing was next to impossible. Mechanical blades required constant cleaning. Compressed air through a series of holes in drilled pipe used too much air, was noisy and didn't make a clean break in the icing.

The Solution: A Model 110018SS 18" (457mm) Stainless Steel Super Air Knife was installed across the conveyor. A photo eye is used to detect the space between the cakes and turn the compressed air on at the precise moment to apply uniform airflow and velocity against the ribbon of icing, creating a nice, clean break.

Comment: The Stainless Steel Super Air Knife was the best choice for this application. Since there was no contact with the icing, no additional cleaning was required. The laminar flow of the Super Air Knife has uniform velocity across the entire length and broke the ribbon of icing evenly. This would never have been possible with the spikes of air from a drilled pipe, nozzles or a blower.

# **Smoke Containment During Engine Test**



The Problem: The last step in an engine assembly process is "burn-in" on a test stand. Each engine is connected to a dynamometer and run for a period of one to five minutes. Residual machining oil on the head produced smoke during the test, and the vent hood at the top of the stand had insufficient capacity to contain it.

The Solution: A Model 110024 24" (610mm) Super Air Knife was mounted on both sides of the test stand. The sheet or "wall" of air produced by the Super Air Knife, captured, contained and diluted the smoke while directing it towards the vent hood. The environmental problem was solved without obstructing the technician's observation of, or access to the stand.

Comment: The use of the Super Air Knife for containment and separation is becoming increasingly common. The advantage, as illustrated here, is the ability of the Super Air Knife to create a screen or barrier with no obstruction. Other typical applications in this mode are:

- · Retaining heat in curing and drying ovens
- · Protecting workers from coolant splatter
- · Isolating industrial camera lenses from airborne contaminants

#### **Drying Crates Following** a Washing Operation

The Problem: A bottling plant places their filled bottles into plastic crates as a final step of their process. When the empty plastic crates are returned from the various retail markets, they must first be washed and sanitized prior to using them again. When the bottler put the crates through the washer, they exited the final rinse dripping wet. Bottles placed in the wet crates were eventually covered with water spots and many product labels were ruined.

The Solution: The company installed (3) Model 110018 18" (457mm) Super Air Knives to completely surround and blowoff the crates. Each Super Air Knife was placed on an angle with the sheet of air blowing against the travel of the crates and directing the water downward toward the floor. The crates were dried and the bottles could be loaded immediately.

Comment: Super Air Knives were the best choice for this application. The uniform sheet of laminar airflow provided complete coverage so there were no dead spots



Three Model 110018 18" (457mm) Super Air Knives completely surround and blowoff crates so they can be loaded immediately.

when blowing across the inside and outside surfaces of the crate. The mounting used made it easy to rearrange and adjust the Super Air Knife depending on the size of the crate. Other companies have used a similar arrangement of the Super Air Knives to blowoff car batteries, blocks of cheese, milk cartons, buckets, and more.











#### Universal Air Knife Mounting System

#### **Provide Precise Positioning For Your Air Knife!**

The Model 9060 Universal Air Knife Mounting System is used to provide secure, precise positioning for any of the EXAIR Air Knives. The Air Knife can quickly and easily be moved within close proximity of the part to improve effectiveness. It can be mounted on the top or bottom of most Air Knives (Super, Standard and Full-Flow Air Knives). The Mounting System has a durable, stainless steel construction that is suitable for a variety of industrial applications.

The mounting system can also be used with EXAIR Static Eliminators. For the Gen4 Super Ion Air Knife, it can be mounted on the top. Bottom mounting is possible on Gen4 Super Ion Air Knives that are 18" or longer. For the Gen4 Standard Ion Air Knife, it can be top mounted on any length. Bottom mounting is possible on Gen4 Standard Ion Air Knives that are 9" or longer.



Model 9060 Universal Air Knife Mounting System

Air Knife Mounting System					
Model #	Description				
9060	Universal Air Knife Mounting System				

The Mounting System can be articulated into any position and provides a maximum extension of 30". A 1/2" diameter hole is required for mounting. Alternatively, the bolt can be threaded directly into a 1/2"-13 tapped hole. For any style Air Knife that is 24" to 54", use (2) Universal Air Knife Mounting Systems. For knives 55" - 71", use (3). For 72" - 95", use (4). For knives 96" and over, use (5).

#### Air Knife Plumbing Kits

Super Air Knives that are 24" or longer must be supplied with compressed air at multiple inlets on the Air Knife. EXAIR's Air Knife Plumbing Kits make it easy to ensure proper airflow to each inlet. They provide properly sized compressed air hose or pipe and fittings to interconnect the bottom or end compressed air inlets for best performance. Plumbing kits for aluminum Super Air Knives include a pressure gauge to monitor pressure at the Super Air Knife, which is an indication of proper air supply. They also include nitrile/PVC hose and brass fittings. Plumbing kits for stainless steel Super Air Knives include cut to length type 316 stainless steel pipe and fittings and will also work on PVDF Super Air Knives.



Model 9076, 9077, 9078 and 9079 Plumbing Kits work with Aluminum Super Air Knives and provide the hose and fittings to couple the inlets for best performance.

Plumbing Kits for Aluminum Super Air Knives						
Model #	Description					
9076	Air Knife Plumbing Kit - for lengths up to 42" (1067mm)					
9077	Air Knife Plumbing Kit - for lengths 48" - 54" (1219 - 1372mm)					
9078	Air Knife Plumbing Kit - for lengths 60" - 84" (1524 - 2134mm)					
9079	Air Knife Plumbing Kit - for lengths 90" - 108" (2286 - 2743mm)					



Stainless Steel Plumbing Kits work with Stainless Steel Super Air Knives and provide the pipe and fittings to couple the inlets for best performance.

Model #	Description	Model #	Description
9240	For 24" (610mm) length	9246	For 60" (1524mm) length
9241	For 30" (762mm) length	9247	For 72" (1829mm) length
9242	For 36" (914mm) length	9248	For 84" (2134mm) length
9243	For 42" (1067mm) length	9249	For 96" (2438mm) length
9244	For 48* (1219mm) length	9250	For 108' (2743mm) length
9245	For 54" (1372mm) length		

#### **Coupling Bracket Kits**

Some applications require a Super Air Knife that is longer than our 108" (2743mm) length. Coupling Bracket Kits that join two Super Air Knives together are available. The kit includes two rigid plates along with the assembly screws. The bottom plate is supplied with a hole to access the bottom compressed air inlets. All models include stainless steel screws.



The Model 110900 Coupling Bracket Kit is used to join two aluminum Super Air Knives.

Model #	Description
110900	Aluminum Coupling Bracket Kit
11090055	Type 303 Stainless Steel Coupling Bracket Kit
11090055-316	Type 316 Stainless Steel Coupling Bracket Kit









#### **Super Air Knife**

#### **Aluminum Super Air Knife Dimensions**











#### Type 303 and 316 Stainless Steel **Super Air Knife Dimensions**







# **PVDF Super Air Knife**





Airflow Length	Aluminum Model	Type 303SS Model	Type 316SS Model	PVDF Model
3" (76mm)	110203	11020355	11020355-316	110203-PVD
6" (152mm)	110206	11020655	110206SS-316	110206-PVD
9" (229mm)	110209	11020955	11020955-316	110209-PVD
12" (305mm)	110212	11021255	11021255-316	110212-PVDI
18" (457mm)	110218	11021855	11021855-316	110218-PVD
24" (610mm)	110224	11022455	11022455-316	110224-PVD
30" (762mm)	110230	11023055	11023055-316	110230-PVD
36" (914mm)	110236	11023655	110236SS-316	110236-PVD
42" (1067mm)	110242	11024255	11024255-316	110242-PVDI
48" (1219mm)	110248	11024855	110248SS-316	110248-PVD
54" (1372mm)	110254	11025455	11025455-316	110254-PVD
60° (1524mm)	110260	11026055	110260SS-316	N/A
72" (1829mm)	110272	11027255	11027255-316	N/A
84" (2134mm)	110284	11028455	110284SS-316	N/A
96" (2438mm)	110296	11029655	110296SS-316	N/A
108" (2743mm)	1102108	110210855	110210855-316	N/A

#### **Deluxe Super Air Knife Kits** Kits include a Super Air Knife, EFC, Universal Mounting System, shim set, filter separator and

	Airflow Length	Aluminum Model	Type 303SS Model	Type 316SS Model
	3° (76mm)	110203DX	110203SSDX	110203SSDX-316
	6" (152mm)	110206DX	11020655DX	110206SSDX-316
	9" (229mm)	110209DX	110209SSDX	1102095SDX-316
	12" (305mm)	110212DX	110212SSDX	1102125SDX-316
	18" (457mm)	110218DX	110218SSDX	1102185SDX-316
	24" (610mm)	110224DX	110224SSDX	110224SSDX-316
	30* (762mm)	110230DX	110230SSDX	1102305SDX-316
	36" (914mm)	110236DX	110236SSDX	110236SSDX-316
	42" (1067mm)	110242DX	1102425SDX	1102425SDX-316
	48" (1219mm)	110248DX	110248SSDX	110248SSDX-316
1	54" (1372mm)	110254DX	110254SSDX	110254SSDX-316
	407 (4534)	HODGODY	4400C0CCDW	ALONGOCCOM DAG

110272DX

110284DX

1102108DX





11027255DX

110284SSDX

1102108SSDX



110272SSDX-316

110284SSDX-316

1102108SSDX-316





Model

N/A

N/A

N/A

N/A

NI/A

N/A

N/A

N/A

N/A

N/A

N/A

N/A

N/A

**Dimensions** 

72" (1829mm)

84" (2134mm)

108" (2743mm)

#### Super Air Knife Shim Sets Green color and .004" (0.10mm) thick Tan color plastic shim. A Red color .002" (0.05mm) thick shim comes installed in the Super Air Knife. Shim sets for stainless steel Super Air Knives include (3) .002" (0.05mm) thick stainless steel shims. PVDF Super Air Knife shim sets include (3) .002" (0.05mm)

Airflow Length	Aluminum Model	Type 303SS Model	Type 316SS Model	PVDF Model
3" (76mm)	110303	11030355	1103035S-316	110303-PVDF
6" (152mm)	110306	110306SS	110306SS-316	110306-PVDF
9" (229mm)	110309	11030955	11030955-316	110309-PVDF
12" (305mm)	110312	11031255	11031255-316	110312-PVDF
18" (457mm)	110318	11031855	11031855-316	110318-PVDF
24" (610mm)	110324	11032455	11032455-316	110324-PVDF
30" (762mm)	110330	11033055	11033055-316	110330-PVDF
36" (914mm)	110336	11033655	11033655-316	110336-PVDF
42" (1067mm)	110342	11034255	11034255-316	110342-PVDF
48° (1219mm)	110348	11034855	11034855-316	110348-PVDF
54" (1372mm)	110354	11035455	11035455-316	110354-PVDF
50" (1524mm)	110360	11036055	110360SS-316	N/A
72" (1829mm)	110372	11037255	11037255-316	N/A
84" (2134mm)	110384	11038455	11038455-316	N/A
96" (2438mm)	110396	11039655	11039655-316	N/A
08" (2743mm)	1103108	110310855	11031085S-316	N/A



Force and flow can be increased by installing additional shims that open the air gap.

Special length Super Air Knives are available. Magnetic bases with Stay Set™ flexible hoses are also available for smaller Super Air Knives. Please contact our factory.

#### Super Air Knives with Plumbing Kits Installed



EXAIR offers Super Air Knives in lengths from 24" (610mm) through 108" (2743mm) with Plumbing Kits that are shipped fully assembled. All components have been properly sized to obtain the best performance from the Super Air Knife.

uper Air Knife with	Plumbing Kit installe	ed.	
Airflow Length	Aluminum Model	Type 303SS Model	Type 316SS Model
24" (610mm)	110024PKI	110024SSPKI	110024SS-316PKI
30° (762mm)	110030PKI	110030SSPKI	110030SS-316PKI
36" (914mm)	110036PKI	110036SSPKI	110036SS-316PKI
42" (1067mm)	110042PKI	110042SSPKI	11004255-316PKI
48" (1219mm)	110048PKI	110048SSPKI	1100485S-316PKI
54" (1372mm)	110054PKI	110054SSPKI	110054SS-316PKI
60" (1524mm)	110060PKI	110060SSPKI	1100605S-316PKI
72" (1829mm)	110072PKI	110072SSPKI	110072SS-316PKI
84" (2134mm)	110084PKI	110084SSPKI	11008455-316PKI
96" (2438mm)	110096PKI	110096SSPKI	110096SS-316PKI
108" (2743mm)	1100108PKI	1100108SSPKI	1100108SS-316PK

uper Air Knife Kit wi	th Plumbing Kit inst	alled.	
Airflow Length	Aluminum Model	Type 303SS Model	Type 316SS Model
24" (610mm)	110224PKI	110224SSPKI	11022455-316PKI
30" (762mm)	110230PKI	110230SSPKI	1102305S-316PK
36" (914mm)	110236PKI	11023655PKI	110236SS-316PKI
42" (1067mm)	110242PKI	110242SSPKI	110242SS-316PKI
48" (1219mm)	110248PKI	110248SSPKI	1102485S-316PKI
54" (1372mm)	110254PKI	110254SSPKI	11025455-316PKI
60" (1524mm)	110260PKI	110260SSPKI	1102605S-316PK
72" (1829mm)	110272PKI	110272SSPKI	1102725S-316PK
84" (2134mm)	110284PKI	110284SSPKI	110284SS-316PKI
96" (2438mm)	110296PKI	110296SSPKI	110296SS-316PKI
108" (2743mm)	1102108PKI	110210855PKI	110210855-316PK

#### EXAIR

#### **Super Air Knife**

	Accessories							
Model #	Description	Model #	Description					
9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)	9067	Pressure Regulator, 1-1/4 NPT, 700 SCFM (19,822 SLPM)					
9032	Auto Drain Filter Separator, 1/2 NPT, 90 SCFM (2,549 SLPM)	9020	Solenoid Valve, 120V, 50/60Hz, 1/4 NPT, 40 SCFM (1,133 SLPM)					
9002	Auto Drain Filter Separator, 3/4 NPT, 220 SCFM (6,230 SLPM)	9034	NEMA 4/4X Solenoid Valve, 120V, 50/60Hz, 1/2 NPT, 100 SCFM					
9066	Auto Drain Filter Separator, 1-1/4 NPT, 400 SCFM (11,327 SLPM)		(2,832 SLPM)					
9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)	9036	NEMA 4/4X Solenoid Valve, 120V, 50/60Hz, 3/4 NPT, 200 SCFM (5.664 SLPM)					
9006	Oil Removal Filter, 3/4 NPT, 50-150 SCFM (1,416-4,248 SLPM)	9065	NEMA 4/4X Solenoid Valve, 24VDC, 1 NPT, 350 SCFM (9,911 SLPM)					
9010	Oil Removal Filter, 1-1/2 NPT, 130-310 SCFM (3,679-8,773 SLPM)	9060	Universal Air Knife Mounting System					
9008	Pressure Regulator, 1/4 NPT, 50 SCFM (1,416 SLPM)	110900	Aluminum Coupling Bracket Kit					
9033	Pressure Regulator, 1/2 NPT, 100 SCFM (2,832 SLPM)	11090055	Type 303 Stainless Steel Coupling Bracket Kit					
9009	Pressure Regulator, 3/4 NPT, 220 SCFM (6,230 SLPM)	110900SS-316	Type 316 Stainless Steel Coupling Bracket Kit					



**EXAIR's Universal Air Knife Mounting** System allows for easy positioning of all EXAIR Air Knives. See page 29 for details.



EXAIR's Plumbing Kits provide properly sized compressed air hose or pipe, and fittings to eliminate pressure loss and provide peak performance. See page 29 and 31 for details.

#### Which Air Knife Is Best For Your Application?

EXAIR manufactures the Super Air Knife, Standard Air Knife and Full-Flow Air Knife. The table below provides a quick comparison of the three styles.

The Super Air Knife provides the best performance with a 40:1 air amplification ratio, making it the most efficient. It is the best choice for all applications. The Super Air Knife has a laminar airstream that is uniform, forceful and quiet. Velocity is the highest of all three air knives. Air consumption is lowest of all three air knives. Compressed air inlets are provided on each end and on the bottom. Multiple Super Air Knives can be mounted "end to end" for longer lengths of uninterrupted airflow.

The Standard Air Knife provides good performance with a 30:1 air amplification ratio that is less efficient than the Super Air Knife. It is a good choice when a less expensive alternative is required. The Standard Air Knife has an airflow that is also uniform and forceful. It is louder and uses more compressed air than the Super Air Knife. Compressed air inlets are provided on each end. Overall length is 1" (25mm) longer than the airflow length.

The Full-Flow Air Knife provides good performance with a 30:1 air amplification ratio. The Full-Flow Air Knife is the least expensive and is a good choice for tight spaces. Force is less than the other two styles. Air consumption and sound level falls between that of the Super Air Knife and the Standard Air Knife. Compressed air inlet(s) are provided on the rear. Inlets are available on each end at a small additional charge, however they are not recommended for applications where uniform flow across the length is required.

	Air Consumption		ir Consumption Velocity		Force per Inch (25mm)		Sound Level	Amp.
	SCFM	SLPM	FPM	M/S	Ozs	Grams	dBA	RATIO
6" (152mm) Super Air Knife	17.4	492	11,800	59.9	2.5	71	69	40:1
6" (152mm) Standard Air Knife	20.4	577	11,000	55.9	2.7	77	83	30:1
6" (152mm) Full-Flow Air Knife	18.6	526	10,000	50.8	2.3	65	80	30:1

ocity and force measured at 6" (152mm) from target. Sound level measured at 3' (914mm). measurements taken at 80 PSIG (5.5 BAR).





Super Air Knife (shown left) Standard Air Knife (shown middle) Full-Flow Air Knife (shown right)

#### Super Air Knife

- Best choice for all applications
- Lowest operating cost
- · Highest efficiency (saves most air)
- Quietest
- 40:1 air amplification ratio
- · Compressed air inlets on each end
- · Airflow length and overall length are

#### Standard Air Knife

- · Good choice, lower purchase price
- · Highest operating cost of the three
- · Good velocity
- Higher dBA rating
- · Compressed air inlets on each end
- · Overall length is 1" (25mm) longer than the airflow length

#### **Full-Flow Air Knife**

#### Good choice, lowest purchase price

- Higher operating cost than the Super Air Knife
- Smallest size
- · Airflow length and overall length are











#### Standard Air Knife

# Standard Air Knife™

Hard hitting curtain of air for web, sheet and part blowoff.



A quiet, energy efficient way to clean, dry or cool parts, webs or conveyors. The Standard Air Knife utilizes the Coanda effect (wall attachment of a high velocity fluid) to create air motion in its surroundings. Using a small amount of compressed air as a power source, the Standard Air Knife pulls in large volumes of surrounding air to produce a high flow, high velocity curtain of air for blowoff.

#### Why The Standard Air Knife?

Amplification ratios (entrained air to compressed air) of 30:1 are achieved with the Standard Air Knife, compared to 3:1 for drilled or slotted pipe. Air savings of 40% to 90% are possible when replacing these "homemade" blowoff devices. Pay-back is normally measured in weeks, not months or years.

The Standard Air Knife dramatically reduces "wind shear" by gradually introducing the entrained air to the ejected compressed air. Noise level is typically cut in half. The result is a high velocity, high volume sheet of air with reduced noise level and air consumption.

Drilled pipe or open jets, by contrast, provide minimal air amplification. They also produce unacceptably high noise levels as the compressed air shears into the still air.

#### **Applications**

- · Part drying after wash
- · Sheet cleaning in strip mills
- Conveyor cleaning
- · Web drying or cleaning
- · Part or component cooling
- · Environmental separation
- · Pre-paint blowoff
- · Bag opening/fill operations

#### Advantages

- · Up to 10 dBA noise reduction
- · Reduced air consumption
- · 30:1 air amplification
- · Aluminum or stainless steel
- · Compact, rugged, easy to install
- Stock lengths to 48" (1219mm)
- No moving parts
- · Compressed air inlets on each end
- Scrap removal on converting operations · Variable force and flow





SCAN & WATCH the video

https://exair.co/04-stdakv



(3) Model 2012 12" (305mm) Standard Air Knives perform the drying cycle in this parts washer.




A Model 2012 12" (305mm) Standard Air Knife opens mustard packets prior to fill.



#### Standard Air Knife


#### **How The Standard Air Knife Works**



Compressed air flows through the inlet (1) into a plenum chamber. It is then throttled through a thin nozzle (2) extending the length of the Standard Air Knife. This primary airstream adheres to the Coanda profile (3), which turns it 90° and directs the flow down the face of the unit. The primary stream immediately begins to entrain surrounding air (4), for an amplification ratio of 30:1 at 6" (152mm) away.



A Model 2006 6" (152mm) Standard Air Knife blows powder loose from a belt so it can be vacuumed away.



Kits include a Standard Air Knife, shim set, filter separator, and pressure regulator (with coupler).

#### Standard Air Knife Specifications

The Standard Air Knife is available in ten standard lengths of 3", 6", 9", 12", 18", 24", 30", 36", 42" and 48" (76, 152, 229, 305, 457, 610, 762, 914, 1067 and 1219mm). This measurement refers to the airflow length. The overall length is 1" (25mm) longer. Special lengths up to 48" (1219mm) are available. Any number of Standard Air Knives may be installed across a given area.

Compressed Air Inlets: A Standard Air Knife has compressed air inlets on each end. Lengths 24" (610mm) and longer should be supplied with compressed air at each end to maintain uniform airflow.

Filtration: The use of clean air is essential. Kits include an automatic drain filter with a 5 micron filter element that is sized properly for flow.

Materials of Construction: The Standard Air Knife is available in either aluminum or stainless steel construction.

Mounting: See page 29 for complete details on the Universal Air Knife Mounting System. The Standard Air Knife can also be supported by the compressed air pipe.

Regulation: A pressure regulator on the compressed air supply provides infinite control of flow, force, and air consumption. Kits include a pressure regulator that is sized properly for flow.

Shim Sets: A Standard Air Knife has a .002" (0.05mm) gap setting. This gap is set with a shim positioned between the cap and body of the Standard Air Knife. Force and flow through the Standard Air Knife may be easily increased by adding shims to open the gap. Standard Air Knife Kits include a shim set (three additional shims). Shim sets for aluminum Standard Air Knives include a .001" (0.03mm) Amber color [10], .003" (0.08mm) Green color [10], and .004" (0.10mm) thick Tan color plastic shims. Shim sets for stainless steel Standard Air Knives include (3) .002" (0.05mm) thick stainless steel shims.

#### Standard Air Knife Performance with 002" (0.05mm) thick shim installed

	sure oply	Air Consumption	per Inch (25mm)	Velocit (152mm) fr		Sound Level @ 3' (914mm)		inch (25mm) n) from targe
PSIG	BAR	SCFM	SLPM	FPM	M/S	dBA	Ozs	Grams
20	1.4	1.3	37	4,000	20.3	65	0.45	13
40	2.8	2.0	57	5,800	29.5	74	1.1	31
60	4.1	2.7	76	8,500	43.2	80	2.0	57
80	5.5	3.4	96	11,000	55.9	83	2.7	77
100	60	41	116	12 000	66.0	96	2.2	0.4

12" (305mm) Standard Air Knife tested













#### Standard Air Knife

#### **Standard Air Knife Dimensions**









## **Universal Air Knife Mounting System**

EXAIR's Universal Air Knife Mounting System allows for easy positioning of all EXAIR Air Knives. See page 29 for details.

Special length Standard Air Knives are available. Magnetic bases with Stay Set™ flexible hoses are also available for smaller Standard Air Knives. Please contact our factory.



Airflow Length	Aluminum Model	Type 303SS Model
3" (76mm)	2003	200355
6" (152mm)	2006	200655
9" (229mm)	2009	200955
12" (305mm)	2012	201255
18" (457mm)	2018	201855
24" (610mm)	2024	202455
30° (762mm)	2030	203055
36" (914mm)	2036	203655
42" (1067mm)	2042	204255
48" (1219mm)	2048	204855

Stan	dard Air Knife	e Kits
Kits include a Star separator and pre		
Airflow Length	Aluminum Model	Type 30355 Model
3" (76mm)	2203	220355
6" (152mm)	2206	220655
9" (229mm)	2209	220955
12" (305mm)	2212	221255
18" (457mm)	2218	221855
24" (610mm)	2224	222455
30" (762mm)	2230	223055
36" (914mm)	2236	223655
42" (1067mm)	2242	224255
48" (1219mm)	2248	224855

Model #	Description			
9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)			
9032	Auto Drain Filter Separator, 1/2 NPT, 90 SCFM (2,549 SLPM)			
9002	Auto Drain Filter Separator, 3/4 NPT, 220 SCFM (6,230 SLPM)			
9066	Auto Drain Filter Separator, 1-1/4 NPT, 400 SCFM (11,327 SLPM)			
9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)			
9006	Oil Removal Filter, 3/4 NPT, 50-150 SCFM (1,416-4,248 SLPM)			
9010	Oil Removal Filter, 1-1/2 NPT, 130-310 SCFM (3,679-8,773 SLPM)			
9008	Pressure Regulator, 1/4 NPT, 50 SCFM (1,416 SLPM)			
9033	Pressure Regulator, 1/2 NPT, 100 SCFM (2,832 SLPM)			
9009	Pressure Regulator, 3/4 NPT, 220 SCFM (6,230 SLPM)			
9067	Pressure Regulator, 1-1/4 NPT, 700 SCFM (19,822 SLPM)			
9020	Solenoid Valve, 120V, 50/60Hz, 1/4 NPT, 40 SCFM (1,133 SLPM)			
9034	NEMA 4/4X Solenoid Valve, 120V, 50/60Hz, 1/2 NPT, 100 SCFM (2,832 SLPM)			
9036	NEMA 4/4X Solenoid Valve, 120V, 50/60Hz, 3/4 NPT, 200 SCFM (5,664 SLPM)			
9065	NEMA 4/4X Solenoid Valve, 24VDC, 1 NPT, 350 SCFM (9,911 SLPM)			

Accessories

#### **Deluxe Standard Air Knife Kits** Kits include a Standard Air Knife, EFC, Universal Mounting System, shim set, filter separator and

Airflow Length	Aluminum Model	Type 303SS Model
3" (76mm)	2203DX	2203SSDX
6" (152mm)	2206DX	2206SSDX
9" (229mm)	2209DX	2209SSDX
12" (305mm)	2212DX	2212SSDX
18" (457mm)	2218DX	2218SSDX
24" (610mm)	2224DX	2224SSDX
30" (762mm)	2230DX	2230SSDX
36" (914mm)	2236DX	2236SSDX
42" (1067mm)	2242DX	22425SDX
48" (1219mm)	2248DX	2248SSDX

Standard Air Knife Shim Sets
ihim Sets include (1) each of a .001" (0.03mm), .003" 0.08mm) and .004" (0.10mm) plastic shim. Stainless teel shim sets include (3) .002" (0.05mm) shims.
ACCIDINITISES INCIDED DY IOUR (U.S.SIMILY STIMILS

Airflow Length	Aluminum Model	Type 30355 Model
3" (76mm)	2303	230355
6" (152mm)	2306	230655
9" (229mm)	2309	230955
12" (305mm)	2312	231255
18" (457mm)	2318	231855
24° (610mm)	2324	232455
30" (762mm)	2330	233055
36" (914mm)	2336	233655
42" (1067mm)	2342	234255
48° (1219mm)	2348	234855

# **Full-Flow Air Knife**

# **Full-Flow** Air Knife™

This low cost choice provides a curtain of air for blowoff, cleaning, drying and cooling.

# licknite Exam

#### What Is The Full-Flow Air Knife?

EXAIR's Full-Flow Air Knife is an effective way to clean, dry or cool parts, webs or conveyors. It utilizes the Coanda effect to pull



in large volumes of surrounding air, producing a high flow, high velocity curtain of air. The "Full-Flow" provides airflow across the entire length. A 12" (305mm) Full-Flow Air Knife measures 12" (305mm). It has the compressed air inlet(s)

#### **Full-Flow Air Knife Specifications**

The Full-Flow Air Knife is available in eight standard lengths of 3", 6", 9", 12", 18", 24", 30" and 36" (76, 152, 229, 305, 457, 610, 762 and 914mm). Special lengths up to 36" (914mm) and unlimited system lengths are available.

Compressed Air Inlet(s): A Full-Flow Air Knife has the compressed air inlet(s) on the rear. Inlets are available on each end at a small additional charge, however, they are not recommended for applications where uniform airflow across the length is required.


Filtration: The use of clean air is essential. Kits include an automatic drain filter with a 5 micron filter element that is sized properly for flow.

Materials of Construction: The Full-Flow Air Knife is available in either aluminum or stainless steel construction.

Mounting: See page 29 for complete details on the Universal Air Knife Mounting System. The Full-Flow Air Knife can also be supported by the compressed air pipe.

Regulation: A pressure regulator on the compressed air supply provides infinite control of flow, force, and air consumption. Kits include a pressure regulator that is sized properly for flow.

Shim Sets: A Full-Flow Air Knife has a .002" (0.05mm) gap setting. This gap is set with a shim positioned between the cap and body of the Full-Flow Air Knife. Force and flow through the Full-Flow Air Knife may be easily increased by adding shims to open the gap. Kits include a shim set. Shim sets for aluminum Full-Flow Air Knives include a .001" (0.03mm) Amber color , .003" (0.08mm) Green color , and .004" (0.10mm) Tan color plastic shims. Shim sets for stainless steel Full-Flow Air Knives include (1) .002" (0.05mm) thick stainless steel shim.



Kits include a Full-Flow Air Knife, shim set. filter separator and pressure regulator (with coupler).

#### Full-Flow Air Knife Performance with 002" (0.05mm) thick shim installed



Pressure Supply		Air Consumpi (25n		Velocity @ 6" (152mm) from target		Sound Level @ 3' (914mm)	Force per li @ 6" (152mm	nch (25mm) ) from target
PSIG	BAR	SCFM	SLPM	FPM	M/S	dBA	Ozs	Grams
20	1,4	1.1	31	3,000	15.2	64	0.4	- 11
40	2.8	1.8	51	5,000	25.4	72	1.0	28
60	4.1	2,4	68	7,500	38.1	76	1.6	45
80	5.5	3.1	88	10,000	50.8	80	2.3	65
100	6.9	3.8	108	12,000	61.0	83	2.9	82













#### **Full-Flow Air Knife**

Accessories

**Airflow Pattern** 



9" (229mm)

12" (305mm)

18° (457mm)

24" (610mm)

30" (762mm)

36" (914mm)

3" (76mm)

6" (152mm)

9" (229mm)

12" (305mm)

18" (457mm)

24" (610mm)

30" (762mm)

36" (914mm)

2809

2812

2818

2824

2830

2836

Full-Flow Air Knife Shim Sets

Shim Sets include (1) each of a .001" (0.03mm), .003"

(0.08mm) and .004" (0.10mm) plastic shim. Stainless

Steel Shim Sets include (1) .002\* (0.05mm) thick shim.

Aluminum Model

2903

2906

2909

2912

2918

2024

2930

280955

281255

281855

282455

283055

283655

Type 30355

290355

290655

290955

291255


291855

292455

293055

A series of Full-Flow Air Knives "float" lavers of plastic film in the confined space of the machine.

#### **Full-Flow Air Knife Dimensions**



Full-Flow Air Knife Only										
Airflow Length	Aluminum Model	Type 303SS Model								
3" (76mm)	2603	260355								
6" (152mm)	2606	260655								
9" (229mm)	2609	260955								
12" (305mm)	2612	261255								
18" (457mm)	2618	261855								
24" (610mm)	2624	262455								

2630

2636

30" (762mm)

36" (914mm)



263055

263655

#### Deluxe Full-Flow Air Knife Kits Kits include a Full-Flow Air Knife, EFC, Universal Mounting System, shim set, filter separator and

Airflow Length	Aluminum Model	Type 303SS Model
3" (76mm)	2803DX	2803SSDX
6" (152mm)	2806DX	2806SSDX
9" (229mm)	2809DX	2809SSDX
12" (305mm)	2812DX	2812SSDX
18" (457mm)	2818DX	2818SSDX
24" (610mm)	2824DX	2824SSDX
30° (762mm)	2830DX	2830SSDX
36" (914mm)	2836DX	2836SSDX

# Model # Description


T			mount	Description
ne.	O DOWNLOAD		9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)
4	drawings at EXAIR.com		9032	Auto Drain Filter Separator, 1/2 NPT, 90 SCFM (2,549 SLPM)
Aluminum	St	ainless Steel	9002	Auto Drain Filter Separator, 3/4 NPT, 220 SCFM (6,230 SLPM)
25mm 0.2	2" -	32mm 0.28*	9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFI (425-1,048 SLPM)
4	03°		9006	Oil Removal Filter, 3/4 NPT, 50-150 SCI (1,416-4,248 SLPM)
	mm.	25mm	9008	Pressure Regulator, 1/4 NPT, 50 SCFM (1,416 SLPM)
1/4 NPT		1/4 NPT	9033	Pressure Regulator, 1/2 NPT, 100 SCFN (2,832 SLPM)
Full	-Flow Air Kni	ife Kits	9009	Pressure Regulator, 3/4 NPT, 220 SCFN (6,230 SLPM)
	ull-Flow Air Knife,		9020	Solenoid Valve, 120V, 50/60Hz, 1/4 NP 40 SCFM (1,133 SLPM)
Airflow	ressure regulator Aluminum	Type 30355	9034	NEMA 4/4X Solenoid Valve, 120V, 50/6 1/2 NPT, 100 SCFM (2,832 SLPM)
Length	Model	Model	9036	NEMA 4/4X Solenoid Valve, 120V, 50/6 3/4 NPT, 200 SCFM (5,664 SLPM)
3" (76mm) 6" (152mm)	2803 2806	2803SS 2806SS	9065	NEMA 4/4X Solenoid Valve, 24VDC, 1 350 SCFM (9,911 SLPM)
o (rozmin)	2300	200033		220 20 m (State 20 M)

Special length **Full-Flow Air Knives and unlimited** system lengths are available. Magnetic bases with Stay Set™ flexible hoses are also available for smaller Full-Flow Air Knives. Please contact our factory.

Inlets on each end are available at a small charge. This is not recommended if uniform flow is desired. Please contact one of our Application Engineers for details

# **Universal Air Knife Mounting System**







#### **Super Air Wipe**

# Super Air Wipe™


An INTELLIGENT COMPRESSED AIR Product

Blowoff, dry, clean and cool pipe, cable, extruded shapes, hose, and wire!

Split design requires no threading!









EXAIR's Super Air Wipe provides a uniform 360° airstream that is ideal for blowoff, drying, cleaning and cooling of pipe, cable, extruded shapes, hose, wire and more. The split design offers easy clamping around the surface of the material moving through it, eliminating the need for threading. Available from 3/8" (10mm) through 11" (279mm) diameters.

All models include stainless steel screws and shims. Stainless steel wire braided hose is also included on sizes up to 4" (102mm) for added corrosion and heat resistance. Aluminum models are rated for temperatures up to 400°F (204°C) and stainless steel models for temperatures up to 800°F (427°C).





A 3/8" Super Air Wipe uniformly dries a hose as it exits a cooling bath.



The stainless steel Super Air Wipe is ideal for food and pharmaceutical applications.






The split design of the Super Air Wipe unlatches easily to eliminate threading.

#### **Applications**

- · Drying after washing, cleaning, plating or coating
- · Blowoff dust and contaminants
- · Cool hot extruded shapes
- · Uniformly wipe surfaces
- · Dry extruded profiles, rod and medical tubing
- · Eliminate solution carryover no cross contamination
- Blow excess water from automotive door gaskets
- · Remove excess coatings, water and oil
- · Dry tube, hose, wire, fiber optics
- · Minimize solution loss due to drag-out
- Clean paint gun tips
- · Dry screen printed or ink jetted surfaces
- · Clean strips and ribbon

#### Advantages

- Quiet
- Low air consumption
- · Uniform 360° airflow
- · Stainless steel hardware resists corrosion
- Aluminum models for temperatures up to 400°F (204°C) Stainless steel models for temperatures up to 800°F (427°C)
- Stainless steel hose supplied on sizes up to 4" (102mm)
- · No electricity, no moving parts
- · Non-contact no wiper blade
- · Split design compact, rugged, easy to install
- · Lightweight, low profile
- · Tapped holes for mounting
- · Variable force and flow
- · Meets OSHA maximum dead end pressure and noise requirements















#### **Super Air Wipe**



#### **How The Air Wipe Works**

Compressed air flows through an inlet (1) of the Air Wipe into an annular chamber (2). It is then throttled through a small ring nozzle (3) at high velocity. This primary airstream adheres to the Coanda profile (4), which directs it down the angled surface of the Air Wipe. A low pressure area is created at the center (5) inducing a high volume flow of surrounding air into the primary airstream. As the airflow leaves the Air Wipe, it creates a conical 360° ring of air that attaches itself to the surface of the material running through it (6), uniformly wiping the entire surface with the high velocity airflow.



The aluminum Super Air Wipe is available in 11 sizes from stock. The stainless steel Super Air Wipe is available in 5 sizes from stock. Other sizes are available by special order.

#### Why The Super Air Wipe?

Prior to the introduction of the Super Air Wipe, the only way to blowoff, dry, clean and cool cylindrical, round, or extruded surfaces was to use a ring of air nozzles. The high air consumption and noise levels of the nozzles along with inconsistent air velocity often delivered poor results. The Super Air Wipe provides a high volume, high velocity airflow that is uniformly ejected from the 360° of its inner diameter. The airstream attaches itself to the material running through it to effectively wipe, clean or dry surfaces. Velocity can be varied from a "blast" to a "breeze". Air consumption and noise are low.

#### Super Air Wipe Is Easy To Use

There is a 1/4 NPT female inlet on each half of the Super Air Wipe on sizes up to 7" (178mm). Sizes 9" (229mm) and larger include two 1/4 NPT female inlets on each half in order to maintain proper air volume and performance. Aluminum Super Air Wipes up to 4" (102mm) include a brass tee that supplies one half directly and a stainless steel wire braided coupling hose rated at 400°F (204°C) to supply the other half. Stainless steel Super Air Wipes up to 4" (102mm) include a stainless steel tee and a stainless steel wire braided coupling hose rated at 800°F (427°C). Larger sizes should be piped directly.

Tapped holes on the downstream side are provided for permanent mounting if the Super Air Wipe is not held in place with rigid pipe. Coupling brackets that hold each half of the Super Air Wipe together are provided which can be installed or removed quickly if required.

#### **Cooling Extruded Tubing**

The Problem: The extruded product, being hot and pliable, would slump and produce a crooked length of tubing. The customer tried using a series of rollers to support the extrusion until it cooled enough to become stiff. This helped somewhat, but they still experienced slump between rollers. The end product still would not meet customer specifications.

The Solution: Using a Model 2401 1" (25mm) Super Air Wipe positioned between two rollers, the product was cooled enough to maintain rigidity. Adding another set of Air Wipe/rollers, they were able to extrude even faster. Comment: Not only were they able to salvage a \$30,000 order, the increased process speed enabled them to requote the job at a lower price and secure future business from their customer.










#### **Super Air Wipe**

Air Wipe Dimensions



Super	Std		A	В		D
****	2420	in	3.13	1.13	0.38	2.38
2399	2429	mm	79	29	10	60
****	2420	in	3.25	1.13	0.50	2.50
2400, 240055	2430	mm	83	29	13	64
2401 240155	2424	in	3.75	1.13	1	2.95
2401, 240155	2431	mm	95	29	25	75
	Topase T	in	4.75	1.13	2	3.95
2402, 240255	2432	mm	121	29	51	100
	2433	in	5.75	1.13	3	4.95
2403, 240355	2433	mm	146	29	76	126
		in.	6.75	1.13	4	5.95
2404, 240455	2434	mm	172	29	102	151
		in	7.75	1.13	5	6.95
2405	2435	mm	197	29	127	176
		in	8.75	1.13	6	7.95
2406	2436	mm	222	29	152	202
2.022		in	9.75	1.13	7	8.95
2407	2437	mm	248	29	178	227
20020	1	in	11.75	1.13	9	10.95
2409	2439	mm	299	29	229	278
****		in	13.75	1,13	11	12.95
2411	2441	mm	349	29	279	329



The Super Air Wipe eliminates the possibility of smoke during machining by wiping hydraulic oil from the bar stock as it enters

#### Air Wipe Performance

80 PSIG (5.5 BAR)	Air Cons	umption	Sound Level @3' (914mm)
Model #	SCFM	SLPM	dBA
2399, 2429	11.1	314	82
2400, 2400SS, 2430	13.9	394	80
2401, 240155, 2431	19.1	541	80
2402, 240255, 2432	29.5	835	81
2403, 240355, 2433	39.8	1,127	82
2404, 240455, 2434	50.2	1,422	82
2405, 2435	60.6	1,716	82
2406, 2436	71.0	2,010	84
2407, 2437	81.3	2,302	85
2409, 2439	102.1	2,891	87
2411, 2441	122.8	3,477	89

#### **Super Air Wipe Specifications**

The Super Air Wipe is available with throat diameters (I.D.) of 3/8", 1/2", 1", 2", 3", 4", 5", 6", 7", 9", and 11" (10, 13, 25, 51, 76, 102, 127, 152, 178, 229, and 279mm). Special diameters are available. Please contact our factory.

Compressed Air Inlets: The Super Air Wipe has compressed air inlets on each half. Stainless steel wire braided hose is supplied with sizes up to 4" (102mm) that couples the air supply of one half to the other. Sizes 9" (229mm) and larger have two inlets on each half that must be supplied with compressed air to maintain uniform airflow.

Filtration: The use of clean air is essential. Kits include an automatic drain filter separator with a 5 micron filter element that is sized properly for flow.

Materials of Construction: The Super Air Wipe is constructed of aluminum or stainless steel. All models use stainless steel shims and screws. Stainless steel wire braided hose is included with sizes up to 4" (102mm).

Temperature: Aluminum Super Air Wipes are rated for temperatures up to 400°F (204°C). Stainless steel models are rated for temperatures to 800°F (427°C).

Mounting: The Super Air Wipe can be supported by the compressed air supply pipe. Tapped holes (1/4-20) on the downstream side of the Super Air Wipe can also be used

Regulation: A pressure regulator on the compressed air supply provides infinite control of flow, force and air consumption. Kits include a pressure regulator that is sized properly for flow.

Shim Sets: The Super Air Wipe has a .002" (0.05mm) gap setting. The compressed air exhausts through a gap which is set with a stainless steel shim positioned between the cap and body of the Super Air Wipe. Force and flow through the Super Air Wipe may be easily increased by adding shims to open the gap. Kits include a shim set. Shim sets include (2) .002" (0.05mm) thick stainless steel shims.











#### Changing Performance By Adding Shims

The compressed air exhausts through a gap which is set with a shim positioned between the cap and the body of the Super Air Wipe. The Super Air Wipe is shipped with a .002" (0.05mm) thick stainless steel shim installed which works best for most applications. Force and flow may be easily increased by adding shims to open the gap. Increasing the gap opening offers higher velocity and harder hitting force. Air consumption and noise will be slightly higher. Super Air Wipe shim sets include two .002" (0.05mm) stainless steel shims that can be stacked. Shim sets are included with all kits or can be purchased separately.

> Special diameter Super Air Wipes are available. Please contact our factory.



The Super Air Wipe Kit includes a stainless steel shim set, filter separator and pressure regulator (with coupler).

# Standard Air Wipe™

This hard-hitting 360° ring of airflow is the economical way to blowoff, dry, clean, and cool!



#### Super Air Wipe Models

Super Air Wipe Only

Super Air Wipe Kits - include the Super Air Wipe, shim set, filter separator and pressure regulator (with couple Super Air Wipe Shim Sets - include (2) .002" (0.05mm) thick stainless steel shims

I.D.	Aluminum Super Air Wipe Only Model	Aluminum Super Air Wipe Kit Model	Stainless Steel Super Air Wipe Only Model	Stainless Steel Super Air Wipe Kit Model	Super Air Wipe Shim Set Model
3/8" (10mm)	2399	2449	N/A	N/A	234955
1/2" (13mm)	2400	2450	240055	245055	235055
1* (25mm)	2401	2451	240155	245155	235155
2" (51mm)	2402	2452	240255	245255	235255
3" (76mm)	2403	2453	240355	24535S	235355
4° (102mm)	2404	2454	240455	245455	235455
5" (127mm)	2405	2455	N/A	N/A	235555
6" (152mm)	2406	2456	N/A	N/A	235655
7" (178mm)	2407	2457	N/A	N/A	235755
9" (229mm)	2409	2459	N/A	N/A	235955
11° (279mm)	2411	2461	N/A	N/A	236155

	Accessories	
Model#	Description	
9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)	
9032	Auto Drain Filter Separator, 1/2 NPT, 90 SCFM (2,549 SLPM)	
9002	Auto Drain Filter Separator, 3/4 NPT, 220 SCFM (6,230 SLPM)	
9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)	
9006	Oil Removal Filter, 3/4 NPT, 50-150 SCFM (1,416-4,248 SLPM)	
9008	Pressure Regulator, 1/4 NPT, 50 SCFM (1,416 SLPM)	
9033	Pressure Regulator, 1/2 NPT, 100 SCFM (2,832 SLPM)	
9009	Pressure Regulator, 3/4 NPT, 220 SCFM (6,230 SLPM)	
9020	Solenoid Valve, 120V, 50/60Hz, 1/4 NPT, 40 SCFM (1,133 SLPM)	
9034	NEMA 4/4X Solenoid Valve, 120V, 50/60Hz, 1/2 NPT, 100 SCFM (2,832 SLPM)	
9036	NEMA 4/4X Solenoid Valve, 120V, 50/60Hz, 3/4 NPT, 200 SCFM (5,664 SLPM)	



A Model 2404 4" (102mm) Super Air Wipe cleans a steel rod after processing.



The flanged end of an axle is lifted through a Super Air Wipe to blow off chips after machining.



EXAIR's 1/2" Super Air Wipe dries a wire as it exits a cooling bath.

#### What Is The Standard Air Wipe?

EXAIR's Standard Air Wipe provides a uniform 360° airstream that is ideal for blowoff, drying, cleaning and cooling of pipe, cable, extruded shapes, hose and more. The split design offers easy clamping around the surface of the material moving through it, eliminating the need for threading.

#### Why The Standard Air Wipe?

The Standard Air Wipe is a good choice when the added durability of stainless steel screws, shims and hose are not required. The Standard Air Wipe uses coated screws, plastic shims and a general purpose PVC coupling air hose on sizes up to 4" (102mm). The Standard Air Wipe is best suited to applications in non-corrosive environments where temperatures do not exceed 150°F (66°C). The dimensions and performance of this product are the same as that of the Super Air Wipe which is detailed on page 40.



The Standard Air Wipe removes liquid from a plastic rod.

#### Standard Air Wipe Specifications

The Standard Air Wipe is available with throat diameters (I.D.) of 3/8", 1/2", 1", 2", 3", 4", 5", 6", 7", 9", and 11" (10, 13, 25, 51, 76, 102, 127, 152, 178, 229, and 279mm). Special diameters are available. Contact our factory.

Compressed Air Inlets: The Standard Air Wipe has compressed air inlets on each half. General purpose compressed air hose is supplied with sizes up to 4" (102mm) that couples the air supply of one half to the other. Sizes 9" (229mm) and larger have two inlets on each half that must be supplied with compressed air to maintain uniform airflow.

Filtration: The use of clean air is essential. Kits include an automatic drain filter with a 5 micron filter element that is sized properly for flow.

Materials of Construction: The Standard Air Wipe is constructed of aluminum. All models use coated screws and plastic shims. General purpose PVC air hose is included with sizes up to 4" (102mm).

Temperature: The Standard Air Wipe is rated for temperatures up to 150°F (66°C).

Mounting: The Standard Air Wipe can be supported by the compressed air supply pipe. Tapped holes (1/4-20) on the downstream side of the Standard Air Wipe can also be used for mounting.

Regulation: A pressure regulator on the compressed air supply provides infinite control of flow, force and air consumption. Kits include a pressure regulator that is sized properly for flow.

Shim Sets: The Standard Air Wipe has a .002" (0.05mm) gap setting. The compressed air exhausts through a gap which is set with a plastic shim positioned between the cap and body of the Standard Air Wipe. Force and flow through the Standard Air Wipe may be easily increased by adding shims to open the gap. Kits include a shim set (three additional shims). Shim sets include two .001" (0.03mm) Amber color 1 , .003" (0.08mm), Green color , and .004" (0.10mm) thick Tan color plastic shims.









#### **Standard Air Wipe**

The Standard Air Wipe Kit includes

a shim set, filter

pressure regulator

separator and

(with coupler).

#### Changing Performance By Adding Shims

The compressed air exhausts through a gap which is set with a shim positioned between the cap and the body of the Standard Air Wipe. It is shipped with a .002" (0.05mm) thick plastic shim installed which works best for most applications. Force and flow may be easily increased by adding shims to open the gap. Increasing the gap opening offers higher velocity and harder hitting force. Air consumption and noise will be slightly higher. Air Wipe shim sets are available that include two each of a .001" (0.03mm) Amber color , .003" (0.08mm) Green color , and .004" (0.10mm) thick Tan color plastic shims. Shim sets are included with all kits or may be purchased separately.



A Model 2431 1" (25mm) Standard Air Wipe blows off the excess coating from a wire into a dip tank.



Standard Air Wipe Models

Air Wipe Kit

2479

2480

2481

2482

2483

2484

2485

2486

2487

Standard Air Wipe Only Standard Air Wipe Kits - include the Standard Air Wipe, shim set, filter

separator and pressure regulator (with coupler).

Standard Air Wipe Shim Sets - include (2) each of a .001" (0.03mm),

Air Wipe Only Model

2420

2430

2431

2432

2433

2434

2435

2436

2439

2441

The Standard Air Wipe blows coolant off the part and back into the centerless arinder.



The Standard Air Wipe is available in sizes from 3/8" (10mm) to 11" (279mm) in diameter.

#### Accessories Model # Description 9001 Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM) Auto Drain Filter Separator, 1/2 NPT, 90 SCFM (2.549 SLPM) Auto Drain Filter Separator, 3/4 NPT, 220 SCFM (6,230 SLPM) 9005 Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM) 9006 Oil Removal Filter, 3/4 NPT, 50-150 SCFM (1.416-4.248 SLPM) Pressure Regulator, 1/4 NPT, 50 SCFM (1,416 SLPM) Pressure Regulator, 1/2 NPT, 100 SCFM (2,832 SLPM) 9033 Pressure Regulator, 3/4 NPT, 220 SCFM (6,230 SLPM) 9020 Solenoid Valve, 120V, 50/60Hz, 1/4 NPT, 40 SCFM (1,133 SLPM) NEMA 4/4X Solenoid Valve, 120V, 50/60Hz, 1/2 NPT,

Special diameter Standard Air Wipes are available. Please contact our factory.

NEMA 4/4X Solenoid Valve, 120V, 50/60Hz, 3/4 NPT, 200 SCFM (5,664 SLPM)

## EXAIR

LD.

3/8" (10mm)

1/2" (13mm)

1" (25mm)

2" (51mm)

3" (76mm)

4" (102mm)

5" (127mm)

6" (152mm)

7" (178mm)

9" (229mm)

11" (279mm)

9036

Air Wipe

Shim Set Model

2349

2350

2351

2352

2353

2354

2355

2356

2357

2359

2361



#### **Air Amplifiers**









# **Air Amplifiers**

An INTELLIGENT OMPRESSED AIR Product

Vent, exhaust, cool, dry, clean with no moving parts!

#### What Are Air Amplifiers?

A simple, low cost way to move air, smoke, fumes, and light materials. Air Amplifiers utilize the Coanda effect, a basic principle of fluid dynamics, to create air motion in their surroundings. Using a small amount of compressed air as their power source, Air Amplifiers pull in large volumes of surrounding air to produce high volume, high velocity outlet flows. Quiet, efficient Air Amplifiers will create output flows up to 25 times their consumption rate.



Air Amplifiers have no moving parts, assuring maintenance-free operation. No electricity is required. Flow, vacuum and velocity are easy to control. Outlet flows are easily adjusted by opening or closing the air gap. Supply air pressure can be regulated to fine tune outlet flow to meet application needs.

Both the vacuum and discharge ends of the Air Amplifier can be ducted, making them ideal for drawing fresh air from another location, or moving smoke and fumes away.







Adjustable Air Amplifiers are ducted to draw clean air for



A series of Model 6042 2" (51mm) Adjustable Air Amplifiers blow coolant off 16 cylinder diesel engines.



A Model 120024 4" (102mm) Super Air Amplifier cools an engine during dynamometer testing.

#### **Applications**

- · Vent welding smoke
- · Cool hot parts
- · Dry wet parts
- · Clean machined parts
- · Distribute heat in molds/ovens
- · Ventilate confined areas
- Dust collection · Exhaust tank fumes

#### Advantages Compared to Fans:

- · Compact, lightweight, portable
- · No electricity
- · No moving parts no maintenance
- · Ends are easily ducted
- · Instant on/off
- · Variable force and flow
- No RF interference

#### **Compared to Venturis** and Ejectors:

- · More air volume with lower compressed air consumption
- · Higher flow amplification
- · No internal obstructions
- · Meets OSHA pressure and noise requirements
- Quiet










#### **Air Amplifiers**



#### Compressed air flows through the air inlet (1) into an annular chamber (2). It is then throttled through a small ring nozzle (3) at high velocity. This primary airstream adheres to the Coanda profile (4), which directs it toward the outlet. A low pressure area is created at the center (5), inducing a high volume flow of surrounding air into the primary airstream. The combined flow of primary and surrounding air exhausts from the Air Amplifier in a high volume, high velocity flow.

#### **Air Amplifier Model Selection Guide**

	Air Amplifier Comparison									
	Efficiency	Sound Level	Mounting Flange	Flow Adjustment	Temp. Rating	Corrosive Applications				
Super Air Amplifier	High	Low	Yes	With Shims	275°F (135°C)	No				
Aluminum Adjustable Air Amplifier	Medium	Variable	No	Infinite (No shims)	275°F (135°C)	No				
Stainless Steel Adjustable Air Amplifier	Medium	Variable	No	Infinite (No shims)	400°F (204°C)	Yes				
High Temperature Air Amplifier	High	Low	No	With Shims	700°F (374°C)	Yes				

#### **Special Air Amplifiers**

EXAIR will manufacture special Air Amplifiers suited to your specific application requirements. The Model 121021 High Temperature Air Amplifier (shown top right) was developed for moving hot air to surfaces requiring uniform heating while in a furnace or oven. Modeled after our Super Air Amplifier, the High Temperature Air Amplifier is the most efficient for pushing high volumes of hot air to points that typically remain cool. This special design is rated for environments up to 700°F (374°C) and its surface is protected from heat stress by a mil-spec. coating process (developed for the aircraft industry), allowing easy disassembly for changing shims or cleaning.

Another stainless steel version for flange mounting was developed as a fan back-up for exhausting flue gases from a furnace (shown middle right). In the event of a power failure, this special Air Amplifier can quickly evacuate the fumes that could be harmful to workers close by.

A PTFE plug was used with a stainless steel Adjustable Air Amplifier (shown bottom right) to help pull a sticky material through a process and prevent the material from depositing on the Air Amplifier.

EXAIR's Intelligent Compressed Air® products can be manufactured to your special requirements.

If you have special requirements, please contact an Application Engineer to discuss your application.



A Model 121021 1-1/4" (32mm) High Temperature Air Amplifier directs hot air to a rotational mold cavity for uniform wall thickness of the plastic part.



This special stainless steel flange-mount Air Amplifier was designed for exhausting hot flue gases from a furnace.



Adjustable Air Amplifier with PTFE plug helped pull a sticky material through a process and prevented the material from depositing on the Air Amplifier.



#### Super Air Amplifiers









# Super Air Amplifier™

#### Powerful, efficient and quiet air mover for blowoff, cooling, and ventilation.



#### What Is The Super Air Amplifier?


EXAIR's Super Air Amplifier has a patented\* design that uses a special shim to maintain critical position of the component parts. As a result, a precise amount of compressed air is released at exact intervals toward the center of the Super Air Amplifier. These jets of air create a constant, high velocity outlet flow across the entire cross-sectional area. Additional free air is pulled through the unit, resulting in higher amplification ratios. The balanced outlet airflow

minimizes wind shear to produce sound levels that are typically three times quieter than other air movers.

Super Air Amplifiers are supplied with a .003" (0.08mm) slotted air gap which is ideal for most applications. Flow and force can be increased by replacing the shim with a thicker .006" (0.15mm) or .009" (0.23mm) shim. Model 120028 is supplied with a .009" (0.23mm) air gap, A .015" (0.39mm) shim is available for Model 120028.

#### Super Air Amplifier Performance at 80 PSIG (5.5 BAR)

				Air Volume at Outlet				
Model #	SCFM	SLPM	RATIO	SCFM	SLPM	SCFM	SLPM	dBA
120020	6.1	173	12	73	2,066	219	6,198	69
120021	8.1	229	18	146	4,132	436	12,339	72
120022	15.5	439	22	341	9,650	1,023	28,951	72
120024	29.2	826	25	730	20,659	2,190	61,977	73
120028	120	3,396	25	3,000	84,900	9,000	254,700	88



Total Output Flow with .003" (0.08mm) thick shim installed. Excludes downstream entrainment, Model 120028 tested with a .009" (0.23mm) shim.

#### **How To Determine Super Air Amplifier Total Output Flow And Air Consumption**

From the performance curves (above), determine total output Total Airflow: flow for any Super Air Amplifier at any pressure.

Example: A Model 120021 at 60 PSIG (4.1 BAR) supply air pressure has a

total output flow of 120 SCFM (3.398 SLPM). Divide the total output flow by the amplification ratio (shown in the chart) Consumption: to determine air consumption for any Super Air Amplifier at any air pressure.

In the example above, the Model 120021 at 60 PSIG (4.1 BAR) supply air pressure has a total output flow of 120 SCFM (3,398 SLPM). Dividing this total output flow by its amplification ratio of 18 gives an air consumption of 6.7 SCFM (189 SLPM).



Model 120022 2" (51mm) Super Air Amplifiers and Model 1122 2" Flat Super Air Nozzles blow off transmissions after they are machined.



(2) Model 120022 2" (51mm) Super Air Amplifiers dry small parts as they move down along a parts conveyor.




(5) Model 120022 2" (51mm) Super Air Amplifiers cool truck pistons.














#### **Super Air Amplifiers**



The Problem: A newly designed transmission pan presented a myriad of cleaning problems for the die-caster. Because the configuration included channels and blind holes as well as smooth surfaces, a "shaped" air pattern was required for proper cleaning. No single blowoff product would fit the need. An assortment of open copper tubes and drilled pipes was considered, but was rejected as too noisy and expensive to operate. A blower was not an option due to the high purchase price, expensive maintenance costs and frequent downtime.

The Solution: With help from our Application Engineers, the company created a cleaning system incorporating a variety of EXAIR blowoff products. (2) Model 6013 High Velocity Air Jets, with their confined airstream,

cleared the blind holes, while (2) Model 120022 2" (51mm) Super Air Amplifiers cleaned the channels. A Model 2012 12" (305mm) Standard Air Knife was positioned to blow out the casting's underside.

Comment: There's no doubt that the casting could have been cleaned just as well by hooking up a bunch of open copper tubes and throwing a ton of air at it. But, at what cost? EXAIR makes a variety of blowoff products because parts come in a variety of shapes and sizes. And, our products operate at a fraction of the air consumption and noise levels associated with open air pipes. When you need to clean, cool, or dry with air, and you'd like to minimize dollars and decibels, EXAIR can help.

Compressed

Air Supply


#### **Super Air Amplifier Cools Iron Castings**

EXAIR

The Problem: A foundry that produces iron castings for the automotive industry had a problem with certain hot parts that slowed their production. After pouring, the castings gradually cool by traveling along a 200 foot long conveyor. At the end, a shake-out conveyor breaks the sand mold so the casting can be removed. Normally, the operator could pick up the part with special gloves and grind the rough edges. However, some castings such as crankshafts, differential housings, and shift parts retained too much heat, making them too hot to handle. The operator had to wait up to ten minutes for them to cool.

The Solution: They installed (5) Model 120022 2" (51mm) Super Air Amplifiers over the shake-out conveyor. The high output airflow from each Super Air Amplifier rapidly cooled the parts without shocking them (no cracks or imperfections from cooling too rapidly). When the part reached the end of the conveyor, the operator could proceed immediately. The backlog was completely eliminated.

Editor's Comment: This manufacturer had almost given up on finding a cooling solution since the fans and blowers that were tried in the past showed little improvement. Our Super Air Amplifier dramatically reduced the cooling time. As a result, they installed them on their second line. The low cost Super Air Amplifiers are compact, portable and have no moving parts to wear out (which is ideal in a dusty foundry). And, the patented design assures the highest output air volumes possible with the lowest air consumption.



(5) Model 120022

Super Air Amplifiers

2" (51mm)

## For Technical Assistance, Call An EXAIR Application Engineer 1-800-903-9247







#### **Super Air Amplifiers**



The Problem: A company that designs major attractions for theme parks created a huge gorilla to startle the patrons. The animators wanted the oversized ape to appear as "lifelike" as possible. To accomplish this, they used a series of motors and cylinders to make the movement of the eyes, hands, arms and torso appear realistic. They also installed a large speaker system to play an audio sample of a loud roar that matched his mammoth size. The finishing touch was to find a way to create a powerful blast of air that smelled like bananas each time the big ape's mouth opened. Attempts using an electrically powered blower proved unsuccessful due to the noise and the inability to obtain an "instant on" blast of air.

The Solution: They installed a tank of banana extract in his tummy and connected it to his mouth with a Model 120028 8" (203mm) Super Air Amplifier. As the spectators moved into position, a sensor activated the electronics, setting "Old Banana Breath" (name given by the designers) into motion. With a swift movement toward the crowd, his mouth opens and the Super Air Amplifier provides an instantaneous blast of high velocity air (filled with banana fumes) at them.

Comment: Why did the engineers select the Super Air Amplifier? First, simplicity. There are no moving parts to wear out or require maintenance. It uses only filtered compressed air as the power source. Second is the big instantaneous blast of high volume, high velocity airflow that couldn't be obtained using a blower or air nozzles. When it comes to special effects, Super Air Amplifiers are the way to go. When you watch the movies or visit the theme parks and see fast moving fog, smoke effects, or objects flying through the air, chances are a Super Air Amplifier is being used.

#### Cleaning Brake Rotors

The Problem: An automotive machine shop that manufactures brake rotors was having problems with chip build-up inside the part. They tried compressed air tubing flattened on their ends with little success. This resulted in high compressed air usage, high sound levels, and danger to their employees.


The Solution: A Model 120021 1-1/4" (32mm) Super Air Amplifier was substituted for the tubing. It provided a larger pattern of air, used less compressed air, the sound level was substantially lower, and it couldn't be dead ended.

Comment: Bent tubing or drilled pipe are inexpensive and easy to make. However, the initial cost is overshadowed by its high energy use; holes can be blocked and noise level is excessive - both of which are OSHA violations. EXAIR's Super Air Amplifiers are compact and dependable since there are no parts to wear out. Our patented design moves the most airflow possible while using the smallest amount of compressed air. The lower sound level was another bonus!





The Problem:








#### **Super Air Amplifiers**


#### **Super Air Amplifier Dimensions**

Mode		A	В	C	D	E	F	G	Н	J	K	L	M
120020	in	0.45	0.75	0.98	1.77	2.28	0.20	0.18	0.53	0.73	2.50	0.59	1/0
120020	mm	11	19	25	45	58	5	5	13	19	64	15	NP
120021	in	0.84	0.94	1.50	2.40	3.03	0.27	0.21	0.75	1.22	2.88	0.59	1/
120021	mm	21	24	38	61	77	7	5	19	31	73	15	NP
120022	in	1.64	1.69	2.95	3.58	4.14	0.27	0.25	0.75	2	3	0.62	3/
120022	mm	42	43	75	91	105	7	6	19	51	76	16	NP
120024	in	3.02	2.81	4.91	6.89	8.42	0.55	0.55	1.75	3.97	4.75	0.94	1/
120024	mm	77	71	125	175	214	14	14	44	101	121	24	NPT
120020	in	6.20	4.50	9	***	11.25	***	****	2.44	8	8.94	2.38	3/4 NPT
120028	mm	157	114	229	1000	286	***	1000	62	203	227	60	




Model 120028

#### **Airflow Pattern**



Mode	1 #	A	В	C	D
120020	in	1.25	2.2	4.1	6
120020	mm	32	56	104	152
120021	in	2	2.9	4.7	6.5
120021	mm	51	74	119	165
120022	in	2.75	3.55	5.15	6.7
120022	mm	70	90	131	171
	in	4.5	5.3	6.9	8.5
120024	mm	114	135	175	216



Super Air Amplifier Only

Super Air Amplifier Kits

include a Super Air Amplifier, shim set, filter separator and pressure regulator (with coupler).

Deluxe Super Air Amplifier Kits -

include a Super Air Amplifier, EFC, shim set, filter separator and pressure regulator (with coupler).

Super Air Amplifier Shim Sets -

include (1) .006" (0.15mm) and (1) .009" (0.23mm) stainless steel shims

(except 8" which include (1) .015" (0.39mm) stainless steel shim)

Outlet Diameter	Super Air Amplifier Only Model	Super Air Amplifier Kit Model	Deluxe Super Air Amplifier Kit Model	High Temperature Air Amplifier Only Model	High Temperature Air Amplifier Kit Model	Super Air Amplifier Shim Set Model
3/4" (19mm)	120020	120220	120220DX	N/A	N/A	120320
1-1/4" (32mm)	120021	120221	120221DX	121021	121221	120321
2" (51mm)	120022	120222	120222DX	N/A	N/A	120322
4" (102mm)	120024	120224	120224DX	N/A	N/A	120324
8" (203mm)	120028	120228	120228DX	N/A	N/A	120328

Model #	Description					
9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)					
9032	Auto Drain Filter Separator, 1/2 NPT, 90 SCFM (2,549 SLPM)					
9002	Auto Drain Filter Separator, 3/4 NPT, 220 SCFM (6,230 SLPM)					
9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)					
9006	Oil Removal Filter, 3/4 NPT, 50-150 SCFM (1,416-4,248 SLPM)					
9008	Pressure Regulator with Gauge, 1/4 NPT, 50 SCFM (1,416 SLPM)					
9033	Pressure Regulator with Gauge, 1/2 NPT, 100 SCFM (2,832 SLPM)					
9009	Pressure Regulator with Gauge, 3/4 NPT, 220 SCFM (6,230 SLPM)					



Kits include a Super Air Amplifier, shim set. filter separator and pressure regulator (with coupler).













#### **Adjustable Air Amplifiers**







# Adjustable Air Amplifier™

# Highly effective air mover that easily

# adjusts to your application!


#### What Is The Adjustable Air Amplifier?

The air gap is infinitely adjustable which regulates the consumption and outlet flow from a "breeze" to a "blast". They are available in aluminum or in stainless steel for food service, higher temperatures (400°F/204°C), and corrosive applications. High Temperature Stainless Steel Air Amplifiers for temperatures up to 700°F (374°C) are also available. Please contact an Application Engineer.

Force and flow for the Adjustable Air Amplifier is changed by turning the exhaust end (with the knurled ring loose) to open or close the continuous air gap. When desired performance is obtained, the knurled ring can be tightened to lock the flow at that setting. In most cases, a .002" to .004" (0.05mm to 0.10mm) air gap is ideal.

#### Adjustable Air Amplifier Performance at 80 PSIG (5.5 BAR)

	Air Cons				olume utlet		olume (52mm)	
Model #	SCFM	SLPM	RATIO	SCFM	SLPM	SCFM	SLPM	dBA
6030, 6040	8.9	252	10	89	2,520	267	7,560	78
6031, 6041	12.9	365	16	206	5,833	618	17,500	81
6032, 6042	21.5	608	20	430	12,176	1,290	36,529	82
6033, 6043	35.2	997	22	774	21,917	2,323	65,780	83
6034, 6044	50	1,416	24	1,200	33,980	3,600	101,941	84



Total Output Flow with .002" (0.05mm) gap setting. Excludes downstream entrainment.

#### **How To Determine Adjustable Air Amplifier Total Output Flow And Air Consumption**

**Total Airflow:** From the performance curves (above), determine total output flow for any Adjustable Air Amplifier at any pressure.

A Model 6031 at 60 PSIG (4.1 BAR) supply air pressure Example: has a total output flow of 165 SCFM (4,672 SLPM).

Air Consumption: Divide total output flow by the amplification ratio (shown in the chart) to determine air consumption

for any Adjustable Air Amplifier at any air pressure. In the example above, the Model 6031 at 60 PSIG (4.1 BAR) supply air pressure has a

total output flow of 165 SCFM (4,672 SLPM). Dividing this total flow by its amplification ratio of 16 gives an air consumption of 10.3 SCFM (292 SLPM).







Model 6042 2" (51mm) Adjustable Air Amplifiers with swivel fittings cool inductively heated axles prior to installing the hubs.



Metal parts are dried using a series of Model 6042 2" (51mm) Adjustable Air Amplifiers.



A series of Adjustable Air Amplifiers dry and cool a large machined casting as it exits a high temperature wash.








#### **Adjustable Air Amplifiers**

#### **Adjustable Air Amplifier Dimensions**







Adjustable Air Amplifiers and High Velocity Air Jets dry an engine block prior to assembly.

**Airflow Pattern** 

18" 457mm -

12" 305mm --

Need

Air Amplifiers.

Swivels?

EXAIR's Swivel Fittings make

it easy to adjust the aim of

See page 68 for details.

# 6040 6041 6032 6033 5 3.02 1.50 1.75 2.13 4.50

#### **Adjustable Air Amplifier Systems**

Adjustable Air Amplifier Only

EXAIR

Adjustable Air Amplifier Kits - include an Adjustable Air Amplifier, filter separator

Deluxe Adjustable Air Amplifier Kits - include an Adjustable Air Amplifier, EFC.

Outlet Diameter	Aluminum Adjustable Air Amplifier Only Model	Aluminum Adjustable Air Amplifier Kit Model	Deluxe Aluminum Adjustable Air Amplifier Kit Model	Stainless Steel Adjustable Air Amplifier Only Model	Stainless Steel Adjustable Air Amplifier Kit Model	Deluxe Stainless Steel Adjustable Air Amplifier Kit Model
3/4" (19mm)	6040	6240	6240DX	6030	6230	6230DX
1-1/4" (32mm)	6041	6241	6241DX	6031	6231	6231DX
2" (51mm)	6042	6242	6242DX	6032	6232	6232DX
3" (76mm)	6043	6243	6243DX	6033	6233	6233DX
4" (102mm)	6044	6244	6244DX	6034	6234	6234DX

Accessories					
Model #	Description				
9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)				
9032	Auto Drain Filter Separator, 1/2 NPT, 90 SCFM (2,549 SLPM)				
9002	Auto Drain Filter Separator, 3/4 NPT, 220 SCFM (6,230 SLPM)				
9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)				
9006	Oil Removal Filter, 3/4 NPT, 50-150 SCFM (1,416-4,248 SLPM)				
9008	Pressure Regulator with Gauge, 1/4 NPT, 50 SCFM (1,416 SLPM)				
9033	Pressure Regulator with Gauge, 1/2 NPT, 100 SCFM (2,832 SLPM)				
9009	Pressure Regulator with Gauge, 3/4 NPT, 220 SCFM (6,230 SLPM)				



5.8

Kits include an Adjustable Air Amplifier, filter separator and pressure regulator (with coupler).

#### FAX (513) 671-3363 \* E-mail: techelp@exair.com \* www.exair.com

#### Air Nozzles and Jets









## Air Nozzles and Jets

An INTELLIGENT OMPRESSED AIR Product

**Engineered Air Nozzles and Jets** reduce noise levels and air costs.

"Go Green" by upgrading your blowoff, cooling and drying operation to the awardwinning Super Air Nozzles!

#### What Are Air Nozzles and Jets?

A simple solution to reduce excessive air consumption and noise levels on compressed air blowoff operations. EXAIR Air Nozzles and Jets produce outlet flows up to 25 times compressed air consumption using a small amount of compressed air as the power source. Many power companies now provide attractive rebates to plants who switch to engineered Super Air Nozzles!

#### Why Air Nozzles and Jets?

Air savings, compared to open copper tubes or pipes commonly used for blowoff, can be as high as 80%. Less compressed air means less noise. The typical noise level reduction is 10 dBA. All EXAIR Air Nozzles and Jets meet Occupational Safety and Health Administration (OSHA) maximum dead end pressure and sound level exposure requirements and carry the CE mark.

An open 1/4" (6mm) copper tube, by contrast, ejects pure compressed air at up to 40 SCFM (1,133 SLPM), the entire output of a 10 horsepower compressor. Annual energy cost can exceed \$1,000 per year. Noise levels in excess of 100 dBA are commonly produced. When supply pressure exceeds 30 PSIG (2 BAR), an open pipe, tube or drilled holes violates OSHA static pressure requirements.





Flexible Stay Set Hoses™ are ideal where frequent repositioning of air nozzles is required.

This PEEK material Atto Super Air Nozzle was chosen because of its non-marring quality for a blowoff application on a

#### **Applications**

- · Part cleaning
- · Chip removal
- · Part drying
- · Liquid blowoff
- · Part cooling
- Material conveying
- · Part ejection
- Fiber conveying
- Air assist

#### Advantages

- · Reduced compressed air cost
- · 10 dBA average noise reduction
- · Conserve compressed air
- · Improved blowoff performance
- Compact
- · Improved safety
- · Meets OSHA noise level requirements
- · Meets OSHA pressure requirements
- · Improved production









#### Air Nozzles and Jets

#### Safe And Efficient Use Of Compressed Air

The inefficient use of compressed air for blowoff applications may create problems due to the energy costs, noise level and potential danger to personnel who are exposed to high pressure air. Open air pipes, copper tubes and drilled pipes are a few of the common abusers. They consume tremendous amounts of energy and often produce noise levels over 100 dBA.

#### Open Air Pipe or Copper Tube



Turbulent compressed air blasts straight out of the pipe or tube. It not only wastes huge amounts of compressed air but also violates OSHA noise and dead end pressure requirements.

#### **Reduce Energy Costs**

The best way to cut energy costs is through proper maintenance and use of the compressed air system. Leaks and dirty filters require maintenance on a regular basis. Energy savings can also be realized when replacing outdated compressor motors and controls with high efficiency models that often pay for themselves in a short period of time.

The most important factor to dramatically boost efficiency is proper use. Using engineered products like EXAIR's Super Air Nozzles can cut operating costs since they use only a fraction of the compressed air of typical blowoffs. In addition, all of the Air Nozzles and Jets shown in this catalog can be cycled on and off with an instantaneous response. EXAIR's EFC (shown on page 7) is an electronic flow control that limits compressed air use by turning on the air only when a part is present.

#### **Reduce Noise Levels**

High noise levels are a common problem for many plants. Compressed air noise often exceeds OSHA noise level exposure requirements, resulting in hearing loss to those working in close proximity. Noisy blowoffs at 80 PSIG (5.5 BAR) that produce noise levels of 100 dBA can be reduced to only 74 dBA when using a Super Air Nozzle. At that pressure, it is still possible to obtain hard-hitting force without the high noise.

OSHA Maximum	Allov	vable	Nois	e Exp	osure		
Hours per day (constant noise)	8	7	4	3	2	1	0.5
Sound level dBA	90	91	95	97	100	105	110

#### **Eliminate Harmful Dead End Pressures**

Air can be dangerous when the outlet pressure of a hole. hose or copper tube is higher than 30 PSIG (2 BAR). In the event the opening is blocked by a hand or other body part, air may enter the bloodstream through the skin, resulting in a serious injury. All of the Air Nozzles and Jets manufactured by EXAIR have been designed for safety. All are safe to be supplied with higher pressure compressed air and meet OSHA Standard 29 CFR 1910.242(b).

#### Air Consumption of Open Tube And Pipe


	ssure Sup	piy			ption of	Homema	ide Blowe	offs
			C	opper Tu	be		Open Pip	e
PSIG	BAR		1/4"	5/16"	3/8*	1/8*	1/4"	3/8"
80	5.5	SCFM	33	58	87	70	140	240
80	5.5	SLPM	934	1,641	2,462	1,981	3,962	6,792

#### Saving Money and Compressed Air

The table above shows the air consumption for typical homemade blowoffs. The pages that follow give the air consumption and other data on EXAIR's

Consider the following example where a Model 1102 Mini Super Air Nozzle replaces an 1/8" open pipe. The compressed air savings is easy to calculate and proves to be dramatic. Payout for Air Nozzles and Jets, including filter and installation cost is measured in weeks - not years, as is the case for other cost reduction equipment. Based on a 40 hour work week, 52 weeks a year.

- 1. Existing blowoff is 1/8" open pipe at 80 PSIG (5.5 BAR) supply. Air consumption, from the table above, is 70 SCFM (1,981 SLPM).
- 2. Use a 1/8 FNPT Model 1102 Mini Super Air Nozzle also at 80 PSIG (5.5 BAR) supply. Air consumption, from the table on page 54, is 10 SCFM (283 SLPM).
- 3. Compressed air saved = 70 10 = 60 SCFM (1,981 283 = 1,698 SLPM)
- 4. For this example, the blowoff is continuous. If the duty cycle was 20%, then air saved would be  $60 \times .2 = 12 \text{ SCFM } (1.698 \times .2 = 340 \text{ SLPM}).$
- 5. Most large plants know their cost per 1,000 standard cubic feet of compressed air (10,000 standard liters). If you don't know your actual cost per 1,000 SCF, \$0.25 is a reasonable average to use. (Cost per 10,000 standard liters is approximately \$0.089.)
- 6. Dollars saved per hour = SCFM saved x 60 minutes x cost/1,000 SCF (SLPM saved x 60 min x cost/10,000 SL) = 60 x 60 x \$0.25/1,000 (= 1,698 x 60 x \$0.089/10,000)
  - = \$0.90/hour
  - = \$0.90/hr. is \$36.00/week and
  - = \$1,872.00/year savings for One nozzle!







#### Air Nozzles











An INTELLIGENT OMPRESSED AIR Product

Air Nozzles use the Coanda effect to amplify compressed airflow up to 25 times or more. As illustrated on the left, compressed air (black arrows) is ejected through a series of nozzles on the outer perimeter. As the air travels along the outer wall of the nozzle, surrounding air (blue arrows) is entrained into the stream. The airstream that results is a high volume, high velocity blast of air at minimal consumption The air is always ejected so it can vent safely, well below OSHA dead end pressure requirements. should the nozzle end be blocked.

#### Selecting The Right Air Nozzle

EXAIR manufactures a wide selection of Air Nozzles and lets, which are divided into two groups. The first group includes Air Nozzles and Jets that deliver force up to 22 ounces (624 grams) and are suitable for most applications. The second group includes Air Nozzles that produce high force up to 23 lbs (10.43 kg) where additional reach and force are required.

- Type 303 Stainless Steel- high temperatures and corrosive environments. Max temp 800°F (426°C)
- · Type 316 Stainless Steel- high temperatures, corrosive
- environments, and mechanical wear. Max temp 1000°F (538°C) • Brass- general purpose applications. Max temp 400°F (204°C)
- · Zinc aluminum alloy- general purpose applications. Max temp 250°F (121°C)
- · PEEK- replaces metals in harsh environments. Offers chemical resistance, non-marring. Max temp 320°F (160°C)

	Air Nozzies And Jets	Comparison (sorted by	compressed a			_			
Model	Material	Description	Inlet	Air Cons	1000000	100000	orce	Sound	More
model		a carription	ex	SCFM	SLPM	Ozs	Grams	dBA	Detai
110855	Stainless Steel - Type 316	Atto Super Air Nozzle	M4 x 0.5	2.5	71	2.0*	57	58	p. 55
1108-PEEK	PEEK (Plastic)	Atto Super Air Nozzle	M4 x 0.5	2.5	71	2.0*	57	58	p. 55
1108SS-NPT	Stainless Steel - Type 316	Atto Super Air Nozzle	1/8 MNPT	2.5	71	2.0*	57	58	p. 5
1108-PEEK-NPT	PEEK (Plastic)	Atto Super Air Nozzle	1/8 MNPT	2.5	71	2.0*	57	58	p. 5
110955	Stainless Steel - Type 316	Pico Super Air Nozzle	M5 x 0.5	4.9	139	5.0*	142	68	p. 5
1109-PEEK	PEEK (Plastic)	Pico Super Air Nozzle	M5 x 0.5	4.9	139	5.0*	142	68	p. 5
1109SS-NPT	Stainless Steel - Type 316	Pico Super Air Nozzle	1/8 MNPT	4.9	139	5.0*	142	68	p. 5
1109-PEEK-NPT	PEEK (Plastic)	Pico Super Air Nozzle	1/8 MNPT	4.9	139	5.0*	142	68	p. 55
111055	Stainless Steel - Type 316	Nano Super Air Nozzle	M6 x 0.75	8.3	235	8.1*	230	75	p. 55
1110-PEEK	PEEK (Plastic)	Nano Super Air Nozzle	M6 x 0.75	8.3	235	8.1*	230	75	p. 55
1110SS-NPT	Stainless Steel - Type 316	Nano Super Air Nozzle	1/8 MNPT	8.3	235	8.1*	230	75	p. 5
1110-PEEK-NPT	PEEK (Plastic)	Nano Super Air Nozzle	1/8 MNPT	8.3	235	8.1*	230	75	p. 5
1001	Brass	Safety Air Nozzle	1/8 FNPT	10	283	9*	255	78	p. 6
1102	Zinc Aluminum alloy	Mini Super Air Nozzle	1/8 FNPT	10	283	9*	255	71	p. 5
1102-PEEK	PEEK (Plastic)	Mini Super Air Nozzle	1/8 FNPT	10	283	9*	255	71	p. 5
110255	Stainless Steel - Type 316	Mini Super Air Nozzle	1/8 FNPT	10	283	9*	255	71	p. 5
1103	Zinc Aluminum alloy	Mini Super Air Nozzle	1/8 MNPT	10	283	9*	255	71	p. 5
110355	Stainless Steel - Type 316	Mini Super Air Nozzle	1/8 MNPT	10	283	9*	255	71	p. 50
1126	Zinc Aluminum alloy	1" Flat Super Air Nozzle	1/8 FNPT	10.5	297	9.81	278	75	p. 57
112655	Stainless Steel - Type 316	1" Flat Super Air Nozzle	1/8 FNPT	10.5	297	9.8†	278	75	p. 5
101055	Stainless Steel - Type 303	Micro Air Nozzle	1/8 MNPT	13	368	12*	340	80	p. 55
1009	Aluminum	Adjustable Air Nozzle	1/8 MNPT	13	368	12**	340	79	p. 60
100955	Stainless Steel - Type 303	Adjustable Air Nozzle	1/8 MNPT	13	368	12**	340	79	p. 6
1100	Zinc Aluminum alloy	Super Air Nozzle	1/4 ENPT	14	396	13*	369	74	p. 5
1100-PEEK	PEEK (Plastic)	Super Air Nozzle	1/4 FNPT	14	396	13*	369	74	p. 50
110055	Stainless Steel - Type 316	Super Air Nozzle	1/4 FNPT	14	396	13*	369	74	p. 56
1101	Zinc Aluminum alloy	Super Air Nozzle	1/4 MNPT	14	396	13*	369	74	p. 5
110155	Stainless Steel - Type 316	Super Air Nozzle	1/4 MNPT	14	396	13*	369	74	p. 56
1002	Brass	Safety Air Nozzle	1/4 FNPT	17	481	16*	454	80	p. 60
100255	Stainless Steel - Type 303	Safety Air Nozzle	1/4 FNPT	17	481	16*	454	80	p. 6
1003	Brass	Safety Air Nozzle	3/8 FNPT	18	509	18*	510	83	p. 6
6019	Brass	Adjustable Air Jet	1/8 MNPT	18	509	16***	454	83	p. 6
601955	Stainless Steel - Type 303	Adjustable Air Jet	1/8 MNPT	18	509	16***	454	83	p. 6
6013	Brass	High Velocity Air Jet	1/8 MNPT	22	622	20†	567	82	p. 6
601355	Stainless Steel - Type 303	High Velocity Air Jet	1/8 MNPT	22	622	20†	567	82	p. 6
1122	Zinc Aluminum alloy	2" Flat Super Air Nozzle	1/4 FNPT	22	622	22†	624	77	p. 5
112255	Stainless Steel - Type 316	2" Flat Super Air Nozzle	1/4 FNPT	22	622	22†	624	77	p. 5
1144	Zinc Aluminum/Steel	2" Super Air Scraper	1/4 FNPT	22	622	22†	624	77	p. 5
100455	Stainless Steel - Type 316	Back Blow Air Nozzle	M4 x 0.5	4.5	127	NA	NA	75	p. 5
100655	Stainless Steel - Type 316	Back Blow Air Nozzle	1/4 FNPT	22	622	NA	NA	80	p. 5

Force measured at 12° (305mm) from target. \*\* Force measured at 12" (305mm) from target with a .008" (0.20mm) factory setting All sound levels measured at 3 feet (914mm)

All measurements taken at 80 PSIG (5.5 BAR)

+ Force measured at 12" (305mm) from target with a .015" (0.38mm) shim installed









#### Atto Super Air Nozzles™

(actual size)

Model 1108SS M4 x 0.5 Material: Type 316 Stainless Steel Model 1108-PEEK M4 x 0.5 Material: PEEK (plastic)



Model 1108SS-NPT 1/8 NPT male Material: Type 316 Stainless Steel Model 1108-PEEK-NPT 1/8 NPT male Material: PEEK (plastic)

#### Model 1108SS, 1108-PEEK, 1108SS-NPT, 1108-PEEK-NPT Atto Super Air Nozzle

EXAIR's Atto Super Air Nozzle delivers the smallest, most precise blowoff. The air pattern for this tiny nozzle is focused, measuring 1.0" in diameter when positioned 6" away from the surface. The 58 dBA noise level is a fraction of ordinary air nozzles.

Air Cons	umption	Fo	rce*	Sound Level	
SCFM	SLPM	Ozs	Grams	dBA	
2.5	71	2.0	57	58	

Force measured at 12" (305mm) from target Sound level measured at 3' (914mm).



## Pico Super Air Nozzles™

(actual size)

Model 1109SS M5 x 0.5 Material: Type 316 Stainless Steel Model 1109-PFFK M5 x 0 5 Material: PEEK (plastic)



Model 1109SS-NPT 1/8 NPT male Material: Type 316 Stainless Steel Model 1109-PEEK-NPT 1/8 NPT male All measurements taken at 80 PSIG (5.5 BAR). MCDUBE

#### Model 1109SS, 1109-PEEK, 1109SS-NPT, 1109-PEEK-NPT Pico Super Air Nozzle

EXAIR's Pico Super Air Nozzle delivers a precise blowoff with a highly focused, forceful blast of airflow. The narrowly focused air pattern measures 1.3" in diameter at 6" away from the surface. The noise level is only 68 dBA.

Air Cons	Air Consumption		rce*	Sound Level	
SCFM	SLPM	Ozs	Grams	dBA	
4.9	139	5.0	142	68	

Force measured at 12" (305mm) from target Sound level measured at 3' (914mm).



#### Nano Super Air Nozzles™



Material: PEEK (plastic)

Model 1110SS M6 x 0.75 Material: Type 316 Stainless Steel Model 1110-PEEK M6 x 0.75 Material: PEEK (plastic)



Model 1110SS-NPT 1/8 NPT male Material: Type 316 Stainless Steel Model 1110-PEEK-NPT 1/8 NPT male Material: PEEK (plastic)

#### Model 1110SS, 1110-PEEK, 1110SS-NPT, 1110-PEEK-NPT Nano Super Air Nozzle

EXAIR's Nano Super Air Nozzle delivers a highly focused, forceful blast of airflow. The air pattern for this small nozzle measures 1.5" in diameter at 6" away from the surface. The noise level is a low 75 dBA. Overall length measures only 0.78".

SCFM	SLPM	Ozs	Grams	dBA	
9.3	235	81	230	75	

Sound level measured at 3' (914mm)

All measurements taken at 80 PSIG (5.5 BAR)



#### Micro Air Nozzle"



Model 1010SS 1/8 NPT male Material: Type 303 Stainless Steel

#### Model 1010SS Micro Air Nozzle

EXAIR's Micro Air Nozzle optimizes entrainment for a directed, high volume, high velocity airflow. The compact size permits mounting where space is limited. Sound level and air consumption are low.


Air Consumption					
SCFM	SLPM	Ozs	Grams	dBA	
13	368	12	340	80	


\* Force measured at 12" (305mm) from target Sound level measured at 3' (914mm). All measurements taken at 80 PSIG (5.5 8AR).


#### The Air Nozzles and Jets shown on pages 55 -61 deliver up to 22 ounces (624 grams) of force. making them suitable for most applications. All models shown use a small amount of compressed air to entrain large volumes of surrounding room air. They have been engineered to provide the best performance with low sound levels and high efficiency.

#### **Dimensions and Airflow Patterns**









#### An INTELLIGENT Product

#### Air Nozzles

#### Mini Super Air Nozzles™



Model 1102 1/8 NPT female Material: Zinc Aluminum alloy Model 1102-PEEK 1/8 NPT female Material: PEEK (plastic) Model 110255 1/8 NPT female Material: Type 316 Stainless Steel

#### Model 1102, 1102-PEEK, 1102SS, 1103 and 1103SS Mini Super Air Nozzles

The 1/8 NPT Mini Super Air Nozzles provide a forceful, concentrated stream of high velocity airflow. It has fewer holes than the larger Super Air Nozzles, resulting in lower sound levels, air consumption and force.


Air Consumption				
SCFM	SLPM	Ozs	Grams	dBA
10	283	9	255	71

Sound level measured at 3' (914mm) All measurements taken at 80 PSIG (5.5 BAR)





#### **Dimensions and Airflow Pattern**



Super Air Nozzles with Stay Set Hoses provide adjustability and precision.

#### Material: Type 316 Stainless Steel Super Air Nozzles™



Model 1103 1/8 NPT male

Material: Zinc Aluminum allov

Model 1103SS 1/8 NPT male

Model 1100 1/4 NPT female Material: Zinc Aluminum alloy Model 1100SS 1/4 NPT female Material: Type 316 Stainless Steel





Model 1101 1/4 NPT male Material: Zinc Aluminum alloy Model 1101SS 1/4 NPT male Material: Type 316 Stainless Steel



The aerodynamic design of the Model 1100 Super Air Nozzle directs air to a single point of

#### Model 1100, 1100SS, 1100-PEEK, 1101 and 1101SS Super Air Nozzles

EXAIR's award winning Super Air Nozzles deliver high performance suitable for a wide range of blowoff, drying and cooling applications. The aerodynamic design of this engineered Super Air Nozzle directs the air to a single point of convergence, delivering hard-hitting force. It dramatically reduces air consumption and, in many cases, can cut the noise level in half. All Super Air Nozzles eject the compressed air through holes located in recessed grooves that cannot be blocked or dead ended.

Air Consumption					
SCFM	SLPM	Ozs	Grams	dBA	
14	396	13	369	74	

Sound level measured at 3' (914mm) All measurements taken at 80 PSIG (5.5 BAR).





# **Dimensions and Airflow Pattern**



Most EXAIR Air Nozzles have a standard hex base making them easy to install with a socket wrench.

#### **Build Your Own System**


EXAIR's Swivel Fittings, available for all our nozzles up to 1 NPT, make it easy to adjust the aim of the Air Nozzles and Jets. Correct placement of the blowing angle can help optimize performance, reduce noise levels and improve efficiency. See page 68 for details.

Swivel Fittings can be added to most EXAIR Nozzles by adding a "W" to the Model#.

1122 (2" Flat Super Air Nozzle) + W (Swivel Fitting)

1122W













# Flat Super Air Nozzles COMPRESSED AND



#### Flat Super Air Nozzles™



Model 1126 1/8 NPT female Material: Zinc Aluminum allov Model 1126SS 1/8 NPT female Material: Type 316 Stainless Steel

Shim sets for the 1" Flat Super Air Nozzles include a .005" (0.13mm), .010" (0.25mm), and .020" (0.51mm)

Stainless Steel 1\* 1136SS Flat Super Air Nozzle Shim Set

Model 1122 1/4 NPT female

thick shim

Material: Zinc Aluminum alloy

Model 1122SS 1/4 NPT female

Material: Type 316 Stainless Steel

Shim sets for the 2" Flat Super Air

Nozzles include a .005" (0.13mm),

1132SS Flat Super Air Nozzle

.010" (0.25mm), and .020" (0.51mm)

Stainless Steel 2"

#### Model 1126, 1126SS, 1122 and 1122SS 1" and 2" Flat Super Air Nozzles

EXAIR's 1" and 2" Flat Super Air Nozzles are highly efficient, unique flat air nozzles. Their patented† design uses a special shim to maintain the critical position of the component parts. A precise amount of air is released through the thin slot, across a flat surface. The result is a wide, forceful stream of high velocity, laminar airflow with minimal air consumption and noise.

	Air Cons	umption	For	rce *	Sound Level
Model	SCFM	SLPM	Ozs	Grams	dBA
1126/112655	10.5	297	9.8	278	75
Force measured a Sound level meas All measurement .015" (0.38mm) sh	ured at 3' (914 s taken at 80 P	mm).	PRODUCT -YEAR	A	NA HOS


The 1" and 2" Flat Super Air Nozzles are shipped with a .015" (0.38mm) air gap opening that is set with a stainless steel shim positioned between the cap and the body. Force and flow may be easily increased or decreased by installing a different shim.


Model	SCFM	SLPM	Ozs	Grams	dBA
1122/112255	21.8	622	22	624	77

Force measured at 12" (305mm) from target. Sound level measured at 3' (914mm). All measurements taken at 80 PSIG (5.5 BAR). .015" (0.38mm) shim installed.









2" Super Air Scraper

0

0

18" 457mm --

# Shim Set



Model 1144 1/4 NPT female Material: Zinc Aluminum alloy/Steel

Shim sets for the 2" Flat Super Air Nozzles include a .005" (0.13mm). .010" (0.25mm), and .020" (0.51mm) thick shim.

Stainless Steel 2" 113255 Flat Super Air Nozzle

#### Model 1144 2" Super Air Scraper

EXAIR's 2" Super Air Scraper is a patented nozzle† used to eliminate stubborn debris from work or machine surfaces. This 2" flat nozzle utilizes a corrosion resistant scraper blade to provide the needed leverage to get underneath and scrape away fixed debris before the air can remove it from a surface. Applications include removal of tape, gaskets, adhesive, labels and stickers, grease, paint and sealant. A scraper nozzle can assist in cleaning sub plates, machining tables and difficult to sweep metal chips, flakes or discs. They are ideal when used as a Soft Grip Super Air Scraper (see page 114).

Model	SCFM	SLPM	Ozs	Grams	dBA
1144	21.8	622	22	624	77
Sound level me	at 12" (305mm) asured at 3" (914 its taken at 80 P shim installed.	mm).		100	A

2" Super Air Scraper can eliminate stubborn debris.





#### EXAIR's 2" Flat Super Air Nozzle Theirs (Old Technology) - 2004 Product Of The Year Winner · Your choice of zinc/aluminum or Type 316 stainless steel · Flexible Stay Set Hoses™, swivel fittings and magnetic bases are available - Meets or exceeds OSHA standards PRODUCT - Quietest flat nozzle available · Easy to change the force and flow

. Can consume over 30 SCFM

the Competition:

Save Over \$1,200 Per Year

By Replacing One Outdated Air Nozzle!

We've all seen flat air nozzles. Some are yellow. Others are orange.

The oldest ones are blue or metal. Those other manufacturers want

protecting your workers from harmful noise levels. In reality, those

colorful air nozzles that blow the air out of holes consume enormous

amounts of air. The plastic ones often break off. Some might even get

EXAIR's award winning 2" Flat Super Air Nozzle™ has been engineered

that can be blocked. EXAIR's patented, award winning design is efficient,

maintaining a precise amount of airflow through a thin slot. The result

consumption and noise. You can increase or decrease the force of each

flat air nozzle - using shims to tune it to the application so you'll never

waste compressed air. EXAIR also offers a 1" Flat Super Air Nozzle™,

Flat nozzles from other manufacturers can consume over 30 SCFM

(a refrigerator sized compressor) and aren't adjustable. Some manufac-

turers offer different flow rates but you need to guess at which one will

do the job since you can't adjust them once you've made the purchase.

By default, most users feel bigger is better and go with the highest

flow rate, wasting compressed air. See page 57 for more details.

with the same laminar airflow, to fit in tighter spaces.

is a forceful stream of high velocity, laminar airflow with minimal air

to replace those outdated flat nozzles. There are no dangerous holes

you an OSHA fine due to the dangerous dead ended pressures that

exist if someone blocks the air exhaust.

you to believe you'll save money by conserving compressed air while

• Expensive - metal or plastic

· No easy adjustment wasted compressed air · May not be OSHA safe

· Significantly louder · Plastic is easily broken

- One popular flat nozzle consumes 31 SCFM @ 80 PSIG.
- EXAIR's 2" Flat Super Air Nozzle with .015" shim consumes 21.8 SCFM @ 80 PSIG.
- · 31 SCFM (theirs) 21.8 SCFM (EXAIR's) = 9.2 SCFM compressed air saved.

Most large plants know their cost per 1,000 standard cubic feet of compressed air. If you don't know your actual cost per 1,000 SCF, 25¢ is a reasonable average to use.

- SCFM saved x 60 minutes x cost/1,000 SCF = dollars saved per hour.
- In this case, 9.2 SCFM x 60 x .25/1.000 SCF= 13.8 cents saved per hour.
- 13.8 cents per hour x 24 hours = \$3.31 saved per day.
- \$3.31 per day x 365 days = \$1,208.88 saved in one year (in this 24/7 operation).

#### And, This Savinas Is For One Nozzle!

Air Nozzle	Air Consumption @ 80 PSIG	Noise Level dBA	lbs. of Force @ 80 PSIG
Yellow	29 SCFM	83	1.7
Orange	28 SCFM	82	1.7
Blue	26 SCFM	78	1.5
Metal (machined)	29 SCFM	82	1.7
Metal (cast)	31 SCFM	80	1.9
EXAIR 2" Flat Super Air Nozzle	*7.3-30 SCFM	62-81	0.5 - 1.9

\*Air consumption dependent upon shim size.

can pay for itself in less than 27 days. Put the 2" Flat Super Air Nozzle to work in your blowoff, cooling or drying application. We're sure you'll agree that it blows away the competition!

For Technical Assistance, Call An EXAIR Application Engineer 1-800-903-9247 Toll Free FAX (866) 329-3924 · E-mail: techelp@exair.com · www.exair.com







11510 Goldcoast Drive • Cincinnati, OH 45249-1621 • Phone (513) 671-3322 FAX (513) 671-3363 \* E-mail: techelp@exair.com \* www.exair.com

#### **Back Blow Air Nozzles**





Model 1004SS M4 x 0.5 Material: Type 316 Stainless Steel

# M4 Back Blow Air Nozzle Model 1004SS Back Blow Air Nozzle

EXAIR's M4 Back Blow Air Nozzle delivers the smallest, most effective airflow for cleaning out small diameter tubes, pipes, channels or holes. Its forceful airflow can be used on diameters as small as 1/4" (6.3mm) and up to 1" (25.4mm). Extensions for reaching farther into a pipe, tube, hose, channel or hole are available.

		ir mption	Sound Level*	Use With:
Model	SCFM	SLPM	dBA	Inside Diameters
100455	4.5	127	75	1/4" - 1" (6.3-25.4mm)

#### Dimensions and Airflow Pattern 0.19" 0.42" 11mm FLATS 6" 152mm 12" 305mm 18" 457mm

#### 1/4 NPT Back Blow Air Nozzle




Model 1006SS 1/4 NPT female Material: Type 316 Stainless Steel

#### Model 1006SS Back Blow Air Nozzle

The 1/4 NPT Back Blow Air Nozzle delivers high performance suitable for a wide range of diameters. Recommended diameter range is 7/8"- 4" (22-102mm). A large variety of extensions for reaching farther into a pipe, tube, hose, channel or hole are available.

		ir mption	Sound Level*	Use With:
Model	SCFM	SLPM	dBA	Inside Diameters
100655	22	622	80	7/8"-4" (22-102mm)



#### 1 NPT Back Blow Air Nozzle



Model 1008SS 1 NPT female Material: Type 316 Stainless Steel



EXAIR's largest Back Blow Air Nozzle produces the greatest force for stubborn, sticky materials which may be inside of pipes, tubes, channels or holes. It is capable of reaching into diameters from 2"-16" (51-406mm) so it can handle small and large diameters. Extensions are available.


	Consu	ir nption	Sound Level*	Use With:
Model	SCFM	SLPM	dBA	Inside Diameters
100855	57	1,614	89	2" - 16" (51-406mm)

Sound level measured at 3' (914mm) All measurements taken at 80 PSIG (5.5 BAR).



Chip Shields should be used to protect operators from debris. A Model 901650 Chip Shield is for M4 x 0.5 extensions and a Model 901222 is available for 1/4 NPT extensions.

#### Extensions provide the necessary reach to clean out your pipe, tube, hose or channel, Available up to 72" (1829mm) long Model Description 9492 6" (152mm) Aluminum, M4 x 0.5 9493 12" (305mm) Aluminum, M4 x 0.5 9495 24" (610mm) Aluminum, M4 x 0.5 9497 36" (914mm) Aluminum, M4 x 0.5 12" (305mm) Aluminum, 1/4 NPT 9188 9189 18" (457mm) Aluminum, 1/4 NPT 9190 24" (610mm) Aluminum, 1/4 NPT 36" (914mm) Aluminum, 1/4 NPT 9192 48" (1219mm) Aluminum, 1/4 NPT 9193 60" (1524mm) Aluminum, 1/4 NPT 9194 72" (1829mm) Aluminum, 1/4 NPT 900353 12" (305mm) Aluminum, 1 NPT 901254 36" (914mm) Aluminum, 1 NPT 901259 72" (1829mm) Aluminum, 1 NPT





A Back Blow Air Nozzle cleans chips and coolant from inside a machined pipe.



11510 Goldcoast Drive • Cincinnati, OH 45249-1621 • Phone (513) 671-3322 FAX (513) 671-3363 \* E-mail: techelp@exair.com \* www.exair.com



# An INTELLIGENT OMPRESSED AIR Product

#### Safety Air Nozzles

#### Safety Air Nozzles



Material: Brass

Model 1001 1/8 NPT female Material: Brass Model 1002 1/4 NPT female

Model 1002SS 1/4 NPT female Material: Type 303 Stainless Steel Model 1003 3/8 NPT female Material: Brass




Oddly shaped parts often require a combination of Safety Nozzles for blowoff.

#### Model 1001, 1002, 1002SS and 1003 Safety Air Nozzles


Safety Air Nozzles eject a small amount of compressed air 360° around the outer ring that combines with the air ejected from the center hole to produce a high volume, high velocity blast of air. The slotted end allows air to vent safely should the nozzle end be blocked.

Air Consumption		Fo	rce*	Sound Level	
Model	SCFM	SLPM	Ozs	Grams	dBA
1001	10	283	9	255	78
1002	17	481	16	454	80
100255	17	481	16	454	80
1003	18	509	18	510	83

\* Force measured at 12" (305mm) from target. Sound level measured at 3' (914mm) All measurements taken at 80 PSIG (5.5 BAR).



Model				Hex	Inlet
	in	1.19	0.38	1/2	1/8
1001	mm	30	10	13	NPT
1002	in	1.44	0.50	5/8	1/4
100255	mm	37	13	16	NPT
	in	1.65	0.63	3/4	3/8
1003	mm	42	16	19	NPT



Model		E	F	G	Н
1001	in	1.1	2.1	4.1	6.0
	mm	28	53	104	152
1002	in	1.3	2.3	4.4	6.5
100255	mm	33	58	112	165
1003	in	1.3	2.4	4.7	7.0
	mm	33	61	119	178



Contact an Application Engineer at 1-800-903-9247.

#### Send in your air nozzle for the Award Winning **EXAIR Efficiency Lab Service**

We will test your existing product for air use, noise and force. We'll compare it to our Intelligent Compressed Air® products and provide a full report to help improve your process.

#### Adjustable Air Nozzles



Model 1009 1/8 NPT male Material: Aluminum Model 1009SS 1/8 NPT male Material: Type 303 Stainless Steel




Adjustable Air Nozzles are perfect for a variety of blowoff applications.


#### Model 1009 and 1009SS Adjustable Air Nozzles

Adjustable Air Nozzles are suitable for a wide variety of blowoff applications. The design allows you to "tune in" the force and flow to the application requirements, thereby minimizing air consumption. A micrometer-like dial indicates the gap setting. A set screw in the end can be tightened so the air nozzle holds the setting.

SCFM	SLPM	Ozs	Grams	dBA	
13	368	12	340	79	

# **Dimensions and Airflow Pattern**















#### **How Air Jets Work**

Air lets utilize the Coanda effect (wall attachment of a high velocity fluid) to produce air motion in their surroundings. As illustrated on the right, a small amount of compressed air (black arrows) is throttled through an internal ring nozzle above sonic velocity. A vacuum is produced, pulling large volumes of surrounding, or "free" air, through the jet (blue arrows). Both the outlet and inlet can be ducted for remote positioning. If the end is blocked, flow simply reverses at well below OSHA dead end pressure requirements.



#### **High Velocity Air Jets**



Model 6013 1/8 NPT male Material: Brass Max Temp: 275°F (135°C)



Model 601355 1/8 NPT male Material: Type 303 Stainless Steel Max Temp: 400°F (204°C)



Material: Type 303 Stainless Steel

#### Model 6013 and 6013SS High Velocity Air Jets

Provides maximum thrust with a confined, directed airstream. It is the best choice for part ejection, chip removal, and part drying.

Shim Sets: Shims can be used to change the gap on the Model 6013 and 6013SS High Velocity Air Jet Shim Set.

SCFM	SLPM	Ozs	Grams	dBA
22	622	20	567	82

Sound level measured at 3' (914mm All measurements taken at 80 PSIG (\$ 5 BAR)

The Model 6313 Air Jet Shim Set for the High Velocity Air Jet includes a .006" (0.15mm) and a .009" (0.23mm) thick shim. A .015" (0.38mm) shim comes installed with the Model 6013 and 6013SS Air Jet.



#### Adjustable Air Jets



Model 6019 1/8 NPT male Material: Brass Max Temp: 275°F (135°C)



Model 6019SS 1/8 NPT male Material: Type 303 Stainless Steel Max Temp: 400°F (204°C)

#### Model 6019 and 6019SS Adjustable Air Jets


This is an adjustable version of the Model 6013 High Velocity Air Jet. Airflow and thrust are easily adjusted using the micrometer gap indicator.


Air Cons	umption			Sound Level	
SCFM	SLPM	Ozs	Grams	dBA	
18	509	16	454	83	

Force measured at 12" (305mm) from target with a .006" (0.15mm) setting. Sound level measured at 31/014mm) All measurements taken at 80 PSIG IS.S RAR



combination of Model 6013SS High **Velocity Air Jets** dry this chainsaw









#### A Steel Plant Reduces Air Use by 59%

A steel plant was using open ended pipes on their cold rolled process to blow away a dense fog of oil vapor so the operator could see the process. Each pipe consumed 195 SCFM (5,521 SLPM) of compressed air. With only a 3:1 air amplification ratio, the open ended pipe did a poor job of clearing the fog. The pipes were dangerous since they could potentially be dead ended (an OSHA violation). Even with hearing protection, workers complained that it was loud.

They installed (2) Model 1106 1/2 NPT Stainless Steel Super Air Nozzles with Model 9069 Swivel Fittings (to aim them) to blow the fog across the 6' (1.8m) width. The Super Air Nozzles completely cleared the fog and the workers complimented the significant noise drop. Each open pipe that used to consume 195 SCFM (5,521 SLPM) was reduced to only 60 SCFM (1,699 SLPM) when the Super Air Nozzles were installed.





#### Air Nozzles

#### How Much Air Does It Really Use?

The amount of compressed air wasted by copper tubes, drilled pipe and other compressed air blowoffs can easily cost thousands of dollars per year. To quantify it, air consumption can be translated into electrical energy use. One horsepower of compressor (746 Watts) generates 4 to 5 SCFM (113 to 142 SLPM). The SCFM (SLPM) output depends on the efficiency of the compressor. Wasteful blowoffs can drain the compressed air system where a plant will experience frequent and sizeable pressure drops. The lack of air can be eliminated when the inefficient blowoffs are replaced.

Efficient products like EXAIR's engineered Super Air Nozzles are quiet while being capable of pulling in 25 parts of room air for every one part of compressed air. Companies who want to "Go Green" and minimize compressed air use should listen for the loud compressed air noise in their plant. Once the noisy blowoff is located, EXAIR's Digital Sound Level Meter (shown on page 17) can isolate the source and measure the sound level. Replacing one drilled pipe or other homemade blowoff with one Super Air Nozzle can amount to a large air savings. Here's a typical example:



**EXAIR's Digital Sound** Level Meter detects the source of high noise. (See page 17)





Digital Flowmeter with USB Data Logger and wireless mo are available. See pages 10-16 for full details.

Compressed air products should not be used at pressures higher than indicated by the manufacturer since this wastes air. When looking for places to conserve air, it is important to measure the air consumption of everything connected to the compressed air supply rather than relying on the numbers printed in a manufacturer's literature. Some manufacturers of compressed air products understate the air consumption of their products. It is hard to say if it is done intentionally or in error. One possibility is that their flow meter has not been regularly calibrated. Another reason could be a failure to properly use their flow meter.

Most flow meter manufacturers require that any measurement made on their meter be multiplied by a correction factor in order to get the exact air consumption measurement. This takes into account the conditions under which the flow meter was calibrated. If a company using one of these flow meters takes the reading but fails to multiply it by the appropriate correction factor, it would appear their product uses a lot less compressed air - easily half of what it actually consumes. EXAIR's Digital Flowmeter and wireless models (starting on page 10) are an easy to use solution that does not require regular calibration and provides the actual reading without having to use a correction factor.













## High Force Air Nozzles COMPRESSED AIR

Product

Some applications require extremely high force with extensive reach. EXAIR offers most standard nozzles in a high force version. With incredibly high blowing forces these nozzles are ideal for part ejection as well as blowoff, cooling and drying applications. EXAIR has engineered Large Super Air Nozzles that put the blowing capability of multiple nozzles into one single air nozzle. Hard-hitting force is measured in pounds, not ounces. All meet OSHA noise level and dead end pressure requirements.

#### High Force Air Nozzles "Quick Pick" Comparison

Model	Material	Description	Inlet	Air Consumption at 80 PSIG (5.5 BAR)		Force		Sound Level	More Details
				SCFM	SLPM	Lbs	Grams	dBA	Detail
HP1126	Zinc Aluminum alloy	1" High Power Flat Super Air Nozzle	1/8 FNPT	17.5	495	1	454	82	p. 63
HP1126SS	Stainless Steel - Type 316	1" High Power Flat Super Air Nozzle	1/8 FNPT	17.5	495	1	454	82	p. 63
HP1002	Brass	High Power Safety Air Nozzle	1/4 FNPT	32	906	1.8*	816	87	p. 64
HP100255	Stainless Steel - Type 303	High Power Safety Air Nozzle	1/4 FNPT	32	906	1.8*	816	87	p. 64
1104	Zinc Aluminum alloy	Super Air Nozzle	3/8 FNPT	35	991	1.9*	862	82	p. 64
110455	Stainless Steel - Type 316	Super Air Nozzle	3/8 FNPT	35	991	1.9*	862	82	p. 64
1104-PEEK	PEEK (Plastic)	Super Air Nozzle	3/8 FNPT	35	991	1.9*	862	82	p. 64
1105	Zinc Aluminum alloy	Super Air Nozzle	3/8 MNPT	35	991	1.9*	862	82	p. 64
110555	Stainless Steel - Type 316	Super Air Nozzle	3/8 MNPT	35	991	1.9*	862	82	p. 64
HP1125	Zinc Aluminum alloy	2" High Power Flat Super Air Nozzle	1/4 FNPT	37	1,039	2.2	998	83	p. 64
HP112555	Stainless Steel - Type 316	2° High Power Flat Super Air Nozzle	1/4 FNPT	37	1,039	2.2	998	83	p. 64
1111-4	Zinc Aluminum alloy	Super Air Nozzle Cluster	3/8 FNPT	56	1,585	3.2*	1,451	82	p. 6
100855	Stainless Steel - Type 316	Back Blow Air Nozzle	1 FNPT	57	1,614	NA	NA	89	p. 59
1106	Zinc Aluminum alloy	Super Air Nozzle	1/2 FNPT	60	1,699	3.3*	1,497	87	p. 6
110655	Stainless Steel - Type 316	Super Air Nozzle	1/2 FNPT	60	1,699	3.3*	1,497	87	p. 6
1107	Zinc Aluminum alloy	Super Air Nozzle	1/2 MNPT	60	1,699	3.3*	1,497	87	p. 65
110755	Stainless Steel - Type 316	Super Air Nozzle	1/2 MNPT	60	1,699	3.3*	1,497	87	p. 65
1112	Zinc Aluminum alloy	Super Air Nozzle	3/4 FNPT	91	2,577	4.5*	2,041	96	p. 6
111255	Stainless Steel - Type 316	Super Air Nozzle	3/4 FNPT	91	2,577	4.5*	2,041	96	p. 6
1113	Zinc Aluminum alloy	Super Air Nozzle	3/4 MNPT	91	2,577	4.5*	2,041	96	p. 65
111355	Stainless Steel - Type 316	Super Air Nozzle	3/4 MNPT	91	2,577	4.5*	2,041	96	p. 6
1111-7	Zinc Aluminum alloy	Super Air Nozzle Cluster	1/2 FNPT	98	2,773	5.7*	2,585	85	p. 67
1114	Zinc Aluminum alloy	Super Air Nozzle	1 FNPT	135	3,823	6.6*	2,994	99	p. 65
1114SS	Stainless Steel - Type 316	Super Air Nozzle	1 FNPT	135	3,823	6.6*	2,994	99	p. 65
1115	Zinc Aluminum alloy	Super Air Nozzle	1 MNPT	135	3,823	6.6*	2,994	99	p. 65
111555	Stainless Steel - Type 316	Super Air Nozzle	1 MNPT	135	3,823	6.6*	2,994	99	p. 6
1111-12	Zinc Aluminum alloy	Super Air Nozzle Cluster	1 FNPT	168	4,754	9.8*	4,445	89	p. 6
1116	Zinc Aluminum alloy	Super Air Nozzle	1-1/4 FNPT	188	5,324	9.4*	4,264	102	p. 6
1117	Zinc Aluminum alloy	Super Air Nozzle	1-1/4 MNPT	188	5,324	9.4*	4,264	102	p. 6
1118	Zinc Aluminum alloy	Super Air Nozzle	1-1/4 FNPT	300	8,495	15*	6,804	106	p. 6
1119	Zinc Aluminum alloy	Super Air Nozzle	1-1/4 MNPT	300	8,495	15*	6,804	106	p. 6
1120	Zinc Aluminum alloy	Super Air Nozzle	1-1/4 FNPT	460	13,026	23*	10,433	109	p. 6
1121	Zinc Aluminum alloy	Super Air Nozzle	1-1/4 MNPT	460	13,026	23*	10,433	109	p. 6

#### 1" High Power Flat Super Air Nozzles™



Model HP1126 1/8 NPT female Material: Zinc Aluminum alloy Model HP1126SS 1/8 NPT female Material: Type 316 Stainless Steel



A 1" High Power Flat Super Air Nozzle is used to tip a part from All measurements taken at 80 PSIG (5.5 BAR). a chute and on to a conveyor.

#### Model HP1126 and HP1126SS 1" High Power Flat Super Air Nozzles

EXAIR's 1" High Power Flat Super Air Nozzles produce a flat 1" (25mm) wide airstream with a blowing force of 1 pound. The unique design of this super-efficient nozzle makes it an ideal fit for both tight spaces and tight budgets. It uses EXAIR's patented technology to maximize entrained airflow while reducing noise levels.


	umption	Force*		
SCFM	SLPM	Lbs	Grams	dBA
17.5	495	1	454	82

Force measured at 12° (305mm) from target Sound level measured at 3" (914mr 025° (0.64mm) shim installed

# **Dimensions and Airflow Pattern**

The Model HP1136SS Shim Set for the 1" High Power Flat Super Air Nozzle Includes a .020" (0.51mm) and .030" (0.76mm) thick shim: A .025" (0.64mm)







# An INTELLIGENT OMPRESSED AIR Product

#### **High Force Air Nozzles**



Model HP1002 1/4 NPT female Material: Brass

Model HP1002SS 1/4 NPT female Material: Type 303 Stainless Steel

#### Model HP1002 and HP1002SS **High Power Safety Air Nozzles**

Provide strong blowing force for applications requiring high thrust and velocity. It uses more compressed air than other air nozzles but is low when compared to typical blowoffs delivering the same force.

				Sound Leve	
SCFM	SLPM	Lbs	Grams	dBA	
32	906	1.8	816	87	

Sound level measured at 3' (914mm).

# **Dimensions and Airflow Pattern** 12\* 305mm

#### 2" High Power Flat Super Air Nozzles'



Model HP1125 1/4 NPT female Material: Zinc Aluminum allov Model HP1125SS 1/4 NPT female Material: Type 316 Stainless Steel



#### Model HP1125 and HP1125SS


#### 2" High Power Flat Super Air Nozzles EXAIR's 2" High Power Flat Super Air

Nozzles produce a flat 2" (51mm) wide airstream with a strong blowing force of 2.2 pounds (998 grams). The adjustable force is more than three times that of ordinary air nozzles. It uses EXAIR's patented† technology to maximize entrained airflow while reducing noise levels.

Air Cons	Air Consumption			Sound Level
SCFM	SLPM	Lbs	Grams	dBA
37	1,039	2.2	998	83

Force measured at 12" (305mm) from tarnet Sound level measured at 3' (914mm) All measurements taken at 80 PSIG (5.5 BAR). .025" (0.64mm) shim installed.

Patent #5402938



Note: For highest force and flow, order Model 900633 .030" (0.76mm) shim.



The Model HP1132SS Shim Set for the 2" High Power Flat Super Air Nozzle includes a .020" (0.51mm) and .030" (0.76mm) thick shim. A .025" (0.64mm) shim is installed.

#### Large Super Air Nozzles™



Model 1104 3/8 NPT female Material: Zinc Aluminum alloy Model 1104SS 3/8 NPT female Material: Type 316 Stainless Steel Model 1104-PEEK 3/8 NPT female Material: PEEK (plastic)




Model 1105 3/8 NPT male Material: Zinc Aluminum alloy Model 1105SS 3/8 NPT male Material: Type 316 Stainless Steel

#### Model 1104, 1104SS, 1104-PEEK, 1105 and 1105SS 3/8 NPT Super Air Nozzles

EXAIR's 3/8 NPT Super Air Nozzles produce 1.9 lbs (862 grams) of strong blowing force that is 2.3 times that of the standard Super Air Nozzle. The protective aerodynamic slots guide the airflow to a single point of convergence for hard-hitting force and dramatic noise reduction over typical blowoffs.

Air Consumption				Sound Level	
SCFM	SLPM	Lbs	Grams	dBA	
35	991	1.9	862	82	

Sound level measured at 3' (914mm) All measurements taken at 80 PSIG (5.5 BAR)











All measurements taken at 80 PSIG (5.5 BARI).

#### **High Force Air Nozzles**



#### Large Super Air Nozzles™



Model 1106 1/2 NPT female Material: Zinc Aluminum alloy Model 1106SS 1/2 NPT female Material: Type 316 Stainless Steel




Model 1107 1/2 NPT male Material: Zinc Aluminum alloy Model 110755 1/2 NPT male Material: Type 316 Stainless Steel

#### Model 1106, 1106SS, 1107 and 1107SS 1/2 NPT Super Air Nozzles

EXAIR's 1/2 NPT Super Air Nozzles produce 3.3 lbs (1.5 kg) of blowing force - 4 times that of ordinary nozzles. Air consumption and noise are extremely low compared to that of open pipe or copper tubes.

SCFM	SLPM	Lbs	Kg	dBA
60	1,699	3.3	1.5	87
	ured at 12" (30 measured at ments taken a	3' (914mi	m).	PRODUCT



# An INTELLIGENT OMPRESSED AIR Product

#### **High Force Air Nozzles**

EXAIR's 1-1/4 NPT Super Air Nozzles

provide exceptionally strong blowing force.

They produce 9.4 lbs (4.25 kg) of blowing

force - almost 12 times that of the standard

#### Large Super Air Nozzles™



Model 1116 1-1/4 NPT female Material: Zinc Aluminum alloy

#### Super Air Nozzle. SLPM Lbs Kg SCFM 5,324 9.4 4.26 188

Force measured at 12" (305mm) from target. Sound level measured at 3' (914mm). All measurements taken at 80 PSIG (5.5 BAR). OSHA allows 1 hour of exposure per day without hearing protection.

Model 1118 and 1119

Super Air Nozzle.

Model 1120 and 1121

1-1/4 NPT Super Air Nozzles

These 1-1/4 NPT Super Air Nozzles have

the largest orifices that provide additional

blowing force of any single air nozzle. They

almost 28 times that of the standard Super

air velocity, and generate the strongest

1-1/4 NPT Super Air Nozzles

These 1-1/4 NPT Super Air Nozzles have

larger orifices than the Model 1116 / 1117


that provide additional air velocity. They

almost 18 times that of the standard

generate 15 lbs (6.80 kg) of blowing force -

Model 1116 and 1117

1-1/4 NPT Super Air Nozzles





Model 1117 1-1/4 NPT male Material: Zinc Aluminum alloy

Model 1112 3/4 NPT female Material: Zinc Aluminum alloy Model 1112SS 3/4 NPT female Material: Type 316 Stainless Steel




Model 1113 3/4 NPT male Material: Zinc Aluminum alloy Model 1113SS 3/4 NPT male Material: Type 316 Stainless Steel

#### Model 1112, 1112SS, 1113 and 1113SS 3/4 NPT Super Air Nozzles

EXAIR's Super Air Nozzles are available in larger sizes where extreme force is required. The 3/4 NPT Super Air Nozzles produce 4.5 lbs (2.04 kg) of blowing force - over 5 times that of ordinary nozzles.

Air Consumption					
SCFM	SLPM	Lbs	Kg	dBA	
91	2,577	4.5	2.04	96	


Sound level measured at 3' (914mm). All measurements taken at 80 PSIG (5.5 BAR). OSHA allows 3 hours of exposure per day without



Model 1118 1-1/4 NPT female Material: Zinc Aluminum alloy



SLPM Lbs Kg SCFM 300 8,495 15 6.80 Force measured at 12" (305mm) from target Sound level measured at 3' (914mm). All measurements taken at 80 PSIG (5.5 BAR). OSHA allows 1/2 hour of exposure per day



Model 1119 1-1/4 NPT male Material: Zinc Aluminum alloy

Model 1114 1 NPT female Material: Zinc Aluminum alloy Model 1114SS 1 NPT female Material: Type 316 Stainless Steel



Model 1115 1 NPT male Material: Zinc Aluminum alloy Model 1115SS 1 NPT male Material: Type 316 Stainless Steel


#### Model 1114, 1114SS, 1115 and 1115SS 1 NPT Super Air Nozzles

EXAIR's 1 NPT Super Air Nozzles optimize entrained airflow across the nozzle surface to minimize the noise level while providing extremely strong blowing force. They produce 6.6 lbs (3.01 kg) of blowing force - over 8 times that of ordinary nozzles.

	Air Consumption			Sound Level	
SCFM	SLPM	Lbs	Kg	dBA	
135	3,823	6.6	2.99	99	

All measurements taken at 80 PSIG (5.5 BAR) OSHA allows 2 hours of exposure per day






# Air Nozzle.

Model 1120 1-1/4 NPT female


Material: Zinc Aluminum alloy


SCFM SLPM Lbs Kg 460 13,026 23 10.43 Force measured at 12" (305mm) from target.

Sound level measured at 3' (914mm). All measurements taken at 80 PSIG (5.5 BAR). OSHA allows 1/2 hour of exposure per day without hearing protection.



Model 1121 1-1/4 NPT male Material: Zinc Aluminum alloy






















#### Super Air Nozzle Clusters

**Dimensions and** 

**Airflow Pattern** 

**Dimensions and Airflow Pattern** 

2.25"

2.75"

1 NPT

An INTELLIGENT Product

24° 610mm

18" 457mm 12" 305mm

# Super Air Nozzle Clusters Model 1111-4 Super Air Nozzle Cluster

co (2)	Air Cons	umption			
1000	SCFM	SLPM	Lbs	Kg	dBA
Most report	56	1,585	3.2	1.45	82
ALC: V		ired at 12* (30 measured at ments taken i	3' (914m	m).	

Model 1111-4 3/8 NPT female Material: Nozzles - Zinc Aluminum allov Body - Aluminum



Model 1111-7 Super Air Nozzle Cluster

SCFM SLPM 98 2,773 force measured at 12' (305n sound level measured at 3' Ill measurements taken at 8'			5ound Leve	
SCFM	SLPM	Lbs	Kg	dBA
98	2,773	5.7	2.59	85
Force measu	red at 12" (30	25mm) fr	om targe	et.
Sound level	measured at	3°(914m	m).	
All measurer	ments taken a	at 80 PSI	G (5.5 BA)	R).

Model 1111-7 1/2 NPT female Material: Nozzles - Zinc Aluminum allov Body - Aluminum




Model 1111-12 Super Air Nozzle Cluster

SCFM	SLPM	Lbs	Kg	dBA
168	4,754	9.8	4,45	89

Sound level measured at 3' (914mm) All measurements taken at 80 PSIG (5.5 BAR).

Model 1111-12 1 NPT female Material: Nozzles - Zinc Aluminum alloy Body - Aluminum



Flexible Stay Set Hoses bend and keep their aim until physically moved.

#### Flexible Stay Set Hoses™

#### **Adding Flexibility**

For applications where frequent repositioning of the standard force Air Nozzles or Jets is required, the Flexible Stay Set Hoses™ are ideal. Simply mount the hose in close proximity to the application and bend it to aim the airstream at the target. Since the hose has "memory", it will not creep or bend. It always keeps the aim until physically moved to the next position.

Two versions of the Stay Set Hoses are available in a variety of lengths. The 1/4 MNPT x 1/4 MNPT hose has a 1/4 NPT male fitting on each end and the 1/4 MNPT x 1/8 FNPT hose has a 1/4 NPT male fitting on one end and 1/8 NPT female fitting on the other.











# An INTELLIGENT OMPRESSED AIR Product

#### **Nozzle Accessories**

#### Flexible Stay Set Hoses™ continued

The Air Nozzles shown below can be used with the following Stay Set Hoses (1/4 NPT male fitting on each end):

Model #	Description	Model #	Description
9206	6" (152mm) 1/4 MNPT x 1/4 MNPT	9224	24" (610mm) 1/4 MNPT x 1/4 MNPT
9212	12" (305mm) 1/4 MNPT x 1/4 MNPT	9230	30* (762mm) 1/4 MNPT x 1/4 MNPT
9218	18" (457mm) 1/4 MNPT x 1/4 MNPT	9236	36" (914mm) 1/4 MNPT x 1/4 MNPT

Model 1002

Model 100255 SS Safety Air Nozzle Model HP1002

High Power Safety Air Nozzle Model HP1002SS SS High Power Safety Air Nozzle



2" (S1mm) Flat Super Air Nozzle Model 112255 2" (51mm) SS Flat Super Air Nozzle

Model HP1125 2" (51mm) High Power Flat Super Air Nozzle Model HP1125SS



Model 1100 Super Air Nozzle Model 1100SS SS Super Air Nozzle Model 1100-PEEK

PEEK Super Air Nozzle Model 1006SS SS Back Blow Air Nozzle

The Air Nozzles and Jets shown below can be used with the following Stay Set Hoses (1/4 NPT male fitting on one end, 1/8 NPT female on the other):

Model #	Description	Model #	Description
9256	6" (152mm) 1/4 MNPT x 1/8 FNPT	9274	24" (610mm) 1/4 MNPT x 1/8 FNPT
9262	12" (305mm) 1/4 MNPT x 1/8 FNPT	9280	30" (762mm) 1/4 MNPT x 1/8 FNPT
2260	10" (467) 1 (4 MAIDT 1/9 ENIDT	0396	345 (014 mm) 1/4 MAIDT - 1/9 FAIDT



Model 1108SS-NPT

Model 1109SS-NPT

Pico Super Air Nozzle

Model 1110SS-NPT Model 1110-PEEK-NPT

Model 1109-PEEK-NPT

Nano PEEK Super Air Nozzle

Model 1108-PEEK-NPT

Atto PEEK Super Air Nozzle







Model HP1126 1" (25mm) High Power Flat Super Air Nozzle Model HP1126SS 1" (25mm) SS High Power Flat Super Air Nozzle











Flexible Stay Set Hoses bend to fit your application and will maintain their orientation until the position needs to be re-adjusted. The airstream can be aimed at precisely the correct spot.

#### **Swivel Fittings**



EXAIR's Swivel Fittings make it easy to adjust the aim of the Air Nozzles and Jets. Correct placement of the blowing angle can help optimize performance, reduce noise levels and improve efficiency. Swivel Fittings permit a movement of 25 degrees from the center axis for a total movement of 50 degrees. Type 303 or 316 Stainless Steel.

Model #	Description
9201	M4 x 0.5mm female x 1/8 MNPT, 316SS
9202	M5 x 0.5mm female x 1/8 MNPT, 316SS
9203	M6 x 0.75mm female x 1/8 MNPT, 316SS
9052	1/8 MNPT x 1/8 FNPT, 303SS
9053	1/4 MNPT x 1/4 FNPT, 303SS
9068	3/8 MNPT x 3/8 FNPT, 303SS
9069	1/2 MNPT x 1/2 FNPT, 303SS
9023	3/4 MNPT x 3/4 FNPT, 303SS
9204	1 MNPT x 1 FNPT, 303SS

#### Magnetic Bases


Magnetic bases are suited to applications where frequent movement of the Air Nozzle or Jet is required. The powerful magnet permits horizontal or vertical mounting that will hold the blowing position of the Stay Set Hose. A shutoff valve is provided that can be used to vary the force and flow.














#### Blowoff Systems An INTELLIGENT



#### **Build Your Own System**

Now you can put together the best combination that suits your blowoff, cooling, drying or cleaning application. Select the model number that includes your choice of Air Nozzle or Jet, a length of Stay Set Hose, and a one or two outlet magnetic base. Here's how:

- 1. Choose the Air Nozzle or Jet model. Example: Model 1122 Super Air Nozzle
- 2. You have the option to include a length of Stay Set Hose. Simply list the model of the Stay Set Hose (shown on previous page) as a dash number after the Air Nozzle or Jet model number. Example: A Model 1122 Super Air Nozzle with a Model 9212 12" (305mm) Stay Set Hose is a Model 1122-9212.
- 3. You have the option to include a magnetic base, If you want a One Outlet Magnetic Base, change the second digit of the "added on" dash number to a "3". If you would like the Two Outlet Magnetic Base, change the second digit to a "4". By using a "4", you will receive (2) Air Nozzles or Jets and (2) Stay Set Hoses to attach to the Two Outlet Magnetic Base.

Example: Two Model 1122 Super Air Nozzles with two 12" (305mm) Stay Set Hoses and Two Outlet Magnetic Base is a Model 1122-9412.



A Model 1122-9412 includes two Model 1122 Super Air Nozzles with two 12" (305mm) Stay Set Hose and Two Outlet Magnetic Base.



# **EXAIR** White Papers



# **Understanding** Compressed Air Safety and Savings

Save Your Bottom Line and Protect Your Personnel -Download Now!



# Model # 1100-9312 Blowoff Kit (1) 1100 Super Air Nozzle (1) 9212 12" (305mm) Stay Set Hose

(1) 9042 Magnetic Base

1103-9462

Blowoff Kit

(2) 1103 Mini Super Air Nozzles

(1) 9043 Magnetic Base

(2) 9262 12" (305mm) Stay Set Hose











(2) 9212 12" (305mm) Stay Set Hose (1) 9043 Magnetic Base (1) 9042 Magnetic Base



# Model #

#### Blowoff Kit

- (1) 1102 Mini Super Air Nozzle (1) 1009 Adjustable Air Nozzle
- (1) 1100 1/4 NPT Super Air Nozzle
- (1) 1104 3/8 NPT Super Air Nozzle
- (1) 1106 1/2 NPT Super Air Nozzle (1) 1122 2" Flat Super Air Nozzle
- (1) 6013 High Velocity Air Jet (1) 6019 Adjustable Air let



# Stainless Steel Blowoff Kit

- (1) 11025S 1/8 NPT Mini Super Air Nozzle
- (1) 1009SS Adjustable Air Nozzle (1) 1100SS 1/4 NPT Super Air Nozzle
- (1) 1104SS 3/8 NPT Super Air Nozzle
- (1) 1106SS 1/2 NPT Super Air Nozzle
- (1) 1010SS 1/8 NPT Micro Air Nozzle (1) 1122SS 2" Flat Super Air Nozzle

## Model # Instant Blowoff Station

- (1) 1100 Super Air Nozzle
- (1) 9212 12\* (305mm) Stay Set Hose
- (1) 9042 Magnetic Base
- (2) 900061 10' (3m) Compressed Air Hose



#### Why is compressed air safety a concern?

Compressed air is commonly referred to as the "fourth utility" because it is very common as a resource within manufacturing, mining and processing environments. Employees or contractors in every industrial company or setting are exposed to compressed air's effects regularly and compressed air should be handled with responsibility and care. The primary dangers from compressed air come from high pressure and noise exposure. Personnel being exposed to compressed air which exits an open line or non-safety nozzle at a pressure higher than 30 PSI risk the air entering the bloodstream and causing air embolism, a serious health risk.

Improper use of compressed air commonly exceeds OSHA's noise exposure standards and causes noise induced hearing loss (NIHL). The CDC reports NIHL as one of the most common occupational diseases and the second most self-reported occupational illness or injury. According to the Bureau of Labor Statistics, occupational hearing loss is the most commonly recordable occupational illness in manufacturing, accounting for 1 in 9 recorded illnesses.

#### How can engineers effectively limit pressure and noise?

The CDC provides their Hierarchy of Controls, to lead engineers toward better solutions in order to improve safety for employees and operators. One option is to eliminate nozzles with loud and unsafe pressure by first designing with quiet and pressure-safe engineered compressed air products like air nozzles, air knives and air amplifiers. More options can be found in this whitepaper. Engineers should also take steps to replace existing products with engineered solutions that meet the OSHA Standards 29 CFR 1910.242(b) and 29 CFR 1910.95(a).

#### How do engineered air nozzles work?

Air nozzles use the Coanda effect to amplify airflow up to 25 times or more. As illustrated to the left, compressed air is ejected through a series of nozzles on the outer perimeter. As the air travels along the outer wall of the nozzle, surrounding air is entrained into the stream. The resulting airstream is a high volume, high velocity blast of air at minimal compressed air consumption. The air is always ejected so it can vent safely, well below OSHA dead end pressure requirements, should the nozzle end be blocked.

EXAIR's six page White Paper will help you learn how engineers can effectively limit dangerous pressure and noise, as well as reduce the cost of your manufacturing processes.



https://exair.co/04-cass or scan the gr code provided













## Air Atomizing Spray Nozzles COMPRESSED AIR

# Product

# **Air Atomizing Spray Nozzles**

#### All stainless steel construction for durability and corrosion resistance!

#### What Are Atomizing Nozzles?

EXAIR's Atomizing Spray Nozzles atomize fluids (most commonly water) Built to in a range of spray patterns for a variety of uses. They combine liquid and compressed air to create a mist of atomized liquid that can be easily adjusted to meet the needs of your application. All models use stainless steel construction for durability and corrosion resistance. Atomizing spray nozzles are available in 1/8 NPT, 1/4 NPT and 1/2 NPT sizes.

EXAIR's atomizing nozzles are available in 3 basic families:

#### Internal Mix:

Internal mix nozzles mix the liquid and air inside the air cap and produce the finest atomization. Internal mix nozzles can be used on liquids with a viscosity up to 300 cP. Both air and liquid sides are pressure fed.

#### Siphon Fed:

Siphon fed nozzles require no liquid pressure and can be used with gravity fed liquids or liquids from a siphon height as much as 36 inches (91cm). Siphon fed nozzles can be used on liquids with a viscosity up to 200 cP.

#### Why Atomizing Nozzles?

With EXAIR's atomizing nozzles, you can coat, cool, treat and paint a variety of products. Used with water, they are an efficient way to cool hot items in your automated process. These nozzles are also an excellent choice for dust mitigation.

Sound levels for the individual Atomizing Spray Nozzles are not provided. The fluid, pressure, surfaces being treated and surrounding enclosures used in conjunction with the Atomizing Spray Nozzle to form the system will determine the actual sound levels (which can vary greatly). Max temperature is 400°F (204°C) for Atomizing Spray Nozzles. All atomizing nozzles are € compliant.

#### **Applications**

- Washing
- Rinsing
- Coating
- Cooling
- · Quenching
- · Wetting (moistening)
- Humidification
- Dust Control

#### Advantages

- · Fully adjustable
- · Maximizes liquid dispersion
- · Minimizes liquid consumption
- · All stainless steel construction
- Compact
- Versatile
- Interchangeable liquid and air caps
- · Minimizes air consumption
- · Fine atomization





A Model SR1010SS is used to supply a cooling mist for a drilling operation.



(2) Model EB1030SS atomizing nozzles are used to give a final sanitary rinse prior to labeling wine bottles.



Mounting Brackets are available - Model 901786 for 1/8 NPT, Model 901318 for 1/4 NPT and Model 901556 for 1/2 NPT atomizing nozzles.

#### EXAIR





#### **Air Atomizing Spray Nozzles**

#### Internal Mix Narrow Angle Round Pattern - 1/8 NPT



An INTELLIGENT OMPRESSED AIR Product



Model: AN8010SS Material: Type 303 Stainless Steel



Model: AN8020SS Material: Type 303 Stainless Steel





Model: AN8030SS Material: Type 303 Stainless Steel



Model: AN8040SS Material: Type 303 Stainless Steel






Material: Type 303 Stainless Steel


#### Model AN8010SS, AN8020SS, AN8030SS, AN8040SS and AN8050SS

1/8 NPT internal mix narrow angle round pattern nozzles are excellent for spraying a concentrated mist of liquid. Because of the versatility of their adjustments, they can apply a heavy coat up close or send a very fine mist over 16 feet away! They are often used for precision application of lubricants during assembly, or marking items as they move through an assembly line. Narrow angle round pattern atomizing nozzles are capable of delivering the most liquid of any of our 1/8 NPT internal mix atomizing nozzles.

For pressure fed applications not requiring independent air and liquid control.



The modifiable spray pattern can generate a heavy or precision engineered mist for distances over 16 feet!



	10	PSI	/0.7	BAR	Liq	uid	20	PSI	/1.4	BAR	Liq	uid	30	PSI	2.1	BAF	l Liq	uid	40	PSI/	2.8	BAF	Lic	uid	60	PSI/	4.11	BAR	Liq	uid				Spra	ıy l	Dim	ens	sion	5		
lebo		ir sure	GPH	/LPH	sc	FM/ PM		Air ssure	GPH	/LPH	SCI		Pres	ir sure		PH/	SC	FM/	Pres	ir sure	GP LP		sc	FM/ PM	Pres	ir sure	GPH	/LPH	SCI	FM/ PM	250	Press PSI/	Liqu	uid		١	Widt	th	c	Mi De	
ž	PSI/	BAR			SL	PM.	PSI	/BAR			SL	PM	PSI	BAR	L	М	SL	PIVI	PSI/	BAR	LP	m	2r	PM	PSI/	BAR			SE	PM.		AR	PS BA	iR.	in	cm	in c	om in	cm	fee	
S	10	0.7	0.97	3,7	0.25	7.1	14	1.0	1.83	6.9	0.32	9.1	24	1.7	1.97	7.5	0.52	14.7	32	2.2	223	8.4	0.67	19.0	50	3,4	2.63	10.0	0.98	27.7	10	0.7	10	0.7	3	8	3.5	9 4.5	11	3.5	1,1
ANBOTOSS	12	0,8	0.80	3.0	0.32	9.1	18	1.2	1.5	5.7	0.39	11.0	28	1.9	1.7	6,4	0.59	16.7	36	2.5	1.97	7.5	0.74	20.9	54	3.7	2.37	9.0	1.02	28.9	18	1.2	20	1.4	3	8	4 1	10 5	13	5	1.5
NBC	14	1.0	0.60	2.3	0.4	11,3	22	1.5	1.27	4.8	0.52	14.7	32	2.2	1.37	5.2	0.71	20.1	40	2.8	1.67	6.3	0.84	23.8	58	4.0	2.1	7.9	1.12	31.7	32	2.2	30	2.1	3	8	4 1	10 5.5	14	7	2.1
⋖	-	-	-	-	-	-	26	1.8	0.73	2.8	0.67	19.0	38	2.6	0.8	3.0	0.93	26.3	48	3.3	1.00	3.8	1,09	30.9	66	4.6	1.7	6.4	1.21	34,3	48	3.3	40	2.8	3	8 4	15 1	11 6	15	8	2.4
s	10	0.7	1.33	5,0	0.43	12.2	18	1.2	1,83	6.9	0,71	20.1	24	1,7	2.27	8.6	0.91	25.8	30	2.1	2.63	10.0	1,05	29.7	40	2.8	3.33	12.6	1.31	37.1	10	0.7	10	0.7.	2	5	3	B 4	10	5	1.5
AN802055	12	0.8	1,17	4.4	0.5	14.2	20	1.4	1.73	6.5	0.75	21.2	28	1.9	2.07	7.8	0.99	28.0	34	2.3	2.47	9.3	1.12	31.7	46	3.2	3.13	11.8	1.4	39.6	20	1,4	20	1.4	2.5	6	3.5	9 4,5	11	7	2.1
N80	14	1.0	1.03	3.9	0.6	17.0	22	1.5	1.63	6.2	0.84	23.8	32	2.2	1.9	7.2	1.09	30.9	38	2.6	2.33	8.8	1.20	34.0	52	3.6	2.87	10.9	1.6	45.3	32	2.2	30	2.1	2.5	6 3	15	9 4.5	11	7	2.1
⋖	-	.=	-	-	-	-	-	-	-	-	-	-	40	2.8	1.57	5.9	1.45	41,0	48	3.3	1.87	7.1	1,53	43.3	70	4,8	2.2	8.3	2.2	62.3	70	4,8	60	4.1	3.5	9 4	4.5 1	11 6.5	17	10	3.0
s	12	0.8	2.20	8.3	0.47	13.3	22	1.5	2.9	11.0	0.75	21.2	30	2.1	3.7	14.0	0.96	27.2	36	2.5	4.47	16.9	1,09	30.9	48	3.3	6.3	23.8	1.28	36.2	12	0.8	10	0.7	2	5	3	8 4.5	11	6	1.8
AN803055	16	1,1	1,60	6.1	0.56	15.9	26	1.8	2.43	9.2	0.82	23.2	34	2.3	3.2	12.1	1.00	28.3	40	2.8	4.17	15.8	1.12	31.7	52	3.6	5.87	22.2	1.3	36.8	26	1,8	20	1.4	2.5	6 1	3.5	9 5	13	6	1.8
N80	24	1.7	0.67	2.5	0.95	26.9	38	2.6	1.13	43	1.35	38.2	46	3.2	1.8	6.8	1.45	41.0	52	3.6	2.67	10.1	1,49	42.2	64	4.4	4.56	17.3	1.59	45.0	52	3.6	40	2.8	3	8	4 1	10 6	15	11	3,4
4	28	1,9	0.47	1.8	1.07	30.3	42	2.9	0.77	2.9	1.53	43.3	52	3.6	1.4	5.3	1.76	49.8	60	4.1	2.00	7.6	1.87	52.9	70	4,8	3.8	14,4	1.84	52.1	70	4.8	60	4.1	4	10	5 1	13 6.5	17	11	3,4
s	16	1.1	4.87	9.6	2.54	71.9	28	1.9	6.60	25.0	3,64	103.0	40	2.8	7.83	29.7	4,70	132.9	48	3.3	9.33	353	5,40	153	65	4.5	12.0	45,4	6.70	190	16	1,1	10	0.7	2.5	6	3	8 4	10	10	3.0
405	20	1,4	3.57	11.0	2.92	82.6	32	2.2	5.60	21.2	3.98	112.6	44	3.0	6.87	26,0	4.99	141.3	55	3.8	8.17	30.9	5,98	169	75	5.2	10.8	41.0	7.57	214	32	2.2	20	1.4	3	8	4 1	10 5.5	14	11	3.4
AN804055	26	1.8	1,87	13.6	3.60	101.8	44	3.0	2.43	9.2	5.16	146.1	60	4.1	2.80	10.6	6.43	182.0	80	5.5	2.53	9.6	8.58	243	90	6.2	8.17	30.9	9.03	256	80	5.5	40	2.8	3	8	4 1	10 5.5	14	13	4.0
4	30	21	1.03	15,4	4.06	115.0	50	3.4	1.33	5.0	5.92	167.7	70	4.8	1.23	4.7	7.78	220.4	90	6.2	1.27	4.8	9.61	272	100	6.9	6.13	23.2	9.90	280	100	6.9	60	4.1	3.5	9 4	15 1	11 6	15	15	4.6
	12	0.8	7,60	28.8	1.76	49.8	20	1.4	11.63	44.0	2.37	67.1	30	2.1	13.5	51.1	3.42	96.8	38	2.6	15.4	58.2	3.99	113	54	3,7	18.9	71.7	5.17	146	12	0.8	10	0.7	3	8	4 1	10 6	15	9	2.7
N805055	14	1.0	6.10	23.1	1.97	55.8	22	1.5	10.53	39.9	2.85	80.7	34	2.3	11.37	43.0	3.92	111.0	42	2.9	14.1	53.3	4.50	127	60	4.1	17.2	65,1	5.83	165	22	1.5	20	1.4	3	8	4 1	10 6	15	11	3.4
180	16	1.1	4.80	18.2	2.18	61.7	24	1.7	9.43	35.7	3.11	88.0	38	2.6	9.07	34.3	4.4	124.6	46	3.2	12.3	46.7	4.95	140	65	4.5	15.7	59,4	6.45	183	38	2.6	30	2.1	3	8 4	45 1	11 6	15	14	4,3
F	_	_	-	_	_	-	32	2.2	5.07	19.2	4.19	118.6	46	3.2	5.6	21,2	5.52	156.3	56	3.9	7.7	29.0	6.24	177	85	5.9	8.13	30.8	8.58	243	85	5.9	60	4.1	4	10	5 1	13 6.5	17	16	4.9







External mix nozzles have the highest

flow rates and allow the air and liquid

flows to be adjusted independently.

These nozzles are best where precise

liquid flow is needed. External mix

nozzles can be used on liquids with a

viscosity above 300 cP. Both air and

liquid sides are pressure fed.

# Air Atomizing Spray Nozzles Compressed Air Product



#### Internal Mix Wide Angle Round Pattern - 1/8 NPT





Model: AW8010SS Material: Type 303 Stainless Steel





Model: AW8020SS Material: Type 303 Stainless Steel





Model: AW8030SS Material: Type 303 Stainless Steel





Model: AW8040SS Material: Type 303 Stainless Steel


#### Model AW8010SS, AW8020SS, AW8030SS and AW8040SS

EXAIR's 1/8 NPT internal mix wide angle round pattern atomizing nozzles are great for covering a broad area. They can be adjusted for a light mist or a heavy soaking spray. They are popular for dust mitigation, humidification, and cooling of products, people or livestock in a broad area. These nozzles are also perfect for applying a coating to parts packed in large containers, for example, misting a container of stamped steel parts with oil to prevent oxidation prior to shipment.

#### For pressure fed applications not requiring independent air and liquid control.



1/8 NPT Internal Mix Wide Angle Round Pattern atomizing nozzles are perfect for covering broad areas. They are ideal for dust migration, humidification and a variety of cooling applications.



	10	PS	1/0.7	BA	R Lic	quid	20	PS	/1.4	BAI	R Lie	quid	30	PSI	/2.1	BAI	₹ Lic	uid	40	PSI/	2.8	BAR	Liq	uid	60	PSI	/4.1	BAR	Liq	uid	П			Spr	ay l	Dim	en	sio	ns			
Model	Pre	Air ssur /BA	e 1	PH/ PH	SC	FM/ .PM	Pre	Air ssur l/BAF	9 1	PH/ PH	SC SI	FM/ PM	Pre	Air ssure /BAR		PH/ PH	SC SI	FM/ .PM	Pre	Air ssure /BAR	GF	PH/	SCI	200	Pre	Air ssure /BAR	GF LI	H/ PH		FM/ PM	Air	PSI/	Lic		in	A	Wic		in		Ma Dep feet	pth
S	8	0,0	1,10	0 42	0.31	8.8	14	1.0	1.60	6.1	0.33	9.4	22	1.5	2.00	7.6	0.43	123	30	21	2.00	7.6	0.61	17.2	44	3.0	2.60	9.8	0.69	19.7	8	0.6		0.7						19	2	0.6
105	10	0.3	0.7	0 26	0.27	7.6	16	1,1	1.40	5.3	0.43	12.1	26	1.8	1.80	6.8	0.52	14.7	34	2.3	1.80	6.8	0.65	18.4	48	3.3	2.20	8.3	0.87	24.6	16	1,1	20	1.4	6	15	8	20	10	25	3	0.9
W80	-	-	-	-	-	-	22	1.5	0.60	2.3	0.60	16.9	-	-	-	-	-	-	-	-	_	-	-	-	65	4.5	0.60	2.3	1.56	44.2	26	1.8	30	2.1	7	18	9.0	23	11	28	4	1.2
A	-	-	-	-	-	-	-	-	-	-	-	-	-	-	_	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	65	4.5	60	4.1	7	18	10	25	12	30	4	1,2
s	12	0.8	3.7	3 14.1	1.65	46.7	22	1.5	5.00	19.2	2.28	64.7	30	2.1	6.40	24.2	2.67	75.4	38	2.6	8.00	30.3	3.05	86.2	54	3.7	9.83	37.2	3.81	108	12	0.8	10	0.7	8	20	9.5	24	11	28	6	1.8
AW802055	14	1,0	3.0	0 11.4	1.90	53.9	24	1.7	4,43	16.8	2.54	71.9	32	22	6.00	22.7	2.92	82.6	42	29	6.73	25.5	3.55	100.6	56	3.9	9.33	35.3	4.06	115	24	1.7	20	1.4	8	20	10	25	13	33	8	2.4
W80	-	-	-	-	-	-	26	1.8	3,83	14.5	2.79	79.0	36	2.5	493	18.7	3.43	97.0	46	3.2	5.77	21.8	4.06	115.0	60	41	8.33	31.5	457	129	36	2.5	30	2.1	8	20	10	25	13	33	10	3.0
¥	-	-	-	_	-	-	-	-	-	-	-	-	_	-	-	-	-	_	52	3.6	4.27	16.2	4.82	1365	75	5.2	5.47	20.7	6.47	183	75	5,2	60	4.1	8	20	10	25	13	33	14	4.3
s	10	0.3	6.3	7 24.1	1.3	36.8	20	1.4	7.83	29.8	1.87	52.8	30	21	10.0	37.9	2.52	71.3	40	2.8	11.3	429	3.04	86.0	56	3.9	15.0	56.8	3.21	90.9	12	0,8	10	0.7	7.5	19	10	25	13.5	34	8	2.3
305	12	0.0	5,10	0 19.3	1,65	46.7	22	1.5	6.73	25.5	2.17	61.4	32	2.2	9.33	35.3	2.73	77.A	42	2.9	10.3	39.1	3.30	93.4	58	4.0	145	54.9	3.91	111	22	1.5	20	1,4	7.5	19	10	25	13.5	34	9	2.7
WBO	14	1.5	3,4	7 13.1	1.91	54.1	24	1.7	5.95	22.5	2.43	68.8	36	25	6.83	25.9	3.39	95.8	46	3.2	8.33	31.5	3.95	111,8	65	4.5	120	45,4	4.90	139	36	2.5	30	2.1	7.5	19	10	25	13.5	34	10	3.0
A	-	-	-	-	-	-	26	1.8	4.80	18.2	2.65	75.0	40	2.8	407	15.4	4.04	114.3	50	3.4	5.80	22.0	4.47	126.6	75	5.2	6.73	25.5	6.38	181	50	3.4	40	2.8	7.5	19	10	25	13.5	34	11	3.4
s	18	13	113	3 42.9	2.89	81.8	30	2.1	143	54.9	4.16	117.8	44	3.0	16.3	61,8	5.53	156.5	60	4.1	18.0	68.1	7.04	199,3	80	5.5	22.3	84.5	8.89	252	18	1.2	10	0.7	8	20	10.5	27	12	30	9	2.7
405	26	1.5	9.3	3 35.3	3.74	105.5	38	2.6	12.7	47.9	5.04	142.8	55	3.8	15.0	56.8	6.72	190.2	80	5.5	14.7	55.5	9.18	259.9	90	6.2	21.0	79.5	9.89	280	38	2.6	20	1.4	8	20	10	25	12	30	11	3.4
W80	34	2	6.6	7 25.2	4.58	129.7	60	4.1	6.7	25.2	7.27	205.7	80	5.5	8.67	32.8	9.18	259.9	100	6.9	10.0	37.9	11.1	315.1	-	-	-	-	-	-	55	3.8	30	2.1	7.5	19	10	25	11	28	14	4.3
4		1_		-	12	-	1 -	-	1-	-						-	-	_	_	-	-	-		_	-	_	-	_	-	_	80	5.5	40	2.8	7.5	19	10	25	11	28	15	4.6







# **Air Atomizing Spray Nozzles**

#### Internal Mix Flat Fan Pattern - 1/8 NPT





An INTELLIGENT COMPRESSED AIR Product

Model: AF8010SS Material: Type 303 Stainless Steel





Model: AF8020SS Material: Type 303 Stainless Steel





Model: AF8030SS Material: Type 303 Stainless Steel





Model: AF8040SS Material: Type 303 Stainless Steel

#### Model AF8010SS, AF8020SS, AF8030SS and AF8040SS

1/8 NPT internal mix flat fan pattern atomizing nozzles are designed with efficiency in mind. Especially good for vertical or horizontal assembly lines, their broad thin pattern makes efficient use of your expensive liquids. Their output can be adjusted for a very light film or a heavy coat of whatever liquid you're working with. Whether it's applying paint to hanging sheet metal, or using a water mist to cool a laminate web, flat fan atomizing nozzles cover a wide flat area, ideal for products moving on a conveyor.

#### For pressure fed applications not requiring independent air and liquid control.



1/8 NPT Internal Mix Flat Fan atomizing nozzles can apply a light or heavy film coat to products moving on a conveyor.



10 PSI/0.7 BAR 20 PSI/1. Liquid Liquid Liquid Pressure GPH/ SCFM/ Pressure LPH SLPM											AR			301		2.1 uid	BAR	Ü		40		/2.8 quid	BAR		j	60 1	PSI/-		BAR					_	ray	Di	-	nsio	ns					
Model	Pres		e (			SCFA SLPI		Pres			PH/ PH		SCF SLP		Pres PSI/	sure	GI	PH/	SCI SL		Pre	ir ssure BAR	G	PH/ PH		M/ PM	Pre	Air ssure /BAR	GF	PH/ PH	SCI SL	FM/ PM	Air I	Pres PSI/ VR	Liq	1,000	in	cm	Wie	dth	in	C	De	lax. epth et/m
S	10	0.7	1.6	50 6.	1 0	71 2	0.05	18	1.2	2.13	8	1 1	.11	31.5	28	1.9	2.63	10.0	1.53	43.4	38	2.6	2.87	10.9	1.95	55.1	55	3.8	3.47	13.1	2.57	72.7	10	0.7	10	0.7	14	36	18	46	25	64	1	0.3
105	14	1.0	1.4	13 5.4	4 0	1,76 2	1.6	26	1,8	1.87	7.	1 1	.44	40.7	36	2.5	2.20	8.3	1,94	54.8	46	3.2	2.57	9.7	2.28	64.7	75	5.2	2.93	11.1	3.42	96.9	26	1.8	20	1.4	15	38	22	56	30	76	2	0.6
AF801055	22	1.5	0.5	3 3.	5 1	.03 2	9.1	40	2.8	1.40	5.	3 1	.94	55.0	55	3.8	1.63	62	2.67	75.4	70	4.8	2.07	7.8	3,17	89.8	100	6.9	2.37	9.0	4.33	123	36	2.5	30	2.1	14	36	22	56	30	76	2	0.6
<	-	-	T	-	-	_	-	-	-	-	T-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	100	6.9	60	4.1	22	56.	30	76	46	117	3	0.9
	18	1.2	1.5	53 5.1	8 1	.04 2	9.5	30	2.1	2.30	8.	7 2	2.30	65.1	42	2.9	2.87	10.9	2.05	57.9	55	3.8	3.53	13.4	2.56	725	75	5.2	4.27	16.2	3.25	91.9	18	1.2	10	0.7	14	36	17	43	24	61	2	0.6
205	22	1.5	1.4	10 5.	3 1	.17 3	3.2	36	2.5	1.90	7.	2 1	.90	53.8	46	3.2	2.60	9,8	2.20	62.2	65	4.5	2.67	10.1	2.98	84.4	85	5.9	3.67	13.9	3.69	105	36	2.5	20	1,4	18	46	24	61	32	81	3	0.9
AF802055	26	1.8	1.0	00 31	8 1	.29 3	6.5	40	2.8	1.63	6.	2 1	.63	46.2	50	3,4	2.20	8.3	2.38	67.5	-	-	-	_	_	-	-	_	-	-	-	-	46	3.2	30	21	23	58	29	74	37	94	3	0.9
Ŧ	_	-	T	-		_	_	44	3.0	0.85	3.	2 0	1.85	24.1	-		_	-	-	-	-	-	-	-	100	-	-	-	-	_	-	-	55	3.8	40	2.8	30	76	34	86	47	119	4	1.2
	16	1.1	7.8	3 29	6 1	42 4	10.3	28	1.9	10.8	41	0 2	2.00	56.7	38	2.6	13.0	49.2	2.54	71.8	46	3.2	147	55.5	2.94	83.1	65	45	17.0	64.4	4.00	113	16	1.3	10	0.7	21	53	26	66	32	81	3	0.9
105	18	1.2	7.8	3 29	6 1	.56 4	4.1	30	2.1	10.7	40	4 2	2.14	60.4	40	2.8	13.0	49.2	2.67	75.6	50	3.4	142	53.6	3.20	90.7	70	4.8	16.7	63.1	4.14	117	30	2.1	20	1.4	24	61	30	76	39	99	4	1.2
AF803055	20	1.4	7.5	50 28	4 1	.69 4	7.9	32	2.2	10.3	39	1 2	224	63.5	42	2.9	125	473	2.80	79.3	52	3.6	142	53.6	3.28	92.9	75	5.2	16.5	625	454	128	42	2.9	30	2.1	29	74	36	91	44	112	4	1.2
AF	24	1.7	7.4	13 28	1 1	82 5	1.6	36	2.5	10.3	3 39	1 2	1.49	70.5	46	3.2	125	47.3	2.94	83,1	56	3.9	13.7	51.7	3.47	98.2	85	5.9	16.2	61.2	4.76	135	56	3.9	40	2.8	32	81	39	99	47	119	4	1.2
	12	0.8	11	2 42	3 1	.08 3	0.5	22	1.5	14.8	56	2 1	.56	44,1	34	2.3	17.8	675	2.15	60.9	46	3.2	20.3	77.0	2.71	76.7	65	45	28.0	106	3.61	102	12	0.8	10	0.7	20	51	24	61	31	79	3	0.9
4055	14	1.0	10	3 39	1 1	.19 3	3.6	26	1.8	143	54	3 1	1.72	48.7	38	2.6	17.3	65.6	2.28	64.5	50	3.4	19.7	74.4	2.92	82.8	75	5.2	26.3	99.7	4.14	117	26	1.8	20	1.4	25	64	29	74	36	91	4	1.2
AF804	20	1.4	8.3	3 31.	5 1	51 4	2.7	34	2.3	123	46	7 2	215	60.9	48	3.3	153	58.0	2.75	779	60	4.1	183	69.4	3.36	95.0	90	6.2	233	88.3	4.80	136	60	4.1	40	2.8	26	66	31	79	42	107	6	1.8
Ą	_	-				_		38	2.6	11.7	44	2 2	43	68.7	50	3.4	148	56.2	2.88	81.6	70	4.8	17.0	64.4	3.91	111	100	69	22.7	85.8	533	151	100	69	60	41	32	81	39	99	44	112	7	21







#### External Mix Narrow Angle Flat Fan Pattern - 1/8 NPT





Model: EF8010SS Material: Type 303 Stainless Steel





Model: EF8020SS Material: Type 303 Stainless Steel





Material: Type 303 Stainless Steel





Model: EF8040SS Material: Type 303 Stainless Steel




Model: EF8050SS Material: Type 303 Stainless Steel

#### Model EF8010SS, EF8020SS, EF8030SS, EF8040SS and EF8050SS

1/8 NPT external mix narrow angle flat fan pattern nozzles are great where liquid is needed over a more concentrated area than the internal mix flat fan nozzles. Since they are external mix, airflow and liquid flow can be controlled independently. External mix flat fan pattern nozzles are the best choice where thicker liquids for a heavier coating are needed over a narrow band, such as a paint line.

#### For pressure fed applications with independent air and liquid control.



1/8 NPT External Mix Flat Fan atomizing nozzles are very versatile. They can apply a light or heavy film coating to products on a variety of different products.



Model EF8010SS applies lubricant to a drawer slide.



		10		0.7 B	AR			20		1.4 B	AR			30	PSI/		AR			40	PSI/2		AR					Spr	ay	Dim	ien	sio	ns				L
Model	Pres	iir isure BAR	GPH	uid /LPH	SCI		Pre:	Air ssure /BAR	GPH	uid //LPH	SCE		Pre	Air ssure /BAR	GPH		SCI	FM/ PM	Pre	ir sure BAR	GPH		SCI	FM/ PM	Air!		Liqu PS BA	1/	A		Wid B		in		Ma Dej feet	pth	
s	10	0.7			1.20	34.0	10	0.7			1.20	34.0	10	0.7			1,20	34.0	10	0.7			1.20	34.0	10	0.7	10	0.7	4	10	5	13	4	10	4	1.2	m
105	30	2.1	1.22	46	2.29	64.8	30	2.1	1.64	6.2	2.29	64.8	30	2.1	1.82	6.9	2.29	64.8	30	2.1	2.00	7.6	2.29	64.8	30	2.1	20	1.4	4	10	5	13	6	15	6	1.8	F80
EF801055	50	3.4	1.22	4.0	3,41	965	50	3.4	1,04	0.2	3,41	96.5	50	3.4	1.02	0/9	3.41	96.5	50	3.4	200	7.00	3.41	96.5	30	2.1	30	2.1	4	10	5	13	6	15	6	1.8	EF801055
w	-	-				-	-	-			-	-	-	-			-	-	-	-			-	-	50	3.4	40	2.8	4	10	5	13	8	20	8	2.4	S
s	10	0.7			1.20	34.0	10	0.7			1.20	34.0	10	0.7			1,20	34.0	10	0.7			1.20	34.0	10	0.7	10	0.7	3	8	4.5	11	4	10	4	1.2	m
202	30	2.1	2.00	7.6	2.29	64.8	30	2.1	2.56	9.7	2.29	64.8	30	2.1	2.67	10.1	2.29	64.8	30	2.1	2.93	113	2.29	64.8	30	2.1	20	1.4	3	8	4.5	11	6	15	6	1.8	F80
EF802055	50	3.4	200	7.0	3.41	96.5	50	3.4	230	9.7	3.41	96.5	50	3.4	2.07	10.1	3.41	96.5	50	3.4	2.93	11.1	3.41	96.5	30	21	30	2.1	3	8	45	11	7	18	7	2.1	EF802055
₩	-	-			-	-	-	-			-	-	-	-			-	-		-			-	100	-50	3.4	40	2.8	3	8	4.5	11	8	20	8	2.4	S
S	10	0.7			1.20	34.0	10	0.7			1.20	34.0	10	0.7			1.20	34.0	10	0.7			1.20	34.0	10	0.7	10	0.7	4	10	5	13	5	13	5	15	m
305	30	21		roug.	2.29	64.8	30	2.1	tarina.	200	2.29	64.8	30	2.1		Viana in	2.29	64.8	30	2.1	-	200	2.29	64.8	30	2.1	20	1.4	4	10	5	13	7	18	7	2.1	F80
EF803055	50	3.4	4.47	16.9	3.41	96.5	50	3.4	5.60	21.2	3.41	96.5	50	3.4	6.30	23.8	3.41	96.5	50	3.4	7,67	29.0	3.41	965	30	2.1	30	2.1	4	10	5	13	8	20	8	2.4	EF803055
-	-	-			-	-	-	-			-	-	-	-			-	-	-	-			-	-	50	3.4	40	2.8	4	10	5	13	9	23	9	2.7	SS
s	20	1.4			1.95	55.2	20	1.4			1.95	55.2	20	1.4	-		1.95	55.2	20	1.4			1.95	55.2	20	1.4	10	0.7	5.5	14	7	18	7	18	7	2.1	_
105	30	2.1			2.50	70.8	30	2.1			25	70.8	30	2.1			2.5	70.8	30	2.1			2.5	70.8	30	2.1	20	1.4	5.5	14	7	18	9	23	9	2.7	F80
EF804055	40	2.8	8.67	32.8	3.13	88.6	40	2.8	10.75	40.7	3.13	88.6	40	2.8	13.00	49.2	3.13	88.6	40	2.8	14.42	54.6	3.13	88.6	40	2.8	30	2.1	5.5	14	7	18	10	25	10	3.0	EF804055
1	50	3.4			3.68	104.2	50	3.4			3.68	104.2	50	3.4	1		3.68	104.2	50	3.4			3.68	104	50	3.4	40	2.8	5.5	14	7	18	11	28	11	3.4	SS
	30	2.1			2.28	64.5	30	2.1			2.28	64.5	30	2.1			2.28	64.5	30	2.1			2.28	645	30	2.1	10	0.7	7	18	9	23	9	23	9	27	_
EF805055	40	2.8			2.84	80.4	40	2.8	1		2.84	80.4	40	2.8	1		2.84	80.4	40	2.8			2.84	80.4	40	2.8	20	1.4	7	18	9	23	10	25	10	3.0	F80
808	60	-41	12.6	47.7	3.87	109.6	60	4.1	16.6	62.8	3.87	109.6	60	4.1	20.17	76.4	3.87	109.6	60	4.1	25.00	94.6	3.87	110	70	4.8	40	2.8	7	18	9	23	12	30	12	3.7	805055
1	70	48			4.45	126.0	70	48			4.45	126.0	70	48			4.45	126.0	70	4.8			4.45	126													SS





## **Air Atomizing Spray Nozzles**

#### Siphon Fed Round Pattern - 1/8 NPT





An INTELLIGENT COMPRESSED AIR Product

Model: SR8010SS Material: Type 303 Stainless Steel





Model: SR8020SS Material: Type 303 Stainless Steel





Material: Type 303 Stainless Steel



Model: SR8040SS Material: Type 303 Stainless Steel



Model: SR8050SS Material: Type 303 Stainless Steel


#### Model SR8010SS, SR8020SS, SR8030SS, SR8040SS and SR8050SS

1/8 NPT siphon fed round pattern nozzles are great where no liquid pressure is available and a thin coating is needed at a specific area. Flow rate is adjustable via the adjusting valve. Siphon nozzles work best with a suction height of 36" (914mm) or less. Since these nozzles are siphon fed, the compressed airflow draws the liquid in and mixes it internally. Liquid flow is dependent both on the gravity or suction height and the airflow. Siphon fed round pattern nozzles provide the most liquid flow of any siphon fed nozzle.

#### Siphon or gravity fed for non-pressurized applications.



The amount of liquid applied by the Siphon Fed atomizing nozzles varies depending on valve or inlet pressures.



								Liqu	aid F	low in	GPH	I/LPH									Sp	ray D	imer	sion	s at 8	" (20	cm) S	iphor	ı Heig	ht.
		A	ir			G	ravit	y Hea	ıd					Si	pho	Heig	ght				A	ir			Wi	dth				
Model	Pres PSI/		SCF		18"	46cm	12"	30cm	6	15cm	4"	10cm	8"	20cm	12"	30cm	24"	61cm	36"	91cm		sure BAR	in	A cm	in	B	in	C cm	Max. I fee	
s	10	0.7	0.48	13.6	0.35	1.3	0.33	1.2	0.27	1.0	0.21	0.8	0.21	0.8	0.17	0.7	-	-	-	100	10	0.7	1,5	4	2	5	3	8	1.5	0.5
105	20	1.4	88.0	19.2	0.41	1.6	0.40	1.5	0.43	1.6	0.27	1.0	0.26	1.0	0.24	0.9	0.23	0.9	-	- 77	20	3.4	1.5	4	2	5	3	8	1.5	0.5
SRB01055	40	2.8	1.35	38.3	0.49	1.9	0.48	1.8	0.46	1.7	0.35	1.3	0.32	1.2	0.30	1,1	0.26	1.0	0.23	0.9	40	2.8	1.5	4	2	5	3	8	2	0.5
S	60	4.1	2.12	59.9	0.53	2.0	0,52	2.0	0.50	1.9	0.40	1.5	0.42	1,6	0,33	13	0.28	1.1	0.25	0.9	60	4.1	1.5	4	2	5	3	8	3	0.9
s	10	0.7	0.59	16.7	0.61	2.3	0.53	2.0	0.48	1.8	0.35	1.3	0.33	1.2	0.24	0.9	-	-	-	-	10	0.7	1.5	4	2	5	3	8	1.5	0.5
205	20	1.4	1.16	32.8	0.73	2.8	0.7	2.6	0.66	2.5	0.58	2.2	0.55	2.1	0.4	1.5	0.35	1.3	-	-	20	1.4	1.5	4	2	5	3	8	2	0.6
SR802055	40	2.8	1.9	53.8	0.88	3.3	0.8	3.0	0.76	2.9	0.66	25	0.58	22	0.53	2.0	0.45	1.7	0.38	1.4	40	2.78	1.5	-4	2	5	3	8	3	0.6
v	60	4.1	2.62	74.2	0.96	3.6	0.92	3.5	0.82	3.1	0.75	2.8	0.68	2.6	0.6	2.3	0.52	2.0	0.46	1.7	60	4.1	1.5	4	2	5	3	8	4	1.2
s	10	0.7	0.55	15.6	131	5.0	1.22	4.6	0.96	3.6	0.76	2.9	0.61	23	0.53	2.0	=	-	-	-	10	0.7	1.5	-4	2	5	3	8	1.5	0.5
SR8030SS	20	1.4	1.06	30.0	1.66	6.3	1.59	6.0	1.23	4.7	1.07	4.1	1.13	43	0.92	3.5	0.76	2.9	-	-	20	1.4	1.5	4.1	2	5	3	8	3	0.9
R80	40	2.8	1.86	52.7	1.89	7.2	1.8	6.8	1.53	5.8	1.34	5.1	1.49	5.6	1.19	4.5	1.05	4.0	0.82	3.1	40	2.78	1.5	4	2	5	3	8	4	1.2
S	60	4.1	2.45	69.4	1.98	7.5	1.86	7.0	1.58	6.0	1.46	5.5	1.74	6.6	1.34	5.1	1,29	4.9	1.04	3.9	60	4.1	1.5	4	2	5	3	8	5	1.5
s	10	0.7	1.40	39.5	2.65	10.0	2.43	9.2	2.12	8.0	1.22	4.6	1.00	3.8	-	-	-	-	-	-	10	0.7	1.5	4	2	- 5	3	8	3	0.9
405	20	1.4	2.03	57.5	3.01	11.4	2.86	10.8	2.53	9.6	1.78	6.7	1.57	6.0	1.37	5.2	-	-	-	-	20	14	1.5	4	2	5	3	8	4	1.2
SR804055	40	2.8	3.17	89.8	3.58	13.6	3.55	13.4	3.29	12.0	2.54	9.6	2,48	9.4	2.18	8.2	1.98	75	1,22	4.6	40	2.78	1,5	4	2	5	3	. 8	4	1.2
N	60	4,1	4.42	125	4.09	15.5	3.99	15.1	3.75	14.0	3.03	11.5	2.98	11.3	2.85	11.0	2.59	9.8	2.11	8.0	60	4.1	1.5	4	2	5	3	8	5	1.5
50	10	0.7	1.84	52.1	1.84	7.0	4.16	15.7	3.83	14.0	3.28	12.4	3.1	11.7	2.45	9.3	0.74	2.8	-	-	20	1.4	1.5	4	2	5	3	8	5	1.5
SR805055	20	1,4	2.93	82.9	2.93	11,1	5.53	20.9	3.7	14.0	4.12	15.6	3.51	13.3	3.98	15.0	3.35	12.7	1.8	6.8	40	2.8	1.5	4	2	5	3	8	7	2.1
R80	40	2.8	4.02	114	4.02	15.2	5.83	22.1	4.39	17.0	4.6	17.4	431	16.3	5.08	19.0	4.16	15.7	2.93	11.1	60	4.1	1.5	4	2	5	3	8	9	2.7
N	60	4.1	5.12	145	5,12	19.4	5.92	22.4	5.56	21.0	5.5	20.8	5.09	19.3	533	20.0	5.18	19.6	3.84	14.5	80	5.5	1.5	4	2	5	3	8	10	3.0









#### Siphon Fed Flat Fan Pattern - 1/8 NPT



Model: SF8010SS Material: Type 303 Stainless Steel





Model: SF8020SS Material: Type 303 Stainless Steel





Model: SF8030SS Material: Type 303 Stainless Steel


#### Model SF8010SS, SF8020SS and SF8030SS

1/8 NPT siphon fed flat fan pattern nozzles are great where no liquid pressure is available and a thin coating is needed over a wide band. Flow rate is adjustable via the adjusting valve, Siphon nozzles work best with a suction height of 36" (914mm) or less. Since these nozzles are siphon fed, the compressed airflow draws the liquid in and mixes it internally. Liquid flow is dependent both on the gravity or suction height and the airflow. Siphon fed flat fan pattern nozzles are the best choice where liquid is needed over a broad band such as a moving assembly line.

#### Siphon or gravity fed for non-pressurized applications.



1/8 NPT Siphon Fed Flat Fan atomizing nozzles apply a light coating of liquid over a wide band.



								Liqu	ıid F	low in	GPF	I/LPH									S	oray E	)ime	nsion	s at 8	" (20	cm) S	iphor	n Hei	ght	Г
		A	ir			G	ravit	y Hea	d					Si	pho	n Heig	ght				A	ir			Wi	dth					1
Model		ssure /BAR		FM/ PM	18"	46cm	12"	30cm	6*	15cm	4"	10cm	8"	20cm	12"	30cm	24"	61cm	36"	91cm	Pre:	sure BAR	in	A cm	in	B	in	cm		Depth et/m	
52	10	0.7	1.07	30.3	0.32	1.2	0.30	1.1	0.25	1.0	0.24	0.9	0,23	0.9	0.18	0.7	0.17	0.7	0.14	0.5	10	0.7	7	18	9	23	12	30	2	0.6	9
SF8010SS	20	1.4	1.31	37.1	0.36	1,4	0.35	1,3	0.31	1.2	0.31	1.2	0.30	1.1	0.25	0.9	0.23	0.9	0.19	0.7	20	1,4	7	18	9	23	12	30	2	0.6	9100100
SF	60	4.1	1,69	47.9	0.43	1.6	0.40	1.5	0.35	1.3	0.34	1.3	0.32	12	0.27	1.0	0.26	1.0	0.24	0.9	30	2.1	7	18	9	23	12	30	2	0.6	00
	20	1.4	1.81	51.3	1.52	5.8	1.33	5.0	1.10	42	0.80	0.9	0.76	2.9	0.71	2.7	0.50	1.9	0.36	1.4	20	1,4	8	20	9	23	12	30	2	0.6	Ī
5502	30	2.1	2.30	65.1	1.18	45	1,16	4.4	1.06	4.0	0.85	3.2	0.79	3.0	0.77	2.9	0.52	2.0	0.44	1.7	30	2.1	9	23	11	28	13	33	2	0.6	31002033
SF80205S	40	2.8	2.83	80.2	1,01	3.8	0.90	3.4	0.83	3.1	0.70	2.6	0.67	25	0.63	2.4	0.42	1.6	0.27	1.0	40	2.8	9	23	10	25	13	33	2	0.6	-
50118	50	3.4	3.34	94.6	0.85	3.2	0.71	2.7	0.59	2.2	0.48	1.8	0.41	1.6	0.51	1.9	0.32	1.2	1	-	50	3.4	7	18	8	20	9	23	3	0.9	١
	20	1.4	1.78	50.3	1.45	5.5	1.40	53	1.38	52	0.94	3.6	0.90	3.4	0.77	2.9	0.72	2.7	0.61	23	20	1.4	7	18	8	20	9.5	24	2	0.6	Ī
3005	30	2.1	2.24	63.5	1.16	4.4	1.12	42	1.10	42	1.00	3.8	0.98	3.7	0.86	3.2	0.81	3.1	0.69	2.6	30	2.1	7	18	8	20	95	24	2	0.6	20.00
SF803055	40	2.8	2.75	77,8	0.98	3.7	0.96	3.6	0.85	3.2	0.90	3.4	0.87	3.3	0.79	3.0	0.66	2.5	0.52	2.0	40	2.8	7	18	8	20	9.5	24	3	0.9	-
	50	3,4	3.00	85.0	0.83	3.2	0.79	3.0	0.70	2.6	0.75	2.8	0.69	2.6	0.66	2.5	0.51	1,9	0,44	1.7	50	3.4	7	18	8	20	9.5	24	3	0.9	1



## Order Direct We Ship From Stock

## **Air Atomizing Spray Nozzles**

Model AN1010SS, AN1020SS, AN1030SS, and AN1040SS

#### Internal Mix Narrow Angle Round Pattern - 1/4 NPT







Model: AN1010SS Material: Type 303 Stainless Steel

An INTELLIGENT COMPRESSED AIR Product



Model: AN1020SS Material: Type 303 Stainless Steel



Model: AN1030SS Material: Type 303 Stainless Steel



Material: Type 303 Stainless Steel The amount of liquid applied can be greatly varied by adjusting the valve

or inlet pressures.

precision application of lubricants during assembly, or marking items as they move through an assembly line. Narrow angle round pattern atomizing nozzles are capable of delivering the most liquid of any of our 1/4 NPT internal mix atomizing nozzles. For pressure fed applications not requiring independent air and liquid control. **Dimensions and Airflow Pattern** 

1/4 NPT internal mix narrow angle round pattern nozzles are excellent for spraying a

concentrated mist of liquid. Because of the versatility of their adjustments, they can apply

a heavy coat up close or send a very fine mist over 30 feet away! They are often used for



For more information about droplet size and spray angle, see page 98.

		10		0.7 Juid	BAR	Ů,		20		/1.4 quid		1		30		2.1 uid	BAR			40		/2.8 quid				60 1		4.1 E uid	BAR					_	oray	Dir	nen	sion	15				
Model		iir sure BAR	G	PH/ PH	SCI	FM/ PM	Pre	Air ssun /BAF	e G	PH/ LPH	sc	FM/ PM	Pre	kir ssure /BAR	GI	PH/ PH	SCI	M/	Pre:	Air ssure /BAR	GF	PH/ PH	sc	FM/ PM	Pres	ir sure BAR	G	PH/ PH	SCI	FM/ PM	Air	Pres PSI/ AR	Liq	uid	in	A cm	Wic	dth B cm	in		Mi De fee	pth	
	10	0.7	1.4	5.3	0.6	17	18	1.2	1.8	6.8	0.9	25	24	1.7	2.3	8.7	1.0	28	30	2.1	2.7	10.2	1.2	34	40	2.8	33	12.5	1.5	42	12	0.8	10	0.7	2.3	6	33	8	5.0	13	6	1.8	
1055	12	0.8	1.2	4.5	0.7	20	22	15	1.6	6.1	1.0	28	32	2.2	1.9	7.2	1.3	37	38	2.6	2.3	8.7	1.5	42	52	3.6	2.8	10.6	1.9	54	20	1,4	20	1.4	2.8	7	3.8	10	6.0	15	8	2.4	N
AN1010SS	14	1.0	1.1	4.2	0.8	23	24	1.7	1.5	5.7	1.1	31	36	2.5	1.6	6.1	1.5	42	44	3.0	1.9	72	1.7	48	62	43	23	8.7	2.4	68	34	2.3	30	2.1	3.0	8	43	11	6.5	17	9	2.7	10105
3	Ë	-		-	-	_	26	1.8	13	49	1.2	34	40	2.8	13	49	17	48	48	3.3	1.7	6.4	20	57	20	4.8	19	72	28	79	42 58	2.9	60	4.1	3.5	10	50	13	7.0	17	10	3.0	SS
	16	**	22	140	2.8	70	28	19	-	197	-	112	40	20	60	22.7	F 2	147	48	2.2	70	26.6	50	167	45	4.5	0.0	225	70	100	24	1.7	10	0.7	2.5	6	35	13	5.5	14	11	3.4	H
SS	100	31.3	3./	1700	-		-	100	100	120	100	1113	-	2.0	0.0	221	3.2	147	1000	3.3	7.0	20.5	-	100	60	4.5	9.9	3/3	7,00	190	38	2.6	20	1.4	2.8	7	40	10	65	17	12	3.7	A
AN10205S	20	1.4	25	9.5	3.4	96	36	1000		1000			48	3.3	3.8	14.4		181	65	4.5	3.6	200	8,1	229	80	5.5	6.6	25.0	-	244	55	3.8	30	2.1	3.0	8	4.5	11	6.5	17	13	4.0	N10205
S	24	1.7	1.4	5.3	4.0	113	40	2.8	1,7	6.4	5.7	161	55	3.8	2.1	7.9	7.3	207	75	5.2	1.4	5.3	9.8	277	90	6.2	45	17.0	10.1	286	65	45	40	28	3.5	9	5.0	13	7.0	18	14	4.3	550
	28	1.9	0.6	2.3	46	130	-44	3.0	0.8	3.0	6.4	181	60	4.1	1.1	4.2	8.1	229	80	5.5	0.8	3.0	10.2	289	100	6.9	2.4	9.1	11.3	320	85	5.9	60	4.1	4.0	10	5.5	14	7.5	19	18	5.5	
S	12	0.8	7.8	29.5	1,9	54	20	3,4	12	9 48.8	2.5	71	30	2.1	15.1	57.2	3.4	96	38	2.6	18.0	68.1	4.1	116	54	3.7	23.0	87.1	5.3	150	14	1.0	10	0.7	2.8	7	45	11	65	17	10	3.0	
AN103055	14	1.0	6.0	22.7	2.2	62	24	1.7	9.8	37.1	3.0	85	38	2.6	9,4	35.6	4.5	127	46	3.2	13.1	49.6	5.1	144	65	4.5	17.1	64.7	6.7	190	26	1.8	20	1.4	3.3	8	5.0	13	7.0	18	16	4.9	NI
10	16	1.1	44	16.7	2.6	74	28	1.9	7.0	26.5	3.6	102	42	2.9	7.0	26.5	5.1	144	52	3.6	9.6	36.3	6.0	170	75	5.2	12.3	46.6	8.0	227	40	2.8	30 40	2.1	3.8	10	5.5	14	7.0	18	19	5.8	0305
8	18	1.2	33	12.5	29	82	32	2.2	4.1	15.5	4.4	125	46	3.2	5.0	189	59	167	56	39	7.3	27.6	6.6	187	85	5.9	7.3	27.6	9.6	272	70	3.4	60	43	4.0	10	6.0	15	8.0	20	26	7.0	SS
i	14	1.0	-	23.8		99	20	1.4					28	1.9	33.0	125	3.0	96	32	22	46.5	176	28	79	42	2.9	66.0	250	27	76	14	1.0	10	0.7	3.0	8	45	11	6.5	17	17	5.2	-
550		1.1	3.0		42		24	-		0 497			32	-	24.0	908	2.4	130	40		30.0		5.1	144	50		540		41	122	24	1.7	20	1.4	3.5	9	6.0	15	7.5	19	23	6.4	A
AN104055	16			11.8	4.2	119	120		100	-				1000		2000	4.6		-	1770	- Contra	10000	222	-	2000	3.4	10000	-			34	2.3	30	2.1	40	10	6.5	17	8.0	20	26	7.9	N104
A	-	-	-	-	-	-	26	1.8	-	200	-	139	36	2.5		47.3		167	46	3.2	-	625	6.8	193	58	4.0	39.0	148	6.6	187	44	3.0	40	2.8	45	11	7.0	18	8.5	22	30	9,1	055
	-	-	-	-	-	-	28	1.9	5.5	20.8	5.6	159	40	2.8	6.0	22.7	7.4	210	50	3.4	10.3	39.0	8.2	232	70	4.8	15.8	60	10.2	289	64	4.4	60	4.1	5.0	13	7.0	18	9.0	23	35	10.7	



## Air Atomizing Spray Nozzles COMPRESSED AIR




#### Internal Mix Wide Angle Round Pattern - 1/4 NPT







Model: AW1010SS Material: Type 303 Stainless Steel



EXAIR's 1/4 NPT internal mix wide angle round pattern atomizing nozzles are great for covering a broad area. They can be adjusted for a light mist or a heavy soaking spray. They are popular for dust mitigation, humidification, and cooling of products, people or livestock in a broad area. These nozzles are also perfect for applying a coating to parts packed in large containers, for example, misting a container of stamped steel parts with oil to prevent oxidation during shipment.

For pressure fed applications not requiring independent air and liquid control.



Model: AW1020SS Material: Type 303 Stainless Steel




Model: AW1030SS Material: Type 303 Stainless Steel



Model: AW1040SS Material: Type 303 Stainless Steel



A Model AW1030SS is used to keep dust down during charcoal briquette production.



		10	PSI/	0.7 l uid	BAR			20		1.4 I uid	BAR			301		2.1 I uid	BAR	+		40		2.8 juid	BAF				SI/4	I.1 B	AR					Sį	oray	y Di	mer	nsio	ns				
Mondal	Pre	Air ssure /BAR	G	PH/ PH	SCF		Pres	Air ssure /BAR	G	PH/ PH	SCI	FM/ PM	Pres	ir sure BAR	GI	PH/ PH	SCF		Pres	ir ssure/BAR	G	PH/ PH	sc	FM/ PM	Pres	ir sure BAR	GP	H/	SCF	M/	Air	Pres PSI/ AR	Liq	_	in	A.	Wi	dth	in	C	Ma Dep feet	oth	
	. 8	0.6	1.8	6.8	0.3	8	14	1.0	2.4	9.1	0.4	11	22	1.5	2.7	10.2	0.5	14	30	2.1	3.0	11.4	0.7	20	44	3.0	3.5	13.2	0.9	25	10	0.7	10	0.7	7	18	9	23	14	36	5	1.5	
990	10	0.7	1.6	6.1	0.4	11	18	1.7	2.1	7.9	0.5	14	30	1000		100		20	38	2.6	26	0.8	0.8	23	55	3.8	3.1	11.7	11	31	20	1.4	20	1,4	9	23	11	28	15	38	6	1.8	W
3710106	10	1000	100	5.7	1000		22	1.5	-	10000	1000	3000	100	200	1.9	1000	10000	20	1000	1555	200	7.9	2000	1000	65	NO.	2.5	0.0	* *	27	34	2.3	30	2.1	10	25	12	30	16	41	8	2.4	2
AVA	12	0.8	-	-	1000	11	22	7700	1177	7.2	-	1	-	2.5	1.9	7.2	8.0	23	46	3.2	2.1	7.9	1.0	28	00	4.5	2.5	9.5	1.5	3/	42	2.9	40	2.8	10	25	12	30	16	41	9	2.7	250
	14	1.0	1.3	4.9	0.5	14	26	1.8	1.6	6.1	0.7	20	40	2.8	1.6	6.1	0.9	25	50	3.4	1.9	7.2	1,1	31	75	5.2	2.1	7.9	1.5	42	60	4.1	60	4.1	10	25	12	30	16	41	12	3.7	50
	12	0.8	2.8	10.6	1.7	48	22	1.5	4.0	15.1	2.3	65	30	2.1	5.4	20.4	2.5	71	38	2.6	6.4	24.2	2.9	82	54	3.7	8.5	32.2	3.5	99	12	0.8	10	0.7	10	25	13	33	17	43	9	2.7	D
03060	14	1.0	1.6	6.1	2.0	57	24	1.7	3.1	11.7	2.5	71	34	2.3	3.8	14.4	3.2	91	44	3.0	4.4	16.7	3.9	110	58	4.0	7.0	26.5	4.1	116	24	1.7	20	1.4	11	28	13	33	18	46	11	3.4	¥
9	2						26	1.8	20	7.6	20	92	38	2.6	10	6.8	40	112	48	22	26	9.8	4.6	130	65	45	SA	20.4	52	147	34	2.3	30	2.1	11	28	13	33	18	46	12	3.7	02
1			-		-		20	1.0	2.0	-	-	02	-			0.0	71.00	113	70	21.0	2.0	3.0	100	1,50	00	7.0	3.7	20.4	3.6	177	46	3.2	40	2.8	11	28	14	36	18	46	14	4.3	SS
L	-	***	***	***	200	***		***	***	***	***	200	40	2.8	0.9	3.4	4.5	127	52	3.6	1.0	3.8	5,4	153	75	5.2	1.7	6.4	7.1	201	60	4.1	60	4.1	11	28	14	36	19	48	16	4.9	
	10	0.7	6.8	25.7	1.1	31	20	1.4	8.5	32.2	1.5	42	30	2.1	9.0	34.1	2.0	57	40	2.8	10.0	37.9	2.6	74	56	3.9	15.0	56.8	2.9	82	-	8.0	10	0.7	10	25	13	33	18	46	9	2.7	D
WINDOCC	12	0.8	4.5	17.0	1.4	40	22	1.5	6.0	22.7	1.9	54	34	2.3	5.8	22.0	2.8	79	44	3.0	7.0	26.5	3.4	96	60	4.1	12.0	45.4	3.5	99	22	1.5	20	1.4	11	28	13	33	18	46.	11	3.4	Z
2	14	1.0	2.2	8.3	1.9	54	24	1.7	4.5	17.0	2.3	65	38	2.6	2.4	9.1	3.8	108	48	3.3	3.7	14.0	42	119	70	4.8	5.0	18.9	5.6	159	34	2.3	30	2.1	11	28	14	36	18	46	13	4.0	030
2		-	-	-	1	-	26	1.8	-	9.8	2.7	76	40	-		F 2	4.3	122	63	-	10	6.7	6.3		80		Δ.0	3.0	77	210	46	3.2	40	2.8	-11	28	14	36	19	48	15	4.6	SS
-		***	1				1000		11100	-	2.7	1000		2.8	1,4	2.2		122	32	3.6	1.5	3.7	3.2	147	au	5,5	0.0	3.0	1.1	210	05	4.5	60	4.1	11	28	14	36	20	.51	19	5,8	-
	24	1.7	6.0	22.7	5.4	153	38	2.6	9.3	35.2	7.7	218	48	3.3	15.5	58.7	8.4	238	60	4.1	19.3	73.1	10.3	292	85	5.9	24.0	91.0	13.8	391	28	1.9	10	0.7	10	25	14	36	16	41	16	4.9	P
4000	28	1.9	4.0	15.1	6.1	173	44	3.0	5.5	20.8	9.1	258	56	3.9	9.0	34.1	10.6	300	70	4.8	12.0	45.4	12.8	362	90	6.2	21.3	80.6	15,2	430	46	5.2	20	1.4	11	28	14	36	18	46	16	3.5	2
AW/10		2.1	2.5	9.5	6.7	190	48	3.3	3.5	13.2	10.0	283	62	4.3	6.0	22.7	12.1	343	80	5.5	6.5	24.6	14.7	416	95	6.6	18.5	70.0	16.5	467	60	4.1	30	Z1	12	30	16	41	21	53	21	0.4	040
1	32	2.2	2.0	7.6	7.3	207	52	36	1.0	72	10.8	306	70	4.8	28	10.6	13.4	379	90	62	28	10.6	17.2	487	100	6.9	15.8	50.8	173	490	75	5.2	40	4.8	12	30	16	41	22	58	25	7.5	SS







## **Air Atomizing Spray Nozzles**

#### Internal Mix Flat Fan Pattern - 1/4 NPT





An INTELLIGENT COMPRESSED AIR Product



Model: AF1020SS Material: Type 303 Stainless Steel




Model: AF1030SS Material: Type 303 Stainless Steel



Model: AF1040SS Material: Type 303 Stainless Steel



Model: AF1050SS Material: Type 303 Stainless Steel





A Model AF1030SS is used to spray an anti-corrosion coating on stamped steel parts as they travel on a conveyor.



designed with efficiency in mind. Especially good for vertical or horizontal assembly lines, their broad thin pattern makes efficient use of your expensive liquids. Their output can be adjusted for a very light film or a heavy coat of whatever liquid you're working with. Whether it's applying paint to hanging sheet metal, or using a water mist to cool a laminate web, flat

fan atomizing nozzles cover a wide flat area, ideal for products moving on a conveyor. For pressure fed applications not requiring independent air and liquid control.





		101		0.7 I uid				20		I/1. iqui		AR			301		2.1 uid	BAR			40	PSI.	/2.8 guid				60 F	SI/4 Liq		AR	Į.	_		_	pray	Di	mer	nsio	ns	L		
Model	Pres	ir sure BAR	1	PH/ PH		FM/ PM	Pre	Air essur I/BA	e	GPH LPH	1/	SCF	DAA	Pres	ir ssure BAR		PH/ PH		FM/ PM	Pre	Air ssure /BAR		PH/ PH	SCI	FM/ PM	Pre	Air ssure /BAR			SCFA SLPI	A/ A	ir PS		ire iquid il/BAF	in	A	Wi	dth B	in	C	De	ax. pth t/m
120	10	0.7	1.6	6.1	0.7	20	18	13	2	1 7	9	1.0	_	28	1.9	2.4	9.1	1.4	40	38	2.6	2.6	9.8	1.7	48	55	3.8	3.2	12.1	2.2	52	6 1	1 10	0.7	9	23	12	30	15	38	5	1,5
055	14	1.0	1.4	5.3	0.9	25	26	1.8	1	7 6	4	1.3	37	40	2.8	1.8	6.8	1.8	51	50	3.4	2.0	76	2.1	59	75	5.2	2.2	-	3.0	-	00 2	1 20	1.4	11	28	13	33	17	43	6	1.8
F1010	10	1.0	1.7	1000	-	23	34		100			1.3	10000	48	10000	1.4	-	1110	-	60	100		6.1		71	90	7	ANCH	100		02	0 2	8 30	2.1	12	30	14	36	20	51	6	1.8
AF	18	1,2	1.1	4.2	4	31		-	1		,5	1.7	48	-	3.3		annound.	-	-	20	4,1	1110	411	2.5	11		6.2	1.6	6.1	3.6 1	02	30 3	4 40	0 2.8	14	36	16	41	22	56	7	2.1
-	22	1.5	0.8	-	-	37	40	_	-	_	_	1.9	54		3.8	1.0	3.8	2.4	-	70	-		4.5	3.0	85	100	-	1.3	4.9	4.1 1	16	35 5	9 60	0 4.1	14	36	17	43	23	58	7	2.1
S	12	0.8	2.4	9.1	0.7	20	20	1.4	3.	4 1	2.9	0.9	25	30	2.1	3.9	14.8	1.2	34	38	2.6	4.6	17.4	1.4	40	65	4.5	4.7	17.8	2.2		6 1			11	28	14	36	19	48	5	1.5
F102055	16	1.1	1.8	6.8	0.9	25	28	1.5	2.	4 9	1.1	1.2	34	38	2.6	2.9	11.0	1.5	42	50	3.4	3.2	12.1	1.9	54	75	5.2	3.7	14.0	2.6	74	00 2	0 30	-	14	36	1/	45	21	53	-6	1.8
10	18	1.2	1.5	5.7	1.0	28	32	2.3	1	8 6	.8.	1.5	42	46	3.2	2.0	7.6	1.9	54	60	4.1	2.2	8.3	2.3	65	85	5.9	2.8	10.6	3.0	35	00 3	4 40	2.1	16	41	10	AR	26	66	7	3.1
A	20	1.4	1.3	4.9	1.1	31	36	2.	1	4 5	3	1.7	48	50	3.4	1.6	6.1	2.1	59	70	4.8	1.4	5.3	2.8	79	95	6.6	2.1	7.9	3.6 1	02	10 5	5 60	0 4.1	16	41	21	53	29	74	8	2.4
13	16	1.1	4.5	170	2.0	57	28	1 15	6	0 2	2.7	28	79	38	2.6	70	36.5	25	99	46	3.2	8.5	32.2	40	113	65	4.5	11.0	41.6	5 3 1	50	10. 1	4 10	0.7	11	28	14	36	19	48	10	3.0
355	20		11.0	12.5	-	-	-	2.7	-	-			88	-	2.9		-	-	100	1	-	7.5	-	-	127					5.7 1	61	32 2	2 20	1.4	15	38	17	43	23	58	11	3.4
F10305		-	1000	-	10000	100		1000	1	100	4110	270	1000	1000	10000	-	10000		-	1000	1000	1	1000		140	200	1000		-		- B	12 2	9 30	2.1	16	41	21	53	29	74	12	3.7
5	24	- 22	2.4	1000	2.7	-	34	-	+	5 1	-		-	-	3.2	210	-	-	-	-	100	-	23.8	111111	139	80	210	1717	30.3	6.4 1	81	4 3	7 40	2.8	19	48	25	64	33	84	14	4.3
_	28	1.9	1.5	5.7	3.1	88	36	_	-	.9 1	_			48	3.3	5.1	19.3	4.4	125	60	4.1	6.0	22.7	5.2	147	90	6.2	6.4	24.2	7.2 2	04	5 5	2 60	0 4.1	20	51	26	66	35	89	15	4.6
S	12	0.8	8.1	30.7	1.4	40	22	1.5	12	0.4	5.4	1.9	54	34	2.3	13.1	49.6	2.7	76	46	3.2	14.3	54.1	3.4	96	65	4.5	18.3	69.3	4.5 1	27	6 1	1 10	0.0	14	36	18	46	24	61	10	3.0
4055	16	1.1	5.9	22.3	1.8	51	30	2.1	7.	1 2	6.9	2.7	76	42	2.9	8.9	33.7	3,4	96	54	3.7	10.3	39.0	4.1	116	80	5.5	11.9	45.0	5.9 1	67	2 2	2 20	100	15	38	19	48	27	69	12	3.7
2	18	1.2	5.0	18.9	2.0	57	34	2.3	5	6 2	1.2	3.1	88	48	3.3	6.3	23.8	4.1	116	60	4.1	7.9	29.9	4.8	136	90	6.2	8.5	32.2	6.8 1	93	60 3	2 30	2.1	20	63	23	58	30	76	15	4.0
A	22	1.5	3.3	12.5	2.4	68	38	1 26	4	1 1	5.5	3.5	99	52	3.6	5.0	18.9	4.5	127	70	4.8	4.6	17.4	5.8	164	100	6.9	6.0	22.7	7.9 2	24	80 5	9 60	0 41	21	53	27	69	36	91	15	4.6
155	14	1.0	-	33.3	-	-	26	-	-	54				34	-	-	-	4.6	-	-	100		114	_	136	58	-	42.0	150	5.5 1	56	4 1	0 10	0.7	14	36	18	46	23	58	10	3.0
155	14	100	-	-	1000	-		-	+	-	-	-	100	-			-	100	-	1	-	-			100	-	1100	1000	100			-	8 20	00	15	38	19	48	24	61	13	4.0
1050	16	1,1	5.3	20.1	3.7	105	28	1.5	7.	8 2	9.5	4.9	139	-	-	-	-		139	46	1000	20.5	-	-	173	-	-	10000	Laborate Control	6.8 1	-d 6	8 2	6 30	2.1	16	41	20	51	25	64	16	4.9
E	***	200	***	-	***	149						***	***	40	2.8	9.0	34.1	6.1	173	50	3.4	13.5	51,1	7.3	207	70	4.8	21.0	79.5	8.7 2	46	18 3	3 40	0 28	17	43	20	51	27	69	18	5.5
4	***	-	+++	***	***	+++			1	- 4	40	***	***	42	2.9	6.3	23.8	7.0	198	54	3.7	7.5	28,4	8.4	238	80	5.5	8.5	32.2	11.2 3	17	0 4	8 60	0 4.1	17	43	21	53	29	74	19	5.8





#### Internal Mix Deflected Flat Fan Pattern - 1/4 NPT




#### Model AD1010SS

1/4 NPT internal mix deflected flat fan nozzles are designed for applications where space is at a premium. The flat fan pattern sprays at a right angle to the nozzle's orientation, allowing spray to be placed precisely where it's needed in close quarters. These nozzles are ideal for coating the inside of enclosures and ductwork.

For pressure fed applications not requiring independent air and liquid control.



A Model AD1010SS is used to apply a protective coating to wood panels.



		10		0.7 l	BAR			20		1.4 I uid	BAR			301		2.1 uid				40		/2.8 guid	BAR			60 F		4.1 E uid	AR					_	ray	Dir	nen	sio	ns			
Model	Pre: PSI		G	PH/ PH	SCE	M/	Pre	Air ssure /BAR	G	PH/ PH	SC	FM/ PM	Pres PSI	ir sure BAR	G	PH/ PH	SC	FM/ PM	Pre	Air ssure /BAR	G	PH/ PH	SCI	FM/ PM	Pre	Air ssure /BAR	GF	PH/ PH	SCI	M/PM	Air		Lic	1000	in	A	Win	dth	in	cm	M De in/	pth
2	6	0.4	3.0	11.5	1.4	41	14	1.0	4.0	15.1	2.3	66	22	1.5	4.6	17.6	3.2	90	26	1.8	5.7	21.4	3.5	98	38	2.6	6.9	26.0	4.7	133	12	0.8	10	0.7	9	23	14	36	16	41	36	91
ŝ	g	0.6	2.7	10.1	1.8	50	18	1.2	3.3	12.4	2.9	82	26	18	41	15.4	3.7	105	32	22	49	18.6	4.3	121	54	3.7	53	20.1	66	188	22	1.5	20	1,4	11	28	13	33	16	41	42	107
5	-	-	-		110		10		0.0	12.17	2.0	02			-	-	-	-	-	-		-	-	_	-		_	_	_	_	34	2.3	30	2.1	8	20	12	30	16	41	45	114
5	10	0.7	2.2	8.3	2.1	59	20	1.4	2.9	11.0	3.2	91	30	2.1	3.4	12.9	4.3	122	38	2.6	4.2	15.7	5.1	144	62	4.3	4.6	17.3	7.8	221	46	3.2	40	2.8	9	23	12	30	15	38	48	122
4	12	0.8	1.8	6.9	2.4	69	22	1.5	23	8.9	3.6	101	34	23	2 R	10.4	5.0	140	46	3.7	2.7	10.3	6.3	180	70	4.8	3.1	11.9	9.1	258	70	48	60	41	12	30	15	28	18	46	42	107

#### Internal Mix 360° Hollow Circular Pattern - 1/4 NPT



Model: AT1010SS Material: Type 303 Stainless Steel




This 360° circular pattern nozzle can be used to coat inside diameters or cover a broad area of over 4' (1219mm)

#### Model AT1010SS

1/4 NPT internal mix 360° nozzles are designed for applications where the spray pattern must be oriented away from the nozzle in all directions. 360° nozzles are ideal where a smooth, even coating is needed on the ID of pipe or similar ductwork. They also work great for operations where a mist over a broad area is needed, such as dust suppression, humidification and cooling.

For pressure fed applications not requiring independent air and liquid control.



	155	707	1777	300				7.55																													
	10	PSI	0.7	BAR	Liqu	ıid	2	o PSI	/1.4	BAR	Liqu	ıid	3(	PSI	/2.1	BAR	Liqu	id	40	PSI	/2.8	BAR	Liqu	iid	61	D PSI	4.11	BAR	Liqu	id	5	pra	y Di	men	isior	15	
	A	ir						Air			- A	_		ir						Air				-		lir .	_		1/6			Pres	sure		Dian	neter	
Mode	Pres		GPH	/LPH		FM/ PM	Pre			VLPH	SC	FM/ PM	Pres		GPH	/LPH	SCI	PM	Pres		GPH	/LPH	SCI	FM/ PM	Pres	ssure BAR	GPH	/LPH	SCF	PM	PSI/		Liq PSI/	uid BAR	in	cm	
	20	1.4	4.5	16.8	4.3	121	34	2.3	7.3	27.5	6.4	182	50	3.4	8.1	30.6	8.9	251	60	4.1	11.5	43.5	10.0	283	85	5.9	14.7	55.7	13.3	376	20	1.4	10	0.7	36	.91	_
2	24	17	2.6	9.7	5.3	150	38	2.6	52	10.6	72	206	56	3.9	5.4	20.3	10.0	285	70	4.8	71	26.8	11.0	225	90	62	12.7	47.9	141	209	34	2.3	20	1,4	39	99	3
5				9.1	3.3	150		-	_	-	_	-	_	-	_	_	_	_	-	-		-		-			-		-	-	50	3.4	30	2.1	44	112	10105
5	26	1.8	2.0	7.5	5.7	162	42	2.9	3.6	13.5		and the same	60	and the last		15.7		and the last	and the same	NAME OF TAXABLE		15.4		Transition in	and other land	NAME OF TAXABLE		40.2	0.000	ALCOHOL: UNK	60	4.1	40	2.8	49	124	So
•	28	1.9	1.6	5.9	6.2	176	48	3.3	2.1	7.8	9.3	264	70	4.8	2.0	7.4	12.6	356	90	6.2	2.0	7.7	15.5	439	100	6.9	8.9	33.7	15.8	449	85	5.9	60	4.1	53	135	S



FAX (513) 671-3363 \* E-mail: techelp@exair.com \* www.exair.com



## **Air Atomizing Spray Nozzles**

#### External Mix Round Pattern - 1/4 NPT



An INTELLIGENT COMPRESSED AIR Product

Material: Type 303 Stainless Steel



Model: ER1020SS Material: Type 303 Stainless Steel



Model: ER1030SS Material: Type 303 Stainless Steel



Model: ER1040SS Material: Type 303 Stainless Steel



Model: ER1050SS Material: Type 303 Stainless Steel


#### Model ER1010SS, ER1020SS, ER1030SS, ER1040SS and ER1050SS

1/4 NPT external mix round pattern nozzles are great where a high volume of liquid is needed over a specific area or general area, but not in a flat pattern. Applications include spot treatments of parts, covering irregularly shaped objects or covering a container of parts with a heavy coat. They are also an excellent choice for controlling heavy dust and particulates. Since they are external mix, airflow and liquid flow can be controlled independently.


For pressure fed applications with independent air and liquid control.



(2) Model ER1020SS atomizing nozzles are used to apply a fire retardant coating to wood trim.



		31	PSI/O	.2 B uid	AR			51		0.3 Juic		R		101		0.7 uid	BAR	1		201	PSI/	1.4 uid		K.	17	40 F	SI/2 Liq		BAR					Spi	ay	Din	nen	sior	ns			
_			Lite	uiu			-	Air	-	, une		_	1	\ir	Liq	uiu		-	1	\ir	Line	-		-	-	ür	Liq	-			-91	Pres	ure	4			Wie	dth			M	
Mode	Pres	Air ssure /BAF	2 11	H/	SCF		Pre P	ssun SI/ AR		PH/ PH		CFM/ LPM	Pre:	ssure SI/ AR		PH/	SCI		Pre P	SI/ AR		PH/ PH	SCI	PM	Pres	SUre SI/ AR	GP LP		SCE		Air I		PSI BAI	1	A	cm	in	cm	in	cm	Dep	pth
52	5	0.3			0.9	25.5	5	0.3			0.	9 25.5	10	0.7			1.3	36.8	20	1.4			1.9	53.8	20	1.4			1.9	53.8		0.7	-		3.0	7.6	4.3	10.9	6.3	16.0	9	2.7
ER1010SS	10	0.7	1.0	3.8	1.3	36.8	10	0.7		53	1.	3 36.8	20	1.4	1.9	-	1.9	53.8	40	2.8		10.2	3.0	85.0	40	2.8	3.8		3.0	85.0	20	1.4	-	0.3	13	8.4	4.5	11.4	6.8	17.3	11	3.4
110	20	1.4		3.8	1.9	53.8	30	2.1	1.4	3.3	2	4 68.0	40	28	1.9	12	3.0	85.0	60	4.1	2.1	10.2	4,1	116	60	4.1	3,8	14,4	4.1	116	40	2.8	10 (	0.7	5	8.9	5.3	13.5	7.5	19.1	13	4.0
m	40	2.8			3.0	85.0	50	3.4			3.	5 99.1	60	4.1			4.1	116	90	6.2			5.7	161	90	6.2			5.7	161	60	4.1	40	2.8	40	10.2	5.5	14.0	8.0	20.3	15	4.5
S	6	0.4			0.9	25.5	10	0.7		П	1.	3 36.8	10	0.7			1.3	36.8	20	1.4			2.9	82.1	40	2.8			3.0	85.0	10	0.7	3 (	0.2	3.8	9.7	5.0	12.7	7.5	19.1	10	3.0
202	10	0.7			13	36.8	20	1.4			. 1.	8 51.0	20	1.4			1.9	53.8	40	2.8	in a		3,1	87.8	60	4.1			4.1	116	20	1.4	5 (	3.3	10 1	10.2	5.8	14.7	7.0	17.8	12	3.7
ER102055	30	21	25	9.5	2.4	68.0	40	2.8	3.2	12.	3.	1 87.8	40	2.8	4.3	16.3	3.1	87.8	60	4.1	5.9	22.3	4.1	116	80	5.5	7.5	28,4	5.3	150	40	2.8	10 (	0.7	1.3 1	10.9	6.0	15.2	8.3	21.1	15	4.6 4.6
5	50	3.4			3.6	102	60	4.1	Ш		4.	1 116	60	4.1			4.1	116	90	6.2			5.9	167	90	6.2			5.9	167	40	2.8	20	1.4	1.5	11.4	6.0	15.2	8.3	21.1	15	-
s	10	0.7			4.0	113	10	0.7		П	4	0 113	15	1.0			4.9	139	30	2.1			7.7	218	40	2.8			9.5	269	80	4.1	40 3	2.8	1.0	12.7	6.0	16.5	8.5	21.6	16	4.9
305	20	1.4	100	333	6.0	170	20	1.4	137		6	0 170	30	2.1	1	330	7.7	218	40	2.8		100	9.5	269	50	3.4	942	1000	11.2	317	40	2.8	5 1	3.3	45	11.4	6.5	16.5	8.5	21.6	23	70
ER1030SS	40	2.8	44	16.7	9.5	269	40	2.8	5.5	201	9	5 269	SO	3.4	7.6	28.8	11.2	317	60	4.1	11.0	41.6	11.7	331	60	4.1	14.0	53.0	11.7	331	40	2.8	10	0.7	4.8	12.2	6.8	17.3	9.0	22.9	24	7.3
=	50	3.4			11.2	317	60	4.1			11	.7 331	70	4.8			13,4	379	80	5.5			15.3	433	80	5.5			15.3	433	60	4.1	20	1.4	1.5	11.4	6.8	17.3	9.0	22.9	29	8.8
s	15	1.0			4.9	139	20	1.4		П	6	0 170	30	2.1			7.7	218	40	2.8			9.5	269	50	3.4			11.2	317	60	4.1	40	2.8	5.3 1	13.5	7.0	17.8	9.3	23.6	30	9.1
ER1040SS	30	2.1			7.7	218	30	2.1			7.	7 218	40	2.8			9.5	269	50	3.4			11.2	317	60	4.1			11,7	331	20	1.4	3 0	0.2	1.8	14.7	7.5	19.1	10.0	25.A	15	4.6
10	40	2.8	10.0	37.9	9.5	269	40	2.8	13.5	51.	9.	5 269	60	4.1	18.8	71.2	11.7	331	60	4.1	27.6	104	11.7	331	70	4.8	31.0	117	13.4		60	2.8	10	3.3	10 1	15.2	8.0		10.3	26.2	19	5.8
8	50	3.4			11.2	317	60	4.1			11	.7 331	80	5.5		1	15.3	433	80	5.5			15.3	433	80	5.5			15.3	433	60	4.1	20	1.4	5.5	14.0	7.0	17.8	9.0	22.9	24	7.3
10	40	2.8	-		14.0	396	55	3.8			18	.0 510	-	4.5			21.0	595	80	5.5			25.3	716	_	-			-	-	80	5.5	40	2.8	1.5	11.4	6.5	16.5	9.5	24.1	30	9.3
ER1050SS	50	3.4			16.8	470	65	45			21	0 595	70	4.8			22.3	631	90	6.2		1	27.9	790	-	_			-	-	40	2.8	3 (	0.2	5.5 1	16.5	8.8	22.4	11.0	27.9	23	7.0
105	60	4.1	18.0	68.1	19.7	558	70	4.8	26.0	98.	22	3 631	80	5.5	41.0	155		716		-	60.0	227	-	-	-	-			-	-	70	4.8	5 (	0.3	1.5	6.5	9.0	22.9	10.0	25.4	28	8.5
8	65	45			21.0	595	80	5.5			25	3 716	90	6.2			27.9	790	-	_			-	_	-	_			-		90	5.5	10 (	0.7	6.5 1	16.5	9.0	20.3	11.0	27.9	30	9.1











#### External Mix Narrow Angle Flat Fan Pattern - 1/4 NPT



Model: EF1010SS Material: Type 303 Stainless Steel

#### Model EF1010SS, EF1020SS, EF1030SS and EF1040SS

1/4 NPT external mix narrow angle flat fan pattern nozzles are great where a high volume of liquid is needed over a concentrated area. Since they are external mix, airflow and liquid flow can be controlled independently. External mix narrow angle flat fan pattern nozzles are the best choice where thicker liquids for a heavy coating are needed over a narrow band, such as a paint line.

### For pressure fed applications with independent air and liquid control.



Model: EF1020SS Material: Type 303 Stainless Steel



Model: EF1030SS Material: Type 303 Stainless Steel



Model: EF1040SS Material: Type 303 Stainless Steel



A Model EF1020SS is used to supply humidification for a corrosion test

+	2.69*
2.25"	
0.90*	0.93* 24mm
25mm	
1.69" 117 108	
43mm LHL	
	152mm
1/A ENDT Liquid Inlet	229mm
1/4 / Hr 1 Enquire titlet -	15" 381mm
	57mm 0.90° 23mm

		31			BAR		- 8	5 P			BAR			10 F				1		20			BA	R		40 1			BAI	ŧ				5	pray	y Dir	mer	rsio	ns				
70		Air		puid PH/	SCFM			ir		uid PH/	sci			ir.	GF	uid		FM/		Air	Т	pH/				Air	Liq				36	Pres	sure Liq				Wi	dth				ax.	
Mod	P	ssun SI/ AR		PH/	SLPM		PS	SI/ AR		PH/	SLI			sure SI/ AR		H/		PM/	F	ssun SI/ IAR		PH/ PH		FM/ PM	P	ssure SI/ AR	LP		SL	PM/		PSI/ AR	P:	SI/	in	A cm	in	B cm	in	cm		pth t/m	
	5	0.3			0.8 22	7	10	0.7			1.0	28.3	15	1.0			13	36.8	25	1.7			1.8	51.0	45	3.1			2.7	76.5	-	0.3	3	0.2	4.0	10.2	5.8	14.7	9.5	24.1	6	1.8	
EF101055	10	0.7			1.0 28	3	20	1.4	100		15	42.5	25	1.7	2.2	-	1.8	51.0	40	2.8			2.5	70.8	60	4,1	-		3.4	96.3	25	1.7	5	0.3	5.5	-	-	20.3	1415		12	3.7	EF10
F10	20	1,4		3.8	1.5 42	5	30	2.1	1.4	53	2.0	56.6	40	2.8	1.9	7.2	25	70.8	60	4.1	21	10.		96.3	75	5.2	3.8		4.1	116	25 50	1.7	20	1.4	6.3	16.5		-	and before	33.0	-	4.0	105
ш	40	2.8			2.5 70	8	50	3,4			2.9	82.1	60	4.1			3,4	96.3	90	6.2			4.7	133	95	6.5			5.1	144	75	5.2	40	2.8	6.5	-	-	-	-	33.0	-	5.5	S
	10	0.7			1.0 28	3	15	1.0			1.3	36.8	20	1.4		-	1.5	42.5	35	2.4			2.2	62.3	50	3.4			2.9	82.1	10	0.7	3	0.2	4.5	11.4	7.0	17.8	11.0	27.9	9	2.7	
950	20	1.4	4		1.5 42	-11	1000	1.7			1100	51.0	-	2.1				56.6	-	1			-	82.1		4.1			-	96.3	30	2.1	5	0.3	6.0	15.2	10.0	25.4	14.0	35.6	14	4.3	Ŧ
EF102055	30	-		9.5	2.0 56	-		2.8	3.2	12.1		70.8	-	3.4	4.3	16.3	-	82.1		100	5.9	22.	3	108	-	5.5	7.5	28.4		122	35	2.4	20	1,4	6.5	and the latest terminal	-	-	100000	40.6	-	5.2	020
#	50	1			2.9 82	-	7.5	4.1			-	96.3	-	4.8			-	108	-	100			1000	133	-	100		- 1	5.2		60	4.1	20	1,4	7.5	of the Parket		and the same	4-1000	45.7	-	6.1	SS
	10		-		3.5 99	-0	20	1.4		-		150		1.7	-			173		2.8		+	-	238	-	3.4		-	_	283	10	0.7	40	0.2	60	15.2	-	1	-	-	-	3.7	Н
SS	-	-	4		A-10					1		7.00	-				-	70.0	-	-			-	-	-	81.1		- 1	-		35	2.4	5	0.3	-	1	-	-	-	30.5	-	6.1	4
EF10305S	20	-		16.7				2.1	55	20.8		195			7.6	28.8	-	215	Н		11/	41,	6	283	-		14.0	53.0		326	40	2.8	10	0.7	7.0	17.8	10.0	25.4	13.0	33.0	23	7.0	103
=	30	2.1			6.9 19	S	40	2.8			-	238		3.4			-	283	-				12.	7 360	80	5.5			13.7	388	60	4.1	20	1.4	7.0	17.8	11.0	27.9	14.0	35.6	28	8.5	250
	50	-			10.0 28	13	60	4.1		L	11.5	326	70	4.8			12.7	360	90	6.2		1	14.	8 419	95	6.5		-	_	428		5.2	40	2.8	7.0	-	_		-	35.6	-	9.1	Щ
vs	15	1.0			4.4 12	25	25	1.7			6.1	173	35	2.4			7.6	215	45	3.1			9.2	261	55	3.8			10.7	303	15	1.0	3	0.2	-	15.2	1000	-	-		-	4.0	m
405	25	1.7		37.9	6.1 17	3	35	2.4	13.5	51 1	7.6	215	45	3.1	18.8	71.2	9.2	261	55	3.8		10		7 303	65	4.5	31.0		12.2	345	50	2.4	10	0.2	7.5	-	-	30.5	1	35.6	-	5.2	F10
EF1040SS	40	2.8		21.3	8.4 23	8	50	3.4	133	1	10.0	283	60	4.1	10.0	1 6-4	11.5	326	70	4.8		100		360	80		21.00		13.7	388	60	4.1	20	1.4	-	20.3	-	-	-	0.011	-	7.6	200
-	50	3.4			10.0 28	3	60	4.1			11.5	326	80	5.5			13.2	388	90	6.2			14,	419	100	6.9			162	459	80	5.5	40	2.8	7.0	17.8	11.0	279	15.0	38.1	27	8.2	~







## **Air Atomizing Spray Nozzles**

#### External Mix Wide Angle Flat Fan Pattern - 1/4 NPT



An INTELLIGENT COMPRESSED AIR Product

Model: EB1010SS Material: Type 303 Stainless Steel

#### Model EB1010SS, EB1020SS, EB1030SS and EB1040SS

1/4 NPT external mix wide angle flat fan pattern nozzles are great where a high volume of liquid is needed over a wide area such as a conveyor line. Because they are external mix, airflow and liquid flow can be controlled independently. Common applications are those which require a moderate application of liquid over a broad area, such as cooling or coating wide webs.

#### For pressure fed applications with independent air and liquid control.



Material: Type 303 Stainless Steel




Model: EB1030SS Material: Type 303 Stainless Steel



Model: EB1040SS Material: Type 303 Stainless Steel



(2) Model EB1040SS nozzles are used to rinse wine bottles after capping.



		31		0.2		Ž.		5		/0.3		ŧ		10 F				R		20 I						401								Sp	oraș	Dir	ner	isio	ns				ı
70		Air	Т	quic				Air		quic				lir	Liq					Air		uid				ir		uid	100			Press		11111			Wi	dth				ax.	1
Model	P	essur PSI/ BAR		PH/	SCF		F	SSUI SSI/ SAR		SPH/ LPH		FM/ LPM	P	ssure SI/ AR		PH		FM/ PM	P	ssure SI/ AR		PH/ PH	SCI		P	sure SI/ AR	GP		SCI		Air Bi	PSI/ AR	P	juid SI/ AR	in	cm	in	B cm	in	cm		pth t/m	
	5	0.3	3		0.9	25.5	5	0.	3		0.9	25.5	8	0.6			1.1	31.1	10	0.7			1.3	36.8	15	1.0			1.7	48.1	10	0.7	5	0.3	8.0	20.3	11.0	27.9	14.0	35.6	9	2.7	1
EB101055	8	0.6			1.1	31.1	10	0.				36.8	10	0.7			1.3	36.8	20	1,4				56.6	20	1.4			2.0	56.6	15	1.0	10	0.7	-	111111	-	11111	-	43.2	11	3.4	4
810	10	0.7		3.8	1.3	36.8	15	1,1		4 5.3		48.1	20	1.4	1.9	7.2	2.0	56.6	30	2.1	2.7	10.2		73.6	30	2.1	3.8	14.4	2.6	73.6	20	1.4	20 30	-	-2770	-	and the same	-	-	48.3		3.4	1
-	15	1.0	0		1.7	48.1	20	1,	4		2.0	56.6	30	2.1		П	2.6	73.6	35	2.4			3.0	85.0	35	2.4			3.0	85.0	25	1.7	40	-		10000	-	1000	-	53.3	-	43	1
Т	6	0.4	4		1.0	28.3	6	0,			1.0	283	6	0.4			1.0	28.3	10	0.7			1.3	36.8	20	1.4			2.0	56.6	В	0.6	5	0.3	11.0	27.9	16.0	40.6	19.0	48.3	8	2.4	1
055	7	0.5	5		1.1	31.1	8	0.1	5		1.1	31.1	8	0.6		1	1.1	31.1	12	0.8			1.5	42.5	25	1.7			2.3	65.1	15	1.0	20	1.4	11.0	27.9	16.0	40.6	21.0	53.3	11	3,4	i
EB10205S	8	0.6		9.5	1.1	31.1	9	0.0		2 121		34.0	10	0.7	4.3	16.3		36.8	15	1.0	5.9	223		48.1	30		7.5	28.4	26	74.0	20	1.4	20	1.4	1775	-	7110	1.111	-	55.9	110	3.7	
	10	0.7	,		1.3	36.8	10	0.3	,		1.3	36.8	12	0.8		i	1.5	42.5	20	1.4			-	56.6					3.0	85.0	30	1.7	30 40	-	1000	-	-	-	-	61.0	-	3.7	
_	8		-			963	10				3.6						-	136	-					238	50	3.4			11.0		15	1.0	3		-		_	-	_	53.3	_	4.0	
950	15	-	-		-	136	-	1/			-	167	-			1		190	-	3.1				286	65	4.5			12.3		25	1.7	10	0.7	12:0	30.5	18.0	45.7	23.0	58.4	16	4.9	į
EB103055	20		4/	16.7	-	167	25	-	5.	5 20.8	3	190		24	7.6	28.8	3	238			11.0	41.6		331	-		14.0	53.0	15.7	10000	45	3.1	20	100		7600	-	1000	-	61,0	-	6.4	
EB	25	-	-		6.7	190	30	-			7.6	-				1		263	-	4.1			-	340	95				16.8		60	4,1	30	2.1	minute.	<b>HOPERS</b>	olimatics.	-	decin	61.0	26	7,9	
-	10	-	-	+	3.8		Н	1/	-	+	4.5	-	-	1.7			6.7		-	3.1				286	75	5.2			13.7	-	30	21	40	0.3	_	35.6		-	-	61.0	17	5.2	d
250	-	1.0			4.8		1	1/			-	167	30	1			1000	215		3.4			11.0		85	5.9			15.7	-	45	3.1	20	1.4		-	-	1000	-	66.0	19	5.8	ì
EB1040SS	1	-	10	0 37.9	-	1,00		1	13	5 51.1		1000		-	18.8	71.2	2	200		-	27.6	104	1000	-	-	20000	31.0	117	1000	Transfer of	65	4.5	20	1.4	15.0	38.1	21.0	53.3	27.0	68.6	23	7.0	
E8.	20	100	4	100	-	100	-	-			-	215	-	-			-	263		-	1000			379		-	1000		16.8	37/2	80	5.5	20	Sealers to	rsie/sApr	war en	estables.	-	-	71,1	26	7.9	
	25	1.7	7		6.7	190	35	2.	\$		8.4	238	45	3.1			10.1	286	80	5.5			14.8	419	100	6.9			18.3	518	90	6.2	40	2.8	16.0	40.6	22.0	55.9	28.0	71.1	26	7.9	ĺ







## **Air Atomizing Spray Nozzles**



#### Siphon Fed Round Pattern - 1/4 NPT





Model: SR1010SS Material: Type 303 Stainless Steel





Model: SR1020SS Material: Type 303 Stainless Steel





Model: SR1030SS Material: Type 303 Stainless Steel



Model: SR1040SS Material: Type 303 Stainless Steel


## Model SR1010SS, SR1020SS, SR1030SS and SR1040SS

1/4 NPT siphon fed round pattern nozzles are great where no liquid pressure is available and a thin coating is needed at a specific area. Flow rate is adjustable via the adjusting valve. Siphon nozzles work best with a suction height of 36" (914mm) or less. Since these nozzles are siphon fed, the compressed airflow draws the liquid in and mixes it internally. Liquid flow is dependent both on the gravity or suction height and the airflow. Siphon fed round pattern nozzles provide the most liquid flow of any siphon fed nozzle.

#### Siphon or gravity fed for non-pressurized applications.



The SR1020SS has a focused, round pattern for precision application of coatings or coolant.



										Li	quid	Flow	in G	PH/LP	н						Sp	ray C	imer	rsion	s at 8	" (200	:m) Si	pho	n Heig	ht	ı
		А	ir			G	ravit	y Hea	d					Si	phon	Heig	ht				A	ir			Wi	dth					1
Model	Pres PSI/			FM/ PM	18"	46cm	12"	30cm	6	15cm	4"	10cm	8"	20cm	12"	30cm	24"	61cm	36"	91cm	Pres PSI/		in	A cm	in	B cm	in	cm	Max.	Depth t/m	h
	10	0.7	0.5	14.2	0.6	2.3	0.5	1.9	0.4	1.5	0.2	0.8	0.2	0.8	***		***	***	***	***	10	0.7	2.5	6	4.0	10	5.8	15	7	2.1	1
SRIOTOSS	20	1.4	0.7	19.8	0.6	2.3	0.6	2.3	0.5	1.9	0.4	1.5	0.4	1.5	0.3	1.1		***	***	***	20	1.4	3.3	8	4.3	11	6.0	15	9	2.7	1
R10	40	2.8	1.2	34.0	0.7	2.6	0.7	2.6	0.6	2.3	0.5	1.9	0.5	1.9	0.4	1.5	0.3	1.1	0.2	0.8	40	2.8	3.8	10	5.0	13	6.8	17	10	3.0	
S	60	4.1	1.6	45.3	0.8	3.0	0.8	3.0	0.7	2.6	0.6	2.3	0.5	1.9	0.5	1.9	0.4	1.5	0.2	0.8	60	4.1	3.8	10	5.0	13	6.8	17	11	3.4	
	10	0.7	0.7	19.8	1.1	4.2	0.9	3.4	0.8	3.0	0.5	1.9	0.4	1.5	0.3	1.1	***	***			10	0.7	3.3	8	4.8	12	6.8	17	9	2.7	
SR1020SS	20	1.4	1.1	31.1	1.3	4.9	1.1	4.2	1.0	3.8	0.8	3.0	0.7	2.6	0.6	2.3	0.3	1.1		***	20	1.4	3.5	9	5.0	13	7.0	18	11	3.4	
R10.	40	2.8	1.7	48.1	1.6	6.1	1.5	5.7	1.4	5.3	1.2	4.5	1.0	3.8	1.0	3.8	0.7	2.6	0.4	1.5	40	2.8	3.8	10	5.5	14	7.5	19	14	4.3	1
S	60	4.1	2.3	65.0	1.9	7.2	1.7	6.4	1.6	6.1	1.4	5.3	1.2	4.5	1.2	4.5	0.9	3,4	0.5	1.9	60	4.1	4.0	10	5.8	15	8.0	20	16	4.9	
	20	1.4	2.0	56.6	4.3	16.3	3.8	14.4	3.3	12.5	2.5	9.5	1.8	6.8	1.3	4.9	0.3	1.1			20	1.4	3.5	9	5.0	13	7.0	18	12	3.7	1
1055	40	2.8	3.2	90.6	5.0	18.9	4.4	16.7	4.0	15.1	3.3	12.5	2.9	11.0	2.5	9.5	1.3	4.9	1.0	3.8	40	2.8	3.8	10	5.3	13	7.5	19	13	4.0	1
SR1030SS	60	4.1	4.3	122	5.5	20.8	4.9	18.5	4.5	17.0	3.7	14.0	3.4	12.9	3.1	11.7	1.9	7.2	1.5	5.7	60	4.1	3.8	10	5.5	14	8.0	20	15	4.6	
S	80	5.5	5.6	158	5.8	22.0	5.3	20.1	4.9	18.5	4.1	15.5	3.9	14.8	3.7	14.0	2.6	9.8	1.7	6.4	80	5.5	4.0	10	5.8	15	8.3	21	18	5.5	
	30	2.1	5.7	161	12.3	46.6	11.0	41.6	9.3	35.2	6.3	23.8	5.3	20.1	4.5	17.0	0.6	2.3		***	30	2.1	4.8	12	6.5	17	8.8	22	19	5.8	Ī
SR1040SS	40	2.8	6.9	195	13.0	49.2	11.8	44.7	10.0	37.9	7.3	27.6	6.5	24.6	5,5	20.8	1.5	5.7	0.3	1.1	40	2.8	5.2	13	7.0	18	9.3	24	21	6.4	
R104	60	4.1	9.5	269	14.3	54.1	13.0	49.2	11.5	43.5	8.5	32.2	7.5	28.4	6.5	24.6	2.3	8.7	1.5	5.7	60	4.1	5.5	14	7.5	19	9.8	25	24	7.3	1
S	80	5.5	12.0	340	15.0	56.8	13.5	51.1	12.5	47.3	9.5	36.0	8.5	32.2	7.5	28.4	3.5	13.2	1.9	7.2	80	5.5	5.8	15	7.8	20	10.0	25	27	8.2	1





## **Air Atomizing Spray Nozzles**

#### Siphon Fed Flat Fan Pattern - 1/4 NPT







An INTELLIGENT COMPRESSED AIR Product

Model: SF1010SS Material: Type 303 Stainless Steel



Model: SF1020SS Material: Type 303 Stainless Steel



Model: SF1030SS Material: Type 303 Stainless Steel


#### Model SF1010SS, SF1020SS and SF1030SS

1/4 NPT siphon fed flat fan pattern nozzles are great where no liquid pressure is available and a thin coating is needed over a wide band. Flow rate is adjustable via the adjusting valve. Siphon nozzles work best with a suction height of 36" (914mm) or less. Since these nozzles are siphon fed, the compressed airflow draws the liquid in and mixes it internally. Liquid flow is dependent both on the gravity or suction height and the airflow. Siphon fed flat fan pattern nozzles are the best choice where liquid is needed over a broad band such as a moving assembly line.

#### Siphon or gravity fed for non-pressurized applications.



A Model SF1020SS is used to apply a light coating of oil to prevent sockets from rusting prior to a packaging operation.



								Liqu	aid F	low in	GPH	I/LPH									Sp	ray D	imer	sions	at 8	" (20	m) S	ipho	n Hei	ght
		A	ir			G	ravit	y Hea	d					Si	phor	Heig	ht				A	ir			Wi	dth				
Model		sure BAR		FM/ PM	18"	46cm	12"	30cm	6"	15cm	4"	10cm	8"	20cm	12"	30cm	24"	61cm	36"	91cm		sure BAR	in	A cm	in	B cm	in	cm	Max. fee	Depth rt/m
SS	10	0.7	0.9	25.5	0.4	1.5	0.3	1.1	0.3	1.1	0.2	0.8	0.2	0.8	0.2	0.8	0.2	0.8	0.1	0.4	10	0.7	9	23	11	28	13	33	5	1.5
SF101055	20	1.4	1.3	36.8	0.4	1.5	0.3	1.1	0.3	1.1	0.3	1,1	0.3	1.1	0.3	1.1	0.2	0.8	0.2	0.8	20	1.4	10	25	12	30	14	36	6	1.8
SF	30	2.1	1.7	48.1	0.3	1.1	0.3	1.1	0.3	1.1	0.3	1.1	0.3	1.1	200	***			***	***	30	2.1	11	28	13	33	15	38	7	2.1
П	20	1.4	2.3	65.1	1.2	4.5	1.1	4.2	1.0	3.8	0.9	3.4	0.8	3.0	0,8	3.0	0.6	2.3	0.5	1.9	20	1.4	10	25	14	36	19	48	6	1.8
5002	30	2.1	2.9	82.1	1.1	4.2	1.1	4.2	1.0	3.8	0.8	3.0	0.8	3.0	0.8	3.0	0.6	2.3	0.5	1,9	30	2.1	11	28	15	38	21	53	7	2.1
SF10205S	40	2.8	3.5	99.1	1,0	3.8	0.9	3.4	0.8	3.0	0.7	2.6	0.7	2.6	0.7	2.6	0.5	1.9	0,4	1.5	40	2.8	13	33	16	41	23	58	6	2.1
	50	3.4	4.3	122	0.8	3.0	0.7	2.6	0.5	1.9	0.5	1.9	0.4	1.5	0.3	1.1		***	***		50	3.4	14	36	18	46	25	64	6	1.8
	20	1.4	2.2	62.3	1.8	6.8	1.6	6.1	1.5	5,7	1.4	5.3	1,4	5.3	1.3	4.9	1.1	4.2	1,0	3.8	20	1.4	9	23	11	28	15	38	8	2.4
3055	30	2.1	2.8	79.2	1.9	7.2	1.8	6.8	1.8	6.8	1.7	6.4	1.7	6.4	1.6	6.1	1.4	5.3	1.2	4.5	30	2.1	10	25	13	33	17	43	9	2.7
SF1030SS	40	2.8	3.3	93.4	1.8	6.8	1.8	6.8	1.7	6.4	1.6	6.1	1.6	6.1	1.5	5.7	1.3	4.9	1.2	4.5	40	2.8	11	28	14	36	17	43	10	3.0
	50	3.4	4.0	113	1.6	6.1	1.5	5.7	1.4	5.3	1.4	5.3	1.3	4.9	1.3	4.9	1.1	4.2	1.0	3.8	50	3.4	-11	28	14	36	18	46	11	3.4









#### Internal Mix Narrow Angle Round Pattern - 1/2 NPT

#### Model AN5010SS and AN5020SS

1/2 NPT internal mix narrow angle round pattern nozzles are excellent for spraying a concentrated mist of liquid. Because of the versatility of their adjustments, these larger atomizing nozzles can apply a heavy coat up close or send a very fine mist over 40 feet away! They are often used for higher volume application of lubricants during assembly, or marking items as they move through an assembly line.

pressure fed applications not requiring independent air and liquid control.

Model: AN5010SS Material: Type 303 Stainless Steel



Model: AN5020SS Material: Type 303 Stainless Steel

With adjustable liquid flow, these nozzles can be used to apply a heavy coat or a precise volume of liquid.

> For more information about droplet size and spray angle see page 98.

No Drip M	odels Only	5.16"	
1/2 F	NPT Air Inlet	131mm	
l <del>-</del>		4.14*	
2.25" — • 57mm		- reamin	
1.24"		1.66* 42mm	
			1
2.5"	1 101-		
64mm LJ	h put	H	
-		152mm	
		- 9" -	
	1/2 FNPT		15"
	Liquia inlet	36	1mm
	2.25° 57mm 1.24° 31mm 4.50° 64mm	57mm 1,24° 17mm 44mm	1/2 FNPT Air Inlet  2.25° 57mm 1.24° 105mm 4.14° 105mm 42mm 1.26° 131mm 1.27° 125mm 2.29° 2.29mm

					Spr	ay Di	mens	ions					ı
7		Pres	sure	- 1			Wi	dth			M	ax.	1
Model		PSI/ AR	Lic	uid BAR	in	A cm	in	B	in	cm		pth t/m	L
-	20	1,4	5	0.3							22	6.7	L
105	36	2.5	15	1.0	3.5	9	5.75	146	8.5	22	30	9.1	ANSOTOSS
ANSOTOSS	50	3.4	25	1.7	3.3	9	3./3	14.6	8.5	22	34	10.4	2000
5	60	4.1	35	2.4							37	11.3	1
	10	0.7	5	0.3	4	10	6	15.2	8.5	22	20	6.1	Ī,
AN50205S	32	2.2	25	1.7	5.5	14	7.5	19.1	10	25	27	8.2	NOC
N50	44	3.0	35	2.4	6	15	9	22.9	10.5	27	35	10,7	ANS02035
4	64	4.4	55	3.8	6	15	9	22.9	10.5	27	42	12.8	ľ

		5 P.S	1/0.3	BAR	Liqu	iid		15 P	SI/1.0	BAR	Liqui	id		25 P	SI/1.7	BAR	Liqu	id		35 P	SI/2.4	BAR	Liqu	id		55 PS	1/3.8	BARL	.iquid	a j
Model	Pre	Air ssure l/BAR	GPH	/LPH	SCFI	M/SLPM	Pre	Air ssure l/BAR	GPH	/LPH	SCFM	/SLPM	Pre	Air ssure /BAR	GPH	I/LPH		FM/ .PM	Pre	Air ssure /BAR	GPH	/LPH	SCFN	I/SLPM	Pres	Air ssure BAR	GPH	I/LPH	SCFM	/SLPM
s	18	1.2	9	34.1	12	339.8	28	1.9	27	102.2	14.5	411	38	2.6	51.6	195.3	16.4	464	48	3.3	75.6	286	18.4	521		- 1992	***		700	
ANSOTOSS	20	1.4	7	26.5	12.8	362.5	32	2.2	20	75.7	16.2	459	44	3.0	32.4	122.6	19.5	552	60	4.1	36.6	139	25.3	716		***		777	***	***
NSO	22	1.5	6	22.7	13.6	385.2	38	2.6	20	75.7	19	538	54	3.7	22	83.3	24.3	688	72	5.0	21.6	82	31.0	878		***	***	***	***	***
<	24	1.7	4.5	17.0	14.5	410.6	42	2.9	12.5	47.3	20.4	578	60	4.1	18	68.1	26.9	762	78	5.4	16.8	64	33.7	954						
s	10	0.7	30	113.6	13.7	388.0	18	1.2	98.4	372.4	15,6	442	26	1.8	159	601.8	17.6	498	36	2.5	183	693	20.0	566	54	3.7	231	874.3	26.0	736
205	12	8.0	18.6	70.4	16.2	458.8	20	1.4	73.2	277.1	17.9	507	32	2.2	99	374.7	23.7	671	42	2.9	126	477	26.1	739	60	4.1	168	635.9	33.4	946
ANS0205S				***			22	1.5	63.6	240.7	20.3	575	36	2.5	75	283.9	28.6	810	46	3.2	96	363	31.0	878	72	5.0	76	287.7	47.2	1337
4							24	1.7	52.8	199.8	22.6	640	40	2.8	57.6	218.0	33.0	935	52	3.6	71	269	37.7	1068	76	5.2	54	204.4	51.3	1453







## **Air Atomizing Spray Nozzles**

#### Internal Mix Wide Angle Round Pattern - 1/2 NPT



An INTELLIGENT COMPRESSED AIR Product

Model: AW5010SS Material: Type 303 Stainless Steel



Model: AW5020SS Material: Type 303 Stainless Steel



Model: AW5030SS Material: Type 303 Stainless Steel


#### Model AW5010SS, AW5020SS and AW5030SS

EXAIR's 1/2 NPT internal mix wide angle round pattern atomizing nozzles are great for covering a broad area. These larger atomizing nozzles can be adjusted for a light mist or a heavy soaking spray. They are popular for dust mitigation, humidification, and cooling of products, people or livestock in a broad area. These nozzles are also perfect for applying a coating to parts packed in large containers, for example, misting a container of stamped steel parts with oil to prevent oxidation during shipment.

For pressure fed applications not requiring independent air and liquid control.



hard hitting spray with these adjustable liquid nozzles.



9		_	_		Liq	uid					LIG	uia			100			quie						quie				res	sur	e			Wie	dth				ax.	
	SCF	M/	Pre:	Air ssure /BAR	1	PH/ PH		FM/ PM	Pre	ir ssure BAR	1.1	PH/ PH		FM/ PM	Pre	Air ssure /BAR	11	PH/ PH		FM/ PM	Pre	Air ssure /BAR	100	PH/ PH		FM/ PM	P	iir SI/ AR	Liq P: B:		in	A	E	B cm	in	7	De	pth et/m	
٠		***			***	***	***		28	1.9	33	125	7.6	215	40	2.8	28,8	109	11.0	312	58	4.0	66	250	11.7	331	30	2.1	25	1.7	12.5	31.8	18	46	26	66	18	5.5	3
-	***								30	2.1	20,4	77	10.0	283	42	2.9	18	68	13.3	377	60	4.1	49	185	13.4	379	40	2.8	35	2.4	13	33.0	19	48	26	66	20	6.1	100
-					-								-	***		144				***	62	4.3	36	136	16.8	476	60	4.1	55	3.8	14	35.6	19	48	26.5	67	22	6.7	000
1	12.0	340	26	1.8	36.8	139	21.8	617	40	2.8	60.6	229	29.9	847	54	3.7	70	265	37.4	1059	75	5.2	115	435	45.6	1291	12	0.8	5	0.3	15	38.1	19.5	50	25	64	22	6.7	Ι,
7	14.5	411	30	2.1	28.8	109	25.6	725	44	3.0	40.8	154	33.5	949	58	4.0	49.2	186	41.2	1167	80	5.5	94	356	50.2	1422	46	3.2	25	1.7	16	40.6	20	51	25	64	35	10.7	,
0	16.2	459	32	2.2	21	79	27.7	784	48	3.3	26.4	100	38.2	1082	62	4.3	36	136	44.7	1266				-			60	4.1	35	2.4	15	38.1	18	46	22	56	40	12.2	207
-		-	34	2.3	15.6	59	29.6	838	50	3.4	20.4	77	39.1	1107	65	4.5	27	102	46.9	1328		***	+14	***	***	000	80	5.5	55	1000		33.0				52		Property.	- 6
8	12.8	362	18	1.2	112	424	14.6	413	26	1.8	180	681	17.0	481	36	2.5	210	795	21.2	600	54	3.7	264	999	28.2	799	10	0.7	5	0.3	16	40.6	21	53	31	79	20	6.1	Ι,
3	15.15	429	20	1,4	87	329	16.5	467	30	2.1	138	522	20.6	583	40	2.8	177	670	25.0	708	62	4.3	216	818	36.0	1020	20	1,4	15	1.0	16	40.6	20.5	52	27	69	22	6.7	N.
-	-	-	22	1.5	72	273	18.5	524	36	2.5	B3.4	316	26.7	756	48	3.3	102	386	32.5	920	70	4.8	150	568	42.4	1201	44	3.0	35	2.4	13	33.0	17	43	22	56	35	10.7	200
-			24	1.7	60	227	20.4	578	40	2.8	61.2	232	31.0	878	52	3.6	82.2	311	36.7	1039	76	5.2	111	420	48.1	1362	64	4.4	55	3.8	13.5	34.3	17	43	22	56	44	13.4	4





Pressure LPH

10 0.69 32 121 12 0.83 20.4 77 14 0.97 13.2 50 10 0.69 31.2 118 12 0.83 18.6 70



#### Internal Mix Flat Fan Pattern - 1/2 NPT



Model: AF5010SS Material: Type 303 Stainless Steel



Use the adjustable liquid valve to apply just the right amount of liquid upon your application. Material: Type 303 Stainless Steel

## **Need Help Choosing The Best**

**Atomizing Nozzle For Your Application?** 

Not sure which atomizing nozzle is required?


Model: AF5020SS

Our Application Engineers can assist you in determining the correct model. Call 1-800-903-9247 to speak with an Application Engineer.

#### Model AF5010SS and AF5020SS

1/2 NPT internal mix flat fan pattern atomizing nozzles are designed with efficiency in mind. Especially good for vertical or horizontal assembly lines, the broad thin pattern of these larger atomizing nozzles makes efficient use of your expensive liquids. Their output can be adjusted for a very light film or a heavy coat of atomized liquid. Whether it's applying paint to hanging sheet metal, or using a water mist to cool a laminate web, flat fan atomizing nozzles cover a wide flat area, ideal for products moving on a conveyor.

For pressure fed applications not requiring independent air and liquid control.



-		Pres	sure			ray Dii	100	dth			м	ax.	1
Model		PSI/ AR		uid BAR	in	A cm	in	B	in	cm		pth t/m	
12	20	1.4	10	0.7	25	64	34	86	45	114	14	4.3	Þ
AF501055	40	2.8	20	1,4	28	71	36	91	46	117	18	5.5	F5010SS
150	50	3,4	25	1.7	29	74	38	97	48	122	22	6.7	10
₹	70	4.8	40	2.8	32	81	42	107	.51	130	27	8.2	S
92	10	0.7	5	0.3	21	53	27	69	36	91	13	4.0	Þ
AF502055	20	1.4	15	1.0	34	86	42	107	52	132	15	4.6	AF502055
20	-44	3.0	35	2.4	39	99	47	119	64	163	19	5.8	20
\$	64	4.4	55	3.8	40	102	50	127	68	173	20	6.1	SS

ation about droplet size and spray angle, see page 98

		5 PS	1/0.3	BAR	Liqu	id		15 P	\$1/1.0	BAR	Liqui	id		25 P	SI/1.7	BAR	Liqu	id		35 P	SI/2.	4 BAR	Liqu	id		55 P	51/3.8	BAR	Liqui	d
Model	Pre	ir sure BAR	GPH	/LPH	SCFN	I/SLPM	Pre	Air ssure /BAR	GPH	/LPH	SCFM	/SLPM	Pre	Air ssure /BAR	GPH	/LPH	S	FM/ LPM	Pre	Air ssure l/BAR	GPH	/LPH	SCFN	I/SLPM	Pres	ir ssure BAR	GPH	/LPH	SCFM	/SLPM
		***	***	***	***	***	28	1.9	33.6	127	23.4	663	44	3.0	38.4	145	32.4	918	58	4.0	46.2	175	40.3	1141	***		***	***	1440	***
1055	***	***	***	***	***	***	30	2.1	25.2	95	25.3	716	48	3.3	35.8	136	36.2	1025	62	4.3	34.8	132	43.5	1232		***	***		***	-
F50	***	***	***		***	***	34	2.3	12.6	48	28.7	813	50	3.4	18	68	38.0	1076	65	4.5	25.2	95	46.0	1303		***	***		-	***
-			***		***		36	2.5	11.5	44	31.2	884	60	4.1	3.5	13	46.0	1303	70	4.8	16.2	61	49.7	1408						1000
	10	0.69	18	68	18.0	510	18	1.2	87.6	332	15.6	442	26	1.8	150	568	17.9	507	36	2.5	177	670	22.3	632	54	3.7	231	874	29.3	830
202	12	0.83	6	23	6.0	170	20	1.4	62.4	236	18.4	521	30	2.1	99	375	22.3	632	40	2.8	132	500	26.6	753	60	4.1	186	704	35.6	1008
F50205							22	1.5	45.6	173	20.6	583	36	2.5	50.4	191	29.9	847	46	3.2	76.8	291	34.4	974	68	4.7	108	409	44.4	1257
	***	***	+++	-	***		24	1.7	30.6	116	23.3	660	40	2.8	26.4	100	35.2	997	52	3.6	38.4	145	41.5	1175	76	5.2	66	250	53.13	1505



# An INTELLIGENT COMPRESSED AIR Product

## **Air Atomizing Spray Nozzles**


#### ternal Mix 360° Hollow Circular Pattern - 1/2 NPT




#### Model AT5010SS

1/2 NPT internal mix 360° nozzles are designed for applications where the spray pattern must be oriented away from the nozzle in all directions. These larger 360° nozzles are ideal where a smooth, even coating is needed on the ID of pipe or similar ductwork. They also work great for operations where a mist over a broad area is needed, such as dust suppression, humidification and cooling.

For pressure fed applications not requiring independent air and liquid control.





360° circular pattern nozzles can be used to coat inside diameters or cover a broad area up to 13' (4m).

	10	PSI	/0.7	BAR	Liq	uid	20	0 PSI	/1.4	BAR	Liqu	iid	30	PSI	/2.1	BAR	Liqu	iid	40	PSI	/2.8	BAR	Liqu	ıid	60	PSI	/4.1	BAR	Liqu	id		Spra		nen	sion	
	Pres PSI/	sure	GPH	/LPH	SC SL	FM/ PM	Pre	Air ssure /BAR	GPH	/LPH	SCI	FM/ PM	Pres	ir sure BAR	GPH	/LPH	SCI	M/ PM	Pre	Air ssure /BAR	GPH	/LPH	SCI	FM/ PM	Pres	lir ssure BAR	GPH	/LPH	SCI	FM/ PM	PSI	Pres ir BAR	Liq PSI/	uid BAR	Dian	cm
•	14	1.0	54	204	13.7	388	24	1.7	100	379	17.3	490	36	2.5	114	431	23.7	671	48	3.3	132	500	29.6	838	72	5.0	150	568	41.5	1175	16	1.1	10	0.7	56	142
2	14	1.1	33.6	127	16.3	462	28	1.9	66	250	21.8	617	40	2.8	83	314	28.0	793	54	3.7	85	322	36.2	1025	76	5.2	120	454	45.6	1291	42	2.9	30	2.1	112	284
2	18	1.2	16.8	64	18.5	524	32	2.2	32.5	123	26.7	756	46	3.2	38.4	145	34.6	980	60	4.1	42	159	42.7	1209	78	5.4	108	409	47.9	1357 1458	56	3.9	40	2.8	144	366
2	20	1.4	10.8	41	20.0	566	36	2.5	12	45	30.8	872	50	3.4	14.4	55	39.1	1107	66	4.6	15.6	59	49.9	1413	82	5.7	84	318	51.5	1458	80	5.5	60	4.1	156	396







#### External Mix Narrow Angle Flat Fan Pattern - 1/2 NPT



Model: EF5010SS Material: Type 303 Stainless Steel

#### Model EF5010SS


1/2 NPT external mix narrow angle flat fan pattern nozzles are great where a high volume of liquid is needed over a concentrated area. Since they are external mix, airflow and liquid flow can be controlled independently. External mix narrow angle flat fan pattern nozzles are the best choice where thicker liquids for a heavy coating are needed over a narrow band, such as a paint line.

For pressure fed applications with independent air and liquid control.

# **Dimensions and Airflow Pattern** 1/2 FNPT Air Inlet For more information about droplet size and spray angle, see page 98.







External mix narrow angle flat fan nozzles provide a high volume of liquid in a concentrated area.

	31	PS1/0	).2 E	AR	Liq	uid	5	PSI/	0	3 BAF	t L	qu	ıid	71	·SI/(	).5	BAR	Liq	uid	10	PS	/0.7	BA	AR Lic	uid	1	5 PS	1/1.	.0 BA	R Liq	uid				Sp	ray	Dir	ne	nsid	ons			
_	1	Air		200	tarous.	0000		Air	Т	-30599		500		,	lir	4.5		200	1000	,	\ir		00.0		SHOW E		Air	Г	(11)	1000	and the same of		Pres	sur	e	Г		Wi	dth			.,	lax.
Mode	P	ssure SI/ AR	GP LP		SCF		F	SSUF SI/ AR		GPH/ LPH		CFI			sure SI/ AR		PH/	SC	FM/ PM	P	SI/ AR	GI LI	PH		PM		PSI/ BAR		SPH/ LPH	SC	PM	Air B.	PSI/ AR	P	uid SI/ AR	in	A cm	in		in	cm	De	et/m
	30	2.1			30.2	854	40	2.8			36	6 1	1037	45	3.1		-	39.9	1130	55	3.8			45.4	1314	80	5.5			56.0	1586	35	2,4	3	0.2	15	38	18.5	47	22	56	25	7.6
1055	35	2.4	141		34.0	961	45	3.1				4 1	1144	55				47.0	1331	60	4,1	Lan.		49,75	1409	8	5 5.9	L		60.0	1699	50	3.4	5	0.3	15	38	19	48	23	58	31	9.4
EF50	40	28	141		37.3	1055	55	3.8		86 704		4 1	1342	60		218	825	49.5	1402	70	4.8	264	995	52.84	1496	9	6.2	30.	3 1147	61.4	1739	70	4.8	10	0.7	15	38	20	51	25	64	33	10.1
-	45	3.1			40.8	1155	60	4.1			50	0 1	1416	70	4.8			56.8	1609	80	5.5			59.7	1691	10	0 6.9			67.6	1914	90	6.2	15	1,0	15	38	20	51	25	64	35	10.7



## **Air Atomizing Spray Nozzles**

#### Siphon Fed Round Pattern - 1/2 NPT



Material: Type 303 Stainless Steel

An INTELLIGENT OMPRESSED AIR Product

## Model SR5010SS

1/2 NPT siphon fed round pattern nozzles are great where no liquid pressure is available and a heavy coating is needed at a specific area. Flow rate of these larger atomizing nozzles is adjustable via the adjusting valve. 1/2 NPT Siphon nozzles work best with a suction height of 24" or less. Since these nozzles are siphon fed, the compressed airflow draws the liquid in and mixes it internally. Liquid flow is dependent both on the gravity or suction height and the airflow. 1/2 NPT siphon fed round pattern nozzles provide the most liquid flow of any siphon fed nozzle.

Siphon or gravity fed for nonpressurized applications.

# **Air and Liquid Caps** are Interchangeable!













**Dimensions and Airflow Pattern** 1/2 FNPT Liquid tion about droplet size and spray angle, see page 98.

Use a siphon fed nozzle when no liquid pressure is available.

								Liquid	Flow	in GPI	H/LPH								Spray	Dimensi	ons at 8	" (20cm)	Siphon	Height
9		А	ir			(	Gravit	y Head	i					Siphon	Heig	ht			A	ir	Wi	dth		
Mod		sure BAR	SCI	FM/ PM	18"	46cm	12"	30cm	6"	15cm	4"	10cm	8"	20cm	12"	30cm	24"	61cm		sure BAR	in	B		Depth t/m
	20	1.4	19.3	547		000	***	444		ass	22.1	84	14.3	54	200	***	-	***	20	1.4			22	6.7
vs	30	2.1	25.2	714		***	***	***	***	***	28.6	108	25.7	97	12.3	47	755	***	30	2.1			25	7.6
oss	40	2.8	32.8	929		722	56.8	215	41	155	31.5	119	28.4	107	19.6	74	122	222	40	2.8			28	8.5
50	50	3.4	36.7	1039	61	231	57.4	217	42.8	162	32.1	121	30.2	114	21.8	83	***	***	50	3.4	6	15	29	8.8
22	60	4.1	42.2	1195	59.1	224	57.4	217	43.8	166	33.1	125	33	125	25.7	97	9.9	37	60	4.1			31	9.4
	70	4.8	47.7	1351	66	250	58.6	222	43.8	166	35.3	134	35.3	134	29.7	112	12.5	47	70	4.8			35	10.7
	80	5.5	52.9	1498	68.3	259	59.1	224	44.5	168	44.6	169	36.9	140	31.5	119	17.5	66	80	5.5			37	11.3







## No Drip Air Atomizing Spray Nozzles



# **No Drip Air Atomizing Spray Nozzles**











# Eliminate drips to conserve valuable liquids and improve product finishes!

#### What Are No Drip Atomizing Nozzles?

EXAIR's patented<sup>†</sup> no drip atomizing spray nozzles work in the same way our standard atomizing nozzles do, but have the added benefit of positively stopping liquid flow when compressed air is shut off. All models use stainless steel construction for durability and corrosion resistance.

EXAIR's no drip atomizing nozzles are available in 3 basic families:

#### Internal Mix:

Internal mix nozzles mix the liquid and air inside the air cap and produce the finest atomization. Internal mix nozzles can be used on liquids with a viscosity up to 300 cP. Both air and liquid sides are pressure fed. No Drip Internal Mix Atomizing Nozzles are for pressure fed applications not requiring independent air and liquid control.

#### External Mix:

External mix nozzles have the highest flow rates and allow the air and liquid flows to be adjusted independently. These nozzles are best where precise liquid flow is needed. External mix nozzles can be used on liquids with a viscosity above 300 cP. Both air and liquid sides are pressure fed. No Drip External Mix Atomizing Nozzles are for pressure fed applications with independent air and liquid control.

#### Siphon Fed:

Siphon fed nozzles require no liquid pressure and can be used with gravity fed liquids or lift liquids from a siphon height as much as 36 inches (91cm). Siphon fed nozzles can be used on liquids with a viscosity up to 200 cP. No Drip Siphon Fed Atomizing Nozzles are siphon or gravity fed for non-pressurized applications.

#### Why No Drip Atomizing Nozzles?

When spraying any type of liquid, post-spray liquid flow can cause big problems. Unwanted drips can ruin product finishes on painted or coated surfaces. In addition, excess liquid flow wastes precious resources such as expensive coatings, chemicals or water. EXAIR's no drip atomizing nozzles are ideal where no post-spray drip is permissible. When the compressed air supply is shut off, the no drip nozzle positively seals off the flow of liquid eliminating the possibility of drips. They can be used in any situation that our standard atomizing nozzles can be used, including Siphon Fed applications. Unlike some manufacturers, there's no need to run a separate air line to control the no drip mechanism. The same compressed air used to combine and atomize liquid in a variety of patterns is used to open a valve allowing liquid to flow. That makes these ideal for use with EXAIR's money and energy saving EFC (see page 7).

EXAIR's no drip nozzles do not change flow rates from standard atomizing nozzles. Operations that require up to 180 cycles per minute can be achieved. Minimum operating air pressure of 30 PSIG (2.1 BAR) required for 1/4 and 1/2 NPT nozzles, 20 PSIG (1.4 BAR) is required for 1/8 NPT nozzles.



Mounting Brackets are available - Model 901786 for 1/8 NPT, Model 901318 for 1/4 NPT and Model 901556 for 1/2 NPT atomizing nozzles.

#### **Applications**

- Painting
- Coating
- Rinsing Cooling
- Quenching
- · Wetting (moistening)
- Humidification
- Dust Control
- Advantages No post spray drip
- Adjustable
- · Easily used with an EFC
- · Minimizes air and liquid consumption

## All stainless steel construction

- · Fine atomization
- - · Interchangeable liquid and air caps
  - Compact

## EXAM





Model Description

**No Drip Air Atomizing Spray Nozzles** 

No Drip Internal Mix Atomizing Nozzles are for pressure fed applications not requiring independent air and liquid control.

An INTELLIGENT OMPRESSED AIR Product



ı
ı
ı
ı

No Drip I	nternal Mix Narrow	Angle Round	Pattern	Atomizing	Nozzles

igle Round Pattern Atomizing Nozzles, 2.63 GPH/9 96 LPH Max 1/8 NP AN9020SS No Drip Internal Mix Narrow Angle Round Pattern Atomizing Nozzles, 3.33 GPH/12.61 LPH Max. 1/8 NPT AN903055 No. Drip Internal Mix Narrow Angle Round Pattern Atomizing Nozzles, 6.3
GPH/23.85 LPH Max. 1/8 NPT

No Drip Internal Mix Narrow Angle Round Pattern Atomizing Nozzles,

No Drip Internal Mix Narrow Angle Round Pattern Atomizing Nozzles, 18.93 GPH/71.66 LPH Max, 1/8 NPT No Drip Internal Mix Narrow Angle Round Pattern Atomizing Nozzles,

3.3 GPH/12.5 LPH Max. 1/4 NPT No Drip Internal Mix Narrow Angle Round Pattern Atomizing Nozzles, AN202055 No Drip Internal Mila Mario W. ... 9.9 GPH/37.5 LPH Max, 1/4 NPT

No Drip Internal Mix Narrow Angle Round Pattern Atomizing Nozzles, AN203055 23.0 GPH/87.1 LPH Max, 1/4 NPT

No Drip Internal Mix Narrow Angle Round Pattern Atomizing Nozzles, AN2040SS 66.0 GPH/250 LPH Max. 1/4 NPT

No Drip Internal Mix Narrow Angle Round Pattern Atomizing Nozzles, 75.6 GPH/286 LPH Max, 1/2 NPT

No Drip Internal Mix Narrow Angle Round Pattern Atomizing Nozzles.

No Drip Internal Mix Wide Angle Round Pattern Atomizing Nozzles

231.0 GPH/874 LPH Max. 1/2 NPT

P INTER	AW901055	No Drip Internal Mix Wide Angle Round Pattern Atomizing Nozzles, 2.6 GPH/9.84 LPH Max, 1/8 NPT
NODR	AW9020SS	No Drip Internal Mix Wide Angle Round Pattern Atomizing Nozzles, 9.8 GPH/37.22 LPH Max, 1/8 NPT
		No Drip Internal Mix Wide Apple Round Pattern Atomising Novales, 15

GPH/56.78 LPH Max, 1/8 NPT No Drip Internal Mix Wide Angle Round Pattern Atomizing Nozzles, 22.33 GPH/84.54 LPH Max, 1/8 NPT

No Drin Internal Mix Wide Angle Round Pattern Atomizing Nozzles.

No Drip Internal Mix Wide Angle Round Pattern Atomizing Nozzles, 3.5 GPH/13.2 LPH Max. 1/4 NPT

AW2020SS 8.5 GPH/32.2 LPH Max, 1/4 NPT No Drip Internal Mix Wide Angle Round Pattern Atomizing Nozzles, AW203055 15.0 GPH/56.8 LPH Max, 1/4 NPT

No Drip Internal Mix Wide Angle Round Pattern Atomizing Nozzles, 24.0 GPH/91 LPH May 1/4 NPT

No Drip Internal Mix Wide Angle Round Pattern Atomizing Nozzles, 66.0 GPH/250 LPH Max, 1/2 NPT

No Drip Internal Mix Wide Angle Round Pattern Atomizing Nozzles, AW602055 115.0 GPH/435 LPH Max, 1/2 NPT No Drip Internal Mix Wide Angle Round Pattern Atomizing Nozzles, 264.0 GPH/999 LPH Max. 1/2 NPT

For Technical Assistance, Call An EXAIR Application Engineer 1-800-903-9247








# No Drip Air Atomizing Spray Nozzles An INTELLIGENT COMPRESSED AIR Product











# An INTELLIGENT COMPRESSED AIR Product

## **No Drip Air Atomizing Spray Nozzles**

No Drip External Mix Atomizing Nozzles are for pressure fed applications with independent air and liquid control.







**Model Description** 

#### No Drip External Mix Round Pattern Atomizing Nozzles

ER201055	No Drip External Mix Round Pattern Atomizing Nozzles, 3.8 GPH/14.4 LPH Max, 1/4 NPT	
ER202055	No Drip External Mix Round Pattern Atomizing Nozzles, 7.5 GPH/28.4 LPH Max, 1/4 NPT	
ER203055	No Drip External Mix Round Pattern Atomizing Nozzles, 14.0 GPH/53.0 LPH Max, 1/4 NPT	
ER2040SS	No Drip External Mix Round Pattern Atomizing Nozzles, 31.0 GPH/117 LPH Max, 1/4 NPT	
ER2050SS	No Drip External Mix Round Pattern Atomizing Nozzles, 60.0 GPH/227 LPH Max, 1/4 NPT	

#### No Drip External Mix Narrow Angle Flat Fan Pattern Atomizing Nozzles

	EF9010SS	No Drip External Mix Narrow Angle Flat Fan Pattern Atomizing Nozzles, 2.00 GPH/7.57 LPH Max, 1/8 NPT
ZLES	EF9020SS	No Drip External Mix Narrow Angle Flat Fan Pattern Atomizing Nozzles, 2.93 GPH/11.09 LPH Max, 1/8 NPT
NO DRIP EXTERNAL MIX ATOMIZING NOZZLES	EF9030SS	No Drip External Mix Narrow Angle Flat Fan Pattern Atomizing Nozzles, 7.67 GPH/29.03 LPH Max, 1/8 NPT
KATOMIZ	EF9040SS	No Drip External Mix Narrow Angle Flat Fan Pattern Atomizing Nozzles, 14.42 GPH/54.59 LPH Max, 1/8 NPT
RNALMI	EF9050SS	No Drip External Mix Narrow Angle Flat Fan Pattern Atomizing Nozzles, 25.00 GPH/94.64 LPH Max, 1/8 NPT
RIP EXTE	EF2010SS	No Drip External Mix Narrow Angle Flat Fan Pattern Atomizing Nozzles, 3.8 GPH/14.4 LPH Max, 1/4 NPT
NOD	EF2020SS	No Drip External Mix Narrow Angle Flat Fan Pattern Atomizing Nozzles, 7.5 GPH/28.4 LPH Max, 1/4 NPT
	EF2030SS	No Drip External Mix Narrow Angle Flat Fan Pattern Atomizing Nozzles, 14.0 GPH/53.0 LPH Max, 1/4 NPT
	EF2040SS	No Drip External Mix Narrow Angle Flat Fan Pattern Atomizing Nozzles, 31.0 GPH/117 LPH Max, 1/4 NPT
	EF6010SS	No Drip External Mix Narrow Angle Flat Fan Pattern Atomizing Nozzles, 303.0 GPH/1,147 LPH Max, 1/2 NPT

No Drip External Mix Wide Angle Flat Fan Pattern Atomizing Nozzles

EB201055	No Drip External Mix Wide Angle Flat Fan Pattern Atomizing Nozzles, 3.8 GPH/14.4 LPH Max, 1/4 NPT
EB202055	No Drip External Mix Wide Angle Flat Fan Pattern Atomizing Nozzles, 7.5 GPH/28.4 LPH Max, 1/4 NPT
EB203055	No Drip External Mix Wide Angle Flat Fan Pattern Atomizing Nozzles, 14.0 GPH/53.0 LPH Max, 1/4 NPT
EB2040SS	No Drip External Mix Wide Angle Flat Fan Pattern Atomizing Nozzles, 31.0 GPH/117 LPH Max, 1/4 NPT




AT6010SS No Drip Internal Mix 360° Hollow Circular Pattern Atomizing Nozzles,

150 GPH/568 LPH Max, 1/2 NPT









# No Drip Air Atomizing Spray Nozzles COMPRESSED AIR Product



No Drip Siphon Fed Atomizing Nozzles are siphon or gravity fed for non-pressurized applications.






## Model Description No Drip Siphon Fed Round Pattern Atomizing Nozzles SR9010SS No Drip Siphon Fed Round Pattern Atomizing Nozzles, 0.53 GPH/2.02 LPH Max, 1/8 NPT No Drip Siphon Fed Round Pattern Atomizing Nozzles, 0.96 GPH/3.63 LPH No Drip Siphon Fed Round Pattern Atomizing Nozzles, 1.98 GPH/7.50 LPH Max. 1/8 NPT No Drip Siphon Fed Round Pattern Atomizing Nozzles, 4.09 GPH/15.48 LPH No Drip Siphon Fed Round Pattern Atomizing Nozzles, 5.12 GPH/19.38 LPH SR9050SS No Drip Siphon Fed Round Pattern Atomizing Nozzles, 0.8 GPH/3.0 LPH Max, 1/4 NPT No Drip Siphon Fed Round Pattern Atomizing Nozzles, SR2020SS 1.9 GPH/7.2 LPH Max, 1/4 NPT No Drip Siphon Fed Round Pattern Atomizing Nozzles, 5.8 GPH/22.0 LPH Max. 1/4 NPT No Drip Siphon Fed Round Pattern Atomizing Nozzles. SR204055 15.0 GPH/56.8 LPH Max, 1/4 NPT R6010SS No Drip Siphon Fed Round Pattern Atomizing Nozzles.

#### No Drip Siphon Fed Flat Fan Pattern Atomizing Nozzles

68.3 GPH/259 LPH Max, 1/2 NPT

SF9010SS	No Drip Siphon Fed Flat Fan Pattern Atomizing Nozzles, 0.43 GPH/1.62 LPH Max, 1/8 NPT
SF9020SS	No Drip Siphon Fed Flat Fan Pattern Atomizing Nozzles, 1.52 GPH/5.75 LPH Max, 1/8 NPT
SF9030SS	No Drip Siphon Fed Flat Fan Pattern Atomizing Nozzles, 1.45 GPH/5.49 LPH Max, 1/8 NPT
SF2010SS	No Drip Siphon Fed Flat Fan Pattern Atomizing Nozzles, 0.4 GPH/1.5 LPH Max, 1/4 NPT
SF2020SS	No Drip Siphon Fed Flat Fan Pattern Atomizing Nozzles, 1.2 GPH/4.5 LPH Max, 1/4 NPT
SF2030SS	No Drip Siphon Fed Flat Fan Pattern Atomizing Nozzles, 1.9 GPH/7.2 LPH Max. 1/4 NPT





## **Air Atomizing Spray Nozzles**



#### **Droplet Size**

An INTELLIGENT OMPRESSED AIR Product

One of the primary reasons atomizing spray nozzles are used is because of their fine droplet size. Benefits of fine droplet size include even coating and liquid conservation. For reference, a large raindrop is around 6,000 microns (0.236") in diameter. Standard liquid nozzles produce droplet sizes ranging from 4,000 microns (0.157") down to 300 microns (0.012") in diameter. EXAIR's Atomizing Nozzles produce minuscule droplet sizes in the range of 100 microns (0.004") to 20 microns (0.0008")!

Droplet size can be adjusted by varying either the air or liquid pressure. An increase in air pressure or decrease in liquid pressure will generally produce a smaller droplet size. Below is a chart showing various models of atomizing air nozzles and their droplet sizes at selected pressures.

Droplet Size           Model         Liquid Pressure         Air Pressure         Droplet Size um*           20 PSI         40 PSI         71           40 PSI         65 PSI         83           5 PSI         40 PSI         39           ER102055         20 PSI         40 PSI         57							
Model							
ANIOZOSS	20 PSI	40 PSI	71				
AN 102055	40 PSI	65 PSI	83				
	5 PSI	40 PSI	39				
EK102055	20 PSI	40 PSI	57				
	4" Siphon Height	20 PSI	25				
SR1020SS	4" Siphon Height	40 PSI	22				

<sup>\*</sup> Volume Median Diameter D<sub>v</sub>(50.0) of liquid droplets. 1 µm = 1 micron = 0.00004". All tests performed with water.

### Spray Angle

The Spray Angle is the trigonometric angle created by the width of the spray pattern and the distance at which it is measured. This angle can vary greatly within a given family of atomizing nozzles depending on flow rates and pressures, but will generally fall into the ranges below:

Spray Ar	ngle	
Family	Minimum Angle	Maximum Angle
Internal Mix Narrow Angle Round Pattern - AN1010SS, AN2010SS, etc.	20°	45*
Internal Mix Wide Angle Round Pattern - AW1010SS, AW2010SS, etc.	50°	90°
Internal Mix Flat Fan Pattern - AF1010SS, AF2010SS, etc.	50"	120*
Internal Mix Deflected Flat Fan Pattern - AD1010SS, AD2010SS, etc.	67°	90°
External Mix Round Pattern - ER1010SS, ER2010SS, etc.	25°	60"
External Mix Narrow Angle Flat Fan Pattern - EF1010SS, EF2010SS, etc.	35°	70°
External Mix Wide Angle Flat Fan Pattern - EB1010SS, EB2010SS, etc.	50°	105°
Siphon Fed Round Pattern - SR1010SS, SR2010SS, etc.	20"	50"
Siphon Fed Flat Fan Pattern - SF1010SS, SF2010SS, etc.	50°	100°









# **Liquid Atomizing Spray Nozzles**

## Pressurized liquid nozzles increase liquid flow for cooling, washing and rinsing!

## What are Liquid Atomizing Spray Nozzles?

EXAIR's Liquid Atomizing Spray Nozzles require no air to operate. They produce droplets by spinning the liquid and breaking its surface tension through a precision orifice or by impacting the liquid on to a surface of the nozzle. Compared to EXAIR's Air Atomizing Spray Nozzles, liquid atomizing spray nozzles generate more liquid volume and produce a more coarse spray pattern. The higher liquid flow rates benefit some common industrial applications like cleaning, cooling, rinsing, dust suppression and washing. Many liquid atomizing spray nozzles operate well when the liquid they are spraying contains particulate or is a slurry.

## Why Liquid Atomizing Spray Nozzles?

They are good general-purpose nozzles for industry and are commonly used with inexpensive liquids like water, rinse aids or detergents while also very effective with chemicals, pesticides and herbicides. Adjustment of the liquid flow rate can be done with varying liquid pressure but without the same adjustability or refinement of Air Atomizing Spray Nozzles. Their smaller footprint allows for mounting in smaller spaces and with less plumbing required, since no air line is needed. Liquid nozzles, made of Type 303 stainless steel are durable and rugged, with no moving parts and have a maximum operating temperature of 800°F (427°C).

### **Applications**

- Cooling
- Quenching Slurry spraying

· Foam breaking

Sanitizing

Lubricating

- Coating
- Dust suppression Degreasing
- Washing
- Rinsing

#### **Advantages**




#### Model: FL1008SS Material: Type 303 Stainless Steel

and FL1011SS

**Liquid Atomizing Spray Nozzles** 

FullStream™ Cone Nozzles - 1/4 NPT

Cone Nozzles, with a full cone spray pattern, are among the most common type of spray nozzles. Full cone spray nozzles are applied to solve cooling, cleaning, washing, rinsing and dust suppression applications throughout industry. Their tangential flow design is vaneless, which creates wide open internal features to resist clogging. This produces a uniform distribution in a full cone round pattern and medium to large droplets. Their right-angle design is compact and operates at up to 250 PSI liquid pressure. FullStream nozzles also work well with liquids containing particulate.



Model: FL1010SS

Model: FL1011SS Material: Type 303 Stainless Steel

Material: Type 303 Stainless Steel

For maximum liquid conservation and spray control visit page 71.



# Model FL1008SS, FL1010SS

EXAIR's 1/4 NPT FullStream


### How FullStream and HollowStream Cone Nozzles Work

With FullStream and HollowStream nozzles, the atomizing fluid is supplied into the body of the nozzle creating a

swirling action within the vortex chamber. This vortex produces a full cone spray pattern when the precisely machined nozzle breaks the liquid surface tension as it exits the orifice at a controlled spray angle.

**Dimensions and** 

Spray Pattern



1/4 NPT FullStream Cone Nozzle with cone spray pattern is rinsing anodized aluminium pipe.

				Ful	IStream	Cone No	zzles								Spray	Angle				ı																						
Inlet	odel		Max Free				Flow R	ate GPM/	LPM			In	let		100	Wi	dth			1																						
Connection	Mod	Capacity	Passage		3 psi	5 psi	7 psi	10 psi	20 psi	40 psi	60 psi		sure BAR	in	A cm	in	cm	in	cm																							
	SS			SPM	0.50	0.60	0.70	0.80	1.15	1.55	1.80	7	0.5	5.7	14	8.6	22	14.3	36																							
	FL100855	8	0.109"	-	1000000		10100000	100000		20	1.4	7.4	19	11.0	28	18.4	47																									
1/4 NPT TIGN 1/4 LPT			LPM	1.89	2.27	2.65	3.03	4.35	5.87	6.81	60	4.1	8.4	21	12.6	32	21.0	53																								
			GPM	0.48	0.67	0.83	1.00	1.34	1.88	2.36	7	0.5	6.8	17	10.2	26	17.0	43																								
	10	0.125*	0.125*	0.125*	0.125*	0.125*	0.125*	0.125*	0.125*	0.125*			74747						20	1.4	8.7	22	13.1	33	21.8	55	ı															
	55	2.455	10000	1000	1.00				20000	1000		1.00	10		LPM	1.82	2.54	3.14	3.79	5.07	7.12	8.93	60	4.1	10.1	26	15.1	38	25.2	64												
	SS		0.144"																												M M		2.66	7	0.5	6.8	17	10.2	26	17.0	43	1
	FL10115S	11		G 0.62 0.85 0.96 1.10 1.51 2.21 2.66 20	20	1.4	8.7	22	13.1	33	21.8	55																														
				0.144" 20 1.4	4.1	10.1	26	15.1	38	25.2	64																															











#### FullStream™ Cone Nozzles - 3/8 NPT






Material: Type 303 Stainless Steel



Model: FL3013SS Material: Type 303 Stainless Steel















Model: FL3023SS Material: Type 303 Stainless Steel



Model: FL3026SS Material: Type 303 Stainless Steel




Model: FL3029SS Material: Type 303 Stainless Steel

#### Model FL3011SS, FL3013SS, FL3016SS, FL3020SS, FL3023SS, FL3026SS and FL3029SS

EXAIR's 3/8 FullStream Cone Nozzles, with a full cone spray pattern, are among the most common type of spray nozzles. Full cone spray nozzles are applied to solve cooling, cleaning, washing, rinsing and dust suppression applications throughout industry. Their tangential flow design is vaneless, which creates wide open internal features to resist clogging. This produces a uniform distribution in a full cone round pattern and medium to large droplets. Their right-angle design is compact and operates at up to 250 PSI liquid pressure. FullStream nozzles also work well with liquids containing particulate.

Compared to EXAIR's Air Atomizing Spray Nozzles the FullStream will have higher liquid flow rates.

For maximum liquid conservation and spray control visit page 71.



3/8 NPT

FullStream

inside of a

Cone Nozzle washing the





				Full	Stream	Cone No:	zzies								Spray	Angle																									
Inlet	ē		Max Free		Flow Rate GPM/LPM							In	let	Width																											
Connection	Model	Capacity	Passage		3 psi	5 psi	7 psi	10 psi	20 psi	40 psi	60 psi	Pres PSI/	sure BAR	in	cm	in E	cm	in	cm																						
	155	1939	0.00000	GPIM	0.57	0.76	0.91	1.10	1.52	2.20	2.70	7	0.5	8.1	21	12.1	31	20.2	51																						
	FL30115S	11	0.128"	ГРМ	2.16	2.88	3.44	4.16	5.75	8.33	10.22	20 60	1.4	9.9	25 26	14.8 15.6	38 40	24.7	63																						
				GPM	0.75	0.95	1,13	1.30	1.86	2.60	3.34	7	0.5	7.6	19	11.5	29	19.1	49																						
	FL3013SS	13	0.144°	LPM C	2.84	3.60	4.28	4.92	7.04	9.84	12.64	20 60	1.4	9.0	23	13.6	35	22.6	57 66																						
201666					GPM	0.98	1.10	1.25	1.60	2.23	2.90	3.60	7	0.5	7.6	19	11.5	29	19.1	49																					
	L301	16	0.154"	LPM G	3.71	4.16	4.73	6.06	8.44	10.98	13.63	20 60	1.4	9.7	25 26	14.6 15.6	37 40	24.3	62 66																						
		20		GPM L	1.22	1.64	1.88	2.00	2.98	4.24	4.82	7	0.5	8.4	21	12.6	32	21.0	53																						
3/8 NPT	FL302055		0.172"	LPM G	4.62	6.21	7.12	7.57	11.28	16.05	18.24	20 60	1.4	9.9	25 28	14.8 16.8	38 43	24.7	63 71																						
				GPM LI	1.36	1.76	1.96	2.30	3.18	4.56	5.38	7	0.5	9.0	28	13.6	35	22.6	57																						
F130295S F13026SS F13023SS	3023	23	0.189"		3776	177.75	1000	150000	10000	2.59776		20	1.4	10.2	26	15.4	39	25.6	65																						
							8 0																LPM	5.15	6.66	7.42	8.71	12.04	17.26	20.36	60	4.1	11.2	28	16.8	43	18.0	46			
	2655	26					0.204"	0.204"							0.2045	0.204*										GPM	1.26	1.80	2.02	2.60	3.30	5,18	6.12	7 20	0.5	9.7	25	14.6	37	24.3	62
	FL30	20												LPM	4.77	6.81	7.65	9.84	12.49	19.61	23.17	60	4.1	12.0	30	18.0	46	30.0	76												
	5563	-	0.000	GPM	1.30	1.84	2.28	2.90	3.62	5.48	6.48	7	0.5	9.9	25	14.8	38	24.7	63																						
	1302	29	0.221"	0.221"	0.221"				LPM (	4.92	6.97	8.63	10.98	13.70	20.74	24.53	20 60	1.4	10.8	27 30	16.2	41	27.0	69 76																	



## **Liquid Atomizing Spray Nozzles**

#### FullStream™ Cone Nozzles - 1/2 NPT





Model: FL5032SS Material: Type 303 Stainless Steel





Model: FL5040SS Material: Type 303 Stainless Steel





Model: FL5048SS Material: Type 303 Stainless Steel





lodel: FL5056SS





Model: FL5064SS Material: Type 303 Stainless Steel






Model: FL5072SS Material: Type 303 Stainless Steel

#### Model FL5032SS, FL5040SS, FL5048SS. FL5056SS, FL5064SS and FL5072SS

EXAIR's 1/2 NPT FullStream Cone Nozzles, with a full cone spray pattern, are among the most common type of spray nozzles. Full cone spray nozzles are applied to solve cooling, cleaning, washing, rinsing and dust suppression applications throughout industry. Their tangential flow design is vaneless, which creates wide open internal features to resist clogging. This produces a uniform distribution in a full cone round pattern and medium to large droplets. Their right-angle design is compact and operates at up to 250 PSI liquid pressure. FullStream nozzles also work well with liquids containing particulate.

Compared to EXAIR's Air Atomizing Spray Nozzles the FullStream will have higher liquid flow rates.

For maximum liquid conservation and spray control visit page 71.





1/2 NPT FullStream Cone Nozzle with cone spray pattern is cleaning red potatoes.

				Full	Stream (	Cone No:	zzles								Spray	Angle				ı											
Inlet	e		Max Free				Flow Ra	te GPM/	LPM			In	let			Wi	dth	ol .		٦											
Connection	Model	Capacity	Passage		3 psi	5 psi	7 psi	10 psi	20 psi	40 psi	60 psi		ssure /BAR	in	A cm	in	B cm	in	C cm												
	3255			GPM	1.74	2.46	2.80	3.20	4.46	6.28	7.30	7	0.5	9.4	23.9	14.1	35.81	23.4	59.4	-											
	FL503255	32	0.201*	LPM	6.59	9,31	10.60	12.11	16.88	23.77	27.63	60	4.1	10.1	25.7 30.5	15.1	38.3 45.7	25.2 30.0	76.2												
7	950		0.0000000	GPM	2.68	3.14	3,52	4.00	5.60	7.80	8.76	7	0.5	10.1	25.7	15.1	38.4	25.2	64.0	н											
	FL504055	40	0.242"	LPM C	10.14	11.89	13.32	15,14	21.20	29.53	33.16	20 60	4.1	12.0	30.5	18.0	45.7	30.0	76.2	2000											
EI COABCC EI	_			GPM L	3.06	3.56	3.96	4.80	6,81	9.58	11.73	7	0.5	10.1	25.7	15.1	38.4	25.2	64.0												
	5048	48	0.281*	LPM G	11.28	13.48	15.00	18,17	25.78	39.26	44.40	20 60	1.4	12.0	30.5	18.0	45.7	30.0	76.2												
1/2 NPT		56			Antenna .	1975575	100000	TOTAL CO.	2000	No.	13.74	7	0.5	13.1	33.3	19.6	49.8	32.7 27.5	83.1 69.9	-											
	FL5056SS		0.295"	M GPM	3.32	4.18	4.67	5.60	7.89	11.22	10707/4	20	1,4	12.0	30.5	18.0	45.7	30.0	76.2	-											
	_			LPM	12.57	15.82	17.68	21.20	29.87	42.47	52.01	60	4.1	13.1	33.3	19.6	49.8	32.7	83.1												
	6455	64	64	64	64	64	64			0.2201		12.70	15.81	7 20	1.4	11.0	28.0	16.5	42.0	27.5 30.0	69.9 76.2										
	FL5064SS	64	64	64	64	64	64	64	64	64	64	64	0.328"	0.328"	LPM	13.25	17.03	19.49	24.23	34.56	48.07	59.85	60	4.1	13.1	33.3	19.6	49.8	32.7	83.1	
	255	2500	tesservice	GPM	4.08	5.00	6.17	7.20	10.17	14.40	17.64	7	0.5	11.0	28.0	16.5	42.0	27.5	69.9												
	FL507255	72	0.359"	LPM C	15.44	18.93	23.36	27.25	38.50	54.51	66.77	20 60	1.4	12.0	30.5	18.0	45.7	30.0	76.2 83.1												





#### HollowStream™ Cone Nozzles - 1/4 NPT



Model: HL1001SS Material: Type 303 Stainless Steel





Model: HL1002SS Material: Type 303 Stainless Steel





Model: HL1003SS Material: Type 303 Stainless Steel





Model: HL1005SS Material: Type 303 Stainless Steel



Model: HL1008SS Material: Type 303 Stainless Steel



Model: HL1011SS Material: Type 303 Stainless Steel

#### Model HL1001SS, HL1002SS, HL1003SS, HL1005SS, HL1008SS and HL1011SS

EXAIR's 1/4 NPT HollowStream Cone Nozzles produce a ring of liquid upon your target and are among the most common type of spray nozzles. Hollow cone spray nozzles generally use less liquid than full cone spray nozzles. These nozzles will be used when cooling, cleaning, washing, rinsing and dust suppression can be achieved with less liquid than a full cone nozzle. Their tangential flow design is vaneless which creates wide open internal features to resist clogging. They produce a uniform distribution in a hollow cone round pattern and medium to large droplets. The right-angle design is compact and operates at up to 250 PSI liquid pressure. HollowStream nozzles also work well with liquids containing particulate.

# /ATION AWARDS Finalist **Dimensions and Spray Pattern** 0.75°

Compared to EXAIR's Air Atomizing Spray Nozzles the HollowStream will have higher liquid flow rates.

For maximum liquid conservation and spray control visit page 71.

See page 100 for How the FullStream and HollowStream Cone Nozzles Work.

				tollo	wStrear	n Cone N	lozzies								Spray	Angle				ı																							
Inlet	le.	228 380	Max Free				Flow R	ate GPM/	LPM			In	let			Wi	dth			1																							
Connection	Model	Capacity	Passage		3 psi	5 psi	7 psi	10 psi	20 psi	40 psi	60 psi		ssure BAR	in	A cm	in	B cm	in	cm																								
	3510			GPM	0.06	0.07	0.09	0.10	0.13	0.18	0.21	7	0.5	4.8	12.3	6.1	15.5	7.8	19.8	4																							
	HL1001SS	1	0.052"	LPM	0.23	0.26	0.34	0.38	0.49	0.68	0.79	20 60	4.1	7.3	18.5	9.2	23.3	11.7	29.7 49.5	1																							
	HL100255			MdS	0.14	0.17	0.19	0.20	0.27	0.38	0.46	7	0.5	6.1	15.5	8.6	21.7	11.2	28.4																								
1/4 NPT	2	0.086"	LPM.	0.53	0.64	0.72	0.76	1.02	1.44	1.74	60	1.4	9.2	23.3	12.8	32.6 54.4	16.8	42.6 71.1	н																								
			GPIM	0.20	0.24	0.28	0.32	0.45	0.63	0.77	7	0.5	6.8	17.2	10.4	26.5	13.3	33.9	-																								
	3	0.109*	LPM	0.76	0.91	1.06	1.21	1.70	2.38	2.91	20 60	1.4	10.2	25.9 43.1	15.6 26.1	39.7 66.2	20.0	50.8 84.6	-																								
			GPM	0.27	0.35	0.39	0.49	0.65	0.91	1.12	7	0.5	8.4	21.3	9.7	24.7	14.3	36.3	-																								
	HL101155 HL100855 HL100555	5	0.120°	0.120*	0.120°	0.120*	0.120°	0.120°	0.120°	0.120*	0.120*	0.120°	0.120*	0.120*	0.120*	0.120*	0.120*	0.120*	0.120*	0.120*	0.120*	LPM	1.02	1.32	1.47	1.85	2.46	3.44	4.23	20 60	1.4	12.6	32.0 53.4	14.6	37.0 61.7	21.5 35.8	54.5 90.8	÷					
			0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	0.166*	GPM	0.46	0.59	0.73	0.80	1.16	1.60	2.04	7	0.5	7.1	18.0	7.8	19.8	10.1	25.6	-
		8																									0.166*	0.166"	0.166"	LPM G	1.74	2.23	2.76	3.02	4.38	6.05	7.71	20	1,4	10.6	26.9	11.7	29.7
							-					60	4.1 0.5	17.7 9.5	44.9 24.2	19.5	49.5	25.2	63.9 37.6	н																							
		11	0.180*	GPM	0.65	0.81	0.93	1.10	1.47	2.03	2.50	20	1.4	14.3	36.4	18.0	45.7	22.2	56.5																								
		300	200 (1975)	LPM	2.46	3.06	3.52	4.16	5.56	7.67	9.45	60	4.1	23.9	60.6	30.0	76.2	37.0	94.1																								





# **Liquid Atomizing Spray Nozzles**

#### HollowStream™ Cone Nozzles - 3/8 NPT



Model: HL3005SS Material: Type 303 Stainless Steel



Model: HL3008SS Material: Type 303 Stainless Steel





Model: HL3010SS Material: Type 303 Stainless Steel
















Model: HL3030SS Material: Type 303 Stainless Steel

#### Model HL3005SS, HL3008SS, HL3010SS, HL3015SS, HL3020SS, HL3025SS and HL3030SS

EXAIR's 3/8 NPT HollowStream Cone Nozzles produce a ring of liquid upon your target and are among the most common type of spray nozzles. Hollow cone spray nozzles generally use less liquid than full cone spray nozzles. These nozzles will be used for cooling, cleaning, washing, rinsing and dust suppression with less liquid than a full cone nozzle. Their tangential flow design is vaneless which creates wide open internal features to resist clogging. They produce a uniform distribution in a hollow cone round pattern and medium to large droplets. The right-angle design is compact and operates at up to 250 PSI liquid pressure. HollowStream nozzles work well with liquids containing particulate.



See page 100 for How the FullStream and HollowStream Cone Nozzles Work.

Compared to EXAIR's Air Atomizing Spray Nozzles the Hollow-Stream will have higher liquid flow rates.

For maximum liquid conservation and spray control visit page 71.



3/8 NPT HollowStream nozzle lowers emissions inside of a gas scrubber.

			Hol	low!	Stream	Cone No	zzles									Spray	Angle									
Inlat	Inlet 0 Capacity		Max Free				Flo	w Rate C	SPM/LPN	И			In	let			Wi	dth								
Connection			Passage		3 psi	5 psi	7 psi	10 psi	20 psi	30 psi	40 psi	60 psi		sure BAR	in	A cm	in	cm	in	cm						
	555		200000000000000000000000000000000000000	GPM	0.29	0.34	0.39	0.45	0.62	0.75	0.86	1.04	7	0.5	10.1	25.6	15.1	38.4	25.2	63.9						
	HL300555	5	5	5	0.111"	LPM C	1.11	1.30	1.48	1.71	2.35	2.83	3.25	3.95	60	1.4	11.0	27.9	16.5	41.9	27.5	69.8 74.9				
		8		GPM L	0.50	0.60	0.71	0.82	1.12	1.33	1.50	1.80	7	0.5	7.5	19.0	11.2	28.6	18.7	47.6						
	HL300855		0.159*	LPM G	1.88	2.28	2.68	3.09	4.25	5.04	5.68	6.80	20	1.4	8.4	21.3	12.6	32.0	21.0	53.4						
					1,00	2.20	2.00	3.09	4.23	5.04	5.00	0.80	60	4.1	10.1	25.6	15.1	38.4	25.2	63.9						
	H13010SS	10	0.172*	GPM	0.64	0.75	0.89	1.01	1,36	1.62	1.83	2.47	7 20	0.5	8.4 9.5	21.3	12.6	32.0	21.0	53.4 60.6						
		10	0.172	LPM	2.42	2.84	3.36	3.81	5.16	6.13	6.93	9.35	60	4.1	10.4	26.5	15.6	39.7	26.1	66.2						
	-			GPM	0.94	1.10	1.29	1.48	1.98	2.60	2.80	3.60	7	0.5	11.4	28.9	17.1	43.4	28.5	72.3						
3/8 NPT	HL301555	15	0.166*	LPM C	3.54	4.16	4.88	5.60	7,48	9,84	10.60	13.63	20	1.4	13.1	33.3	19.6	49.9	32.7	83.2						
	_				3.34	4.10	4.00	3,00	7,40	9,04	10.60	13.03	60	4.1	13.8	35.1	20.7	52.6	34.5	87.7						
	2055	20	20	20	20	20	20	20	0.203*	GPM	1.28	1.50	1.81	2.00	2.75	3.39	3.92	4.53	7	0.5	11.4	28.9	17.1	43.4	28.5	72.3
	HL302055								0.203	LPM	4.86	5.69	6.86	7.57	10.41	12.84	14.83	17.13	60	1.4	13.1	33.3	18.0	49.9	30.0	76.2 83.2
	-			GPM L	1.45	1,78	2.02	2.45	3.34	4.00	4.52	5.40	7	0.5	10.1	25.6	15.1	38.4	25.2	63.9						
	1025	25 HL302555	0.219*			1,70					4132	3.40	20	1.4	11.0	27.9	16.5	41.9	27.5	69.8						
	Ξ	1000	775800	LPM	5.49	6.75	7.63	9.27	12.65	15,14	17.10	20.44	60	4.1	12.0	30.5	18.0	45.7	30.0	76.2						
	950	2010		GPM	1.80	2.30	2.68	3.10	4.23	5.13	6.03	7.28	7	0.5	8.2	20.9	12.4	31.4	20.6	52.4						
	HL303055	30	0.281*			20,557/1				1000000			20	1.4	8.7	22.1	13.1	33.2	21.8	55.4						
	Ħ			LPM	6.81	8.71	10.13	11.73	15.99	19.40	22.81	27.54	60	4.1	10.1	25.6	15.1	38.4	25.2	63.9						





## HollowStream™ Cone Nozzles – 1/2 NPT



Model: HL5025SS Material: Type 303 Stainless Steel



Model: HL5030SS Material: Type 303 Stainless Steel



Model: HL5040SS Material: Type 303 Stainless Steel




Model: HL5050SS Material: Type 303 Stainless Steel



Model: HL5060SS Material: Type 303 Stainless Steel

### Model HL5025SS, HL5030SS, HL5040SS, HL5050SS, HL5060SS

EXAIR's 1/2 NPT HollowStream Cone Nozzles produce a ring of liquid upon your target and are among the most common type of spray nozzles. Hollow cone spray nozzles generally use less liquid than full cone spray nozzles. These nozzles will be used for cooling, cleaning, washing, rinsing and dust suppression with less liquid than a full cone nozzle. Their tangential flow design is vaneless which creates wide open internal features to resist clogging. They produce a uniform distribution in a hollow cone round pattern and medium to large droplets. The right-angle design is compact and operates at up to 250 PSI liquid pressure. HollowStream nozzles work well with liquids containing particulate.



Compared to EXAIR's Air Atomizing Spray Nozzles the Hollow-Stream will have higher liquid flow rates.

For maximum liquid conservation and spray control visit page 71.



The precision machining of the HollowStream nozzle produces a controlled spray angle in this rinsing operation.

			Holle	owS1	ream (	one No	zzles									Spray	Angle																								
Inlet B			Max Free				Flo	w Rate C	PM/LPI	И			In	let			Wi	dth																							
Connection			Passage		3 psi	5 psi	7 psi	10 psi	20 psi	30 psi	40 psi	60 psi		sure BAR	in	A cm	in	B cm	in	C cm																					
	555			GPM	1.60	1.90	2.40	2.50	3.70	4.40	4.80	6.00	7	0.5	6.9	17.6	10.4	26.4	17.3	44.0																					
	HL300555	5	0.281*	-	200	200	20.22	VENERAL	1000.000	Sec.	Annual I	200	20	1.4	7.5	19.0	11.2	28.6	18.7	47.6																					
			TPM	6.06	7.19	9.08	9.46	14.01	16.66	18.17	22.71	60	4.1	8.4	21.3	12.6	32.0	21.0	53.4																						
	25			GPM	1.90	2.20	2.50	3.00	4.20	5.00	5.60	7.00	7	0.5	8.4	21.3	12.6	32.0	21,0	53.4																					
	HL300855	8	0.313"	-	ialia -		200	200		No. on C			20	1.4	9.0	23.0	13.6	34.5	22.6	57.4																					
	로		ПРМ	7.19	8.33	9.46	11.36	15.90	18.93	21.20	26.50	60	4.1	10.1	25.6	15.1	38.4	25.2	63.9																						
	SS			GPM	2.40	2.80	3.20	3.90	5.20	6.20	6.80	8.20	7	0.5	10.8	27.4	16.2	41.2	27.0	68.6																					
1/2 NPT	HL30105S	10	0.344"		200	0.00	0.803	TO BUILD I	13.12.0			2000	20	1.4	12.0	30.5	18.0	45.7	30.0	76.2																					
	Ħ	1.100		LPM	9.08	10.60	12.11	14.76	19.68	23.47	25.74	31.04	60	4.1	12.9	32.7	19.3	49.0	32.2	81.7																					
	SS																								GPM	3.20	3.80	4.60	5.00	6.80	7.90	9.00	12.50	7	0.5	13.8	35.1	20.7	52.6	34.5	87.7
	HL301555	15	0.344"		Para San			2000			2000		20	1.4	14.3	36.3	21.5	54.5	35.8	90.8																					
	Ħ	275.0	(980)	(989)	37000	LPM	12.11	14.38	17.41	18.93	25.74	29.90	34.07	07 47.32	60	4.1	15.4	39.0	23.0	58.5	38.4	97.5																			
	SS		GPM	3.60	4.20	5.40	6.00	7.80	9.20	11.50	14.00	7	0.5	14.3	36.3	21.5	54.5	35.8	90.8																						
	HL302055	20	0.344"	-	2000	0000				1500			20	1.4	17,1	43.5	25.7	65.3	43.8	111.4																					
	I			LPM	13.63	15.90	20.44	22.71	29.53	34.83	43.53	53.00	60	4.1	18.5	46.9	27.7	70.4	46.2	117.3																					









# **Safety Air Guns**

An INTELLIGENT OMPRESSED AIR Product

## Safety Air Guns use engineered air nozzles for high performance!

### Why EXAIR Safety Air Guns?

Inexpensive air guns are sold through many catalogs and industrial supply companies. Most have triggers or other parts that break quickly. Their performance is similar to open pipe, where they simply blow a lot of compressed air. In addition to the high air consumption, many produce noise levels that violate OSHA requirements. Some even generate dangerous dead end pressures that can result in serious or fatal injuries if blocked.

EXAIR's Safety Air Guns eliminate these problems. They are durable and comfortable to use. Each model uses an engineered Air Nozzle that provides superior performance by entraining large volumes of surrounding air. Safe operation is assured along with low air consumption and noise levels. Airflow that exits the nozzle cannot be blocked, as required by OSHA standard 1910.242(b).

#### Selecting The Right Safety Air Gun

The pages that follow show six Safety Air Guns. The VariBlast® Precision and Compact, Soft Grip, Heavy Duty, TurboBlast\* and Super Blast Safety Air Guns are available with a variety of air nozzles (listed in order of force). Stainless steel air nozzles provide more mechanical wear resistance while withstanding corrosion and high temperatures. PEEK Air Nozzles provide protection from accidental impact with the target and outstanding corrosion resistance. Air consumption, force and sound level are shown for all models. Complete details for each Air Nozzle are shown on pages 52-69.

# **Heavy Duty Safety Air Gur**



- · Variable flow trigger, 1/4 NPT inlet
- · Extremely lightweight, high impact thermoplastic
- · OSHA compliant for noise and pressure

### VariBlast® Compact Safety Air Gun

- · Low to medium airflow and force up to 1 pound
- · Variable flow trigger, (2) 1/4 NPT inlets
- · Cast aluminum body, hanger hook
- OSHA compliant for noise and pressure

## Soft Grip Safety Air Gun

- · Medium to high airflow and force up to 3.3 pounds
- · Full finger trigger, padded grip, 1/4 NPT inlet
- · Cast aluminum body, hanger hook
- · OSHA compliant for noise and pressure



## OSHA compliant for noise and pressure TurboBlast® Safety Air Gun

Wide curved trigger, rubber grip,

Medium to high airflow and

force up to 3.3 pounds

Cast aluminum body

3/8 NPT inlet

- Very high airflow and force up to 23 pounds
- · Ergonomic, soft handle
- One finger push-button trigger
- Adjustable airflow
- OSHA compliant for noise and pressure
- · 1 NPT inlet

#### Super Blast Safety Air Gun


- Very high airflow and force up to 23 pounds
- Spring loaded ball valve trigger, and foam handle
- OSHA compliant for noise and pressure
- 3/8 NPT 1-1/4 NPT Inlets



SCAN & WATCH the video

https://exair.co/qr\_sagv














## Safety Air Guns COMPRESSED AIR



# **Chip Shields**

## **Protect workers from** flying debris and prevent splash back!



#### Why the EXAIR Chip Shield?

Chip Shields are durable polycarbonate shields that protect operators from flying debris often associated with blowing chips off machined parts. Chip Shields are also great for keeping coolant from spreading everywhere during drying operations. EXAIR's Chip Shields help meet the requirements of OSHA 1910.242(b) for safe use of compressed air.

Chip Shields are available for EXAIR's VariBlast Precision and Compact Safety Air Gun, Soft Grip Safety Air Gun and Heavy Duty Safety Air Gun. Chip Shields can be used on Safety Air Guns with or without an Aluminum Extension. Chip Shields are not for use on guns that use a Stay Set Hose.

#### How to Order the EXAIR Chip Shield.

To order a Safety Air Gun with a Chip Shield, simply add a '-CS' to the end of the model number.

Model 1210-CS is a Model 1210 Soft Grip Safety Air Gun with a Chip Shield.

Model 1310-12-CS is a Model 1310 Heavy Duty Safety Air Gun with a 12" (305mm) Aluminum Extension Pipe and Chip Shield.









Model 1696SS-CS shown

Model 1810SS-CS shown

Model 1360SS-CS shown

#### the Chip Shield is supplied with a rubber grommet to ensure a tight fit onto the extension Chip Shield # Safety Air Gun Models Covered 1808SS, 1808-PEEK, 1809SS, 1809-PEEK, 1810SS, 1810-PEEK 1229, 1229SS, HP1229, HP1229SS, 1280SS, 1290, 1290SS, 1296SS, 1296-PEEK, 1297SS, 1297-PEEK, 1298SS, 1298-PEEK, 1299, 12995S, 1299-PEEK, 16965S, 1696-PEEK, 1697-PEEK, 1698SS, 1698-PEEK, 1699, 1699-PEEK, 1699SS, 1698-PEEK, 1699-PEEK, 1699SS, 1698-PEEK, 1699-PEEK, 1699-PEEK, 1699SS, 1698-PEEK, 1699-PEEK, 1699-P 901221 1210, 1210SS, 1210-PEEK, 1230, 1230SS, HP1230, HP1230SS, 1310, 1310SS, 1310-PEEK, 1330, 1330SS, 901222 901223 1240, 1250, 1250SS, 1250-PEEK, 1260, 1260SS, 1340, 1350, 1350SS, 1350-PEEK, 1360, 1360SS

Chip Shields for Safety Air Guns With Aluminium Extensions

Chip Shields are also available to be retrofitted to existing Safety Air Guns. For models that already have an Aluminum Extension in place,

	Chip Shields for Safety Air Guns Without Aluminium Extensions
or models that do not a	stready have an Aluminum Extension in place, a short extension nipple and the necessary adapter are provided
Chip Shield Kit #	Safety Air Gun Models Covered
901231	1229, 1229S, HP1229, HP1229SS, 1280SS, 1290, 1290SS, 1296SS, 1296-PEEK, 1297SS, 1297-PEEK, 1298SS, 1298-PEEK, 1299, 1299SS, 1299-PEEK, 1696SS, 1696-PEEK, 1697SS, 1697-PEEK, 1698SS, 1698-PEEK, 1699S, 1629, 1629SS, 1669S, 1699S, 1629, 1699S, 1629SS, 1629SSS,
901232	1210, 1210SS, 1210-PEEK, 1230, 1230SS, HP1230, HP1230SS, 1310, 1310SS, 1310-PEEK, 1330, 1330SS, HP1330, HP1330SS
901233	1240, 1250, 1250SS, 1250-PEEK, 1340, 1350, 1350SS, 1350-PEEK
901234	1260, 1260SS, 1360, 1360SS



Model 1299-6-CS shown



FAX (513) 671-3363 \* E-mail: techelp@exair.com \* www.exair.com



## An INTELLIGENT Product

## VAFIBLAST Precision Safety Air Guns

#### VARIBLAST Precision Safety Air Gun - 1/4 NPT Inlet

EXAIR's VariBlast\* Precision Safety Air Guns are extremely lightweight and have a focused blast of air that provides remarkable cleaning capability. Designed with a variable flow trigger, the air flow is easily adjustable and able to produce a range of different force values. It comes equipped with a small diameter nozzle and extension that easily fits into tight spaces and delivers a pinpoint, but powerful blast. Two other extension lengths are available.

The VariBlast Precision Safety Air Gun is available with EXAIR's Atto, Pico and Nano Air Nozzles, which are engineered to maximize entrainment of ambient air, while minimizing air consumption and noise. The airflow that exits the nozzle can't be blocked, assuring safe operation and meeting required OSHA standards 1910.242(b). The VariBlast also boasts a 58 to 75 dBA noise level (depending on the nozzle installed) which is well below the limits of OSHA Standard 29 CFR 1910.95(a) for maximum allowable noise exposure.

These intelligent nozzles come in either Type 316 stainless steel for superior corrosion resistance or PEEK plastic for non-marring applications and increased chemical resistance. The air gun body is made of high impact, acetal thermoplastic and all models are available with an impact resistant polycarbonate Chip Shield. Extension material is Type 316 stainless steel. The VariBlast is also fashioned with a 1/4 NPT inlet for easy hook up to your compressed air supply.




#### Add An Extension Pipe

Add an Extension Pipe to your VariBlast Precision Safety Air Gun.



2. To add an Extension Pipe, create the model number by adding a dash and number of the appropriate length after the model of the VariBlast Precision Safety Air Gun. The Model 1808SS VariBlast Precision Safety Air Gun with a 12" (305mm)











## VARIBLAST\* Compact Safety Air Guns COMPRESSED AIR

The VariBlast Compact Safety Air Gun is

easily configurable with EXAIR Nozzles,

**Extension Pipes and Chip Shields** 

Model shown here:

Air flow is easily

adjustable with

Durable, ergonomic

grip for comfort

user friendly

trigger

169955-CS

Product

Chip Shield

Easy storage

Dual 1/4

NPT Air

inlets

The Model 1699-CS

removes chips and

coolant from a

machined part.

hanger

#### VARIBLAST Compact Safety Air Gun - 1/4 NPT Inlet

EXAIR's VariBlast Compact Safety Air Guns are small and lightweight air guns capable of handling tough jobs. Designed with a variable flow trigger, they are able to produce different force values from the same nozzle simply by pulling the trigger more or less. These air guns can be outfitted with all of EXAIR's 1/8 NPT engineered air nozzles and extensions are available up to 72" long.



The wide variety of intelligent compressed air nozzles installed on the VariBlast Compact Safety Air Gun make it a great selection for light to medium duty applications requiring

force values of up to 1 pound while remaining among the most efficient air guns in EXAIR's product line. EXAIR Super Air Nozzles are engineered to maximize entrainment of ambient air while minimizing air consumption and noise. Safe operation is assured since airflow that exits the nozzle cannot be blocked, per OSHA Standard 1910.242(b). The 58 to 82 dBA noise level is well below the limits of the OSHA maximum noise exposure standard 29 CFR 1910.95(a).

Engineered air nozzles are available in Type 316 stainless steel for superior corrosion resistance and mechanical wear, Type 303SS for corrosion resistance, PEEK thermoplastic for nonmarring and chemical resistance or zinc/aluminum alloy or aluminum for general purpose applications. The air gun body is cast aluminum and has two 1/4 NPT air inlets to ensure ergonomic handling. All models are available with an impact resistant polycarbonate Chip Shield.



Model 1699 VariBlast Compact Safety Air Gun

Air Consumption		Fo	rce*	Sound Level		Use Model
SCFM	SLPM	Ozs	Grams	dBA		900750 Coiled Hose
10	283	9	255	71	-	Coned mose

\* Force measured at 12" (305mm) from target. Sound level measured at 3" (914mm). All measurements taken at 80 PSIG (5.5 BAR).



Model 169955 VariBlast Compact Safety Air Gun Nozzle: 110355 Stainless Stee

The Model 1699SS uses the stainless steel Super Air Nozzle steel for rugged use and corrosion resistance.



Model 1699-PEEK Nozzle: 1102-PEEK Plastic Mini

The Model 1699-PEEK uses the PEEK Super Air Nozzle for nonconstructed of Type 316 stainless marring and chemical resistance.



### An INTELLIGENT Product

## VAFIBLAST\* Compact Safety Air Guns



Model 1696SS VariBlast Compact Safety Air Gun Also Available: 1696-PEEK with 1108-PEEK PEEK Plastic Atto Super Air Nozzle

Air Cons	umption		orce*	Sound Level	
SCFM	SLPM	Ozs	Grams	dBA	
2.5	71	2.0	57	58	





Model 1697SS VariBlast Compact Safety Air Gun Also Available: 1697-PEEK with 1109-PEEK

Air Cons	umption	F		Sound Level	
SCFM	SLPM	Ozs	Grams	dBA	
4.9	139	5.0	142	68	





Model 1698SS VariBlast Compact Safety Air Gun Also Available: 1698-PEEK with 1110-PEEK PEEK Plastic Nano Super Air Nozz

Air Cons	umption			Sound Leve	
SCFM	SLPM	Ozs	Grams	dBA	
8.3	235	8.1	230	75	





Model 1629 VariBlast Compact Safety Air Gun Nozzle: 1126 1\* Flat Super Air Nozzle

Also Available: 1629SS with 1126SS Stainless Steel 1" Flat Super Air Nozzle .015" (0.38mm) shim installed

Air Cons	umption	Fe	orce*	Sound Level	
SCFM	SLPM	Ozs	Grams	dBA	
10.5	297	9.8	278	75	







Model 1680SS VariBlast Compact Safety Air Gun

Air Cons	umption	F	orce*	Sound Level
SCFM	SLPM	Ozs	Grams	dBA
13	368	12	340	80





Model 1690 VariBlast Compact Safety Air Gun

Also Available: 1690SS with 1009SS Stainless Steel Adjustable Air Nozzle

Air Cons	umption	Fi	orce*	Sound Level	
SCFM	SLPM	Ozs	Grams	dBA	
13	368	12	340	79	ŀ





Model HP1629 VariBlast Compact Safety Air Gun

Also Available: HP1629SS with HP1126SS Stainless Steel 1" High Power Flat Super Air Nozzle .025" (0.64mm) shim installed

Air Cons	umption	Fe	orce"	Sound Level
SCFM	SLPM	Ozs	Grams	dBA
17.5	495	16	454	82





VariBlast Compact Back Blow Safety Air Gun, 6" extension Nozzle: 1004SS Stainless Steel Back Blow Air No.

Also Available: Models 1604SS-12-CS (12" ext.), 1604SS-24-CS (24" ext.), 1604SS-36-CS (36" ext.), with 1004SS Stainless Steel Back Blow Air Noz. Aluminum Extension and Chip Shield

Air Cons	Air Consumption		Use With:		
SCFM	SLPM	dBA	Inside Diameter		
4.5	127	75	1/4"-1" (6.3-25.4mm)		



Force measured at 12" (305mm) from target. Sound level measured at 3" (914mm). All measurements taken at 80 PSIG (5.5 BAR).

#### Add An Extension Pipe

Add an Extension Pipe to your VariBlast Compact Safety Air Gun. Here's how:


- 1. Choose an EXAIR VariBlast Compact Safety Air Gun. Model 1699
- 2. To add an Aluminum Extension Pipe, create the model number by adding a dash and number of the appropriate extension length after the model of the VariBlast Compact Safety Air Gun. The Model 1699 VariBlast Compact Safety Air Gun with a 12" (305mm) Aluminum Extension Pipe is a Model 1699-12.

Aluminum Extension Pipe
All VariBlast Compact Safety Air Guns with Extension Pipes come fully assembled.
Model

Model Addition #	Length
-6	6" (152mm)
-12	12" (305mm)
-18	18" (457mm)
-24	24" (610mm)
-36	36" (914mm)
-48	48" (1219mm)
-60	60" (1524mm)
-72	72" (1829mm)

* +	•	= 1	
Model# 1699	-CS	1699 -CS	









# Soft Grip Safety Air Guns COMPRESSES Product



#### Soft Grip Safety Air Gun - 1/4 NPT Inlet

EXAIR's Soft Grip Safety Air Gun is ideal for hours of continuous use without fatigue. The ergonomic design keeps the hand in a comfortable position and incorporates a large trigger that permits operation with one or more fingers. The durable cast aluminum body is suited for rugged industrial use and includes a convenient hanger hook for easy storage. The Soft Grip Safety Air Gun is available with Air Nozzles as shown for quiet, safe and efficient use of the compressed air supply. Aluminum Extension Pipes, Stay Set Hoses, and Chip Shields are available for most models. The inlet is 1/4 NPT.









Nozzle: 1100T-PEEK Super Air Nozzle The Model 1210-PEEK uses the PEEK Super Air Nozzle for nonmarring and chemical resistance.

\*Force measured at 12" (305mm) from target. Sound level measured at 3" (914mm). All measurements taken at 80 PSIG (5.5 BAR).



constructed of Type 316

and corrosion resistance.

stainless steel for rugged use



1/4 NPT Air inlet

# An INTELLIGENT COMPRESSED AIR Product

## **Soft Grip Safety Air Guns**



Model 1299 SG Safety Air Gun Nozzle: 1103 Mini Super Air Nozzle

Also Available: 1299SS with 1103SS 1299-PEEK with 1102-PEEK PEEK Plastic Mini Super Air Nozzle

Air Cons	umption			Sound Level	
SCFM	SLPM	Ozs	Grams	dBA	ı
10	283	9.0	255	71	١





Model 1229 SG Safety Air Gun Nozzle: 1126 1" Flat Super Air Nozzle

Also Available: 1229SS with 1126SS .015\* (0.38mm) shim installed

	umption	Fo		Sound Level	
SCFM	SLPM	Ozs	Grams	dBA	
10.5	297	9.8	278	75	





Model 1290 SG Safety Air Gun Nozzle: 1009 Adjustable Air Nozzle

Also Available: 129055 with 100955

Air Cons	umption		rce*	Sound Level
SCFM	SLPM	Ozs	Grams	dBA
13	368	12	340	79







Model 1280SS SG Safety Air Gun Nozzle: 1010SS Micro Air Nozzle

Air Cons	r Consumption		umption Force*			Sound Level
SCFM	SLPM	Ozs	Grams	dBA		
13	368	12	340	80		





Model HP1229 SG Safety Air Gun Nozzle: HP1126 1" High Power Flat Super Air Nozzle

Also Available: HP1229SS with HP1126SS itainless Steel 1" High Power Flat Super Air Nozzle .025" (0.64mm) shim installed

Air Cons	umption	Fo	orce*	Sound Level
SCFM	SLPM	Ozs	Grams	dBA
17.5	495	16	454	82





Model 1230 SG Safety Air Gun Nozzle: 1122 2" Flat Super Air Nozzle Also Available: 123055 with 112255 Stainless Steel 2" Flat Super Air Nozzle .015\* (0.38mm) shim installed

Air Cons	Air Consumption		ir Consumption Force*		orce*	Sound Level
SCFM	SLPM	Ozs	Grams	dBA		
22	622	22	624	77		











## **Soft Grip Safety Air Guns**



Grams

dBA

83



Model 1250 SG Safety Air Gun Also Available: 1250SS with 1104SS 3/8 NPT

1250-PEEK with 1104-PEEK 3/8 NPT PEEK Plastic Super Air Nozzle

Air Cons	Air Consumption		Consumption Force*		Sound Level
SCFM	SLPM	Lbs	Grams	dBA	
35	991	1.9	862	82	

SLPM

1.039

SCFM

37



Model HP1230 SG Safety Air Gun Also Available: HP1230SS with HP1125SS

.025" (0.64mm) shim installed



Model 1240 SG Safety Air Gun Nozzle: 1111-4 Super Air Nozzle Cluster

Air Cons	umption	Fo	rce*	Sound Level
SCFM	SLPM	Lbs	Grams	dBA
56	1,585	3.2	1,451	82

Lbs

2.2



Model 1260 SG Safety Air Gun Nozzle: 1106 1/2 NPT Super Air Nozzle Also Available: 1260SS with 1106SS 1/2 NPT Stainless Steel Super Air Nozzle

Air Cons	Air Consumption		onsumption Force"		Sound Level
SCFM	SLPM	Lbs	Grams	dBA	
60	1,699	3.3	1,497	87	



Model 1204SS-6-CS SG Back Blow Safety Air Gun Nozzle: 1004SS Stainless Steel Back Blow Air Nozzle. Aluminum Extension and Chip Shield

Air Cons	umption	Sound Level	Use With:
SCFM	SLPM	dBA	Inside Diameter
4.5	127	75	1/4" - 1" (6.3-25.4mm)



Model 1206SS-6-CS SG Back Blow Safety Air Gun Nozzle: 1006SS Stainless Steel Back Blow Air Nozzle, Aluminum Extension and Chip Shield


#### The Model 1206SS-6-CS Back Blow Safety Air Gun removes chips from the inside of a machined part.

Air Consumption		Sound Level	Use With:
SCFM	SLPM	dBA	Inside Diameter
22	622	80	7/8" - 4" (22-102mm)

## Add An Extension Pipe Or Stay Set Hose


Add an Extension Pipe or Stay Set Hose to your Soft Grip Safety Air Gun. Here's how:

- 1. Choose an EXAIR Soft Grip Safety Air Gun. Model 1210
- 2. To add an Aluminum Extension Pipe, create the model number by adding a dash and number of the appropriate extension length after the model of the Soft Grip Safety Air Gun. (See table to right) The Model 1210 Soft Grip Safety Air Gun with a 12" (305mm) Aluminum Extension Pipe is a Model 1210-12.
- 3. To add a Stay Set Hose, create the model number by adding a dash and number of the appropriate Stay Set Hose after the model of the Soft Grip Safety Air Gun. (See table to the far right) The Model 1210 Safety Air Gun with a 12" (305mm) Stay Set Hose is a Model 1210-12.



72° (1829mm)

II Soft Grip Safety Air Guns ome fully assembled.	
Model Addition #	Length
-6SSH	6" (152mm)
-125SH	12" (305mm)
-18SSH	18" (457mm)
-24SSH	24" (610mm)
-305SH	30" (762mm)
-36SSH	36" (914mm)





11510 Goldcoast Drive • Cincinnati, OH 45249-1621 • Phone (513) 671-3322 FAX (513) 671-3363 \* E-mail: techelp@exair.com \* www.exair.com

-72



## Soft Grip Super Air Scraper

#### Soft Grip Super Air Scraper™ - 1/4 NPT Inlet

An INTELLIGENT

Patent #10,779,698

Model 1244

Nozzle: 1144 1/4 NPT

2" Super Air Scraper

Soft Grip Super Air Scraper

Product

EXAIR's Soft Grip Super Air Scraper is a safety air gun designed to help remove the most stubborn debris found within industrial facilities. The patented† design uses a scraping blade to assist the powerful compressed air flow removal of debris. This product is perfect for removal of caulk, gaskets, sealant, adhesives, tape, paint, stickers, labels, grease, lubricant and difficult to sweep metal chips, flakes or discs. It will help keep your machining tables, sub plate and assembly stations clean and functional.

The corrosion resistant steel scraper is attached to a 2" Flat Super Air Nozzle and a 3/4" extension to provide the strength and durability necessary for many of your toughest cleaning and housekeeping challenges. Extensions for the Soft Grip Super Air Scraper are available from 6"-72" long to aid in cleaning table tops, inside machines, reaching the floor or other remote surfaces. Chip Shields are also available.

Model#

1144

902007

901223

113255



EXAIR's patented design utilizes the 2" Super Air Scraper.

SCFM SIPM Ozs Grams dR 622 22 624

Replacement scraper blade only

2\* Flat Super Air Nozzle Shim Set

Chip Shield for 3/4" extension

Soft Grip Super Air Scraper Acc

Super Air Scraper replacement nozzle (perforn

7	Coiled Hose
essorie	5
ance deta	ails on page 57)

The Model 1244-36 scrapes and blows old tape off a concrete floor.

#### Add An Extension Pipe

Add an Extension Pipe to your Soft Grip Super Air Scraper. Here's how:

- 1. Choose an EXAIR Soft Grip Super Air Scraper. Example: Model 1244
- 2. To add an Aluminum Extension Pipe, create the model number by adding a dash and number of the appropriate extension length after the model of the Soft Grip Super Air Scraper. Example The Model 1244 Soft Grip Super Air Scraper with a 36" (914mm) Aluminum Extension Pipe is a Model 1244-36.

Extens	ionripe	Gu
	uper Air Scrapers n Pipes come ed.	
Model Addition	Length	
-6	6° (152mm)	Mandal
-12	12" (305mm)	Model
-18	18" (457mm)	ä
-24	24* (610mm)	ple
-36	36" (014mm)	= .







Chip Shields can be added to EXAIR's Safety Air



For Technical Assistance, Call An EXAIR Application Engineer 1-800-903-9247 Toll Free FAX (866) 329-3924 • E-mail: techelp@exair.com • www.exair.com

## Heavy Duty Safety Air Guns COMPRESSED AIR



#### Heavy Duty Safety Air Gun - 3/8 NPT Inlet

Model 1310 Heavy Duty Safety Air Gun



EXAIR's Heavy Duty Safety Air Gun is a powerful air gun that delivers high force for use in rugged, industrial environments. The 3/8 NPT compressed air inlet increases the compressed air flow available to the Super Air Nozzle. resulting in higher force and flow than other air guns. The durable cast aluminum body includes an ergonomic composite rubber grip and wide curved trigger that makes it comfortable for hours of use without fatigue. Aluminum Extension Pipes and Chip Shields are available. (Stay Set Hoses are not available.)





Model 1310SS HD Safety Air Gun Nozzle: 1100SST Super Air Nozzle Type 316 Stainless Steel Super Air Nozzle for rugged use and corrosion resistance.

dBA

Grams

998

dRA





Model 1310-PEEK HD Safety Air Gun Nozzle: 1100T-PEEK Super Air Nozzle PEEK Super Air Nozzle for nonmarring and chemical resistance.

Add An Extension Pipe

Add an Extension Pipe to your

Heavy Duty Safety Air Gun.

Example: Model 1310

Gun. (See table below)

-12

.18

-24

-36

-48

-60

-72

0

. Choose an EXAIR Heavy Duty Safety Air Gun.

2. To add an Aluminum Extension Pipe, create

Here's how:



Model 1330 HD Safety Air Gun

14 396 13 369

1122 2' Flat Super Air Nozzle

1330SS with 1122SS Stainless Steel 2" Flat Super Air Nozzle .015" (0.38mm) shim installed

SCFM SLPM lbs Grams

622 22 624



Model 1350 HD Safety Air Gun

1104 3/8 NPT

35 991 1.9 862 1350SS with 1104SS 3/8 NPT Stainless Steel Super Air Nozzle 1350-PEEK with 1104-PEEK 3/8 NPT PEEK Plastic Super Air Nozzle

SLPM

1,039

-	_	_
ARTICL STREET	-	-
1	THE OWNER OF THE OWNER OWN	-
Flat air pattern	2000	
	Distance of the last	

Street, Square, Square	A STREET
Flat air pattern	9
Model UD1220	D.C. L.L. N. C.

Also Availabl

HP1125 2" High Power Flat

HP1330SS with HP1125SS Stainless Steel 2" High Power Flat Super Air Nozzle .025" (0.64mm) shim installed



Air Cons	umption	Fo	rce*	Sound Leve	
SCFM	SLPM	lbs	Grams	dBA	
56	1,585	3.2	1,451	82	

lhs

2.2

Model 1340 HD Safety Air Gun



All the second second	Air Cons	Air Consumption		Force*	
The second second	SCFM	SLPM	lbs	Grams	dBA
	60	1,699	3.3	1,497	87
Model 1360 HD Safety Air Gun					

SCEM

Nozzle: 1106 1/2 NPT Super Air Nozzle



1000	SCFM	SLPINI	OBA:	inside Diameter
	22	622	80	7/8" - 4" (22-102mm)

1360SS with 1106SS 1/2 NPT Stainless Steel Super Air Nozzle

Model 1306SS-x-CS HD Back Blow Safety Air Gun

1006SS Stainless Steel Back Blow Air Nozzle, Aluminum Extension, and Chip Shield

Also Available



+ -CS (Chip Shield)

1310 (Heavy Duty Air Gun)

1310-CS See page 107 for

## An INTELLIGENT Product

## **Back Blow Safety Air Guns**

#### Back Blow Safety Air Guns - 1/4, 3/8 and 1 NPT Inlet

Back Blow Safety Air Guns are perfect for cleaning out the inside of pipe, tube, hose or channels. EXAIR's engineered Back Blow nozzle provides a powerful 360 degree airflow through an array of holes to remove coolant, chips or debris. Available in our VariBlast, Soft Grip, Heavy Duty or Super Blast version, each gun style can be outfitted with an up to 72" extension to reach far into your application and provide airflow. VariBlast, Soft Grip and Heavy Duty Back Blow Safety Air Guns are outfitted with a Chip Shield to protect the operator from flying debris. Since airflow is directed back toward the operator, personal protection equipment is recommended.



1004SS Stainless Steel Back Blow Air Nozzle Aluminum Extension and

The VariBlast Compact Back Blow Safety Air Gun has dual 1/4 NPT inlets and provides a variable force trigger on a small, powerful and ergonomic air gun.

		lir mption	Sound Level	Use With:
Model #	SCFM	SLPM	dBA	Inside Diameter
160455	4.5	127	75	1/4"-1" (6.3-25.4mm)

dBA

dBA

Model # SCFM SLPM dBA Inside Diamete

Inside Diameter

Model # SCFM SLPM

Model # SCFM SLPM

1204SS 4.5 127 75

Model #	Description	Model #	Description
16045S-6-C5	VariBlast, 6" Extension, Chip Shield	1604SS-24-CS	VariBlast, 24* Extension, Chip Shield
1604SS-12-CS	VariBlast, 12" Extension, Chip Shield	160455-36-C5	VariBlast, 36" Extension, Chip Shield



1004SS Stainless Steel Back Blow Air Nozzle, Aluminum Extension and

The Soft Grip Back Blow Safety Air Gun provides an ergonomic design with a 1/4 NPT inlet and a full grip trigger which is ideal for aure of continuous aparation without fatigue

nours or con	tinuous operation without fatig	,uc.		
Model #	Description	Model #	Description	
12045S-6-C5	Soft Grip, 6" Extension, Chip Shield	1204SS-24-CS	Soft Grip, 24" Extension, Chip Shield	
120455-12-C5	Soft Grip, 12" Extension, Chip Shield	1204SS-36-CS	Soft Grip, 36" Extension, Chip Shield	





the model number by adding a dash and number of the appropriate extension length after the model of the Heavy Duty Safety Air

Example: The Model 1310 Heavy Duty Safety Air Gun with a 12" (305mm) Aluminum Extension Pipe is a Model 1310-12.

**Aluminum Extension Pipe** 

Model Addition # / Extension Length

Chip Shields can be added to EXAIR's Safety Air Guns by adding a "-CS" to the Model#.

Example:

6" (152mm)

12" (305mm)

18" (457mm)

24" (610mm)

36° (914mm)

48" (1219mm)

60° (1524mm)

72" (1829mm)

All Heavy Duty Safety Air Guns with Extension Pipes

Model 1206SS-x-CS Soft Grip Back Blow Safety Air Gun

1006SS Stainless Steel Back Blow Air Nozzle, Aluminum Extension and Chip Shield

The Soft Grip Back Blow Safety Air Gun provides an ergonomic design with a 1/4 NPT

inlet and a full grip trigger which is ideal for hours of continuous operation without fatigue.

Model#	Description	Model #	Description
1206SS-6-CS	Soft Grip, 6" Extension, Chip Shield	12065S-36-C5	Soft Grip, 36" Extension, Chip Shield
1206SS-12-CS	Soft Grip, 12" Extension, Chip Shield	120655-48-C5	Soft Grip, 48" Extension, Chip Shield
120655-18-CS	Soft Grip, 18" Extension, Chip Shield	12065S-60-C5	Soft Grip, 60" Extension, Chip Shield
12065S-24-CS	Soft Grip, 24" Extension, Chip Shield	1206SS-72-CS	Soft Grip, 72" Extension, Chip Shield



1006SS Stainless Steel Back Blow Air Nozzle Aluminum Extension and Chip Shield

The Heavy Duty Back Blow Safety Air Gun has a larger rubber grip and a larger 3/8 NPT inlet. Durable cast aluminum gun body and full

inlet. Durab grip trigger	130655	22	622	80	7/8"-4" (22-102mm)	
Model #	Description	Model #	Descri	ption		
13065S-6-CS	Heavy Duty, 6" Extension, Chip Shield	1306SS-36-CS	Heavy	Duty, 36* I	xtension	, Chip Shield
1306SS-12-CS	Heavy Duty, 12" Extension, Chip Shield	1306SS-48-CS	Heavy	Duty, 48"	Extension	, Chip Shield
1306SS-18-CS	Heavy Duty, 18" Extension, Chip Shield	130655-60-CS	Heavy	Duty, 60"	Extension	, Chip Shield
13065S-24-C5	Heavy Duty, 24" Extension, Chip Shield	130655-72-C5	Heavy	Duty, 72"	Extension	, Chip Shield



Nozzle and Aluminum Extens

	extension, a comfortable soft grip a fautomatically if it is dropped.	and a spring-loaded manu	al valve	which
Model #	Description	Air	Sound	Use
121955	Super Blast, 1' (305mm) Extension	Consumption	Level	With:

Super Blast Back Blow Safety Air Guns provide the strongest blowing force to remove

debris from the largest pipe diameters and deepest channels. These guns are sold with a

Model #	Description			<b>lir</b>	Sound	Use
121955	Super Blast, 1' (305mm) Extension		The second	mption	Level	With:
121955-3	Super Blast, 3' (1m) Extension	Model #	SCFM	SLPM	dBA	Inside Diameter
121955-6	Super Blast, 6' (1.8m) Extension	121955	57	1,614	89	2"-16" (51-406mm)













## 7000 **3LAST** Adjustable Safety Air Guns



Model shown here:

Soft, ergonomic

grips for comfort

available.

Strong and durable

Gate Valve for easy

1 NPT Air Inlet

flow adjustment.

extension. 1', 3', 6'

1928

#### DLAST Adjustable Safety Air Gun

EXAIR's TurboBlast® Safety Air Guns produce the **Engineered Super Air Nozzle** highest force values available through a comfortable. Protective air nozzle guard safe and easy to use handle. TurboBlast Safety Air Guns with a gate valve allow for on-the-fly airflow adjustment when less or more airflow is demanded from the application. The rugged cast aluminum handle is surrounded by an overmolded soft, yet rugged elastomer grip that is UV and chemical resistant. The handle houses a low-profile trigger button, which keeps the trigger protected if dropped. An automatic air shut-off mechanism will engage if the TurboBlast gun is released or dropped, preventing injury to operators. This trigger needs just a slight squeeze to activate any of EXAIR's largest and most powerful air nozzles which can be used to remove stubborn debris, slag, flash or liquids from many harsh processes. It will accommodate EXAIR's five largest Super Air Nozzles, from 3/4 NPT to 1-1/4 NPT and 4.5 to 23 pounds of force (2.04 to 10.43 Kg). Base models include the 1' (305mm) extension, but can also be ordered with a 3' (914mm) or 6' (1829mm) extension. Nozzle guards are included for all models.

Model 1925 Nozzle Material Zinc Aluminum allov Nozzle Airflow Pattern: see Model 1114 on page 65. Model 1925SS with Stainless Steel Nozzle also available







dBA

96

Kg

Kg

4.26

102

			1 FNPT	Air Inlet -
Air Cons	umption	For	rce*	Sound
SCFM	SLPM	lbs	Kg	dBA
300	8,495	15	6.80	106



See page 118 for info on

-800-903-9247

rzle Guards and Extension Pipes

SCFM	SLPM	lbs	Kg	dB/
460	13,026	23	10.43	109

\*Force measured at 12" (305mm) from target. Sound level measured at 3" (914mm). All measurements taken at 80 PSIG (5.5 BAR).



SCFM SLPM lbs

5,324

OSHA 1 hour total exposure per day without hearing protection

Model 1924

Nozzle Material

Zinc Aluminum alloy

Nozzle also available

Nozzle Airflow Pattern:

see Model 1112 on page 65.

Model 1924SS with Stainless Steel

Ibs

91 2,577 4.5 2.04





# **SLAST** Safety Air Gun Model 1914


Product

An INTELLIGENT

Nozzle Material: Zinc Aluminum alloy


Nozzle Airflow Pattern: see Model 1112 on page 65. Model 1914SS with Stainless Steel

Nozzle also available



Air Cons	umption	For		Sound Level
SCFM	SLPM	lbs	Kg	dBA
91	2,577	4.5	2.04	96





Air Cons	umption	For		Sound
SCFM	SLPM	lbs	Kg	dBA
135	3,823	6.6	2.99	99



Model 1916

Nozzle Material:

Zinc Aluminum alloy

Nozzle Airflow Pattern

see Model 1116 on page 66.

Air Cons	umption	For	Force*		
SCFM	SLPM	lbs	Kg	dBA	
188	5,324	9.4	4.26	102	



	3	- 55	1 FN	PT Air Inlet
Air Cons	umption	Fo	rce*	Sound
SCFM	SLPM	lbs	Kg	dBA
300	8,495	15	6.80	106

OSHA 1/2 hour total exposure per day without hearing protection



OSHA 1/2 hour total exposure per day without hearing protection

\*Force measured at 12" (305mm) from target. Sound level measured at 3" (914mm). All measurements taken at 80 PSIG (5.5 BAR).








#### Add a longer extension pipe to your TurboBlast Safety Air Gun.

Create the model number by adding a dash and number of the extension pipe to the TurboBlast Safety Air Gun.

1. The Model 1914 TurboBlast Safety Air Gun with a 3' extension would be a Model 1914-3.




1914-3

All TurboBlast Scome fully asser			Exter	nsion Pipes
Model#		Model A Extension		
1914 or 1914SS				
1924 or 1924SS		36° (914mm)	-6	72* (1829mm)
1915 or 191555				
1925 or 1925SS	-3			
1916 or 1926				
1917 or 1927				
1918 or 1928				









## Super Blast Safety Air Guns COMPRESSED AIR



### **High Force Safety Air Guns**

These hand-held versions of our Super Air Nozzle Clusters and large Super Air Nozzles provide the same strong blowing force with the added convenience of a comfortable soft grip and easy to operate spring-loaded manual valve that automatically shuts off if it is dropped. The Super Blast Safety Air Guns are ideal for long distance, wide area blowoff, cooling and drying applications. All Super Blast Safety Air Guns meet OSHA noise level and pressure requirements.



# Add a longer extension pipe to

The Model 1213-4 Super Blast Safety Air Gun

1213-4 (Super Blast Safety Air Gun) -3 (3' extension)

	last Safety Air Gun assembled.	s with Extension Pipe
Model#	Model Addition	# / Extension Length
1213-4	-3	36° (914mm)
3/8 NPT	-6	72" (1829mm)
1213-7	-3	36" (914mm)
1/2 NPT	-6	72" (1829mm)
1213-12	-3	36" (914mm)
1 NPT	-6	72" (1829mm)

# your Super Blast Safety Air Gun.

Create the model number by adding a dash and number of the extension pipe to the Super Blast Safety Air Gun.

with a 3' extension would be a Model 1213-4-3.

1213-4-3

	last Safety Air Gun assembled.	s with Extension Pipe
Model#	Model Addition	# / Extension Length
1213-4	-3	36° (914mm)
3/8 NPT	-6	72" (1829mm)
1213-7	-3	36" (914mm)
1/2 NPT	-6	72" (1829mm)
1213-12	-3	36" (914mm)
1 NPT	-6	72" (1829mm)



Model 1213-7 1/2 NPT female Nozzles - Zinc Aluminum alloy Body - Aluminum



							25mm
Air Consumption		Force*		Sound Level		Air Cons	umption
SCFM	SLPM	lbs	Kg	dBA		SCFM	SLPM
56	1,585	3.2	1.45	82		98	2,773
		205			4.50		

Sound level measured at 3' (914mm)

Model 1213-4 3/8 NPT female

Nozzles - Zinc Aluminum alloy Body - Aluminum

Airflow Pattern: see Model 1111-4 on page 67.

Airflow Pattern: see Model 1111-7 on page 67.


NPT	1	Across Flats 25mm				
Air Con		umption	For	ce*	Soun	
SC	FM	SLPM	lbs	Kg	dBA	
9	88	2,773	5.7	2.59	85	
Force	measi	ured at 12" (	305mm) f	rom taro	et	

Sound level measured at 3' (914mm)



Model 1213-12 1 NPT female Nozzles - Zinc Aluminum alloy Body - Aluminum

Airflow Pattern: see Model 1111-12 on page 67.



Air Consumption		For	Sound	
SCFM	SLPM	lbs	Kg	dBA
168	4,754	9.8	4.45	89

\* Force measured at 12" (305mm) from target Sound level measured at 3' (914mm) All measurements taken at 80 PSIG (5.5 BAR)






## **Super Blast Safety Air Guns**

#### Super Blast Safety Air Gun™



Model 1214 3/4 NPT female


Material: Nozzles - Zinc Aluminum alloy Airflow Pattern: see Model 1112 on page 65. Model 121455 with Stainless Steel Nozzle also available



Air Consumption		For	Sound Level	
SCFM	SLPM	lbs	Kg	dBA
91	2,577	4.5	2.04	96



Model 1215 1 NPT female Material: Nozzle - Zinc Aluminum alloy Airflow Pattern: see Model 1114 on page 65. Model 1215SS with Stainless Steel Nozzle




Air Consumption		For	Sound	
SCFM	SLPM	lbs	Kg	dBA
135	3.823	6.6	2.99	99

OSHA 2 hour total exposure per day without hearing protectio



The 3' extension on the Model 1215-3 Super Blast Safety Air Gun helps an operator provide maximum blow off force to remote, tight or difficult to access areas.



Model 1216 1-1/4 NPT female Material: Nozzle - Zinc Aluminum alloy Airflow Pattern: see Model 1116 on page 66.



Model 1217 1-1/4 NPT female Material: Nozzle - Zinc Aluminum alloy Airflow Pattern: see Model 1118 on page 66.



Model 1218 1-1/4 NPT female Material: Nozzle - Zinc Aluminum alloy Airflow Pattern: see Model 1120 on page 66.

Models	2CLM	2CF MI	ins	ny	ubn
1216	188	5,324	9.4	4.26	102
1217	300	8,495	15	6.80	106
1218	460	13,026	23	10.43	109
		(305mm) d at 3' (914r		get	

All measurements taken at 80 PSIG (5.5 BAR)
Model 1216 OSHA 1 hour total exposure per day without Model 1217 and 1218 OSHA 1/2 hour total exposure per day without hearing protection

### Add a longer extension pipe to your Super Blast Safety Air Gun.

Create the model number by adding a dash and number of the extension pipe to the Super Blast Safety Air Gun.

#### Example:

The Model 1214 Super Blast Safety Air Gun with a 3' extension would be a Model 1214-3.

1214 (Super Blast Safety Air Gun) -3 (3' extension)


121	4-3			
А	lum	inum Exten	sion	Pipe
		Safety Air Guns v y assembled.	vith E	xtension
Model#	Mo	del Addition #	Exte	nsion Length
1214	-3	36° (914mm)	-6	72" (1829mm)
121455	-3	36" (914mm)	-6	72" (1829mm)
1215	-3	36" (914mm)	-6	72" (1829mm)
121555	-3	36" (914mm)	-6	72" (1829mm)
1216	-3	36" (914mm)	-6	72° (1829mm)
1217	-3	36* (914mm)	-6	72° (1829mm)













## **GET14** Static Eliminators







## **Static Eliminators**

## Eliminate static and dust!

Neutralize and clean at distances up to 20 feet!







#### What Is Static?

Material such as paper, plastic or textiles normally contain an equal number of positive and negative charges - that is, they are electrically balanced. Friction can disturb this balance, causing the material to become electrically charged.

The electrical charge (static) will exert a force on nearby charged objects or a grounded conductor. Among the problems caused by this force are:



- Dust clinging to product
- Product clinging to itself, rollers, machine beds or frames
- Materials tearing, jamming or curling
- Sheet feeding problems
- Hazardous sparks or shocks

Charged conductors (like metals) discharge completely when grounded. Insulators (like plastics) don't conduct electricity and can't discharge when grounded. Grounded brushes or tinsel often have little effect on these surfaces.

When aiming EXAIR's Model 7905 Static Meter at a single plastic surface, it is common to measure many voltages across the same surface. The higher the voltage measures, the stronger the static charge or force at that point. It is also possible for some voltages to have opposite polarities (positive or negative) which determines if two insulators will attract or repel one another.

EXAIR's Gen4 static eliminators (also called ionizers) can eliminate static charge. These shockless ionizers are electrically powered and produce a bulk of positive and negative ions. The charged surface attracts the appropriate number of positive or negative ions from the ionizer to become neutral (discharged).

#### Why Choose Static Eliminators and GET4 Static Eliminator Systems?

EXAIR offers systems for total static control. When static is a problem on moving webs, sheet stock, three dimensional parts, extrusions or packaging, EXAIR has a solution. Our Gen4 static eliminators have undergone independent laboratory tests to certify it meets the rigorous safety, health and environmental standards of the USA, European Union and Canada that are required to attain the CE and UL marks. They are also RoHS compliant. Every Gen4 static eliminator offers:

- · An armored high voltage cable to protect against abrasion, cuts, splits and other damage from the environment.
- · Single wire, integrated ground design which eliminates the need for a separate ground connection
- · Electromagnetic shielding in all cables to protect sensitive electronics
- Selectable Voltage (115V or 230VAC) power supplies with rugged stainless steel connections and integrated fuse protection on the primary input voltage. Available in 2 or 4 outlet versions.



A small Model 112203 3" (76mm) Gen4 Super Ion Air Knife System eliminates contaminants from syringes prior to packaging.





# **GET14** Static Eliminators

#### **GET14** Static Eliminators With Air

Combining our engineered airflow products with ionizers gives us the ability to eliminate a static charge quickly and from great distances. Laminar flow airstreams make it possible to blow away any contaminants and eliminate the charge that attracts them. They are ideal for:

- Hard to reach places or obstructed surfaces
- · Product moving at high speeds
- · Surfaces with an extremely high charge

Compressed air consumption and noise are minimized while providing force that can be adjusted from a "blast" to a "breeze". Tests show these ionizers positioned two feet (610mm) away from a charged surface to be as effective as a Gen4 Ionizing Bar without air delivery positioned one-half inch (13mm) from the surface.

The Gen4 Super Ion Air Knife provides 34% better static elimination than previous Super Ion Air Knife models and the best performance of all EXAIR ionizers. It uses our Super Air Knife (40:1 air amplification) to deliver a uniform sheet of ionized air effective up to 20 feet (6.1m) away.

The Gen4 Standard Ion Air Knife performance is improved by 30% over previous Standard Ion Air Knives. It delivers a sheet of ionized air to the surface with 30:1 air amplification ratio that is less efficient than the Gen4 Super Ion Air Knife.

The Gen4 Super Ion Air Wipe clamps around the part and creates a ring of ionized airflow. It neutralizes and cleans continuous moving surfaces.

The Gen4 Ion Air Cannon uses our Super Air Amplifier (22:1 air amplification) to provide a focused, conical airstream that is capable of removing the charge up to 15 feet (4.6m) away.

The Gen4 Ion Air Gun uses our High Velocity Air Jet (5:1 air amplification) to provide a narrow beam of ionized airflow. This hand-held static eliminator is rugged for industrial use and has incredibly fast static decay rates.

The Gen4 Ion Air Jet uses our High Velocity Air Jet (5:1 air amplification), and is an effective spot cleaner. Available for permanent mount or with flexible Stay Set Hose, this ionizer is the ideal way to focus an ionized airflow at confined areas.

#### **GET14** Static Eliminators Without Air

In some situations, even the smallest amount of airflow can disturb the product. This is especially true for lightweight materials. EXAIR manufactures two styles of ionizers for these critical applications.

Gen4 Ionizing Bars perform 25% better than previous Ionizing Bars and are ideal for relatively flat materials, where the bar can be mounted within 4" of the product surface.

The Gen4 Ionizing Point is effective for spot neutralization. The compact size makes it ideal for winding or slitting operations. It can also be mounted through a duct to neutralize static charges due to moving air or materials.

#### **Special Static Eliminators**

EXAIR manufactures static eliminators suited to specific application requirements. This special ionizer (shown bottom right) was developed for the automotive industry. This air amplifier and ionizer combination is used to dry water based paints on car bodies while eliminating the possibility of a static charge that might attract dust or other contaminants.

> If you have special requirements, please contact an Application Engineer to discuss the application.



A Model 8006 6" (152mm) Gen4 Ionizing Bar eliminates the static charge causing packing peanuts to cling.




This special ionizer dries water based paint on car bodies and eliminates any















# с ЯМ ( € ) ( € ) ( GEЛ4° Super Ion Air Knife (An INTELLIGENT OMPRESSED AIR Product




# GE714° Super Ion Air Knife™

Powerful static eliminator prevents jamming, tearing, shocks and dust up to 20' away!

**Uses The Super Air Knife** 









# https://exair.co/04-siakv

## What Is The GET14 Super Ion Air Knife?

Compared to our previous version, EXAIR's Gen4 Super Ion Air Knife offers 34% improved performance at low pressures allowing you to achieve the same or better results, which saves compressed air and money. Gen4 Super Ion Air Knives remove static electricity from plastics, webs, sheet stock and other product surfaces where tearing, jamming or hazardous shocks are a problem. The laminar sheet of air sweeps surfaces clean of static, particulate, dust and dirt. Production speeds, product quality, and surface cleanliness can improve dramatically.

#### Why The GET 4 Super Ion Air Knife?

The Gen4 Super Ion Air Knife floods an area or surface with static eliminating ions - up to 20 feet (6.1m) away. A uniform airflow across its length will not cause misalignments to critical surfaces such as webs. Force can be adjusted from a "blast" to a "breeze". The Gen4 Super Ion Air Knife is shockless and has no moving parts. It also requires only 3.7 SCFM of compressed air per foot of length at 5 PSIG (105 SLPM per 300mm of length at 0.3 BAR). Sound level is surprisingly quiet at 50 dBA for most applications.

#### **Applications**

- Web cleaning
- Molding machinery
- · Sheeters and
- trimmers
- Cleaning parts
- · Pre-paint dust
- Shrink wrappers
- Package cleaning
- Bag opening/ fill operations
- Printing equipment

- Up to 34% improved performance
- Rugged metal armored and electromagnetically shielded cable
- · Integrated ground eliminates additional ground connection
- · Durable stainless steel connections to Power Supply
- · Low air consumption
- · Uniform airflow across entire length
- · Effective up to 20 feet (6.1m)
- · Shockless, non-radioactive
- · Compact, rugged, easy to install
- Unlimited system lengths of uninterrupted airflow
- Low maintenance
- UR/CE
- EMC Compliant
- Modular power supply cable eases connections and routing



The Gen4 Super Ion Air Knife eliminates the static charge on labels being applied to PET soft drink bottles.



The Model 112118 18" (457mm) Gen4 Super Ion Air Knife System eliminates dust from body care products prior to sealing the boxes in cellophane.



Bumpers, car bodies and fascia are cleaned of dust and fibers prior



# **GE714** Super Ion Air Knife

### How The GET14 Super Ion Air Knife Works



Compressed air flows through an inlet (1) into the plenum chamber of the Gen4 Super Ion Air Knife. The flow is directed to a precise, slotted orifice. As the primary airflow exits, it creates a uniform sheet of air across the entire length that immediately pulls in surrounding room air (2). An electrically powered Gen4 Ionizing Bar (3) fills the curtain of air with positive and negative charges. The airstream delivers these static eliminating ions to the product surface (4) where it instantly neutralizes static and cleans off dust and other particulates.

#### **Added Features**

- Compressed air inlets are provided on each end and the bottom of the Gen4 Super Ion Air Knife. Unlimited lengths available up to 118" (3m).
- Thicker shims can be installed easily if additional hard-hitting velocity is required.
- Primary air does not impact any surface of the Gen4 Super Ion Air Knife which keeps the sound level low.
- Insertion molded emitter points eliminate potential dirt accumulation that could degrade performance or eventually short the ionizing bar.
- Emitter points are sharp, durable stainless steel.
- The high voltage cable is armored to resist cuts and abrasion and has integral grounding, which eliminates an additional connection. The threaded bayonet connector is fully assembled
- · Electromagnetically shielded cable protects sensitive electronics.
- Gen4 Super Ion Air Knife Kits, which include all components necessary for operation, are available.

#### **GET14** Super Ion Air Knife Performance


Pressure	ssure Supply Air		umption*	Sound Level	Dissipates 5kV**
PSIG	BAR	SCFM	SLPM	dBA	SECONDS
5	0.3	3.7	105	39	0.40
10	0.7	5.5	156	51	0.33
20	1.4	13.2	372	57	0.26
40	2.8	20.4	576	61	0.23
60	4.1	27.6	780	65	0.21
80	5.5	34.8	984	69	0.20
100	6.9	42.0	1,188	72	0.18



The Model 112048 48" (1219mm) Gen4 Super Ion Air Knife neutralizes the static electricity and cleans the surface of the

## **GET14** Super Ion Air Knife Dimensions

(152mm) from target r airflow pattern, see Super Air Knife page 24



## **Enhanced Performance and Reliability**

Gen4 Ionizing Bars are most effective with an air delivery system. That allows the static eliminating ions to reach farther with greater coverage. When used by itself, a bar must be mounted within 4 inches of the charged surface to fully neutralize it. This close mounting is impossible when the static is generated in confined areas of a machine. Ion coverage is minimal on oddly configured parts or when high production speeds are involved.

The right type of air delivery is critical. Blowers produce an uneven, turbulent airstream that can cause the positive and negative ions to recombine before hitting the charged material. They are large, suffer mechanical wear and provide limited airflow control. The compact Gen4 Super Ion Air Knife uses a small amount of compressed air to produce a balanced, laminar sheet of air to carry the ions to the charged surface, even when it is far away. Flow and force are easily controlled and there are no moving parts to wear out.













## **GET14** Super Ion Air Knife

#### **GET 4** Super Ion Air Knife Specifications

The Gen4 Super Ion Air Knife is available in standard lengths of 3", 6", 9", 12", 18", 24", 30", 36", 42", 48", 54", 60", 72", 84", 96" and 108" (76, 152, 229, 305, 457, 610, 762, 914, 1067, 1219, 1372, 1524, 1829, 2134, 2438 and 2743mm). Special lengths and unlimited system lengths are available (please contact our factory).

A 5' (1.52m) armored and electromagnetically shielded power cable with ground and assembled bayonet connector are included.

# EXAIR Model 7960 or 7961 Gen4 Power Supply (5kV) is required for Super Ion Air Knife operation.

Power supplies are equipped with a modular 6 (1.83m) power cord, lighted power switch integrated fuse on the primary and (2) or (4) high voltage outlets.

Certifications: Gen4 Ionizing Bars and Gen4

Power Supplies are UL Component Recognized to U.S. and Canadian safety standards, and are CE, EMC

and RoHS compliant.

Compressed Air: 1/4 NPT inlets are provided on each end and the bottom.

For use with Model 7960 or 7961 5 kVrms, 5 milliamperes (max.)

power supply.

Electrical Hazard: Gen4 Ionizing Bars are shockless

(less than 40 microamperes short circuited).

Do not use near flammable materials or gases.

Materials of Construction

Shims:

Metal Parts: Aluminum
Plastic Parts: UL rated 94 HB
Emitters: Stainless Steel

Maximum Ambient Temperature: 165°F (74°C)

Thicker shims can be installed easily if

additional hard-hitting velocity is required. For more information, see "shim sets" on

on page 25.



Model 9060 Universal Air Knife Mounting System provides secure, precise positioning for the Gen4 Super Ion Air Knife. See page 29 for details.



### Static Meter

## **Static Meter**

# Locate the source of the static problem!



#### **Digital Static Meter Locates The Source!**

The Model 7905 Digital Static Meter allows easy onehand static measurements. In most cases, the highest voltage reading will indicate the source of the static problem. Sensitive and responsive, it indicates the surface voltage and polarity on objects up to ±20 kV when measured one inch (25mm) away.

The Digital Static Meter features a push button "hold" for readings, a low battery indicator and an automatic "power off". A "zero" button to zero the instrument ensures an accuracy of ±5% of the reading when it is one inch (25mm) from the charged surface.



The Model 7905 Digital Static Meter comes complete with a hard-shell plastic case and a 9 volt battery. Certification of the accuracy and calibration traceable to NIST (National Institute of Standards and Technology) is also included. Calibration is available.



## **GET14** Super Ion Air Knife


#### **Dust Removal From Car Bodies**

The Problem: Car bodies are primer coated, then sanded before entering the paint booth. Priming dust, attracted to the car body by a static charge, creates imperfections that are captured and magnified in the painting process.

The Solution: An "archway" of Model 112024 24" (610mm) Gen4 Super Ion Air Knives was installed upstream of the paint booth. As the car bodies pass through, a high velocity sheet of ionized air neutralizes the static charge to release the dust and blow it toward a collection system.

Comment: Non-turbulent airflow was the reason this cleaning system worked so well. The compact Gen4 Super Ion Air Knife has the ability to move the bulk of the static eliminating ions to the car surface. It can be adjusted from a gentle breeze of air to a pounding blast, with instant "on/off" capability. Uniform airflow across the entire length assures that all car body surfaces are neutralized and dust free. Best of all, the Gen4 Super Ion Air Knife is easy on the compressed air system and workers' ears. They use much less compressed air than standard blowoffs and are around 69 dBA in most applications.

EXAIR's EFC (shown on page 7) is an electronic flow control for compressed air. It can sense when there is no car present and will automatically turn off the compressed air until the next car is moved into position. It is a perfect addition to this type of application.



#### A Manufacturer Of Perfumes And Fragrances Eliminates Dust From Their Packages



The Problem: A manufacturer of perfumes and fragrances had a problem with the packaging of their fine perfumes. The conveyor belt used to transport the boxes to the cellophane sealer rubbed against the box surface and induced a sizable static electricity charge on it that made it a "dust magnet". The cardboard dust and particulates

in their facility would land on the perfume boxes that were sent through the cellophane sealer. The trapped dust gave a poor appearance to the finished package. The company refused to let the boxes with the poor appearance leave their facility. Attempts to clean them using ordinary air guns produced poor results.

The Solution: The company installed a Model 112018 18" (457mm) Gen4 Super Ion Air Knife prior to the box entering the sealer. The charged surface was completely neutralized with the ionized airflow and the dust and particulates were blown away. The cellophane covered boxes were perfectly clean.

Comment: EXAIR's Gen4 Super Ion Air Knife is used for applications just like these where appearance is vital to the sale of the product. The Gen4 Super Ion Air Knife is commonly used for pre-package cleaning, bag opening and filling operations, cleaning automobile bodies prior to painting, web cleaning, as well as eliminating jams, tears and those painful static electricity shocks.





## **GET14** Super Ion Air Knife

#### Cleaning Porcelain Dishes Prior To Glazing



The Problem: A manufacturer of fine porcelain dinnerware products had a problem with dust ruining the finish on their dishes. Dust particles were adhering to the surface of the dishes which created imperfections that were greatly magnified once the glaze was applied. Prior to glazing, they made attempts to blow the dust particles away using ordinary air nozzles which had little effect, if any. There were abundant rejects.

The Solution: They installed (3) Model 112018 18" (457mm) Gen4 Super Ion Air Knives to surround each dish, neutralize the static charge and remove the dust particles. Any airborne particulate was immediately vacuumed away by their dust collection system. The dishes were completely smooth to the touch with no imperfections.

Comment: A similar problem used to plague automotive manufacturers. The static charge generated by the automobile body tack off operation would cause the car body to attract stray particles of priming dust. Once the paint hits a dust particle, it sticks out like a sore thumb and ruins an otherwise perfect robotic paint job. The Gen4 Super Ion Air Knife is ideal here since it neutralizes the charge and blows the dust away (in the direction of their dust collection system). To minimize compressed air use for these applications, we recommend the use of an EXAIR EFC Electronic Flow Control that automatically turns off the compressed air when no part is present.

#### **GET14** Super Ion Air Knife Models

Gen4 Super Ion Air Knife - includes the Super Air Knife and Gen4 Ionizing Bar assembly.

EXAM

Gen4 Super Ion Air Knife Systems - include a Gen4 Super Ion Air Knife and Model 7960 Gen4 Power Supply

Gen4 Super Ion Air Knife Kits - include a Gen4 Super Ion Air Knife, Model 7960 Gen4 Power Supply, shim set, filter

Gen4 Deluxe Super Ion Air Knife Kits - include a Gen4 Super Ion Air Knife, Model 7960 Gen4 Power Supply, EFC, iversal Mounting System, shim set, filter separator and pressure regulator (with coupler).


Length	Gen4 Super Ion Air Knife Model	Gen4 Super Ion Air Knife Systems Model	Gen4 Super Ion Air Knife Kits Model	Gen4 Deluxe Super Ion Air Knife Kits Model
3* (76mm)	112003	112103	112203	112203DX
6" (152mm)	112006	112106	112206	112206DX
9° (229mm)	112009	112109	112209	112209DX
12* (305mm)	112012	112112	112212	112212DX
18" (457mm)	112018	112118	112218	112218DX
24" (610mm)	112024	112124	112224	112224DX
30" (762mm)	112030	112130	112230	112230DX
36" (914mm)	112036	112136	112236	112236DX
42" (1067mm)	112042	112142	112242	112242DX
48" (1219mm)	112048	112148	112248	112248DX
54" (1372mm)	112054	112154	112254	112254DX
60" (1524mm)	112060	112160	112260	112260DX
72" (1829mm)	112072	112172	112272	112272DX
84" (2134mm)	112084	112184	112284	112284DX
96* (2438mm)	112096	112196	112296	112296DX
108" (2743mm)	1120108	1121108	1122108	1122108DX



Kits include the Gen4 Super Ion Air Knife, shim set, Model 7960 Gen4 Power Supply, filter separator and pressure regulator (with coupler).

## **Universal Air Knife** Mounting System

**EXAIR's Universal Air Knife** Mounting System allows easy positioning of all **EXAIR Air Knives.** See page 29 for details.





## **GE714** Super Ion Air Knife

#### GET 4 Long Super Ion Air Knives

EXAIR offers long Gen4 Super Ion Air Knives in 60" (1524mm). 72" (1829mm), 84" (2134mm), 96" (2438mm) and 108" (2743mm) lengths that are shipped fully assembled. All components have been properly sized to obtain the best performance from the Gen4 Super Ion Air Knife.

#### **GET 4** Super Ion Air Knife Models with Plumbing Kit

Gen4 Super Ion Air Knife with Plumbing Kit - includes Super Air Knife, plumbing kit and Gen4

Gen4 Super Ion Air Knife Systems with Plumbing Kit - include Super Air Knife, plumbing kit and Gen4 Ionizing Bar installed. Includes Model 7960 Gen4 Power Supply (115V, 230V, 50/60Hz) Gen4 Super Ion Air Knife Kits with Plumbing Kit - include Super Air Knife, plumbing kit and Gen4 Ionizing Bar installed. Also includes Model 7960 Gen4 Power Supply (115V, 230V, 50/60Hz), shim set, filter separator and pressure regulator (with coupler).

Length	Gen4 Super Ion Air Knife Model	Gen4 Super Ion Air Knife Systems Model	Gen4 Super Ion Air Knife Kits Model
24" (610mm)	112024PKI	112124PKI	112224PKI
30° (762mm)	112030PKI	112130PKI	112230PKI
36" (914mm)	112036PKI	112136PKI	112236PKI
42° (1067mm)	112042PKI	112142PKI	112242PKI
48" (1219mm)	112048PKI	112148PKJ	112248PKI
54" (1372mm)	112054PKI	112154PKI	112254PKI
60" (1524mm)	112060PKI	112160PKI	112260PKI
72" (1829mm)	112072PKI	112172PKI	112272PKI
84" (2134mm)	112084PKI	112184PKI	112284PKI
96" (2438mm)	112096PKI	112196PKI	112296PKI
108" (2743mm)	1120108PKI	1121108PKI	1122108PKI



This 96" Long Gen4 Super Ion Air Knife cleans an acrylic sheet before protective wrap is applied.

Special length Gen4 Super Ion Air Knives and unlimited system lengths are available.



	Accessories an	d Compo	nents
Model #	Description	Model #	Description
7960	2 Outlet Selectable Voltage Gen4 Power Supply (115V, 230V, 50/60Hz)	7905	Static Meter
7961	4 Outlet Selectable Voltage Gen4 Power Supply (115V, 230V, 50/60Hz)	9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)
8003	3" (76mm) Gen4 Ionizing Bar Only	9032	Auto Drain Filter Separator, 1/2 NPT, 90 SCFM (2,549 SLPM)
8006	6" (152mm) Gen4 lonizing Bar Only	9002	Auto Drain Filter Separator, 3/4 NPT, 220 SCFM (6,230 SLPM)
8009	9" (229mm) Gen4 lonizing Bar Only	9066	Auto Drain Filter Separator, 1-1/4 NPT, 400 SCFM (11,327 SLPM)
8012	12" (305mm) Gen4 Ionizing Bar Only	9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)
8018	18* (457mm) Gen4 Ionizing Bar Only	9006	Oil Removal Filter, 3/4 NPT, 50-150 SCFM (1,416-4,248 SLPM)
8024	24" (610mm) Gen4 Ionizing Bar Only	9008	Pressure Regulator with Gauge, 1/4 NPT, 50 SCFM (1,416 SLPM)
8030	30" (762mm) Gen4 Ionizing Bar Only	9033	Pressure Regulator with Gauge, 1/2 NPT, 100 SCFM (2,832 SLPM)
8036	36* (914mm) Gen4 ionizing Bar Only	9009	Pressure Regulator with Gauge, 3/4 NPT, 220 SCFM (6,230 SLPM)
8042	42* (1067mm) Gen4 Ionizing Bar Only	9067	Pressure Regulator with Gauge, 1-1/4 NPT, 600 SCFM (16,990 SLPM)
8048	48" (1219mm) Gen4 Ionizing Bar Only	9020	Solenoid Valve, 120V, 50/60Hz, 1/4 NPT, 40 SCFM (1,133 SLPM)
8054	54" (1372mm) Gen4 Ionizing Bar Only	9034	NEMA 4/4X Solenoid Valve, 120V, 50/60Hz, 1/2 NPT, 100 SCFM (2,832 SLPM)
8060	60" (1524mm) Gen4 lonizing Bar Only	9035	NEMA 4/4X Solenoid Valve, 240V, 50/60Hz, 1/2 NPT, 100 SCFM (2,832 SLPM)
8072	72" (1829mm) Gen4 lonizing Bar Only	9036	NEMA 4/4X Solenoid Valve, 120V, 50/60Hz, 3/4 NPT, 200 SCFM (5,664 SLPM)
8084	84" (2134mm) Gen4 Ionizing Bar Only	9037	NEMA 4/4X Solenoid Valve, 240V, 50/60Hz, 3/4 NPT, 200 SCFM (5,664 SLPM)
8096	96* (2438mm) Gen4 Ionizing Bar Only	9065	NEMA 4/4X Solenoid Valve, 24VDC, 1 NPT, 350 SCFM (9,911 SLPM)
80108	108° (2743mm) Gen4 Ionizing Bar Only		







## GE714 Standard Ion Air Knife™

A sheet of ionized air is an effective way to eliminate static and clean parts or materials!

### What Is The GET 4 Standard Ion Air Knife?

When compared to our previous model, EXAIR's Gen4 Standard Ion Air Knife offers 30% improved performance at low pressures allowing you to achieve the same or better results, which saves compressed air and money. They are an effective way to eliminate static. Like its "super" counterpart, the Gen4 Standard Ion Air Knife removes static electricity from plastics, webs, sheet stock and other surfaces where tearing, jamming or hazardous shocks are a problem.



This ionizer uses our original Standard Air Knife to carry ions from a Gen4 Ionizing Bar to the charged surface - up to 20 feet (6.1m) away. Though not as efficient as our Gen4 Super Ion Air Knife (40:1 air amplification), the Gen4 Standard Ion Air Knife (30:1 air amplification) still provides fast static decay and strong blowoff force for cleaning. Force can be adjusted from a "blast" to a "breeze". The Gen4 Standard Ion Air Knife is shockless and has no moving parts.

#### Why The GETT4 Standard Ion Air Knife?

When air consumption and noise level are not critical to the application, the lower cost makes the Gen4 Standard Ion Air Knife a good choice. (To compare the Gen4 Super Ion Air Knife and Gen4 Standard Ion Air Knife, see the performance tables on pages 124 and 130.)

Compressed air inlets are provided on each end of the Gen4 Standard Ion Air Knife. For long spans, multiple Gen4 Standard Ion Air Knives can be mounted end-to-end. This produces an air gap at the connection end of about 2" (51mm). (If no air gap is desired, use the Gen4 Super Ion Air Knife.) Special length Gen4 Ionizing Bars up to 119" (3.02m) are available for multiple air knife applications.

The Model 8218 18" (457mm) Gen4 Standard Ion Air Knife System showers parts with static eliminating ions to prevent personnel shocks.



A Model 8212 12" (305mm) Gen4 Standard Ion Air Knife System cleans metal frames prior to powder coating.



A Model 8103 3" (76mm) Gen4 Standard Ion Air Knife removes dust from computer hard disks prior to assembly.

#### **Advantages**

- · Web cleaning
- Molding machinery Sheeters and trimmers
- · Cleaning parts

**Applications** 

- · Pre-paint dust removal
- Shrink wrappers
- Package cleaning
- · Bag opening/fill operations
- · Printing equipment

- · 30% improved performance
- · Rugged metal armored and
- ground connection
- Supply
- Reduced air consumption

- . Effective up to 20 feet (6.1m)
- · Shockless, non-radioactive
- · Compact, rugged, easy to install
- · Unlimited system lengths
- · Variable force and flow

## GE714' Standard Ion Air Knife

#### **GET14** Standard Ion Air Knife Performance

Pres Sup			ir nption*	Sound Level	Dissipates 5kV**
PSIG	BAR	SCFM	SLPM	dBA	SECONDS
5	0.3	6	170	66	0.38
10	0.7	8	227	68	0.28
20	1.4	16	453	69	0.29
40	2.8	24	679	78	0.21
60	4.1	32	906	84	0.21
80	5.5	41	1,160	87	0.21
100	6.9	49	1,387	90	0.21

per foot (205mm) of length

per foot (305mm) for rength 6" (152mm) from target. For airflow pattern, see Standard Air Knife page 35. Note: Performance on lengths over 36" will vary. Contact an Application Engineer for details.



**GET14** Standard Ion Air Knife Models

Gen4 Standard Ion Air Knife - consists of the Standard Air Knife and Gen4 Ionizing Bar assembly.

Gen4 Standard Ion Air Knife Systems - include a Gen4 Standard Ion Air Knife and Model 7960

Gen4 Standard Ion Air Knife Kits - include a Gen4 Standard Ion Air Knife, Model 7960 Gen4 Power

Gen4 Deluxe Standard Ion Air Knife Kits - include a Gen4 Standard Ion Air Knife, EFC, Universal Mounting System, Model 7960 Gen4 Power Supply, shim set, filter separator and pressure regulator

Gen4 Standard Ion Air

8203

8206

8209

8212

8218

8224

8230

8236

8242

Kits include the Gen4 Standard Ion Air Knife, shim set, Model 7960 Gen4 Power Supply, filter separator and pressure regulator (with coupler).

Supply, shim set, filter separator and pressure regulator (with cour

Air Knife Mode

8103

8109

8112

8118

8124

8130

8136

8142

8148

#### **GET14** Standard Ion Air Knife Specifications

The Gen4 Standard Ion Air Knife is available in standard lengths of 3", 6", 9", 12", 18", 24", 30", 36", 42" and 48" (76, 152, 229, 305, 457, 610, 762, 914, 1067 and 1219mm). Special lengths up to 48" (1219mm) and unlimited system lengths are available (please contact our factory). A 5' (1.52m) armored and shielded power cable with ground and assembled bayonet connector are included. EXAIR Model 7960 or 7961 Gen4 Power Supply (5kV) is required for Standard Ion Air Knife operation. See page 142 for details.

Certifications: Gen4 Ionizing Bars and Gen4 Power

Supplies are UL Component Recognized to U.S. and Canadian safety standards, and are CE and RoHS compliant.

CE

Compressed Air: 1/4 NPT inlets are provided on each end. Electrical: For use with 5 kVrms, 5 milliamperes (max.) power supply.

Electrical Hazard: Gen4 Ionizing Bars are shockless (less than 40 microamperes short circuited).

Do not use near flammable materials or gases.

#### Materials of Construction

Metal Parts: Aluminum UL rated 94 HB **Plastic Parts:** Stainless Steel **Emitters:** 

#### Maximum Ambient Temperature: 165°F (74°C)


Shims:

Thicker shims can be installed easily if additional hard-hitting velocity is required, see "shim sets" page 34.

Special length Gen4 Standard Ion Air Knives and unlimited system lengths are available. Please contact our factory.

## **Universal Air Knife** Mounting System

**EXAIR's Universal Air Knife** Mounting System allows easy positioning of all EXAIR Air Knives. See page 29 for details.





electromagnetically shielded cable

· Integrated ground eliminates additional

- Durable stainless steel connections to Power

- · 30:1 air amplification
- Low noise level

- Low maintenance







Gen4 Power Supply (115V, 230V, 50/60Hz)

(with coupler)

Length

3" (76mm

6" (152mm)

9" (229mm)

12" (305mm)

18" (457mm)

24" (610mm)

30" (762mm)

36" (914mm)

42\* (1067mm)

48" (1219mm)



Standard Ion Air

8403

8406

8409

8412

8418

8424

8430

8442

8448

Gen4 Deluxe

nife Kits Model

8403DX

8406DX

8409DX

**8412DX** 

8418DX

8424DX

8430DX

8436DX

8442DX

8448DX











## **GE714** lonizing Bars

# **GET14** lonizing Bars

Low cost GE714' lonizing Bars eliminate static cling!

Compact, rugged design for industrial applications!



#### What Is The GETT 4 Ionizing Bar?



EXAIR's Gen4 Ionizing Bar is engineered to perform up to 25% better than previous models for applications where the bar is mounted within 2" of the surface it is treating. It has also been designed to perform well 100% farther away by providing static elimination up to 4" from a charged surface. Gen4 Ionizing Bars eliminate static electricity on paper, film and plastics that can attract dust and foreign materials, ruin product appearance, produce tearing or jamming, and zap personnel. The electrically powered Gen4 Ionizing Bar is compact, allowing it to fit in the confined spaces of machinery where the charge is generated. A high concentration of positive and negative ions produce fast static decay, neutralizing any surface within 4" (102mm) of the bar.

#### Why The GETT4 Ionizing Bar?

The unique design of the shockless Gen4 Ionizing Bar offers improved performance and reliability in industrial applications. Life expectancy has been extended by insertion molding the stainless steel ion emitters into a durable engineered polymer. There are no openings or grooves to accumulate dirt that could cause shorting or arcing. A 5kV power source provides high performance, eliminating frequent burnouts commonly associated with traditional 7kV bars.

The Gen4 Ionizing Bar includes a five foot shielded cable with ground. A mounting flange is provided for easy installation and all components are fully assembled. Standard lengths up to 108" (2743mm) are available from stock and special lengths up to 118" (3m) are available by special order, EXAIR Model 7960 or 7961 Gen4 Power Supply (5kV) is required for bar operation.

The ability to eliminate static can be greatly improved when attaching the Super Air Knife to the Gen4 Ionizing Bar, The Gen4 Super Ion Air Knife propels the static neutralizing ions over a larger area which is ideal for high speed, high charge applications. Air delivery can also remove dust and clean the product surface.

#### **Applications**

- Labeling
- · Bag making form and fill
- Neutralizing shrink wrap
- Sheet fed and web presses
- Packaging
- · Converting machinery
- · Neutralizing slitting operations
- Textiles
- Screen printing

#### Advantages

- · Significantly improved performance when positioned 2" or closer to a surface
- Effective up to 4" (102mm)
- · Rugged metal armored and electromagnetically shielded cable
- Integrated ground eliminates additional
- ground connection
- Durable stainless steel connections to Power Supply
- · Low cost
- Rapid static decay
- Compact
- · Shockless, non-radioactive
- · Rugged design for industrial environments
- · Easy to install, equipped with mounting flange
- Low maintenance

#### Fully assembled

## EXAM

## **GET14** lonizing Bars

### How The GETT4 Ionizing Bar Works



The electromagnetically shielded power cable (1) carries the 5kVrms power supply output to each inductively coupled stainless steel emitter point (2) of the Gen4 Ionizing Bar. An integrated ground wire (3) within the power cable creates a discharge path from the emitter points to the bar channel (4). The discharge at each emitter charges the molecules of the gases of the surrounding room air, resulting in a shower of ions that are positively and negatively charged (5). If the material surface has a negative charge, it will attract the positive ions from the Gen4 Ionizing Bar and become balanced or neutralized. If the material surface has a positive charge, it will attract the negative ions from the Gen4 Ionizing Bar to become balanced or neutralized.

The voltage potential at each emitter is high enough to ionize the surrounding air without generating a shock when any of the emitters are touched.

GET 4 Ionizing Bars

Gen4 Ionizing Bar Models

8003

8006

8009

8012

8018

8024

8030

8036

8042

8048

8054

8072

8084

8096

80108

Gen4 Ionizing Bars - include a 5' (1,52m) length of armored and

electromagnetically shielded cable and assembled connector.

For other cable lengths, please contact the factory.

Length

3" (76mm)

6" (152mm)

9" (229mm)

12" (305mm)

18" (457mm)

24" (610mm)

30" (762mm)

36" (914mm)

42" (1067mm)

48" (1219mm)

54" (1372mm)


60" (1524mm)

72" (1829mm)

84" (2134mm)

96\* (2438mm)

108" (2743mm)



#### and are CE and RoHS compliant. Electrical: For use with 5 kVrms,

EXAIR Model 7960 or 7961 Gen4 Power Supply (5kV)is required for Gen4 Ionizing Bar operation. See page 142 for details.

Certifications: Gen4 Ionizing Bars and Gen4 Power Supplies are UL Component Recognized to

U.S. and Canadian safety standards.

c FLI us

CE

5 milliamperes (max.) power supply.

**GET 4** Ionizing Bar Specifications

Electrical Hazard: Gen4 Ionizing Bars are shockless (less than 40 microamperes short circuited).

Do not use near flammable materials or gases.

#### **Materials of Construction**


Metal Parts: Aluminum UL rated 94 HB Plastic Parts: Stainless Steel

Maximum Ambient Temperature: 165°F (74°C)

#### **GET14** Ionizing Bar Performance

	Distance From Charged Surface				
	0.50* (13mm)	1" (25mm)	2* (51mm)	3" (76mm)	4* (102mm)
Dissipates 5kV* (seconds)	0.1	0.14	0.29	0.53	0.96

## **GET14** Ionizing Bar Dimensions



Accessories and Components				
Model #	Description			
7960	2 Outlet Selectable Voltage Gen4 Power Supply (115V, 230V, 50/60Hz)			
7961	4 Outlet Selectable Voltage Gen4 Power Supply (115V, 230V, 50/60Hz)			
7905	Static Meter			



Model 8006 6" (152mm) Gen4 lonizing Bar and Model 7960 Gen4 Power Supply.

Special length Gen4 Ionizing Bars up to 118" (3m) are available. Please contact our factory.







# GE714° Super Ion Air Wipe™

## Ring of ionized airflow clamps around the part!

Neutralizes and cleans continuous moving surfaces!

#### What Is The GET 4 Super Ion Air Wipe?



EXAIR's Gen4 Super Ion Air Wipe provides a uniform 360° ionized airstream that is easy to clamp around a part for eliminating static electricity and contaminants. It is ideal for use on pipe, cable, extruded shapes, hose, wire and more. It maximizes ionized airflow while minimizing compressed air consumption.

#### Why The GET 4 Super Ion Air Wipe?

The Gen4 Super Ion Air Wipe provides total coverage of the part moving through it. The high volume, high velocity flow attaches itself to the surface and wipes it down with the static eliminating ions. The airflow stays attached to the surface and is effective up to 15' (4.6m) away from where the Gen4 Super Ion Air Wipe is mounted. An optional pressure regulator provides infinite control of the air volume and velocity. Increasing the pressure increases the forceful wiping action. Lower pressures provide excellent coverage with much lower force and velocity.

The Gen4 Super Ion Air Wipe is the easy way to provide uniform coverage around a continuously moving material. The hinged design, allowing the Air Wipe to open,

makes threading continuous wire, tube or extrusions unnecessary. Arranging a series of other ionizers around the surface would provide uneven airflow and prove to be costly. The split design of the Gen4 Super Ion Air Wipe solves that problem by making it easy to clamp around the surface of the material moving through it, eliminating the need for threading or several ionizers.

The Gen4 Super Ion Air Wipe is lightweight and easy to mount using the tapped holes on the back. It can also be held in place with rigid pipe. Coupling brackets that hold each half of the Gen4 Super Ion Air Wipe together are provided which can be installed or removed quickly if required.

## **Applications**

- · Clean and neutralize extrusions
- · Neutralizing pipe, tubing, wire
- · Cleaning molded parts
- · Neutralizing static for quality printing

#### **Advantages**

- Low air consumption
- Rapid static decay
- Shockless, non-radioactive
- · Compact, rugged, easy to install
- · No moving parts low maintenance
- · Variable force and flow

EXAIR

 Electromagnetically shielded high voltage cable

· Pre-paint dust removal

· Container neutralization


· Armored high voltage cable protects against abrasion, cuts

· Remove chips, shavings and sawdust

- Integrated ground design requires no separate ground connection
- · Replaceable emitter points




The split design unlatches easily to fit around the moving part no threading required.



## **GET14** Super Ion Air Wipe

#### How The GETT 4 Super Ion Air Wipe Works



The Gen4 Super Ion Air Wipe incorporates a Super Air Wipe and a split ionizing collar, energized by a power supply. Compressed air is ejected through the small ring nozzle of the Super Air Wipe at high velocity (1). A conical 360° ring of air is created that induces high volumes of surrounding air (2). The airflow passes through the collar and is ionized by two replaceable emitter points (3). That high velocity, ionized airstream attaches itself to the surface of the material running through the Gen4 Super Ion Air Wipe (4), uniformly eliminating the static electricity and removing any contaminants from the surface.

**GET14** Super Ion Air Wipe

2" (51mm) Gen4 Super Ion Air Wipe and Gen4 Power Supply 4" (102mm) Gen4 Super Ion Air Wipe and Gen4 Power Supply

**GET14** Super Ion Air Wipe Kits

**Accessories and Components** 

2 Outlet Selectable Voltage Gen4 Power Supply

4 Outlet Selectable Voltage Gen4 Power Supply

Pressure Regulator with Gauge, 1/4 NPT, 50 SCFM

Auto Drain Filter Separator, 3/8 NPT, 65 SCFM

Kits include a Gen4 Super Ion Air Wipe, shim set, Model 7960 Gen4 Power Supply,

2" (51mm) Gen4 Super Ion Air Wipe

2\* (51mm) Gen4 Super Ion Air Wipe Kit

8464 4" (102mm) Gen4 Super Ion Air Wipe Kit

(115V, 230V, 50/60Hz)

Static Meter



Model # Description

Model # Description

Model # Description

7961

9001

9008

7905

8162

Model 8462 Gen4 Super Ion Air Wipe Kit includes the Gen4 Super Ion Air Wipe, shim set, Model 7960 Gen4 Power Supply, filter separator and pressure regulator vith coupler).

#### **GET 4** Super Ion Air Wipe Specifications

EXAIR Model 7960 or 7961 Gen4 Power Supply (5kV) is required for Super Ion Air Wipe operation.

See page 142 for details.

Certifications: The Gen4 Super Ion Air Wipe and Gen4 Power

Supply are UL Component Recognized to U.S. and Canadian safety standards.

and are CE and RoHS compliant.

Electrical: For use with 5 kVrms.

5 milliamperes (max.) power supply.

Electrical Hazard: Shockless

(less than 40 microamperes

short circuited).

Do not use near flammable materials or gases.

**Materials of Construction** 

Metal Parts: Aluminum Emitter: Stainless Steel

**Plastic Parts:** UL rated 94 HB

Maximum Ambient Temperature: 165°F (74°C) Shims:


Thicker shims can be installed easily if additional hard-hitting velocity

is required. See "shim sets" page 41. Compressed Air: 1/4 NPT inlet provided.


## **GET14** Super Ion Air Wipe Performance

80 PSIG 5.5 BAR)		ir mption	Sound Level	Dissipates 5kV*
Model	SCFM	SLPM	dBA	SECONDS
8162	29.5	835	77	0.20
8164	50.2	1,422	81	0.20

## **GET14** Super Ion Air Wipe Dimensions



	-			
Model	A	В	C	
8162	2" (51mm)	4.75° (121mm)	2.7" (69mm)	
8164	4" (102mm)	6.75* (171mm)	4.72" (120mm)	
















## GE714° Ion Air Cannon



## GE714° Ion Air Cannon™

## Quiet, efficient, concentrated flow of ionized air removes static and dust!

#### What Is The GET4 Ion Air Cannon?



EXAIR's Gen4 Ion Air Cannon neutralizes static electricity and cleans at distances up to 15 feet (4.6m) with no moving parts. It is ideal for those hard to reach spaces or confined areas that require a concentrated flow of static eliminating ions. With an optional pressure regulator, the air volume and velocity are infinitely adjustable over a wide range, for light to heavy duty applications.

#### Why The GET 4 Ion Air Cannon?

The Gen4 Ion Air Cannon will maximize ionized airflow while minimizing compressed air consumption. A small amount of compressed air is used to entrain a high volume flow of surrounding air. This combined stream is ionized by an emitter point (shockless) and delivered to the charged surface. A hose or tube can be connected to the air intake of the Gen4 Ion Air Cannon to draw quality air from another area. It requires only 10 PSIG (0.7 BAR) for most applications.

The compact design saves bench space and allows mounting in confined areas. The sturdy stand is pre-drilled and can be wall, bench or machine mounted. It incorporates a swivel adjustment for directing the airflow.

EXAIR's EFC (shown on page 7) is an electronic flow control for compressed air. For production lines, it can sense when no part is present and will automatically turn off the compressed air to the Gen4 Ion Air Cannon until the next part moves into position.

#### **Applications**

- · Bag opening form and fill
- · Clean and neutralize parts
- Neutralizing shrink wrap
- Cleaning molded parts
- · Removing static on assemblies
- · Pre-paint dust removal
- Neutralizing slitting operations
- Package cleaning
- Container neutralization

EXAIR

#### Advantages

- · Electromagnetically shielded high voltage cable
- Armored high voltage cable protects against abrasion, cuts
- Integrated ground design requires no separate ground connection
- · Replaceable emitter point
- · Low air consumption
- · Rapid static decay
- Oujet
- · Shockless, non-radioactive
- · Compact, rugged, easy to install
- · Intake can be ducted
- · No moving parts low maintenance
- · Variable force and flow



## solar panel lenses to assist separation of the lenses during production.

Model 8192 Gen4 Ion Air Cannons provide static elimination in between

The Model 8292 Gen4 Ion Air

(3) Gen4 Ion Air Cannons blow

contaminants from car bodies


prior to painting

Cannon System eliminates the static

and dust prior to filling the bottles.

#### How The GETT4 Ion Air Cannon Works

GE714' Ion Air Cannon



The Gen4 Ion Air Cannon incorporates a Super Air Amplifier\* and ionizing collar, energized by a power supply. A small amount of compressed air is injected into the barrel of the cannon (1) inducing a high volume flow of surrounding air to flow through it (2). A replaceable emitter point at the discharge end of the cannon (3) ionizes the entire airstream. The result is a high volume, conical flow of ionized air (4) capable of eliminating static and cleaning at distances up to 15 feet (4.6m). Because more than 90% of the ionized air is induced, the Gen4 Ion Air Cannon produces maximum airflow at minimum air consumption.

\*Patent #5402938



Model 8492 Gen4 Ion Air Cannon Kit includes the Gen4 Ion Air Cannon. shim set, Model 7960 Gen4 Power Supply, filter separator and pressure regulator (with coupler).

#### **GET14** Ion Air Cannon Specifications

EXAIR Model 7960 or 7961 Gen4 Power Supply (5kV) is required for Gen4 Ion Air Cannon operation.

See page 142 for details.

Certifications: The Gen4 Ion Air Cannon and Gen4

Power Supply are UL Component Recognized to U.S. and Canadian safety standards, and are CE and

RoHS compliant.

For use with 5 kVrms, Electrical: 5 milliamperes (max.) power supply.

**Electrical Hazard: Shockless** 

(less than 40 microamperes short circuited).

Do not use near flammable materials or gases.

**Materials of Construction:** 

Metal Parts: Aluminum Plastic Parts: UL rated 94 HB

Stainless Steel **Emitter:** 

Maximum Ambient Temperature: 165°F (74°C)

Shims: Thicker shims can be installed easily if additional

hard-hitting velocity is required. See page 49.

Compressed Air: 3/8 NPT inlet provided.

#### **GET14** Ion Air Cannon Performance


Pressure Supply		Air Consumption		Sound Level	Dissipates 5kV*
PSIG	BAR	SCFM	SLPM	dBA	SECONDS
20	1.4	5.7	161	58	0.75
40	2.8	9	255	64	0.6
60	4.1	12.2	345	70	0.5
80	5.5	15.5	439	72	0.43
100	6.9	18.7	529	74	0.37

	GE714 Ion Air Cannon
Model #	Description
8192	Gen4 Ion Air Cannon includes Super Air Amplifier, Emitter, Stand, and 5' (1.52m) length of armored and electromagnetically shielded cable
8292	Gen4 Ion Air Cannon and Gen4 Power Supply
8492	Gen4 Ion Air Cannon Kit (see image above)

Model #	Description
8492DX	Kits include a Gen4 Ion Air Cannon, EFC, shim set, Model 7960 Gene Power Supply, filter separator and pressure regulator (with coupler)

	Accessories and Components					
Model #	Description					
7960	2 Outlet Selectable Voltage Gen4 Power Supply (115V, 230V, 50/60Hz)					
7961	4 Outlet Selectable Voltage Gen4 Power Supply (115V, 230V, 50/60Hz)					
9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)					
9008	Pressure Regulator with Gauge, 1/4 NPT, 50 SCFM (1,415 SLPM)					
7905	Static Meter					


















GE714° Ion Air Gun



## GE774° Ion Air Gun™

Rugged, ergonomic static eliminating gun that is a lightweight, effective spot cleaner!

#### What Is The GETT4 Ion Air Gun?



EXAIR's Gen4 Ion Air Gun combines incredibly fast static decay rates with low compressed air consumption. It is the ideal way to remove static, contaminants and dust from three dimensional parts prior to assembly, packaging, painting or finishing. The Gen4 Ion Air Gun neutralizes static electricity and cleans at distances up to 15 feet (4.6m).

#### Why The GET 4 Ion Air Gun?

The Gen4 Ion Air Gun induces surrounding airflow through the gun at a ratio of 5:1, minimizing compressed air usage and maximizing ionized airflow. The force can be adjusted from a "blast" to a "breeze". A comfortable grip and hand position allows hours of continuous use without fatigue.

The Gen4 Ion Air Gun is quiet, lightweight and features a hanger hook for easy storage. The 10 foot (3m) armored and electromagnetic shielded power cable is extremely flexible, designed for rugged industrial use.

#### **Applications**

- · Pre-paint dust removal
- · Clean and neutralize three dimensional parts
- Removing dust from optics
- Cleaning molded parts
- Photo finishing
- Lens cleaning
- · Furniture finishing
- Package cleaning Container neutralization

## Advantages

- · Electromagnetically shielded high voltage cable
- · Armored high voltage cable protects against
- · Integrated ground design requires no separate ground connection
- · Replaceable emitter point
- · Rugged, lightweight, easy to use
- · Rapid static decay
- · Low air consumption
- Quiet
- · Shockless, non-radioactive
- · Strong blowoff force and flow
- Low maintenance
- · Meets OSHA pressure and noise level requirements





The Model 8293 Gen4 Ion Air Gun cleaning artwork and glass prior




The Model 8293 Gen4 Ion Air Gun neutralizes and cleans plastic bottles prior to labeling.



## GE714" Ion Air Gun

#### How The GET4 Ion Air Gun Works



The Gen4 Ion Air Gun incorporates a High Velocity Air Jet and electrically energized emitter point. A small amount of compressed air is injected into the air jet (1) inducing high volume flow of surrounding air (2) to pass through it.

The emitter point (shockless) at the discharge end of the gun (3) ionizes the entire airstream. The result is a high volume flow of ionized air (4) capable of neutralizing high static charges in fractions of a second. An optional filter and regulator clean the compressed air and allow infinite adjustment of airflow and velocity.

## **GET14** Ion Air Gun Performance

	Pressure Air Sound Supply Consumption Level						Dissipates 5kV*
PSIG	BAR	SCFM	SLPM	dBA	SECONDS		
20	1.4	7.4	209	67	0.45		
40	2.8	11.5	325	74	0.33		
60	4.1	15.8	447	79	0.24		
80	5.5	22.0	622	82	0.18		
100	6.9	24.0	679	85	0.18		

High Velocity Air Jet on page 61.



Model 8493 Gen4 Ion Air Gun Kit includes the Gen4 Ion Air Gun, Model 7960 Gen4 Power Supply, filter separator and pressure regulator (with coupler).

# **Order Direct**

We Ship From Stock

### **GET14** Ion Air Gun Specifications

EXAIR Model 7960 or 7961 Gen4 Power Supply (5kV) is required for Gen4 Ion Air Gun operation. See page 142

Certifications: The Gen4 Ion Air Gun and

Gen4 Power Supply are UL Component Recognized to U.S. and Canadian safety standards, and are CE and

RoHS compliant.

For use with 5 kVrms, Electrical: 5 milliamperes (max.) power supply.

**Electrical Hazard:**Shockless

(less than 40 microamperes short circuited).

Do not use near flammable materials or gases.

Materials of Construction:

Metal Parts: Brass, Zinc and Stainless Steel

Plastic Parts: UL rated 94 HB Emitter: Stainless Steel

Maximum Ambient Temperature: 165°F (74°C)

Compressed Air: 1/4 NPT inlet provided.




80% of the delivered air is induced, minimizing air consumption of the Gen4 Ion Air Gun.

Model #	Description
8193	Gen4 Ion Air Gun Only includes 10' (3m) shielded cable*
8293	Gen4 Ion Air Gun and Gen4 Power Supply
8493	Gen4 Ion Air Gun Kit includes the Gen4 Ion Air Gun, Model 7960 Gen4 Power Supply, filter separator and pressure regulator (with coupler).

<sup>\*</sup> For special length cables, please contact the factory.

Accessories and Components			
Model #	Description		
7960	2 Outlet Selectable Voltage Gen4 Power Supply (115V, 230V, 50/60Hz)		
7961	4 Outlet Selectable Voltage Gen4 Power Supply (115V, 230V, 50/60Hz)		
9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)		
9008	Pressure Regulator with Gauge, 1/4 NPT, 50 SCFM (1,415 SLPM)		
7905	Static Motor		















## GE714° Ion Air Jet



## GE774°lon Air Jet™

## Air saving Gen4 Ion Air Jet is an effective spot cleaner! Choose permanent mount or flexible hose with base!

#### What Is The GETT4 Ion Air Jet?



EXAIR's Gen4 Ion Air let delivers a concentrated airflow that can cover a precise spot without disturbing other areas. This quiet, focused airstream provides incredibly fast static decay rates and cleaning ability. The Gen4 Ion Air Jet is the ideal way to remove static and dust from small parts prior to shrink wrapping, packaging, printing, painting or finishing.

#### Why The GET14 Ion Air Jet?

The Gen4 Ion Air let induces surrounding airflow at a ratio of 5:1, minimizing compressed air use and maximizing ionized airflow. Force can be adjusted from a "blast" to a "breeze".

#### Your Choice Of Permanent Mount or Flexible Stay Set Hose™

For permanent mount applications, the compact Gen4 Ion Air Jet is the best choice since it is lightweight and easy to install using the 1/8 NPT male inlet. For applications where frequent repositioning is required, the flexible Gen4 Stay Set Ion Air Jet™ is ideal. This version can be placed in close proximity and the hose bent to aim the ionized airstream at the localized area. Since the hose has "memory" it will not creep or bend, always keeping the aim until physically moved to the next position.

The Gen4 Stay Set Ion Air Jet comes complete with a magnetic base that allows easy mounting and portability on a machine, a bench or other surface. A shutoff valve on the base provides infinite control of the force and flow.

#### **Applications**

- · Three dimensional parts
- Bottle cleaning
- Screen printing
- Shrink bands
- · Ink jet printing
- · Part cleaning Package cleaning

EXAIR

#### **Advantages**

- · Low cost
- · Rapid static decay
- · Quiet
- · Shockless, non-radioactive
- · Electromagnetically shielded high voltage cable
- · Armored high voltage cable protects against abrasion, cuts
- Integrated ground design requires no separate ground connection
- · Replaceable emitter point
- · Compact, rugged, easy to install
- · Stay Set Hose for accurate placing
- · Low air consumption



The Model 8294 Gen4 Ion Air Jet with Gen4 Power Supply neutralizes static and removes dust from a counting sensor window on a tablet production machine.



The Model 8194-9362 Gen4 Stay Set Ion Air Jet Kit cleans dust from a glass lens prior to installation on a gauge.



The Gen4 Model 8910 Instant Static Elimination Station removes contaminants on plastic fittings prior to packaging.

8294

8494

#### How The GET4 on Air Jet Works

GE714° Ion Air Jet

The Gen4 Ion Air let functions the same as the Gen4 Ion Air Gun without the blowgun handle. For details on how it works, see page 138 "How The Gen4 Ion Air Gun Works".

#### GETTA Ion Air let Performance

**GET14** Ion Air Jet Dimensions

Pres Sup			ir mption	Sound Level	Dissipate: 5kV*
PSIG	BAR	SCFM	SLPM	dBA	SECONDS
20	1.4	7.4	209	67	0.45
40	2.8	11.5	325	74	0.33
60	4.1	15.8	447	79	0.24
80	5.5	22.0	622	82	0.18
100	6.9	24.0	679	85	0.18

"6" (152mm) from target. For airflow pattern, see Model 6013 High Velocity Air Jet on page 61.

1/8 MNPT AIR INLET

#### **GET14** Ion Air Jet Specifications

EXAIR Model 7960 or 7961 Gen4 Power Supply (5kV)is required for Gen4 Ion Air Jet operation. See page 142 for details.

Certifications: The Gen4 Ion Air Jet and Gen4

Power Supply are UL Component Recognized to U.S. and Canadian

safety standards, and are CE and RoHS compliant.

Electrical: For use with 5 kVrms,

5 milliamperes (max.) power supply.

**Electrical Hazard: Shockless** 

(less than 40 microamperes short circuited).

### Do not use near flammable materials or gases.

**Materials of Construction** Metal Parts: Brass and Stainless Steel

Plastic Parts: UL rated 94 HB Stainless Steel **Emitter:** 

Maximum Ambient Temperature: 165°F (74°C)

Compressed Air:1/8 NPT inlet provided on

Gen4 Ion Air Iet. 1/4 NPT inlet provided on Gen4 Stay Set Ion Air Jet.



5 FT. (1.52m) CABLE LENGTH

	GET14 Stay Set Ion Air Jet
Model #	Description
8194-9362	Gen4 Stay Set Ion Air Jet includes 5' (1.52m) armored and electromagnetically shielded cable*, one outlet magnetic base with shutoff valve and 12" (305mm) Stay Set Hose.
8294-9362	Gen4 Stay Set Ion Air Jet and Model 7960 Gen4 Power Supply (115V, 230V, 50/60Hz)
8494-9362	Gen4 Stay Set Ion Air Jet Kit (see detail at right)
8495-9362	Gen4 Deluxe Stay Set Ion Air Jet Kit (see detail at right)
8910	Gen4 Instant Static Elimination Station (see detail at right)

Model#	Description
7960	2 Outlet Selectable Voltage Gen4 Power Supply (115V, 230V, 50/60Hz
7961	4 Outlet Selectable Voltage Gen4 Power Supply (115V, 230V, 50/60Hz)
9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)
9008	Pressure Regulator with Gauge, 1/4 NPT, 50 SCFM (1,415 SLPM)
7905	Static Meter



Model 8494 Gen4 Ion Air Jet Kit includes the Gen4 Ion Air Jet, Model 7960 Gen4 Power Supply, filter separator and pressure regulator (with coupler).



Model 8494-9362 Gen4 Stay Set Ion Air Jet Kit includes the Gen4 Stay Set Ion Air Jet, Model 7960 Gen4 Power Supply, filter separator and pressure regulator (with coupler).



Model 8910 Gen4 Instant Static Elimination Station includes the Gen4 Stay Set Ion Air Jet, Model 7960 Gen4 Power Supply and (2) 10' (3m) hoses).



Model 8495-9362 Gen4 Deluxe Stay Set Ion Air Jet Kit includes the Gen4 Stay Set Ion Air Jet, Model 7960 Gen4 Power Supply. filter separator and pressure regulator (with coupler) and 10' (3m) hose.







\*For special length cables, please contact the factory

## **GET14** lonizing Point

# GE714° Ionizing Point™


## Single point ionizer for spot neutralization!

#### What Is The GET 4 Ionizing Point?

EXAIR's Gen4 Ionizing Point is a compact, single point ionizer ideal for winding, rewinding or slitting operations. It can also be mounted through a duct to neutralize static charges due to moving air or materials.

The shockless Gen4 Ionizing Point delivers a high concentration of positive and negative ions for fast static decay. It can neutralize any surface within 2" (51mm).

#### **GET14** Ionizing Point Dimensions



#### **GET14** Ionizing Point Performance

	Distance From Charged Surface			
	0.50" (13mm)	1" (25mm)	2" (51mm)	
Dissipates 5kV (seconds)	0.12	0.18	0.24	

## **Applications**

- Winding
- Rewinding
- Slitting
- · Neutralizing ducted air

#### **Advantages**

- Electromagnetically shielded high voltage cable
- Armored high voltage cable protects against abrasion,
- Integrated ground design requires no separate ground connection
- quality.

Labeling

· Form and Fill

 Low cost Replaceable emitter point

· Neutralizing static for print

- · Rapid static decay
- Shockless
- Non-radioactive
- Compact



#### **GET 4** Ionizing Point Specifications

EXAIR Model 7960 or 7961 Gen4 Power Supply (5kV) is required for Gen4 Ionizing Point operation.

See page 142 for details.

Certifications: The Gen4 Ionizing Point and Gen4 Power

Supply are UL Component Recognized to U.S. and Canadian safety standards, and are CE and RoHS compliant.

CE

For use with 5 kVrms, Electrical:

5 milliamperes (max.) power supply.

**Electrical Hazard:** Shockless

(less than 40 microamperes short circuited).

Do not use near flammable materials or gases.

#### Materials of Construction

Metal Parts: Stainless Steel Plastic Parts: UL rated 94 HB Emitter: Stainless Steel

**Maximum Ambient** 

Temperature: 165°F (74°C)



The Model 8299 Gen4 lonizing Point System includes the Gen4 Ionizing Point and Model 7960 Gen4 Power Supply.

G574 Ionizing Point				
Model #	Description			
8199	Gen4 Ionizing Point Only includes 5' (1.52m) shielded cable*			
8299	Gen4 Ionizing Point System (see detail above)			

	Accessories and Components
Model #	Description
7960	2 Outlet Selectable Voltage Gen4 Power Supply (115V, 230V, 50/60Hz)
7961	4 Outlet Selectable Voltage Gen4 Power Supply (115V, 230V, 50/60Hz)
7905	Static Meter



## 11510 Goldcoast Drive • Cincinnati, OH 45249-1621 • Phone (513) 671-3322



## **GET14** Power Supplies







# **GE714** Power Supplies

## Selectable Voltage: For use with all Gen4 Static Eliminators!



## Why Use Gen4 Power Supplies?

The two and four outlet Gen4 Power supplies have selectable voltage which allows you to choose input voltages of 115VAC or 230VAC. The modular cable with electromagnetic shielding protects sensitive electronics against electromagnetic interference while easing connections and routing. An integrated fuse on the primary protects against voltage spikes.

#### **GET14** Power Supplies

The Two and Four Outlet selectable voltage Gen4 Power Supplies require an input of 115VAC, 50/60 Hz or 230VAC, 50/60 Hz. A 6' (1.83m) modular power cord and lighted power switch are included. Power Supplies are UL Component Recognized to U.S. and Canadian safety standards, and are CE and RoHS compliant.







The Model 7960 Gen4 Power Supply has 115VAC or 230VAC selectable voltage, lighted power switch, integral fuse on the primary, electromagnetically shielded modular power cable and (2) 5kV outlets.



The Model 7961 Gen4 Power Supply has 115VAC or 230VAC selectable voltage, lighted power switch, integral fuse on the primary, electromagnetically shielded modular power cable and (4) 5kV outlets.

#### **GET14** Power Supplies: Selectable Voltage Model # Description 2 Outlet Selectable Voltage Gen4 Power Supply 7960 (115V, 230V, 50/60Hz) 4 Outlet Selectable Voltage Gen4 Power Supply (115V, 230V, 50/60Hz)

· Durable, stainless steel high voltage connections

· Electromagnetically shielded modular power cable

· Modular power supply cable eases connections and routing.

Order Direct

We Ship From Stock

· Selectable voltage 115VAC or 230VAC


· Fuse protects against voltage spikes

### **GET14** Power Supply Dimensions

INPUT VOLTAGE: 115/230 VAC INPUT CURRENT: 2/1 A MAX FREQUENCY: 50/60 HZ


OUTPUT VOLTAGE: 5000 Vrms OUTPUT CURRENT: 5 mA MAX

## Model 7960



## Model 7961











Advantages

· Replaceable rocker switch









## INTELLISTAT Ion Air Gun™

## Lightweight solution for static and particulate elimination in sensitive processes!

## Rated Class 5 for clean rooms and controlled environments per ISO 1 4644-1

## What is the INTELLISTAT Ion Air Gun?

Why the INTELLISTAT Ion Air Gun?

Coming equipped with a short-throw, fast acting and

effortless trigger, the Intellistat's lightweight frame

(less than 200 grams) allows extended use without

fatigue, while also providing a dependable and low

maintenance solution. The Model 8500 Intellistat Ion Air Gun is also fitted with handy features such

as a 6mm air connection, red and green LED lights

to signify ionized air is being produced, and a hook

The patented Intellistat is the newest innovation in a long line of EXAIR static elimination solutions. This intelligent product utilizes balanced and ionized compressed air to neutralize static and remove troublesome particulates during clean processes, test procedures and sensitive assembly work. With



a +/-30 volt offset, the Intellistat was designed to consume minimal compressed air while simultaneously delivering precise blowoff and exceptional static decay rates capable of reducing 5000 volts to less than 500 in under one second. The design hosts an efficient, low voltage transformer converting 120V to 24V to assure safety, while also utilizing an EXAIR engineered air nozzle ensuring it meets all OSHA requirements for sound level and dead-end pressure.

### for convenient hanging and storage. The 316SS emitter point is so simple to change, it can be completed in less than one minute. The housing is made of durable static dissipative polycarbonate to further minimize any potential for static electricity discharge around sensitive electronics, sensors or materials. It will produce clean, ionized compressed air essential for removing dust, static, or particulate contaminates in sterile environments

such as laboratories, clean rooms, or for scientific testing.

#### EU Regd. Des. No. 00770318-0001 Pat D903 817

©EXAIR LLC, Mexico No. 60723, Canada No. 194141

#### **Applications**

- · Precision parts assembly
- · Maintain charge neutrality in laboratory processes
- Remove particles from parts and surfaces in clean environments
- · Printed circuit board manufacturing
- Maintain cleanliness during electronics manufacturing and assembly
- · Eliminating electrostatic discharge

EXAM

- · Remove debris from medical products
- · Clean glass containers, slides and lenses

#### Advantages

- Rapid static decay
- · Low voltage operation
- · Quick change emitter point
- · Comfortable, short throw trigger for ionization
- · Light weight for prolonged use
- · OSHA safe air outlet
- · LED indicators for proper and improper functionality

# INTEX LISTAT Ion Air Gun

### How The INTELLISTAT Ion Air Gun Works



Pressing the full finger, short throw trigger (1) activates the static eliminating ions and airflow. Proper or improper functionality is indicated by a green or red LED (2).

The non-marring nozzle (3) provides quiet performance and OSHA compliance. A hanger hook (4) is included to keep the Intellistat conveniently stored.

### INTELLISTAT Ion Air Gun Specifications

Certifications: The Intellistat Ion Air Gun is

UL listed and CE and RoHS

compliant.

Power Supply Input: 100-240V - 50/60 Hz 0.7A Max

Power Supply Output: EXAIR Model 902067

Power Supply (24VDC, 1.0A Max) is required for Intellistat Ion Air Gun operation. Included with Intellistat

Ion Air Gun.

Electrical Hazard: Shockless

(less than 40 microamperes short circuited)

Do not use near flammable materials or gases.

Size of Hand Unit: 6-3/8"W x 6-3/4"L x 1"H

Weight of Hand Unit: 0.42 lbs

Operating Temperature: 32°F to 105°F (0-41°C) Do not use near flammable materials or gases.

**Materials of Construction** 

**Plastic Parts:** Static Resistant Polycarbonate

**Emitters:** Stainless Steel 30psi - 125psi Gas Input:

Clean Dry Compressed Air or Nitrogen

Air Connection: 6mm tube

Cleanroom Classification: ISO 14644-1 Class 5, operational.

### INTELLISTAT Ion Air Gun Performance

Fic	w	Air Cons	umption	Sound Level
PSIG	BAR	SCFM	SLPM	dBA
30	2.1	2.7	76.46	76
80	5.5	5.8	164.21	81

### INTELLISTAT Ion Air Nozzle Force / Discharge Time


Pres Sup	sure ply		Force*			Discharge Time**
PSIG	BAR	LBS	oz	GRAMS		SECONDS
30		0.02	0.33	0.1	1.2	1000V down to 100V
30	2.1	0.02	0.32	9.1	1.2	5000V down to 500V
80				45.4	0.6	1000V down to 100V
80	5.5	0.1	1.6	45.4	0.6	5000V down to 500V

<sup>\* 12&</sup>quot; (305mm) from target. \*\*Discharge rate taken from 1" away.

Intellistat Ion Air Gun		
Model #	Description	
8500	Intellistat Ion Air Gun Includes 24VDC Power Supply with Power Cable and 10 feet x 6mm OD compressed air tubing.	

Accessories and Components			
Model #	Description		
9004	Automatic Drain Filter Separator, 1/4 NPT, 43 SCFM (1,218 SLPM)		
9008	Pressure Regulator with Gauge, 1/4 NPT, 50 SCFM (1,415 SLPM)		
7905	Static Meter		
902067	24VDC Power Supply		

#### Intellistat Ion Air Gun Dimensions
























## INTELLISTAT Ion Air Nozzle™

A mountable nozzle for hands free static elimination at assembly stations and benchtop applications!

## Rated Class 5 for clean rooms and controlled environments per ISO 14644-1



#### What is the INTELLISTAT Ion Air Nozzle?

The patented Model 8505 Intellistat Ion Air Nozzle is EXAIR's latest hands-free innovation in a long line of static elimination solutions. This intelligent product provides a balanced ionized air stream to neutralize static and remove troublesome particulate during sensitive assembly work, test procedures and clean processes. With a +/-30 volt offset, the Intellistat nozzle was designed



to use minimal compressed air while delivering a focused blowoff and exceptional static decay rates capable of reducing 1000 volts to 100 volts in 0.6 seconds. The design includes an efficient, low voltage transformer which converts 120VAC to 24V DC to assure safety. An EXAIR engineered air nozzle delivers the air well below the OSHA standards for noise exposure and deadend pressure, which maintains safety compliance.

#### Why the INTELLISTAT Ion Air Nozzle?

Including a compact stainless steel adjustable mounting bracket, the Intellistat nozzle can be mounted to benchtops and machine frames, for example, to provide hands-free operation when needing both hands to package, test or assemble parts and products. The Intellistat Ion Air Nozzle is designed with other convenient features including a 6mm push-in air connection, and green and red LEDs which indicate proper functionality. The housing is made of durable static dissipative polycarbonate to further minimize any potential for static electricity discharge around sensitive electronics, sensors or materials. The Intellistat Ion Air Nozzle produces an ionized airstream that is essential for removing static, dust, debris and particulate in sterile environments such as pharmaceutical and medical laboratories, clean rooms and electronics labs.

EU Regd. Des. No. 009025463-0001 UK Registered Design No. 6211314

#### **Applications**

- · Precision parts assembly
- Maintain charge neutrality in laboratory processes
- Remove particles from parts and surfaces in clean environments
- PCB manufacturing

- Maintain cleanliness during electronics manufacturing, assembly and testing
- Eliminate electrostatic discharge
- Remove debris from medical products
- Clean lenses, glass containers and slides

- Mountable, hands-free operation
- Quick change emitter point
- · OSHA safe air outlet and noise level
- LED indicators for proper and improper functionality

#### Advantages

- Rapid static decay
- Low voltage operation

## INTEX LISTAT Ion Air Nozzle

#### How The INTELLISTAT Ion Air Nozzle Works



After connecting the 24V power supply, activate the power switch (1) and turn on a compressed air source to supply the 6mm push-in fitting (2) to activate the static eliminating ions and airflow. Proper or improper functionality is indicated by a green or red LED (3). The non-marring nozzle (4) provides quiet performance and OSHA compliance. The compact mounting bracket (5) is included to provide handsfree operation.

#### INTELLISTAT Ion Air Nozzle Specifications

Certifications: The Intellistat Ion Air Nozzle is UL listed and CE and RoHS compliant. ( 6

**Power Supply** 100-240VAC - 50/60 Hz 0.7A Max Input:

**Power Supply** Output:

EXAIR Model 902067 Power Supply (24VDC, 1.0A Max) is required for Intellistat Ion Air Nozzle operation.

Included with Intellistat Ion Air Nozzle.

Electrical Hazard: Shockless

(less than 40 microamperes short circuited)

Do not use near flammable materials or gases.

Ralance:

Operating Temperature: 32°F to 105°F (0-41°C) Do not use near flammable materials or gases.

**Materials of Construction** 

Plastic Parts: Static Resistant Polycarbonate

**Emitters:** Stainless Steel

30psig - 125psig Clean Dry Compressed Gas Input:

Air or Nitrogen

Air Connection: 6mm tube

Cleanroom Classification: ISO 14644-1 Class 5, operational.

# INTELLISTAT Ion Air Nozzle Performance

	Flo	ow.	Air Cons	umption	Sound Level
T	PSIG	BAR	SCFM	SLPM	dBA
	30	2.1	2.7	76.46	76
Г	80	5.5	5.8	164.21	81

## INTELLISTAT Ion Air Nozzle Force / Discharge Time


Pressure Supply		Force*			Discharge Time**	
PSIG	BAR	LBS	OZ	GRAMS		SECONDS
30	2.1	0.02	0.32	9.1	1.2	1000V down to 100V
					1.2	5000V down to 500V
80	5.5	0.1	1.6	45.4	0.6	1000V down to 100V
					0.6	5000V down to 500V

<sup>\* 12&</sup>quot; (305mm) from target. \*\*Discharge rate taken from 1" away.

INTELLISTAT Ion Air Nozzle			
Model #	Description		
8505	Intellistat Ion Air Nozzle includes 24VDC Power Supply with Power Cable, 10 feet x 6mm OD compressed air tubing and mounting bracket.		

Accessories and Components				
Model #	Description			
9004	Automatic Drain Filter Separator, 1/4 NPT, 43 SCFM (1,218 SLPM)			
9008	Pressure Regulator with Gauge, 1/4 NPT, 50 SCFM (1,415 SLPM)			
7905	Static Meter			
902067	24VDC Power Supply			

## INTELLISTAT Ion Air Nozzle Dimensions



























**VARISTAT** Benchtop lonizer™

Mountable hands-free blower for static elimination at assembly stations and benchtop applications

#### What is the VARISTAT?

The EXAIR Varistat Benchtop Ionizer is a blower style static eliminator designed to neutralize static charges on surfaces in demanding industrial settings where static can become troublesome. With the help of ionizing technology, the Varistat supplies a constant stream of ion-balancing airflow to keep products static-free and particulate-free with hands-free operation and without the need of compressed air. Manually adjustable, the Varistat provides full coverage static elimination for workbenches, part assembly, web cleaning and more.

#### Why the VARISTAT?

The Varistat can be easily mounted on equipment or placed on workbenches to assist with consistent static neutralization. Capable of reducing 1000 volts to 100 volts in 0.8 seconds, the Varistat Ionizer removes surface static at a distance with incredible efficiency. The Varistat is engineered to fit various industrial applications and unique processes by offering customizable options such as an adjustable stand for mounting, selectable voltage, variable fan speed and adjustable polarity.

This static eliminator features ion producing emitter points and two 30 PPI replaceable foam filters to ensure optimal performance over extended periods of use. Also offering a built-in LED display that indicates proper function, the Varistat is designed with important safety features such as its current limiting circuit to protect against electrical hazards, and operating quietly and well below OSHA standards for noise exposure. The Varistat static eliminator is a reliable and effective solution for reducing static charges on sensitive products and protecting against static, dust, debris and other pesky particulate.

#### Advantages

- Rapid static decay
- · Low voltage operation
- OSHA safe air outlet and noise level
- improper functionality

#### · Mountable, hands-free operation

- · LED indicators for proper and

## EXAM

· Slitting, sheeting and winding


**Applications** 

· Electronics assembly

· Molding machinery

· Web cleaning

· Cleaning parts



Shrink wrappers

Package cleaning

· Printing equipment

Benchtop assembly



## **VARISTAT** Benchtop Ionizer

#### How the WARISTAT Benchtop Ionizer works



After connecting the 115V or 230V power cable, plug into outlet 1) and check to make sure voltage selector switch 2) is set correctly; then activate power switch to activate static eliminating ions and airflow 3). A green light will indicate that power is turned on, improper functionality is indicated by a flashing red LED 4). Adjust fan speed with dial 5), and polarity with "+" and "-" buttons located on top 6). Adjust angle and height with knobs located on the side 7). Mounting bracket included for hands-free operation 8).

## **VAFISTAT** Benchtop Ionizer Specifications (Ų∟)

The Varistat Ionizer is UL Listed, and RoHS and CE compliant



120-240 VAC, 50/60 Hz - Selectable Input Voltage:

.6A/.4A Input Current: Emitter Voltage: 5-7 kV

**Balance:** 

±100V, manually adjustable to <10V

13 1/2 in. x 10 1/2 in. x 10 in. Dimensions: Weight: 9.1 lbs

Air Output: 10" x 1.5" - covers up to 16" x 10' area Filter: Two replaceable foam filters, 30 ppi

Static Discharge: 0.8 seconds to discharge 1000-100 V -

measured 12" from charged area with fans

at high speed

Sound Level: 67 dBA measured 3' in front of unit with

fans at high speed

Indicator LEDs: Middle green LED indicates unit is on

Blue LEDs indicate balance adjustment

positive and negative


#### Red LED (above green LED):

2 flashes - Electrical Failure

3 flashes - Control Board Malfunction

4 flashes - Fan Malfunction


#### **WARISTAT** Mounting Hole Locations:



	VARISTAT Benchtop Ionizer
Model #	Description
8600	Varistat Benchtop Ionizer with (2) Model 902329 Filter Kits, Model 902350 115V Power Cable and Model 901681 230V Power Cable

Ac	cessories and Components – Replacement Parts
Model #	Description
902425	Replacement Filter (30 PPI)
902358	Fan Speed Knob
7564	Stand Knob
7657	Stand Grommet

#### **VARISTAT** Benchtop Ionizer Dimensions











# **EXAIR** White Papers




# Basics of Static Electricity

Static Electricity and Electrostatic Discharge can be a large disruptor of processes within manufacturing facilities. It will cause problems maintaining product quality, keeping process speeds at optimum levels and will impact the morale of personnel experiencing static shocks. Our white paper starts with electron theory, identifies how static is generated and ends with specific solutions.

#### What Causes Static Electricity?

Static electricity occurs most often on the surface of non-conductive materials but can also occur on ungrounded conductive surfaces. A static (non-moving) electric charge is created.



#### What Determines the Amount of Static Electricity Imbalance?

The Triboelectric Series chart below shows the static buildup tendencies of various materials



#### Types of Static Generation

There are three types of static generation. First is Contact Static Buildup...




EXAIR's White Paper will help you learn what causes static electricity and how it develops. Discover what steps can be taken to eliminate static and which products are helpful to control static within your facility.

or scan the gr code provided



EXAIR





# An INTELLIGENT COMPRESSED AIR Product

#### E-Vac® Vacuum Generators









## E-Vac® Vacuum Generators

## Vacuums for lifting, clamping, mounting and placement!

#### What Is The E-Vac?

EXAIR's compressed air powered E-Vac single stage vacuum generators are the low cost way to create a vacuum for:

- · Pick and place
- · Chucking
- · Clamping
- Alignment
- · Lifting
- Surface mounting Vacuum forming

E-Vac compressed air powered vacuum pumps provide instantaneous response and are most commonly used for pick and place operations. They are available in a variety of sizes and flows for a wide range of applications.

#### Why The E-Vac?

The E-Vac vacuum generators have been engineered for high efficiency to minimize air consumption. These single stage, all aluminum units provide consistent, steady vacuum, unlike mechanical vacuum pumps. Dust and small particulates easily pass through the vacuum generator and they have no moving parts, making them maintenance free.

EXAIR's E-Vac Vacuum Generator is available in 2 styles:

#### In-Line E-Vac Vacuum Generator

These single stage, cylindrical units are compact and easy to mount at the point of use. They can be held in place by threading them directly onto a compressed air line or with the use of a mounting clip. There are 7 models available for use with porous materials, like cardboard, with vacuum levels up to 21" Hg (71 kPa) and vacuum flows up to 18.5 SCFM (524 SLPM). There are 7 models available for use with non-porous materials such as glass, with vacuum levels up to 27" Hg (91 kPa) with vacuum flows up to 15.8 SCFM (447 SLPM).



**SCAN & WATCH the video!** https://exair.co/04-evacv

In-Line E-Vac



Adjustable E-Vac

#### Adjustable E-Vac Vacuum Generator

This series of vacuum generators permits easy adjustment by simply loosening the locknut and turning the exhaust to increase or decrease the level of vacuum and vacuum flow. This style is also an excellent choice where large particulate may be present and passed through the vacuum system. There are 4 models with adjustable vacuum up to 25" Hg (85 kPa) and vacuum flow up to 81 SCFM (2,294 SLPM).

#### **Applications**

- Pick and place parts and equipment
- · Bag/package opening Label placement
- · Vacuum forming
- Mold evacuation
- · Vacuum filling
- · Leak testing
- Evacuate containers

- · Clamping and chucking
- · Paper alignment and feed in printing equipment
- · Vacuum packaging
- Surface mounting
- · Vacuum press for wood veneers and laminates
- · Carton forming
- Robotic tooling · Vacuum liquids for testing
- · Lightweight, rugged
  - · No moving parts -

Advantages

in vacuum

· Compact, portable

· Single stage design

eliminates fluctuations

Instantaneous vacuum

· Easy to mount at point of use

 Durable 6061 aluminum construction

• 18 models

· Fast response -

· Safe operation -

increases cycle time

no electricity









#### How to Build An E-Vac System:

#### 1. Select the E-Vac type.

- A. Determine if the part to be lifted is porous or non-porous (page 152 and 153).
- B. Select a style In-Line Low Vacuum, In-Line High Vacuum, or Adjustable (pages 152, 153 and 155). The E-Vac type determines max, vacuum available for lifting the part and vacuum cup selection.

low vacuum generators max, vacuum = 21" Hg (71 kPa) Porous Non-porous high vacuum generators max. vacuum = 27" Hg (91 kPa) Adjustable E-Vac vacuum generators max. vacuum = 25" Hg (85 kPa)

Need Help Selecting the Correct E-Vac? Our Application Engineers can assist you in determining the correct model E-Vac and vacuum cups (if required). Call 1-800-903-9247 or visit www.exair.com/appassist.htm

- 2. Determine the weight of the part.
- 3. Multiply the weight by the vacuum cup safety factor (see page 157) for the total vacuum cup capacity needed.
- 4. Determine the number of vacuum cups needed by considering the following:
  - A. How many cups are needed to distribute the weight for stable lifting and placement?
  - B. What is the weight that each vacuum cup can lift based on maximum vacuum available (E-Vac type)?
  - C. Select vacuum cups from chart on page 157 based on max, vacuum available (E-Vac type) and holding weight/cup.
- 5. To choose an E-Vac model number, consider the entire vacuum system from the E-Vac to the part.
  - A. Number of vacuum cups per E-Vac.
  - B. Length and size of vacuum tubing.
  - C. Vacuum cup size and type.
- The volume of air to evacuate from your vacuum system and the vacuum flow of the E-Vac you've selected (pages 152, 153 and 156) will determine the time it takes from E-Vac activation to vacuum cup holding the part. As the vacuum level in the system increases, the volume of evacuating air decreases.
- · A lower volume of air in the vacuum system and/or a higher capacity (SCFM/SLPM) E-Vac will give faster pick-up times.
- · An exact pick-up time cannot be calculated.
- . If the E-Vac vacuum generator doesn't meet your needs, return it for a different model, with no restocking charge (U.S. and Canada only).

#### Here is an example using the steps outlined above:

A sheet of material measures 3' x 3' (.91m x .91m) and weighs 25 lbs (11.3kg). Each sheet is in a stack and will be placed on a conveyor.

#### If it is porous, like wood, and positioned vertically:

- 1. Choose a porous, low vacuum In-Line E-Vac. The maximum vacuum is 21" Hg (71 kPa).
- 2. The weight is 25 lbs (11.3kg).
- 3. If the part is picked-up and hung on an overhead conveyor vertically, the safety factor is 4. The vacuum cup capacity needed is 4 x 25 = 100 lbs (45.4kg).
- 4. Four vacuum cups will be used for stability when lifting the sheet. Each cup will need at least a 25 lb (11.3kg) capacity. In the table on page 157, at 21"Hg (71 kPa), the Model 900755 Vacuum Cup will hold up to 25.3 lbs (11.5kg).
- 5. Use 4 small round vacuum cups that are positioned close to one another. The vacuum system has a small to medium volume and pick-up and release time is not critical. To reduce the sound level, use the straight through muffler.
- Order: (1) Model 800008M In-Line E-Vac
  - (4) Model 900755 Vacuum Cups

See Page 160 for other accessories.

#### If it is non-porous, like glass, and positioned horizontally:

- 1. Choose a non-porous, high vacuum In-Line E-Vac. The maximum vacuum is 27" Hg (91 kPa).
- 2. The weight is 25 lbs (11.3kg).
- 3. If the part is picked-up and placed on a belt conveyor horizontally, the safety factor is 2. The vacuum cup capacity needed is 2 x 25 = 50 lbs (22.7kg).
- 4. Four vacuum cups will be used for stability when lifting the sheet. Each cup will need at least a 12.5 lb (5.7kg) capacity. In the table on page 157, at 27" Hg (91 kPa), the Model 900754 Vacuum Cup will hold up to 20.8 lbs (9.4kg).
- 5. Use 4 small round vacuum cups that are positioned close to one another. The vacuum system has a small to medium volume and pick-up and release time is not critical. To reduce the sound level, use the straight through muffler.
- Order: (1) Model 810006M In-Line E-Vac
  - (4) Model 900754 Vacuum Cups

See Page 160 for other accessories.

The Model 840008M Adjustable E-Vac can be substituted for picking up the wood or the glass since the vacuum level and vacuum flow is easily adjusted to suit the porous or non-porous application. The Adjustable E-Vac is especially useful for loads that vary.





#### For Technical Assistance, Call An EXAIR Application Engineer 1-800-903-9247 Toll Free FAX (866) 329-3924 • E-mail: techelp@exair.com • www.exair.com



In-Line E-Vac Vacuum Generators for porous applications



Create your own vacuum system!

In-Line E-Vac with Straight Through Muffler, pushin connectors, vacuum tubing and a round vacuum cup (shown).

In-Line E-Vac Low Vacuum Generators For Porous Applications	Model 1.5 SCFM 43 SLPM	Model 2.1 SCFM 60 SLPM	Model 3.1 SCFM 88 SLPM	Model 5.4 SCFM 153 SLPM	Model 8.4 SCFM 238 SLPM	Model 12.6 SCFM 357 SLPM	Model 16.8 SCFM 476 SLPM
In-Line E-Vac Only	800001	800002	800003	800005	800008	800013	800017
In-Line E-Vac with Straight Through Muffler	800001M	800002M	800003M	800005M	800008M	800013M	800017M
In-Line E-Vac Kit with Straight Through Muffler	801001M	801002M	801003M	801005M	801008M	801013M	801017M
In-Line E-Vac Deluxe Kit with Straight Through Muffler	802001M	802002M	802003M	802005M	802008M	802013M	802017M

Note: Replace 'M' with 'H' for Standard Muffle

flow and vacuum level.

vacuum tubing and a mounting clip.

supply and pressure regulator (with coupler).

E-Vac® Vacuum Generators

**Low Vacuum Generators For Porous Applications** 

Low vacuum units up to 21" Hg (71 kPa) with vacuum flows up

to 18.5 SCFM (524 SLPM) are typically used for porous materials

prevents any warping, marring, dimpling or disfiguring of the surface

overcome porosity and leakage. There are 7 In-Line models that vary by

such as cardboard and delicate materials. The low level vacuum

due to excessive vacuum. This style generates more vacuum flow to

Choose the E-Vac by the SCFM (SLPM) flow that best suits the

performance needed for your application (see Performance Table below).

E-Vac Kits give you the ability to experiment with an assortment of

vacuum cups. Kits include a muffler, an assortment of (4) pairs of

vacuum cups (closely matched to the performance of that E-Vac), (2) straight, (2) elbow and (1) tee vacuum fittings, 10' (3m) of

E-Vac Deluxe Kits include the same items as the standard kit with the

addition of an automatic drain filter separator for the compressed air

	41-5		So	und Level in	dBA				٧	acuu	m Flow	v (SCF	M/SL	PM) v	s. Vac	uum L	evel (	"Hg/I	kPa)				
n-Line E-Vac Model	SCFM @	80 PSIG 5.5 BAR	No Muffler	Standard Muffler	Straight Through Muffler	-	0	3/	10	6/	20	9/	31	12	/41	15	/51	18.	/61	21/	71		lax ac
800001	1.5	42.5	80	72	60	1.52	43.0	1.41	39.9	1.25	35.4	1.10	31.1	0.95	26.9	0.85	24.1	0.56	15.9	0.00	0.0	21	7
800002	2.1	59.5	80	72	63	2.22	62.9	2.05	58.0	1.91	54.1	1.77	50.1	1.45	41.1	0.95	26.9	0.56	15.9	0.00	0.0	21	7
800003	3.1	87.8	89	74	70	3.75	106.2	3.52	99.7	3.15	89.2	2.75	77.9	2.15	60.9	1.20	34.0	0.56	15.9	0.00	0.0	21	7
800005	5.4	152.9	92	83	66	5.59	158.3	5.23	148.1	4.51	127.7	3.75	106.2	3.34	94.6	2.51	71,1	1.25	35.4	0.00	0.0	21	7
800008	8.4	237.9	97	88	74	7.70	218.0	6.95	196.8	6.30	178.4	5.30	150.1	4.23	119.8	3.15	89.2	1.31	37.1	0.00	0.0	21	71
800013	12.6	356.8	99	91	78	15.50	438.9	14.50	410.6	13.15	372.4	11.35	321,4	8.70	246.3	4.03	114.1	0.00	0.0	0.00	0.0	18	61
800017	16.8	475.7	101	91	81	18.50	523.8	17.20	487.0	14.70	416.2	12.40	351.1	9.80	277.5	5.00	141.6	0.00	0.0	0.00	0.0	18	6





#### **High Vacuum Generators For Non-Porous Applications**

High vacuum units up to 27" Hg (91 kPa) with vacuum flows up to 15.8 SCFM (447 SLPM) are typically used for non-porous materials such as glass, steel sheet, and plastic. There are 7 In-Line models that vary by flow and vacuum level.

Choose the E-Vac by the SCFM (SLPM) flow that best suits the performance needed for your application (see Performance Table below).

E-Vac Kits give you the ability to experiment with an assortment of vacuum cups. Kits include a muffler, an assortment of (4) pairs of vacuum cups (closely matched to the performance of that E-Vac), (2) straight, (2) elbow and (1) tee vacuum fittings, 10' (3m) of vacuum tubing and a mounting clip.

E-Vac Deluxe Kits include the same items as the standard kit with the addition of an automatic drain filter separator for the compressed air supply and pressure regulator (with coupler).

EXAIR E-Vacs are available in other materials upon request. Contact an application engineer for an alternate material quote.



In-Line E-Vac Vacuum Generators for non-porous applications.



The In-Line E-Vac with Standard Muffler (shown above) is also available with your choice of accessories that can be found on page 160.

In-Line E-Vac High-Vacuum Generators For Non-Porous Applications	Model 2.3 SCFM 65 SLPM	Model 3.3 SCFM 93 SLPM	Model 6.2 SCFM 176 SLPM	Model 8.4 SCFM 238 SLPM	Model 13.2 SCFM 374 SLPM	Model 23.1 SCFM 654 SLPM	Model 30.8 SCFM 872 SLPM
In-Line E-Vac Only	810002	810003	810006	810008	810013	810023	810031
In-Line E-Vac with Straight Through Muffler	810002M	810003M	810006M	810008M	810013M	810023M	810031M
In-Line E-Vac Kit with Straight Through Muffler	811002M	811003M	811006M	811008M	811013M	811023M	811031M
n-Line E-Vac Deluxe Kit with Straight Through Muffler	812002M	812003M	812006M	812008M	812013M	812023M	812031M

Note: Replace 'M' with 'H' for Standard Muffler

In-Line		Air	Sou	ind Level in	dBA						V	acuui	n Flor	w (SC	FM/SI	PM)	vs. Va	cuum	Leve	("Hg	/ kPa	)					
E-Vac Model	SCFM (	mption 80 PSIG 5.5 BAR	No Muffler	Standard Muffler	Straight Through Muffler	,	0	3/	10	6/	20	9/	31	12	/41	15	/51	18	/61	21/	71	24	/81	27	/91	Max	c Vac
810002	2.3	65.1	86	81	70	1.22	34.5	1.16	33.0	1.00	28.3	0.90	25.5	0.87	24.6	0.74	21.0	0.56	16.0	0.46	13.0	0.20	5.7	0.00	0.0	27	91
810003	3.3	93.4	87	82	73	1.73	49.0	1.59	45.0	1,48	41.9	1.24	35,1	1.09	30.9	1.02	28.9	0.78	22.1	0.67	19.0	0.49	13.9	0.00	0.0	27	91
810006	6.2	175.6	91	82	77	2.75	78.0	2.65	75.0	2.26	64.0	2.05	58.0	1.87	53.0	1.59	45.0	1.13	32.0	0.92	26.0	0.77	21.7	0.00	0.0	27	91
810008	8.4	237.9	97	90	78	4.40	124.6	4.10	116.1	3.75	106.2	3.15	89.2	2.75	77.9	2.39	67.7	1.75	49.6	1.27	36.0	0.99	28.0	0.00	0.0	27	91
810013	13.2	373.8	100	92	83	6.85	194.0	6.50	184.1	5.81	164.5	4.89	138.5	4,12	116.7	3.51	99.4	2.61	73.9	1.92	54.4	1.31	37.1	0.00	0.0	27	91
810023	23.1	654.1	102	92	84	11.95	338.4	11.80	334,1	10.45	295.9	9.02	255.4	8.10	229.4	6.52	184.6	4.54	128.6	3.65	103.4	2.67	75.6	0.00	0.0	27	91
810031	30.8	872.1	105	92	87	15.75	446.0	15.25	431.8	12.67	358.8	11.12	314.9	10.25	290.2	7.97	225.7	5.98	169.3	5.04	142.7	3.41	96.6	0.00	0.0	27	91




# E-Vac® Vacuum Generators

#### In-Line E-Vacs

EXAIR manufactures two versions of the In-Line E-Vac -Low Vacuum and High Vacuum. The application will dictate which type of vacuum is most suitable. The dimensions and performance for each model are shown.

#### How The In-Line E-Vac Works




Compressed air flows through the inlet (1), then through a single directed nozzle (2). As the airstream exhausts, it expands and increases in velocity prior to passing through the venturi (3). A vacuum inlet tangential to the primary airflow (4) is located at the suction point between the orifice and the venturi. The airflow that is drawn through the vacuum inlet mixes with the primary airstream, then exhausts on the opposite end (5).

#### **Need Help Selecting the Correct E-Vac?**


Not sure how much vacuum is required for your application? Our Application Engineers can assist you in determining the correct model E-Vac and vacuum cups (if required). Call 1-800-903-9247 or visit www.exair.com/appassist.htm





#### In-Line E-Vac Dimensions





		In-Line	Vacu	um Gene	rator Dim	ensions					
Model	Air Inlet A	Vacuum Inlet B		c	D	E	F	G	н	J	к
800001, 800002, 800003, 810002,	1/8 NPT	1/8 NPT	in	N/A	N/A	3.00	0.88	0.75	1/4 NPT	N/A	N/A
810003, 810006	1/8 NP1	1/8 NP1	mm	N/A	N/A	76	22	19	1/4 NP1	N/A	N/A
800001H, 800002H, 800003H,	LONDE	A 40 AUDT	in	N/A	5.00	3.00	0.88	0.75	THE NAME OF	N/A	0.81
810002H, 810003H, 810006H	1/8 NPT	1/8 NPT	mm	N/A	127	76	22	19	1/4 NPT	N/A	21
800001M, 800002M, 800003M,	1/8 NPT	1/8 NPT	in	5.25	N/A	3.00	0.88	0.75	1/4 NPT	1/4 NPS	0.75
810002M, 810003M, 810006M	1/8 NP1	1/8 NP1	mm	133	N/A	76	22	19	1/4 NP1	1/4 NPS	19
	E IA SIDT	O IO NIDT	in	N/A	N/A	4.50	1.50	1.00	210 1107	N/A	N/A
800005, 800008, 810008, 810013	1/4 NPT	3/8 NPT	mm	N/A	N/A	114	38	25	3/8 NPT	N/A	N/A
800005H, 800008H, 810008H,	1/4 NPT	3/8 NPT	in	N/A	7.50	4.50	1.50	1.00	240 84007	N/A	1.25
810013H	1/4 NP1	3/8 NP1	mm	N/A	191	114	38	25	3/8 NPT	N/A	32
800005M, 800008M, 810008M,	* 14 5 1000	a in a low	in	7.75	N/A	4.50	1.50	1.00	n to some	3/8 NPS	1.00
810013M	1/4 NPT	3/8 NPT	mm	197	N/A	114	38	25	3/8 NPT	3/8 NPS	25
	4 CT \$100T	240 5400	in	N/A	N/A	6.00	1.88	1.25	120 1400	N/A	N/A
800013, 800017, 810023, 810031	1/2 NPT	1/2 NPT	mm	N/A	N/A	152	48	32	1/2 NPT	N/A	N/A
800013H, 800017H, 810023H,	1/2 MINT	ACC MOT	in	N/A	9.00	6.00	1.88	1.25	212 107	N/A	1.25
810031H	1/2 NPT	1/2 NPT	mm	N/A	229	152	48	32	1/2 NPT	N/A	32
800013M, 800017M, 810023M,	A CO A LIGHT	4.00 4100	in	10.25	N/A	6.00	1.88	1.25	1/2 1/27	1/2 NPS	1.25
810031M	1/2 NPT	1/2 NPT	mm	260	N/A	152	48	32	1/2 NPT	1/2 NPS	32

# Adjustable E-Vac® Vacuum Generators A simple turn can increase or decrease vacuum and flow!


#### What Is The Adjustable E-Vac?

EXAIR's Adjustable E-Vac is a series of low cost, compressed air powered vacuum generators where the vacuum and flow rates can be easily adjusted to suit the application requirements. These vacuum pumps are ideal for a wide variety of pick and place, box opening, clamping, lifting, chucking, and surface mounting applications. They are maintenance free and have no moving parts to wear out.

#### Why The Adjustable E-Vac?

Engineered for high efficiency, the Adjustable E-Vac minimizes compressed air use by allowing it to be tuned to the application. With a simple turn of the unit, the vacuum and flow levels can be changed to overcome porosity and increase or decrease the lifting power. The straight-through, single stage aluminum construction requires no vacuum filter and simply passes contaminants from dirty environments through the unit so there is no clogging or loss of suction.

Adjustable E-Vac is available in 4 sizes that have adjustable vacuum rates up to 25" Hg (85 kPa) and flow rates up to 81 SCFM (2,294 SLPM). Kit configurations that include vacuum cups, fittings, tubing and a mounting clip are available.





The vacuum level of the Adjustable E-Vac can quickly be changed from lifting lightweight pavers to heavy cement blocks.



Compressed air flows through the inlet (1), then through an adjustable annular nozzle (2). As the airstream enters the vacuum flow, it expands and increases in velocity (3). A vacuum flow is induced, creating suction (4). The airflow that is drawn through the vacuum inlet mixes with the primary airstream, then exhausts on the opposite end (5).

					Adjusta	ble Vacu	um Gene	rator Din	nensions				
Model	Air Inlet A	Vacuum Inlet B		c	D	E	F	G	н	L	м	Exhaust Port J	Exhaust Port P
	100 1007	1 /4 NIDT	in	N/A	2.00	4.38	1.19	0.72	N/A	0.63	1.31	1/4 1/07	
840008	1/8 NPT	1/4 NPT	mm	N/A	51	111	30	18	N/A	16	33	1/4 NPT	N/A
******	1/8 NPT	1/4 NPT	in	6.63	2.00	4.38	1.19	0.72	0.75	0.63	1.31	1/4 NPT	1/4 NPS
340008M	1/8 NP1	1/4 NP1	mm	168	51	111	30	18	19	16	33	1/4 NP1	1/4 NPS
	THE REPORT	4 (2 A)(D)T	in	N/A	2.38	5.44	1.31	0.97	N/A	0.63	1.56	A 12 A 10 T	4444
840015	3/8 NPT	1/2 NPT	mm	N/A	60	138	33	25	N/A	16	40	1/2 NPT	N/A
	2 in NOT	100 100	in	9.69	2.38	5.44	1.31	0.97	1.25	0.63	1.56		A CO AUDIC
340015M	3/8 NPT	1/2 NPT	mm	246	60	138	33	25	32	16	40	1/2 NPT	1/2 NPS
	O OR S INT	A ID AUDIT	in	N/A	2.50	6.19	1.44	1.22	N/A	0.75	1.94	DATE AND THE	****
840030	3/8 NPT	1/2 NPT	mm	N/A	64	157	37	31	N/A	19	49	3/4 NPT	N/A
	A SO A STORY	10000	in	13.63	2.50	6.19	1.44	1.22	2.00	0.75	1.94	214 5107	274 8100
340030M	3/8 NPT	1/2 NPT	mm	346	64	157	37	31	51	19	49	3/4 NPT	3/4 NPS
040060	1/2 NPT	2/4 NOT	in	N/A	2.75	6.50	1.56	1.47	N/A	0.75	2.19	4 64007	8178
840060	1/Z NPT	3/4 NPT	mm	N/A	70	165	40	37	N/A	19	56 1 NP1	TNPT	N/A
340060M	1/2 NPT	3/4 NPT	in	13.94	2.75	6.50	1.56	1.47	2.00	0.75	2.19	1 NPT	1 NPS
MUGUUP	1/2 MPT	3/4 MPT	2000	254	70	160	40	99	2.5	10	20	LNPT	1 MPS



11510 Goldcoast Drive \* Cincinnati, OH 45249-1621 \* Phone (513) 671-3322 FAX (513) 671-3363 \* E-mail: techelp@exair.com \* www.exair.com



#### E-Vac® Vacuum Generators

#### Adjustable E-Vac Vacuum Generators

Choose the Adjustable E-Vac by the SCFM (SLPM) flow that best suits the performance needed for your application (see Performance Table below).

Adjustable E-Vac Kits give you the ability to experiment with an assortment of vacuum cups. E-Vac Kits include a muffler, an assortment of (4) pairs of vacuum cups (closely matched to the performance of that E-Vac), (2) straight, (2) elbow and (1) tee vacuum fittings, 10' (3m) of vacuum tubing and a mounting clip.

Adjustable E-Vac Deluxe Kits include the same items as the standard kit with the addition of an automatic drain filter separator for the compressed air supply and pressure regulator (with coupler).

#### Adjustable E-Vac Performance

The amount of vacuum created varies with the porosity of the load being picked up. Units come from the factory set to 15" Hg (51 kPa). A maximum of 25" Hg (85 kPa) can be achieved on a solid, non-porous surface, but will require increasing the air consumption and vacuum flow.



Adjustable E-Vac Vacuum Generators have vacuum levels up to 25" Hg (85 kPa) that can be used with porous and non-porous materials.

Adjustable E-Vac	Model 8.2 SCFM 232 SLPM	Model 15.4 SCFM 436 SLPM	Model 26.4 SCFM 748 SLPM	Model 62.7 SCFM 1,775 SLPM
Adjustable E-Vac Only	840008	840015	840030	840060
Adjustable E-Vac with Straight Through Muffler	840008M	840015M	840030M	840060M
Adjustable E-Vac Kit with Straight Through Muffler	841008M	841015M	841030M	841060M
Adjustable E-Vac Deluxe Kit with Straight Through Muffler	842008M	842015M	842030M	842060M

				Adjusta	Die vac	uum Ge	nerato	rerior	mance	(15 mg/	DIKE					
	Air Cons	umption	Sound Le	vel in dBA			Vacuum I	low (SCFA	//SLPM) v	s. Vacuum	Level ("H	g/kPa)(S	et to 15" H	(g/51 kPa)		
Model	SCFM @	80 PSIG 5.5 BAR	No Muffler	Straight Through Muffler		0	3/	10	6/	20	9/	31	12	/41	15	/51
840008	8.2	232.2	89	77	5.80	164.2	4.68	132.6	3.71	105.0	2.59	73.4	1.53	43.2	0.0	0.0
840015	15.4	436.1	95	77	18.70	529.5	16.00	453.1	12.02	340.3	7.75	219.4	4.05	114.7	0.0	0.0
840030	26.4	747.5	99	74	36.70	1039.2	32.00	906.1	25.63	725.8	17.68	500.5	7.69	217.8	0.0	0.0
840060	62.7	1775.4	107	85	81.00	2293.6	67.00	1897.2	56.33	1595.1	29.00	821.2	11.13	315.3	0.0	0.0

	Air Cons	umption		d Level dBA				٧	acuum	Flow	SCFM	SLPM)	vs. Va	cuum l	.evel (	"Hg/k	Pa) (Se	t to 25	" Hg/8	5 kPa)				
Model		80 PSIG 5.5 BAR	No Muffler	Straight Through Muffler		0	3/	10	6/	20	9/	31	12	/41	15	/51	18	/61	21	/71	24	24/81	25	/85
840008	12.2	345.5	104	89	5.80	164.2	5.58	157.9	5.18	146.5	4.80	135.9	4.33	122.5	3.83	108.3	2.94	83.2	1.93	54.5	0.37	10.5	0.0	0.0
840015	25.9	733.4	107	89	18.00	509.7	16.53	467.9	15.70	444.6	14.18	401.4	12.13	343.3	8.98	254.1	5.65	160.0	2.69	76.1	0.55	15.6	0.0	0.0
840030	44.8	1268.6	107	82	32.00	906.1	29.00	821.2	26.83	759.8	24.12	682.9	20.92	592.3	14.63	414.1	9.90	280.3	6.13	173.7	1.19	33.8	0.0	0.0
840060	105.2	2978.8	114	92	70.00	1982.1	66.33	1878.3	62.33	1765.0	55.50	1571.5	45.00	1274.2	30.67	868.4	18.37	520.1	8.38	237.4	2.10	59.5	0.0	0.0



Compressed air use is minimized by selecting the exact vacuum level required to lift the heavy, porous cardboard cartons.



A series of bellows cups lift one plastic part at a time off of a pallet.







#### Choosing A Suitable Vacuum Cup

## Round Cups are best suited to

smooth, flat surfaces. They will grip and release quickly. These cups hold their shape with extended

use and grip well to vertical surfaces. Round cups with cleats are better at lifting heavy loads. Cups without cleats can be used for light lifting.

Oval Cups provide the most vacuum due to the larger surface area. They provide more vacuum power than round cups and are suited to lifting heavy

loads. They are designed to handle flat rigid sheet materials like wood, glass, cardboard boxes and composites.

Bellows Cups are best suited to

textured, uneven surfaces. The folds, called convolutions, provide a collapsible area that allows the cup to quickly

compress when it touches the uneven surface. The attach and release time is greater due to the significant volume of the cup.

#### Vacuum Cup Safety Factor

## A safety factor of 2

is recommended when the vacuum cup is positioned horizontally.

#### A safety factor of 4

is recommended when the vacuum cup is positioned vertically.

Some companies or local codes may require a specific safety factor.

#### **Using The Tables Below**

Determine the weight of the part to be lifted. Multiply it by the safety factor of (2) when the cup will be positioned horizontally, or by (4) when positioned vertically.

Using the table below, look through the numbers highlighted in orange [ ] for the weight capacity per vacuum cup. Use enough vacuum cups to distribute the weight evenly for stable lifting and placement. The model number(s) for the vacuum cup(s) that can handle for each vacuum cup can be found on page 158.

To the left of the vacuum cup weight you've selected (in that same row) is the vacuum level highlighted in green that is needed. Performance data for the In-Line E-Vacs designed for specific vacuum levels can be found on pages 152-153. For loads that vary, Adjustable E-Vacs are the best choice (performance shown on page 155).

				Weight	in lbs that	a vacuur	n cup can	hold at a	given va	cuum			
Vacuum Co	up Models	900762 900766	900752 900767	900763	900764	900753 900768	900754 900769	900765	900755 900770	900756 900757 900758 900771	900759	900760	900761
Area c		0.4	0.8	1.0	1.5	1.8	3.1	4.4	4.9	8.3	14.2	19.6	28.3
	5	0.5	1.0	1.2	1.8	2.2	3.9	5.3	6.0	10.2	17.4	24.1	34.7
£	10	1.0	1.9	2.5	3.7	4.3	7.7	10.7	12.1	20.4	34.8	48.2	69.4
Ė	15	1.5	2.9	3.7	5.5	6.5	11.6	16.0	18.1	30.6	52.3	72.3	104.2
COU	20	2.1	3.9	4.9	7.4	8.7	15.4	21.4	24.1	40.7	69.7	96.4	138.9
3	21	2.2	4.1	5.2	7,8	9.1	16.2	22.4	25.3	42.8	73.2	101.3	145.8
	27	2.8	5.2	6.6	10.0	11.7	20.8	28.9	32.6	55.0	94.1	130.2	187.5

	Weight in kilograms that a vacuum cup can hold at a given vacuum														
Vacuum Cup Models  Area of cup cm <sup>2</sup>		900762 900766 3	900752 900767	900763	900764	900753 900768	900754 900769	900765	900755 900770	900756 900757 900758 900771	900759	900760	90076		
			3 5		10	11	20	28	32	54	92	127	182		
	17	0.2	0.4	0.6	0.8	1.0	1.7	2.4	2.7	4.6	7.9	10.9	15.7		
KPa.	34	0.5	0.9	1,1	1.7	2.0	3.5	4.8	5.5	9.2	15.8	21.9	31.5		
e x	51	0.7	1.3	1.7	2.5	3.0	5.2	7.3	8.2	13.9	23.7	32.8	47.2		
Vacuui	68	0.9	1.7	2.2	3.4	3.9	7.0	9.7	10.9	18.5	31.6	43.7	63.0		
	71	1.0	1.8	2,3	3.5	4.1	7.3	10.2	11.5	19.4	33.2	45.9	66.1		
	91	13	24	3.0	45	53	9.4	13.1	14.8	25.0	42.7	591	85.0		

#### EXAIR


#### E-Vac® Vacuum Generators

#### **Vacuum Cup Dimensions**


EXAIR vacuum cups are vinyl. They are ideal for general purpose applications and provide excellent resistance to wear. The Durometer rating (used to indicate the flexibility and stiffness of the cup) is A50. Temperature range is 32° to 125°F (0° to 52°C).



			Vacuu	m Cups	- Small	Round			
Model		А	8	c	D	Ε	F	G	Cleats
900752	in	1.00	1.12	0.25	0.81	0.45	0.17	1/4	
900/52	mm	25	28	6	21	- 11	-4	FNPT	No
900753	in	1.50	0.90	0.28	1.25	1.06	0.12	1/4	Mari
	mm	38	23	7	32	27	3	FNPT	Yes
900754	in	2.00	1.00	0.25	1.56	1.31	0.18	1/4	Yes
900/54	mm	51	25	6	40	33	5	FNPT	res
	in	2.50	1.80	0.72	1.35	0.95	0.62	1/4	
900755	mm	64	46	18	34	24	16	FNPT	Yes
900756	in	3.50	1.10	0.56	0.98	0.51	0.37	1/4	***
	mm	89	28	14	25	13	9	FNPT	No



			Vacuu	m Cups	-Large	Round			
Model		Α	В	c	D	Ε	F	G	Cleats
	in	3.25	1.15	0.50	2.23	1.87	0.37	3/8	Yes
900757	mm	83	29	13	57	47	9	FNPT	res
900758	in	3.25	1.15	0.50	2.23	1.87	0.37	1/4	Yes
	mm	83	29	13	57	47	9	FNPT	res
	in	4.25	1.18	0.50	2.75	2.43	0.37	3/8	Yes
900759	mm	108	30	13	70	62	9	FNPT	
	in	5.00	1.75	1.12	3.25	2.65	0.62	3/8	Yes
900760	mm	127	44	28	83	67	16	FNPT	Yes
900761	in	6.00	1.31	0.50	4.75	4.90	0.12	1/2	-980.0
	mm	152	33	13	121	124	3	FNPT	Yes







			Va	cuum	Cups -	Bellov	vs.				
Model		A	В	С	D	E	F	G	н	Cleats	
900766	in	0.73	1.43	0.75	0.67	0.45	0.79	,	1/4	No	
900766	mm	19	36	19	17	11	20	3	FNPT	NO	
000747	in	1.00	1.48	0.85	0.56	0.44	0.85	4	1/8	100	
900767	mm	25	38	22	14	11	22	4	FNPT	No	
900768	in	1.50	1,12	0.71	1.06	1.00	0.31	4	1/4	Yes	
	mm	38	28	18	27	25	8	1	FNPT	162	
	in	2.00	1.54	0.89	1.00	1.17	0.68		1/4		
900769	mm	51	39	23	25	30	17	1	FNPT	Yes	
	in	2.50	2.40	1.75	1.00	1.12	1.80		1/4	***	
900770	mm	64	61	44	25	28	46	2	FNPT	No	
900771	in	3.25	3.00	2.20	1.00	1.53	2.00	12	3/8	- 01	
	mm	83	76	56	25	39	51	2	FNPT	No	









#### Increased Energy And Vacuum Efficiency

Energy and vacuum efficiency are not limited to the Adjustable E-Vac vacuum generators. All E-Vac styles and models can offer significant improvements when looking to reduce the amount of compressed air used for a specific vacuum application. Once the appropriate amount of vacuum and flow for the application are determined, it is important to select the appropriate model that will deliver the best performance while using the least amount of compressed air that it takes to do the job.

Many companies have a centralized vacuum system where the vacuum is generated at a location that is far away from the point of use. The long runs of piping through the plant produce line loss and it is often difficult to obtain that perfect balance of vacuum and flow required for an application. The compact, In-line E-Vac vacuum generators eliminate this problem since they can be mounted at the point where the vacuum source is needed. EXAIR's Application Engineers can help you to select the E-Vac vacuum generator and vacuum cups that provide the right amount of lifting capability while minimizing the amount of compressed air usage.

#### Other Applications For E-Vac

E-Vacs are used in many other "non-lifting" applications. They are commonly used for vessel evacuation, clamping, chucking, and other work holding applications. Many types of automated equipment use vacuum to evacuate, grip, hold, align and insert parts. These vacuums can be used for surface mounting, vacuum packaging, bag opening, label placement, carton forming and container evacuation.

Another popular application is using the E-Vac for liquid sampling. This process can easily be accomplished using an E-Vac vacuum generator attached to a liquid holding tube. When the tube is dipped into a vat, tank or container, the compressed air is turned on so it draws a specific volume of liquid up into the tube. When the compressed air is turned off, the liquid flows from the tube and can be dispensed into a container or machine to be analyzed.

#### **Accessories Needed To Build Your Vacuum System**

EXAIR offers a variety of mufflers, tubing, check valves, and fittings, shown on page 160, that make it easy to build a vacuum system best suited to your vacuum application.

When using E-Vac vacuum generators, it is important to use a source of clean, dry compressed air that will keep them operating at their peak performance. Automatic drain filter separators to keep the compressed air free of contaminants and moisture can be found on page 231. Oil removal filters that remove oil particulates that are common to many compressed air systems are also shown. Pressure regulators, shutoff valves, compressed air hose, and solenoid valves (to electrically turn the compressed air on and off) can be found on pages 231 through 236.

#### Mufflers

Optional silencing mufflers are available that permit maximum exhaust of the E-Vac unit so cycle speed is not reduced. The Standard Muffler (for use with In-Line E-Vacs only) has a closed end and is suitable for applications that are free of dust and debris. The Straight Through Muffler is recommended where particulates are present since it will not accumulate debris that can erode performance. Straight Through Mufflers offer the best sound level reduction (up to 26 dBA). Sound levels are shown on pages 152, 153 and 156.

#### · Fittings and Tubing


The vacuum port of the E-Vac has an NPT thread (a vacuum cup can be threaded directly into it). For vacuum cups that are remotely located, pushin connector fittings (most have global threads for use with NPT and BSP), or hose barb fittings can be installed on the E-Vac and the vacuum cup. Polyurethane vacuum tubing is available (10', 20', 30', 40' and 50' lengths) to connect them. For best performance, the length of the tubing should be minimized to achieve the best attach and release times.

#### · Check Valve

A vacuum check valve is available to hold the vacuum in case of compressed air loss. E-Vac vacuum generators that are used without a check valve will release the load if there is a significant drop in compressed air pressure or the supply of compressed air is lost.

#### E-Vac® Vacuum Generators





Mufflers



900802	Standard Muffler	1/2 MNPT
Straight T	hrough	
Model #	Description	Thread
890001	Straight Through	1/4 MNPS
890002	Straight Through	3/8 MNPS
890003	Straight Through	1/2 MNPS
890004	Straight Through	3/4 MNPS
890005	Straight Through	1 MNPS




Check Valves								
Model#	Description	Thread						
900804	Check Valve	1/4 FNPT						
900805	Check Valve	3/8 FNPT						
900806	Check Valve	1/2 FNPT						











E-	Vac Accessories - continued	
Push-In Bulk	head Connector	
Model #	Description	
900792	Female Union - 1/4 Tube x 1/4 Tube	
900793	Female Union - 3/8 Tube x 3/8 Tube	
900809	Female Union - 1/4 Tube x 1/4 NPT	
900810	Female Union - 3/8 Tube x 1/4 NPT	
Manager Table		



Tubing lengths are 10', 20', 30', 40', and 50'. Select the tubing model number (diameter) and indicate the length with a dash. Example: A Model 900795-20 is 1/4" tubing x

1/4" O.D. Polyurethane Tubing


_		
	•	ď
-	-	
	P	





Но





	Model#	Description
	901845-	1/4" I.D. Hose
ı	900689-	3/8" I.D. Hose
İ	900690-	1/2" I.D. Hose
Ī	900063-	3/4" I.D. Hose
ľ	900064-	1*LD Hose



	Vacuum Gauge	
Model#	Description	Thread
900811	Vacuum Gauge (-30" Hg/-1 BAR/-100 kPa-0)	1/8 MNPT

MNPT = NPT Male FNPT = NPT Female









MNPT = NPT Male FNPT = NPT Female







3/8 Tube x 3/8 Male Global Thread







## Line Vac



## Line Vac™

Convey parts, materials, waste - with no moving parts!

✓ High Conveying Rates!

✓ Ideal For Long Distance!



#### What Is The Line Vac?

A fast, low cost way to convey:

- Plastic pellets Paper
- Scrap trim · Pills/tablets Textiles · Small parts
- Bulk solids Shavings Food products Sawdust
- Chips Granules





EXAIR's compressed air operated Line Vac connects to standard hose or tube to create a powerful in-line conveyor. The compact design features large throat diameters for maximum throughput capability. Eleven sizes in aluminum and ten in stainless steel are suited to a wide variety of transfer applications.

#### Why The Line Vac?

Line Vac conveyors are ideal for moving large volumes of material over long distances. A small amount of compressed air is injected through directed nozzles to produce a vacuum on one end and high output flows on the other, with instantaneous response. The material flow rate is easily controlled with a pressure regulator. An optional bracket permits easy mounting. No moving parts or electricity assures maintenance free operation.



#### **Applications**

- Hopper loading
- · Fiber tensioning
- Material conveying
- · Waste/trim removal
- · Chip removal
- · Part transfer
- · Filling operations

## Advantages

- Compact
- Quiet
- No moving parts
- · Fits standard hose or tube
- · Aluminum or stainless steel
- · Eleven sizes
- · High throughput capability



A Model 6084 2" (51mm) Line Vac transports scrap cellophane trim to a waste barrel.




The Model 6083 1-1/2" (38mm) Line Vac conveys plastic granules to the gravity feed hopper on an extruder.



#### Line Vac

#### How The Line Vac Works



Compressed air flows through the inlet (1) into an annular plenum chamber (2). It is then injected into the throat through directed nozzles (3). These jets of air create a vacuum at the intake (4) which draws material in and accelerates it through the unit (5) for conveying over long vertical or horizontal distances.




Line Vacs are available in many sizes in both aluminum and stainless steel.

#### **Line Vac Conveying Rates**

Line Vacs are available in a number of styles, materials, and sizes. Each has a large, smooth, straight bore that allows as much material to pass through as possible. Infinite control of the flow rate through the Line Vac can be controlled by a pressure regulator. Kits include a pressure regulator that is sized properly for flow.

The actual conveying rate is affected by the size, mass and geometry of the part to be conveyed along with the length, lift and number of bends in the hose, tube or pipe. These variables make it difficult to determine the exact conveying rate for any product, however, our Application Engineers can assist you by comparing the material you want to convey with something that has already been tested.



						Lin	e Vac	Dime	nsion										
	Line Vac Models		Hose	Size		23	1000	745	1	100	Service	100		To the second	60	0.000	100	0.00	220
Alum.	St. St.	Heavy Duty	CITAL SE	A	В	C	D	E	F	G	н	-1	J	K	L	M	N	0	P
6078	6058,	N/A	in	0.38	0.19	1	2.18	1	0.63	1.25	0.63	0.41	0.82	0.17	1.13	0.06	1.07	0.18	1/
6078	6058-316	N/A	mm	10	5	25	55	25	16	32	16	10	21	4	29	2	27	5	NP
	6059.		in	0.50	0.31	1.25	2.62	1.23	0.75	1.25	0.63	0.34	0.68	0.13	1	0.06	1.18	0.18	1/
6079	6059-316	N/A	mm	13	8	32	66	31	19	32	16	9	17	3	25	2	30	5	NP.
Zhendrien -	6060, 6060-316,		in	0.75	0.50	1.88	3.88	1.88	1	2	1	0.76	1.52	0.25	1.38	0.06	1.44	0.20	1/
6080	HT6060, HT6060-316	150075	mm	19	13	48	99	48	25	51	25	19	39	6	35	2	37	5	NP
on-et-	6061, 6061-316.	000000000	in	1	0.75	2.13	3.88	1.88	1	2	1	0.65	1.30	0.26	1.32	0.06	1.56	0.20	0.20 <sub>1/4</sub> <sub>5</sub> NPT
6081	HT6061, HT6061-316		mm	25	19	54	99	48	25	51	25	17	33	7	34	2	40	5	
6062, 6062-316,		in	1.25	1	2.38	3.88	1.88	1	2.50	1.25	1	2	0.31	1.61	0.06	1.68	0.28	1/	
6082	HT6062, HT6062-316	150125	mm	32	25	61	99	48	25	64	32	25	51	8	41	2	43	7	N
6063, 6063-316,		in	1.50	1.25	2.75	4.38	2.13	1.25	2.50	1.25	0.86	1.73	0.25	1.44	0.06	1.88	0.28	3/	
6083	HT6063, HT6063-316	150150	mm	38	32	70	111	54	32	64	32	22	44	6	37	2	48	7	N
na tanana i	6064, 6064-316,	Constitution (1)	in	2	1.75	3.25	4.38	2.13	1.25	3	1.50	1.17	2.34	0.28	1.48	0.06	2.13	0.28	3/8
6084	HT6064, HT6064-316	150200	mm	51	45	83	111	54	32	76	38	30	59	7	38	2	54	7	N
A-SVEG S	6065, 6065-316,	- Vyestation	in	2.50	2.25	3.75	4.38	2.13	1.25	3	1.50	1	2	0.31	1,44	0.06	2.38	0.28	3/
6085	HT6065, HT6065-316	150250	mm	64	57	95	111	54	32	76	38	25	51	8	37	2	60	7	N
	6066, 6066-316,	80008	in	3	2.75	4.25	5.63	2.75	1.75	3.25	1.63	1.20	2.41	0.41	1.44	0.06	2.63	0.28	1/
6086	HT6066, HT6066-316	150300	mm	76	70	108	143	70	45	83	41	31	61	10	37	2	67	7	N
			in	4	3.75	5.25	5.63	2.75	1.75	3.25	1.63	1.34	2.70	0.31	1.59	0.06	3.13	0.28	1
6087	6067	N/A	mm	102	95	133	143	70	45	83	41	34	69	8	40	2	80	7	N
			in	5	4.75	6.25	5.63	2.75	1,75	4.13	2.06	1,70	3.47	0.33	1.52	0.06	3.63	0.28	1/
6088	N/A	N/A	mm	127	121	159	143	70	45	105	52	43	88	8	39	2	92	7	NE







#### Line Vac

#### **Line Vac Performance**

		ir mption	Vacuum		
Model	SCFM	SLPM	"H <sub>2</sub> 0	kPa	
6058, 6058-316, 6078	5.60	158	-120	-29.9	
6059, 6059-316, 6079	7	198	-100	-24.9	
6060, HT6060, 6060-316, HT6060-316, 6080	10.70	303	-72	-18	
6061, HT6061, 6061-316, HT6061-316, 6081	14.70	416	-42	-11	
6062, HT6062, 6062-316, HT6062-316, 6082	25.90	733	-42	-11	
6063, HT6063, 6063-316, HT6063-316, 6083	33	934	-36.8	-9	
6064, HT6064, 6064-316, HT6064-316, 6084	45	1,274	-28.5	-7	
6065, 6065-316, HT6065, HT6065-316, 6085	58.50	1,656	-23.5	-6	
6066, 6066-316, HT6066, HT6066-316, 6086	68.50	1,939	-14.7	-4	
6067, 6087	95	2,690	-13.6	-3.4	
6088	128	3,625	-10.5	-2.6	



Line Vac Kits include a Line Vac, mounting bracket, filter separator and pressure regulator (with coupler).

Sound levels for the individual Line Vac units are not provided. The length, bends and configuration of the hose, tube or pipe used in conjunction with the Line Vac to form the complete conveying system will determine the actual sound levels (which can vary greatly).

#### Selecting The Right Model

Line Vac is available in a wide range of sizes to fit your application. Some of the criteria used to select the proper model are:

- · Diameter of parts being conveyed
- · Diameter of hose or tube
- · Rate (weight or volume)
- · Stainless steel (Type 303 and 316) or aluminum

Aluminum is the economical choice for general purpose conveying. Our standard stainless steel models (Type 303) offer good corrosion resistance and are ideal for food service, abrasive or corrosive applications. For critical applications including certain foods and pharmaceutical products, Type 316 stainless steel models provide excellent corrosion resistance.



A 316 Stainless Steel Line Vac is used by a pharmaceutical company to convey pills and tablets to a packaging station.



The High Temperature Line Vac models are suited for temperatures up to 900°F (482°C). Frequently used for sampling hot flue gases, this High Temperature Line Vac can resist back pressure from long pipe lengths with numerous bends. The Heavy Duty Line Vac shown on page 170 moves the highest volumes and resists wear.



High Temperature Line Vacs can resist temperatures to 900°F (482°C) and are available from stock in hose or threaded models.

For assistance with product selection, contact an Application Engineer at 1-800-903-9247.







#### Line Vac

#### Clear PVC Hose

EXAIR stocks 3/8" (10mm), 1/2" (13mm), 3/4" (19mm), 1" (25mm), 1-1/4" (32mm), 1-1/2" (38mm), 2" (51mm), 2-1/2" (64mm) and 3" (76mm) I.D. PVC hose in lengths up to 50' (15.2m). Ideal for conveying applications, the hose is very flexible and has a smooth internal bore that eliminates material build up. The reinforced, heavy wall of this clear hose provides visual confirmation that the material is moving when air is supplied to the Line Vac. Temperature rating is -4 to 150°F (-20 to 66°C).



#### **Special Line Vacs**

EXAIR manufactures special Line Vacs suited to specific application requirements. Configurations and materials can be made to facilitate your requirements.

The Line Vac can be engineered to retrofit existing machinery. The Line Vac (shown below) has special flanges that permit direct mounting to a machine used in the manufacturing of silicon wafers for the semiconductor industry.



A special 3/4" (19mm) Stainless Steel Line Vac evacuates fumes from a silicon wafer etching operation.

This flanged Line Vac is used to remove acidic vapors resulting from surface etching of a silicon wafer. Ordinarily, EXAIR's Stainless Steel Air Amplifier would have been used since it moves much higher volumes of air. In this case, the Line Vac was the better choice since the exhaust piping was long with many bends that would have created high back pressure. The directed nozzles of the Line Vac overcame this downstream resistance.




This special 1-1/2" (38mm) Line Vac is made of PVDF to withstand a chloride washdown.

The special flanged Line Vac (shown above) is made of PVDF, a plastic that has high chemical resistance. In this case, the 1-1/2" (38mm) Line Vac was regularly exposed to a chloride wash, a chemical that would corrode stainless steel. OF flanges were provided on each end to allow easy removal of the conveying hoses for cleaning purposes.



This special Line Vac is used to fill small packets.

Filling small packets with fine powders or granulated materials such as salt or barite is done using



small tubes that are gravity fed from a hopper. This works well when the material is dry, however, moist materials would often pack the tube, blocking the flow. The special funnel shaped Line Vac (shown bottom center) created a suction on the existing tube to permit continuous product flow.



A special miniature Line Vac used to vacuum microscopic debris measures the same size as a penny!

The special miniature Line Vac with barb fittings (shown above) was designed for a manufacturer of integrated circuit chips. It was used to remove microscopic debris during the chip making process. This small Line Vac generated high vacuum and was the perfect configuration for the confined working space. It has also been used by another manufacturer to vacuum liquid and chips from small drilled holes.








#### Refilling A Vibratory Bowl


The Problem: A manufacturer of metal products deburrs aluminum sleeves in a vibratory bowl filled with abrasive media. As the parts complete the deburring cycle, they are discharged to a screened bed. The abrasive media drops through the bed and the finished parts roll into a box. Refilling the bowl was a back breaking operation that required repetitious lifting of heavy buckets.

The Solution: A Model 6064 2" (51mm) Stainless Steel Line Vac was installed on the vibratory bowl. In minutes. the media was conveyed back up to the bowl through a hose, without the heavy lifting.



Comment: The ability to convey the abrasive media with air was the key to success. The Line Vac is easy to use, and in this case, was the best choice since it will hold up better to the abrasive media conveyed through it.

#### **Conveying Plastic Pellets**



The Problem: Injection molding machines transform plastic pellets into various plastic products. The pellets are gravity fed from a hopper on top of the machine. The "bucket and ladder" method of replenishing the hopper was inefficient and expensive.

The Solution: A Model 6982 1-1/4" (32mm) Line Vac Kit was used to convey the pellets up to the hopper. The mounting bracket included with the kit was used to secure the Line Vac to the machine. A filter assured no contamination of the plastic material and a regulator controlled the plastic flow rate.

Comment: Unlike mechanical transfer systems that break down or wear out, the Line Vac has no moving parts. This low cost method of conveying also gives precise control of material flow into the hopper.

#### Line Vac for Matrix Removal from **Labeling Application**

The Problem: A manufacturer applies labels to their products. After they have been applied, there is a waste stream that is referred to as "the matrix". The matrix is the release liner that labels are affixed to in bulk format prior to being used. The normal method for taking up this waste stream was to use a winder. However, after some amount of time, the winder inevitably becomes filled. Once full, the line is stopped and the winder is manually emptied. They needed a better way to dispose of the matrix.

The Solution: The Line Vac presents a unique advantage in that it can pull the matrix from the machine and convey it out to a waste receptacle. This requires no winder, no stopping the line and no emptying. This solution freed up personnel for other tasks and increased production. The compact design and powerful operation of the Line Vac allowed it to be placed close to the generation of scrap,

trim, or waste. Its powerful conveying capacity allowed it to transport the material to a remote and central location.

Comment: This application illustrates the versatility of the Line Vac product line. Commonly used for hopper loading products in the plastics industry, a Line Vac is also a strong performer for applications like waste/

trim removal, assembly parts conveyance, blasting media recovery, gas sampling and chip removal. Its large variety of materials and sizes makes it well suited for industrial. pharmaceutical, laboratory, high temperature and corrosive environments. No moving parts or electricity assures maintenance free operation.



1" (25mm) Line Vacs remove and discard a label matrix.

#### Line Vac

		Line Va	c Only Model		
Inlet/Outlet Diameter	Aluminum Line Vac Model	Type 303 Stainless Steel Line Vac Model	Type 316 Stainless Steel Line Vac Model	High Temperature Type 303 Stainless Steel Line Vac Model	High Temperature Type 316 Stainless Steel Line Vac Model
3/8" (10mm)	6078	6058	6058-316	N/A	N/A
1/2" (13mm)	6079	6059	6059-316	N/A	N/A
3/4" (19mm)	6080	6060	6060-316	HT6060	HT6060-316
1" (25mm)	6081	6061	6061-316	HT6061	HT6061-316
1-1/4" (32mm)	6082	6062	6062-316	HT6062	HT6062-316
1-1/2" (38mm)	6083	6063	6063-316	HT6063	HT6063-316
2" (51mm)	6084	6064	6064-316	HT6064	HT6064-316
2-1/2" (64mm)	6085	6065	6065-316	HT6065	HT6065-316
3" (76mm)	6086	6066	6066-316	HT6066	HT6066-316
4" (102mm)	6087	6067	N/A	N/A	N/A
5" (127mm)	6088	N/A	N/A	N/A	N/A

		Line V	ac Kit Models		
Line Vac Kits - in	nclude the Line \	/ac, mounting brac	ket, filter separator	and pressure regulat	or (with coupler).
Inlet/Outlet Diameter	Aluminum Line Vac Kit Model	Type 303 Stainless Steel Line Vac Kit Model	Type 316 Stainless Steel Line Vac Kit Model	High Temperature Type 303 Stainless Steel Line Vac Kit Model	High Temperature Type 316 Stainless Steel Line Vac Kit Model
3/8" (10mm)	6978	6958	6958-316	N/A	N/A
1/2" (13mm)	6979	6959	6959-316	N/A	N/A
3/4" (19mm)	6980	6960	6960-316	HT6960	HT6960-316
1" (25mm)	6981	6961	6961-316	HT6961	HT6961-316
1-1/4" (32mm)	6982	6962	6962-316	HT6962	HT6962-316
1-1/2" (38mm)	6983	6963	6963-316	HT6963	HT6963-316
2" (51mm)	6984	6964	6964-316	HT6964	HT6964-316
2-1/2" (64mm)	6985	6965	6965-316	HT6965	HT6965-316
3" (76mm)	6986	6966	6966-316	HT6966	HT6966-316
4" (102mm)	6987	6967	N/A	N/A	N/A
5" (127mm)	6988	N/A	N/A	N/A	N/A

Model #	Description
6994	Mounting Bracket for 3/8" (10mm) and 1/2" (13mm) Line Vac Units
6995	Mounting Bracket for 3/4" (19mm) and 1" (25mm) Line Vac Units
6996	Mounting Bracket for 1-1/4" (32mm) and 1-1/2" (38mm) Line Vac Units
6997	Mounting Bracket for 2" (51mm) and 2-1/2" (64mm) Line Vac Units
6998	Mounting Bracket for 3" (76mm) and 4" (102mm) Line Vac Units
6999	Mounting Bracket for 5" (127mm) Line Vac Unit
9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)
9032	Auto Drain Filter Separator, 1/2 NPT, 90 SCFM (2,549 SLPM)
9002	Auto Drain Filter Separator, 3/4 NPT, 220 SCFM (6,230 SLPM)
9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)
9006	Oil Removal Filter, 3/4 NPT, 50-150 SCFM (1,416-4,248 SLPM)
9008	Pressure Regulator with Gauge, 1/4 NPT, 50 SCFM (1,416 SLPM)
9033	Pressure Regulator with Gauge, 1/2 NPT, 100 SCFM (2,832 SLPM)
9009	Pressure Regulator with Gauge, 3/4 NPT, 220 SCFM (6,230 SLPM)
Select the ho indicate the l	able in 10', 20', 30', 40' and 50' lengths. se model number (diameter) and ength with a dash. Example: A Model D Hose x 20' long.
6928-	Hose 3/8" ID
6929-	Hose 1/2" ID
6930-	Hose 3/4" ID
6931-	Hose 1" ID
6932-	Hose 1-1/4* ID
6933-	Hose 1-1/2" ID
6934-	Hose 2* ID
6935-	Hose 2-1/2" ID
6936-	Hose 3" ID

Accessories







1-1/4" (32mm) Line Vac is mounted on a burr removal tool to suction the plastic shavings and transport them to a













# Threaded Line Vac

EXCUR EXCUR

PRODUCT YEAR



## Threaded Line Vac™

## Low cost conveyor uses ordinary pipe!

## Ideal for long distance conveying!

#### What Is The Threaded Line Vac?

A fast, low cost way to convey:

- · Plastic pellets
- Paper
- Scrap trim Textiles

- · Small parts
- · Bulk solids
- Shavings

· Chips

 Sawdust Granules

EXAIR's Threaded Line Vac air operated conveyors convert ordinary pipe into a powerful conveying system for parts, scrap, trim and other bulk materials. The Threaded Line Vac attaches easily to plumbing pipe couplers, making it easy to build a complete system using ordinary pipe and fittings available from any home center, hardware store or plumbers supply. Performance is the same as our standard Line Vac shown on page 161.

Threaded Line Vac conveyors are ideal for conveying large volumes of material over long distances. They eject a small amount of compressed air to produce a vacuum on one end with high output flows on the other. Response is instantaneous. Regulating the compressed air pressure provides infinite control of the conveying rate. Models from 3/8 NPT to 3 NPT are available in aluminum and stainless steel, which are suited to a wide variety of conveying applications. An optional mounting bracket permits easy mounting. No moving parts or electricity assures maintenance free operation.

#### **Applications**

- Hopper loading
- · Fiber tensioning
- · Material conveying
- · Waste/trim removal
- · Chip removal Part transfer
- · Filling operations

EXAIR

#### **Advantages**

- Compact
- Quiet
- No moving parts
- · Fits standard pipe
- · Aluminum or stainless steel
- · Available from stock
- · High throughput capability



A drawer slide manufacturer conveys

ball bearings with the Model 141125

1-1/4 NPT Stainless Steel Threaded Line Vac to an assembly station.


Plastic color concentrate pellets are

added to a plastic extrusion process.

A special Threaded Line Vac has a smooth diameter for hose on the intake and threads on the exhaust that attach to PVC pipe.

#### Threaded Line Vac

# **Dimensions**



#### **Threaded Line Vac Performance**

80 PSIG (5.5 BAR)	Air Cons	umption	Vac	uum
Model	SCFM	SLPM	"H <sub>2</sub> 0	kPa
140038, 141038, 141038-316	5.60	158	-120	-29.9
140050, 141050, 141050-316	7	198	-100	-24.9
140075, 141075, 141075-316, HT141075, HT141075-316	10.70	303	-72	-18
140100, 141100, 141100-316, HT141100, HT141100-316	14.70	416	-42	-11
140125, 141125, 141125-316, HT141125, HT141125-316	25.90	733	-42	-11
140150, 141150, 141150-316, HT141150, HT141150-316	33	934	-36.8	-9
140200, 141200, 141200-316, HT141200, HT141200-316	45	1,274	-28.5	-7
140250, 141250, 141250-316, HT141250, HT141250-316	58.50	1,656	-23.5	-6
140300, 141300, 141300-316, HT141300, HT141300-316	68.50	1,939	-14.7	-4


							hread	ed Lin	e Vac	Dime	nsion									
- 4	Line Vac Mod	els	A		.20	2000	1525	25	SERVICE.	4000	W OW	100001	200	100	0.05	0	0000	2007	200	. Secre
Alum.	303 St. St.	316 St. St.	Pipe:	Size	В	c	D	E	F1	F2	G	н	1	1	К	L	М	N	0	P
002222	1200000	**********	3/8	in	0.19	1.00	2.83	1.13	1.23	0.72	1.25	0.63	0.41	0.82	0.17	1.13	0.06	1.07	0.18	1/8
140038	141038	141038-316	NPT	mm	5	25	72	29	31	18	32	16	10	21	4	29	2	27	5	NP
			1/2	in	0.31	1.25	3.38	1.38	1.31	0.88	1.25	0.63	0.34	0.68	0.13	1.00	0.06	1.18	0.18	1/8
140050	141050	141050-316	NPT	mm	8	32	86	35	33	22	32	16	9	17	3	25	2	30	5	NP
140075	141075	******	3/4	in	0.50	1.88	3.88	1.88	1	1	2	1	0.76	1.52	0.25	1.38	0.06	1.44	0.20	1/4
1400/5	1410/5	141075-316	NPT	mm	13	48	99	48	25	25	51	25	19	39	6	35	2	37	5	NP
140100	141100	141100-316	1	in	0.75	2.13	4.25	2.06	1.19	1.19	2	1	0.65	1.30	0.25	1.32	0.06	1.56	0.20	1/4
140100	141100	141100-316	NPT	mm	19	54	108	52	30	30	51	25	17	33	6	34	2	40	5	NP
140125	141125	141125-316	1-1/4	in	1	2.38	4.63	2.25	1.38	1.38	2.50	1.25	1	2	0.31	1.61	0.06	1.68	0.28	1/4
140125	141123	141123-310	NPT	mm	25	60	118	57	35	35	64	32	25	51	8	41	2	43	7	NP
140150	141150	141150-316	1-1/2	in	1.25	2.75	4.63	2.25	1.38	1.38	2.50	1.25	0.86	1.73	0.25	1.44	0.06	1.88	0.28	3/8
140150	141150	141150-316	NPT	mm	32	70	118	57	35	35	64	32	22	44	6	37	2	48	7	NP
140200	141200	141200-316	2	in	1.75	3.25	4.63	2.25	1.38	1.38	3	1.50	1.17	2.34	0.28	1.48	0.06	2.13	0.28	3/8
140200	141200	141200-310	NPT	mm	44	83	118	57	35	35	76	38	30	59	7	38	2	54	7	NP
140250	141250	141350 316	2-1/2	in	2.25	3.75	5.38	2.56	1.81	1.69	3	1.50	1	2	0.31	1.44	0.06	2.38	0.28	3/8
140250	141250	141250-316	NPT	mm	57	95	137	65	46	43	76	38	25	51	8	37	2	60	7	NP.
140300	141300	141300-316	3 NPT	in	2.75	4.25	5.67	2.75	1.81	1.75	3.25	1.63	1.20	2.41	0.41	1,44	0.06	2.63	0.28	1/2
140300	141300	141300-316	2 WAL	mm	70	108	144	70	46	45	83	41	31	61	10	37	2	67	7	NP

						Thr	eade	d Line	Vac I	Dimer	sions									
	Line Vac Mo	dels	,		0.0		1,540.00		,,,,,,,,	VC.754-	65554	201		2940	1,050040	155	or-state	201	100	- 12
Heavy Duty	High Temp 303 SS	High Temp 316 SS		Size	В	c	D	E	F1	F2	G	н	-1	J	К	L	М	N	0	P
151075	HT141075	HT141075-316	3/4	in	0.50	1.88	3.88	1.88	1	1	2	1	0.76	1.52	0.25	1.38	0.06	1.44	0.20	1/
1510/5	H11410/5	H11410/3-316	NPT	mm	13	48	99	48	25	25	51	25	19	39	6	35	2	37	5	NP
151100	HT141100	HT141100-316	1	in	0.75	2.13	4.25	2.06	1.19	1.19	2	1	0.65	1.30	0.25	1.32	0.06	1.56	0.20	1/
151100	H1141100	H1141100-316	NPT	mm	19	54	108	52	30	30	51	25	17	33	6	34	2	40	5	NF
	1174 44400		1-1/4	in	1	2.38	4.63	2.25	1.38	1.38	2.50	1.25	1	2	0.31	1.61	0.06	1.68	0.28	1/
151125	HT141125	HT141125-316	NPT	mm	25	60	118	57	35	35	64	32	25	51	8	41	2	43	7	NP
			1-1/2	in	1.25	2.75	4.63	2.25	1.38	1.38	2.50	1.25	0.86	1.73	0.25	1.44	0.06	1.88	0.28	3/1
151150	HT141150	HT141150-316	NPT	mm	32	70	118	57	35	35	64	32	22	44	6	37	2	48	7	NF
			2	in	1.75	3.25	4.63	2.25	1.38	1.38	3	1.50	1.17	2.34	0.28	1,48	0.06	2.13	0.28	3/
151200	HT141200	HT141200-316	NPT	mm	44	83	118	57	35	35	76	38	30	59	7	38	2	54	7	NF
	/ same and a same a		2-1/2	in	2.25	3.75	5.38	2.56	1.81	1.69	3	1.50	1	2	0.31	1.44	0.06	2.38	0.28	3/
151250	HT141250	HT141250-316	NPT	mm	57	95	137	65	46	43	76	38	25	51	8	37	2	60	7	NF
			2 1/27	in	2.75	4.25	5.67	2.75	1.81	1.75	3.25	1.63	1.20	2.41	0.41	1.44	0.06	2.63	0.28	1/
151300	HT141300	HT141300-316	3 NPT	mm	70	108	144	70	46	45	83	41	31	61	10	37	2	67	7	NP









#### Threaded Line Vac

		Thre	aded Line Vac Models		
hreaded Line Va	c Only				
Inlet/Outlet Thread Size	Aluminum Threaded Line Vac Only Model	Type 303 Stainless Steel Threaded Line Vac Only Model	High Temperature Type 303 Stainless Steel Threaded Line Vac Only Model	Type 316 Stainless Steel Threaded Line Vac Only Model	High Temperature Type 316 Stainless Steel Threaded Line Vac Only Model
3/8 NPT	140038	141038	N/A	141038-316	N/A
1/2 NPT	140050	141050	N/A	141050-316	N/A
3/4 NPT	140075	141075	HT141075	141075-316	HT141075-316
1 NPT	140100	141100	HT141100	141100-316	HT141100-316
1-1/4 NPT	140125	141125	HT141125	141125-316	HT141125-316
1-1/2 NPT	140150	141150	HT141150	141150-316	HT141150-316
2 NPT	140200	141200	HT141200	141200-316	HT141200-316
2-1/2 NPT	140250	141250	HT141250	141250-316	HT141250-316
3 NPT	140300	141300	HT141300	141300-316	HT141300-316

#### Threaded Line Vac Kit Models

Threaded Line Vac Kits - include the Line Vac, mounting bracket, filter separator and pressure regulator (with coupler)

nlet/Outlet Thread Size	Aluminum Threaded Line Vac Kit Model	Type 303 Stainless Steel Threaded Line Vac Kit Model	High Temperature Type 303 Stainless Steel Threaded Line Vac Kit Model	Type 316 Stainless Steel Threaded Line Vac Kit Model	High Temperature Type 316 Stainless Steel Threaded Line Vac Kit Model
3/8 NPT	142038	143038	N/A	143038-316	N/A
1/2 NPT	142050	143050	N/A	143050-316	N/A
3/4 NPT	142075	143075	HT143075	143075-316	HT143075-316
1 NPT	142100	143100	HT143100	143100-316	HT143100-316
1-1/4 NPT	142125	143125	HT143125	143125-316	HT143125-316
1-1/2 NPT	142150	143150	HT143150	143150-316	HT143150-316
2 NPT	142200	143200	HT143200	143200-316	HT143200-316
2-1/2 NPT	142250	143250	HT143250	143250-316	HT143250-316
3 NPT	142300	143300	HT143300	143300-316	HT143300-316

	Accessories
Model #	Description
6994	Mounting Bracket for 3/8 NPT and 1/2 NPT Threaded Line Vac Units
6995	Mounting Bracket for 3/4 NPT and 1 NPT Threaded Line Vac Units
6996	Mounting Bracket for 1-1/4 NPT and 1-1/2 NPT Threaded Line Vac Units
6997	Mounting Bracket for 2 NPT and 2-1/2 NPT Threaded Line Vac Units
6998	Mounting Bracket for 3 NPT Line Vac Units
9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)
9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)
9008	Pressure Regulator with Gauge, 1/4 NPT, 50 SCFM (1,416 SLPM)

EXAIR



Threaded Line Vac Kits include the Threaded Line Vac, mounting bracket, filter separator and pressure regulator (with coupler).

## 11510 Goldcoast Drive • Cincinnati, OH 45249-1621 • Phone (513) 671-3322



An INTELLIGENT COMPRESSED AIR Product

# **Heavy Duty Line Vac™**

**Heavy Duty Line Vac** 

## Our most powerful Line Vac moves high volumes of material and resists wear!



#### What Is The Heavy Duty Line Vac?

The Heavy Duty Line Vac is EXAIR's most powerful conveyor. The appearance is similar to the standard Line Vac but performance has been boosted dramatically. The Heavy Duty Line Vac has been engineered to convey materials over longer vertical and horizontal distances. The hardened alloy construction helps prevent premature wear that could occur with ordinary aluminum or stainless steel Line Vacs.

#### Why The Heavy Duty Line Vac?

Many applications require that materials be transported over longer distances. The Heavy Duty Line Vac can move more material over longer lengths. They have been designed for rugged, industrial applications.

The table below gives a quick comparison of our Light Duty Line Vac, standard Line Vac, and the Heavy Duty Line Vac models. For comparison, the test shows the 2" (51mm) model of each style conveying the same material over various lengths. Heavy Duty Line Vac conveys more material in less time.

	Rock Salt Conveying	ng Rate Comparisor
	100 Feet (30.5m)	200 Feet (61m)
Model 130200 2" (51mm) Light Duty Line Vac	166 lbs/hr. (75.3 kg/hr.)	N/A
Model 6084 2" (51mm) Line Vac	334 lbs/hr. (151.5 kg/hr.)	85 lbs/hr. (38.6 kg/hr.)
Model 150200 2" (51mm) Heavy Duty Line Vac	524 lbs/hr. (237.7 kg/hr.)	200 lbs/hr. (90.7 kg/hr.)
to the section of the		

## **Applications**

- Hopper loading
- · Fiber tensioning
- · Material conveying
- · Waste/trim removal
- · Chip removal
- · Part transfer
- Filling operations

#### Advantages

- · Hardened alloy construction
- · Highest throughput capability
- Compact
- Quiet
- No moving parts
- · Fits standard hose, tube and pipe
- · Available from stock










The hardened alloy construction of the Heavy Duty Threaded Line Vac resists wear when conveying abrasive steel shot.



Metal parts are conveyed with the Model 150200 2" (51mm) Heavy Duty Line Vac as they drop off the edge of the conveyor.









## **Heavy Duty Line Vac**



#### **Heavy Duty Threaded Line Vac**

EXAIR's Heavy Duty Threaded Line Vac air operated conveyors convert ordinary pipe into a powerful conveying system for parts, scrap, trim and other bulk materials. The engineered Heavy Duty Threaded Line Vac attaches easily to ordinary NPT pipe and fittings available from any home center, hardware store or plumbers supply. With its hardened alloy construction, the Heavy Duty Threaded Line Vac withstands premature wear which could occur with aluminum and stainless steel.

## **Heavy Duty Line Vac Performance**

80 PSIG (5.5 BAR)				ir mption	Vacuum		
Model	in	mm	SCFM	SLPM	"H <sub>2</sub> 0	kPa	
150075, 151075	0.75	19	26	736	-144	-36	
150100, 151100	1	25	35	991	-105	-26	
150125, 151125	1.25	32	49	1,388	-83	-21	
150150, 151150	1.50	38	55	1,557	-60	-15	
150200, 151200	2	51	75	2,124	-42	-10	
150250, 151250	2.50	64	90	2,548	-28	-7	
150300, 151300	3	76	108	3,058	-20	-5	



#### **Dimensions**

For Heavy Duty Line Vac Dimensio	ns, see:
Line Vac	pg 162
Threaded Line Vac	pa 168

		<b>Heavy Duty Li</b>	ne Vac Models		
Heavy Duty Line Heavy Duty Line (with coupler).	Vac Only Vac Kits - include t	he Line Vac, mount	ing bracket, filter se	parator and pressu	re regulator
Inlet/Outlet	Heavy Duty	Heavy Duty	Inlet/Outlet	Heavy Duty Threaded	Heavy Duty Threaded

Inlet/Outlet Diameter	Heavy Duty Line Vac Only Model	Heavy Duty Line Vac Kit Model	Inlet/Outlet Thread Size	Heavy Duty Threaded Line Vac Only Model	Heavy Duty Threaded Line Vac Kit Model
3/4" (19mm)	150075	152075	3/4 NPT	151075	153075
1" (25mm)	150100	152100	1 NPT	151100	153100
1-1/4" (32mm)	150125	152125	1-1/4 NPT	151125	153125
1-1/2" (38mm)	150150	152150	1-1/2 NPT	151150	153150
2" (51mm)	150200	152200	2 NPT	151200	153200
2-1/2" (64mm)	150250	152250	2-1/2 NPT	151250	153250
3" (76mm)	150300	152300	3 NPT	151300	153300





Heavy Duty Line Vac Kits include a Heavy Duty Line Vac, mounting bracket, filter separator and pressure regulator (with coupler).

	Accessories
Model #	Description
6995	Mounting Bracket for 3/4" (19mm) and 1" (25mm) Line Vac Units
6996	Mounting Bracket for 1-1/4" (32mm) and 1-1/2" (38mm) Line Vac Units
6997	Mounting Bracket for 2" (51mm) and 2-1/2" (64mm) Line Vac Units
6998	Mounting Bracket for 3" (76mm) Line Vac Units
9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)
9032	Auto Drain Filter Separator, 1/2 NPT, 90 SCFM (2,549 SLPM)
9002	Auto Drain Filter Separator, 3/4 NPT, 220 SCFM (6,230 SLPM)
9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)
9006	Oil Removal Filter, 3/4 NPT, 50-150 SCFM (1,416-4,248 SLPM)
9008	Pressure Regulator with Gauge, 1/4 NPT, 50 SCFM (1,416 SLPM)
9033	Pressure Regulator with Gauge, 1/2 NPT, 100 SCFM (2,832 SLPM)
9009	Pressure Regulator with Gauge, 3/4 NPT, 220 SCFM (6,230 SLPM)

	e is available in 10', 20', 30', 40' and 50' ths. Select the hose model number
(dia	meter) and indicate the length with a das

6930-	Hose 3/4 ID
6931-	Hose 1° ID
6932-	Hose 1-1/4" ID
6933-	Hose 1-1/2" ID
6934-	Hose 2* ID
6935-	Hose 2-1/2" ID
6936-	Hose 3" ID

If you have special requirements, please contact an Application Engineer to discuss the application.



(51mm) Heavy Duty Line Vac.











# **Sanitary Flange** Line Vac™

An INTELLIGENT OMPRESSED AIR Product

Convey materials, parts, waste - with easy disassembly and cleanup!



#### What Is The Sanitary Flange Line Vac?

EXAIR's Sanitary Flange Line Vac is the best way to convey materials in systems which require frequent or mandatory cleaning. The Sanitary Flange Line Vac fits within your current sanitary flange piping system and converts it into a conveyor for waste, parts and bulk materials.

#### Why The Sanitary Flange Line Vac?

When your piping system requires sanitary flanges, which make it easy to dismantle and clean its components, the Sanitary Flange Line Vac will suit your needs. They are made from Type 316SS to provide superior corrosion resistance and cleanliness. These flanged Line Vacs limit entrapment areas where bacteria can grow and the clamp style sanitary flanges are compatible with ISO 2852. Sanitary Flange Line Vacs are designed with the same performance characteristics of EXAIR's standard and

Threaded Line Vacs which makes them a versatile solution for your conveying needs. Conveying rates are easy to control by regulating the compressed air supply pressure.

The Sanitary Flange Line Vacs are available from stock in four common flange sizes, 1-1/2" (38mm), 2" (51mm), 2-1/2" (64mm) and 3" (76mm). All metal parts are made from Type 316SS. No moving parts or electricity assures maintenance free operation.

#### Sanitary Flange Line Vac Performance

80 PSIG (5.5 BAR)	) Size Air Consumption			Vacuum		
Model	in	mm	SCFM	SLPM	"H <sub>2</sub> 0	kPa
161150-316	1.5	38	33	934	-36.8	-9
161200-316	2	51	45	1,274	-28.5	-7
161250-316	2.5	64	58.5	1,657	-23.5	-6
161300-316	3	76	68.5	1,939	-14.7	-4

Horizontal conveying tested at 80 PSIG (5.5 BAR)

#### **Applications**

- · Material conveying
- · Part transfer
- Waste/trim removal
- Hopper loading
- · Filling operations
- · Chip removal
- Fiber tensioning

#### **Advantages**

- ISO 2852 compatible
- Type 316SS
- · Fits standard sanitary flanges
- · Four sizes available from stock
- No moving parts
- Compact
- · High throughput capability
- Quiet








## Sanitary Flange Line Vac™

#### **Dimensions**





			Sanitary	Flange Lin	e Vac Dime	nsions				
Sanitary Flange Line Vac Models		Α	В	С	D	E	F	G	H (air inlet)	1
******	in	2	1.25	2.75	4.38	2.13	1.25	1.69	3/8 NPT	20
161150-316	mm	51	32	70	111	54	32	43	3/8 NP1	20
141300 314	in	2.52	1.75	3.25	4.38	2.13	1.25	2.22	3/8 NPT	20
161200-316	mm	64	44	83	111	54	32	56	3/0 NF1	20
161250-316	in	3.05	2.25	3.75	4.38	2.13	1.25	2.78	3/8 NPT	20
161250-316	mm	77	57	95	111	54	32	71	3/8 NP1	20
161300-316	in	3.58	2.75	4.25	5.63	2.75	1.75	3.28	1/2 NPT	299.3
161300-316	mm	91	70	108	143	70	44	83	3/2 NP1	21.3


Sani	ary Flange Line Vac N	lodels
	Only Kits - include the Line Vac, m ire regulator (with coupler).	ounting bracket,
Inlet/Outlet Diameter	Sanitary Flange Line Vac Only Model	Sanitary Flange Line Vac Kit Model
1-1/2" (38mm)	161150-316	163150-316
2" (51mm)	161200-316	163200-316
2-1/2" (64mm)	161250-316	163250-316
3* (76mm)	161300-316	163300-316

	Accessories
Model#	Description
9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)
9002	Auto Drain Filter Separator, 3/4 NPT, 220 SCFM (6,230 SLPM)
9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)
9006	Oil Removal Filter, 3/4 NPT, 50-150 SCFM (1,416-4,248 SLPM)
9008	Pressure Regulator with Gauge, 1/4 NPT, 50 SCFM (1,416 SLPM)
9009	Pressure Regulator with Gauge, 3/4 NPT, 220 SCFM (6,230 SLPM)

#### Line Vac Drum Cover

#### **Line Vac Drum Cover**


EXAIR's fine mesh non-woven Drum Cover is built to fit over the top of 55 or 30 gallon drums. The breathable material allows the air from a Line Vac air operated conveyor to circulate, whether moving material in or out of the drum. The cover prevents contamination of your material and keeps material from escaping the drum, which keeps your work environment cleaner and safer. Since it is fabricated to fit 55 or 30 gallon drums, it is the simplest of solutions when needing a containment vessel for your transferred scrap, trim, waste, parts, chips or pellets. It is suitable for Line Vac conveyance hoses from 3/4" through 3" inside diameters and comes complete with hose clamps and a durable spring buckle strap for quick and easy installation.













# **Light Duty Line Vac**







# **Light Duty Line Vac™**

An INTELLIGENT OMPRESSED AIR Product

An effective way to convey small volumes of material over short distances!

#### What Is The Light Duty Line Vac?

EXAIR's Light Duty Line Vac is the ideal way to convey small volumes of materials over short distances. Like the Line Vac shown on page 161, the Light Duty Line Vac converts an ordinary hose or tube into a conveyor for scrap, trim and bulk materials.

#### Why The Light Duty Line Vac?

When lower throughputs at short distances are desired, the Light Duty Line Vac is a good choice. This simplified design utilizes a two-part threaded construction to provide effective conveying at a lower cost. Air consumption is reduced to a volume appropriate for moving small volumes of material at short distances. Conveying rates are easy to control by regulating the compressed air supply pressure.

The Light Duty Line Vac features inlet and outlet diameters common to hose and tube sizes. Eight sizes for diameters from 3/4" to 6" (19 to 152mm) are available. Standard construction is aluminum. (For corrosion resistant stainless steel models that are suitable for high temperature and food service, please see Line Vac models on page 166.) No moving parts or electricity assures maintenance free operation. (If higher conveying rates or mounting brackets are desired, see the Line Vac models on page 166.)





The low cost Model 130200 2" (51mm) Light Duty Line Vac conveys fibers to to fill pillows, stuffed animals, diapers, etc.

#### **Applications**

- Hopper loading
- · Fiber tensioning
- Material conveying
- · Waste/trim removal
- · Chip removal
- · Part transfer
- Filling operations

#### **Advantages**

- Compact
- Quiet
- No moving parts
- · Fits standard hose or tube
- Aluminum
- · Eight sizes
- · Moderate throughput capability





A Model 130125 1-1/4" (32mm) Light Duty Line Vac can fill or empty the packing peanuts from shipping cartons.








## **Light Duty Line Vac**

		Li	ght Duty	Line Vac	Dimensio	ns		
Model	*	A	В	c	D	E	F	G
120075	in	0.75	0.50	1.88	4.53	2.31	1.06	1/4
130075	mm	19	13	48	115	59	27	NPT
130100	in	1	0.75	2.13	4.53	2.41	1.06	1/4
130100	mm	25	19	54	115	61	27	NPT
130125	in	1.25	1	2.38	4.53	2.41	1.06	1/4
130123	mm	32	25	60	115	61	27	NPT
130150	in	1.50	1.25	2.75	4.63	2.41	1.06	3/8
130130	mm	38	32	70	117	61	27	NPT
130200	in	2	1.75	3.25	4.66	2.47	1.06	3/8
130200	mm	51	45	83	118	63	27	NPT
130300	in	3	2.75	4.25	5.06	2.75	1.06	3/8
130300	mm	76	70	108	129	70	27	NPT
130400	in	4	3.75	5.25	5.06	2.75	1.06	1/2
130400	mm	102	95	133	129	70	27	NPT
130600	in	6	5.75	7.38	5.56	2.88	1.06	1/2
130000	mm	152	146	187	141	73	27	NPT



#### **Light Duty Performance**

80 PSIG (5.5 BAR)					
Model #	SCFM	SLPM			
130075	7.30	207			
130100	10.70	303			
130125	14.70	501			
130150	20	566			
130200	27.50	778			
130300	45	1,274			
130400	58.50	1,656			
130600	80.20	2,270			



Light Duty Line Vacs are available in eight sizes for diameters from 3/4" to 6" (19 to 152mm).



Kits include a Light Duty Line Vac, filter separator and pressure regulator (with coupler).

#### **Light Duty Line Vac Systems**

#### Light Duty Line Vac Models

Light Duty Line Vac Only Light Duty Line Vac Kits - include the Light Duty Line Vac, filter separator and pressure regulator

Inlet/Outlet Diameter	Light Duty Line Vac Only Model	Light Duty Line Vac Kit Model		
3/4" (19mm)	130075	132075		
1" (25mm)	130100	132100		
1-1/4" (32mm)	130125	132125		
1-1/2" (38mm)	130150	132150		
2" (51mm)	130200	132200		
3" (76mm)	130300	132300		
4" (102mm)	130400	132400		
67 (15 E 7 mm)	170600	122600		

at EXAIR.com



Hose is available in 10', 20', 30', 40' and 50' lengths. Select the hose model number (diameter) and indicate the length with a dash. Example: A Model 6931-20 is 1" ID Hose x 20' long


6930-	Hose 3/4" ID	
6931-	Hose 1" ID	
6932-	Hose 1-1/4" ID	
6933-	Hose 1-1/2" ID	
6934-	Hose 2" ID	
6936-	Hose 3° ID	



PVC hose is available in lengths up to 50' (15.2m) and diameters up to 3" (76mm).









#### For Technical Assistance, Call An EXAIR Application Engineer 1-800-903-9247 Toll Free FAX (866) 329-3924 + E-mail: techelp@exair.com + www.exair.com







# **Light Duty Line Vac**

**Live Vac Conveyance Data** The table below shows conveyance rates for EXAIR 1", 1-1/2" and 2" Line Vacs in both standard and heavy duty styles when used with various materials and bulk densities. Exact, application-specific conveyance rates are best determined through hands-on testing. Contact an EXAIR Application Engineer to learn more and configure a system suitable for your application.

Description	Line Vac Model	Horizontal Run (ft)	Vertical Rise (ft)	Rate (lb/min)
	6081 (1" Aluminum)	7	5	8.8
	6083 (1-1/2" Aluminum)	7	5	13.8
Ground Corn Cobs Ground Corn Cobs (density: 25 lbs/cu.ft)	6084 (2" Aluminum)	7	5	26
	150100 (1" Heavy Duty)	7	5	12.9
	150150 (1-1/2" Heavy Duty)	7	5	20.3
	150200 (2" Heavy Duty)	7	5	40
		50	0	3.68
		100	0	1.23
	6081 (1" Aluminum)	0	11.33	3.69
		0	20.75	1.03
		25	11	2.6
		50	0	9.3
		100	0	2.89
	6083 (1-1/2" Aluminum)	0	11.33	13.58
		0	20.75	5.54
		25	11	11.16
		50	0	15.52
		100	0	5.41
	6084 (2" Aluminum)	0	11.33	16.39
		0	20.75	8.03
Tumbling Media		25	11	15.52
density: 64 lbs/cu.ft)		50	0	6.43
		100	0	1.18
	150100 (1" Heavy Duty)	0	11.33	9.54
		0	20.75	4.35
		25	11	4.84
		50	0	18.98
		100	0	9.02
	150150 (1-1/2" Heavy Duty)	0	11.33	22.52
		0	20.75	8.62
		25	11	16.13
		50	0	30.93
		100	0	10.86
	150200 (2" Heavy Duty)	0	11.33	24.97
		0	20.75	7.73
		25	11	24.42

## **Light Duty Line Vac**

Description	Line Vac Model	Horizontal Run (ft)	Vertical Rise (ft)	Rate (lb/min)
	6083 (1-1/2" Aluminum)	50	0	1.6
Rock Salt (density: 68 lbs/cu.ft)	0083 (1-1/2" Aluminum)	35	15	0.6
		100	0	5.57
	6084 (2" Aluminum)	200	0	1.42
		35	15	0.6
	150150 (1.1/2* Henry Duty)	50	0	8.32
	150150 (1-1/2" Heavy Duty)	35	15	5.62
	150200 (2" Heavy Duty)	100	0	8.73
	130200 (Z. Heavy Duty)	200	0	3.33
		50	0	2.57
	6081 (1" Aluminum)	100	0	1.18
	ever (1 Aluminum)	0	11.33	2.85
		0	20.75	1.1
		50	0	6
	6083 (1-1/2" Aluminum)	100	0	3.12
		0	11.33	8.67
		0	20.75	3.37
1		50	0	10.29
	6084 (2" Aluminum)	100	0	4.73
	0004 (2 Aluminum)	0	11.33	10.12
Crushed Glass		0	20.75	5.21
lensity: 85 lbs/cu.ft)		50	0	2.55
	150100 (1" Heavy Duty)	100	0	0.85
	(30100 (1 neavy Duty)	0	11.33	3.72
		0	20.75	1.42
		50	0	6.48
	150150 (1-1/2" Heavy Duty)	100	0	2.83
	130130 (1-1)2 neavy butty)	0	11.33	9.39
		0	20.75	4.17
		50	0	12
	150200 (2" Heavy Duty)	100	0	4.83
	.Jozov (z. neavy Duty)	0	11.33	13.26
		0	20.75	5.35



## **Industrial Housekeeping Products**

# **EXAIR** Industrial Housekeeping **Products**

## Eliminate expensive electric vacuum cleaners that wear out quickly!

#### What are EXAIR Industrial **Housekeeping Products?**

Busy industrial environments often produce byproducts, both liquid and solid, that can create troublesome messes that can be hard to handle for ordinary vacuums. Certain manufacturing processes, like manufacturing, milling, drilling, trimming, lubricating, washing and cleaning, all leave behind materials that must be cleaned, transported or repurposed in order to maintain smooth production flow.

EXAIR offers a full line of pneumatic products that are



specifically engineered to quickly and quietly vacuum a wide variety of material into standard drums for easy switchout, transfer, filtering, storage and more.

#### **Why Pneumatic** Vacuums?

Electric vacuums have limitations when used in industrial settings. Liquids, chips and other debris can overwork motors, and cause them to burn out quickly, leaving your process with expensive repairs or replacements. EXAIR vacuums operate solely on compressed air, meaning no electricity is needed at any point, making it safer to use in processes around, or involving liquids. Pneumatic vacuums also don't employ any motors or moving parts to wear out, making them relatively maintenance-free. This allows for extended use of the vacuums in applications requiring constant operation, as well as continued efficiency over long periods of time. EXAIR vacuums also meet all OSHA standards for noise exposure and vacuum quietly, while still maintaining the power and durability necessary for tough environments.

EXAIR's line of Industrial Housekeeping products offers adaptable and versatile solutions to handle your industrial cleanup needs.



#### EasySwitch® Wet-Dry Vac

The EasySwitch Wet-Dry Vac is an allencompassing vacuum that offers both a dry and liquid cleanup solution with the simple switch of its patented filter lid. Capable of handling any job - wet, dry, light and heavy - the EasySwitch is a versatile cleanup solution for any process.



#### **Reversible Drum Vac**

The Reversible Drum Vac utilizes a two-way action, stainless-steel pump that allows for easy emptying and filling of drums. Able to empty or fill a 55-gallon drum in under two minutes, it's a great solution for processes needing easy pick up, transfer or storage of liquids.



#### High Lift Reversible Drum Vac

The High Lift Reversible Drum Vac employs the two-way action ideal for vacuuming and emptying drums but with the additional power necessary to pump liquids up to 15 ft in the air. Provides extra strength and lift for below grade areas such as sumps or tanks.



#### Chip Trapper

The Chip Trapper provides an efficient solution for cleaning debris like chips, swarf and shavings from used liquids. Employing a filter bag, particulate-filled liquids are pumped into the drum and then filter out any pesky debris and recycle valuable liquids.



#### **High Lift Chip Trapper**

The High Lift Chip Trapper offers a fast and easy way to filter chips and other debris from used liquids but with the extra power to handle lifting thicker and heavier liquids like coolants and oils higher in the air, or over longer distances.



#### Chip Vac

The Chip Vac is a durable industrial-duty vacuum designed with a powerful direct flow action for vacuuming media like metal, wood and plastic. Perfect for cleaning chips and other materials from work floors, machining centers, lathes, mills



#### **Heavy Duty HEPA Vac**

The Heavy Duty HEPA Vac can transform an ordinary drum into a powerful HEPA (High Efficiency Particulate Air) quality industrial cleaner. Using a powerful micron filter, the HEPA vac is engineered to vacuum and filter contaminants in dusty environments or processes requiring frequent cleaning.



#### **Heavy Duty Dry Vac**

The Heavy Duty Dry Vac is EXAIR's strongest and most durable vacuum, able to handle rugged and abrasive cleanups. While useful in general purpose applications, it's also capable of handling tougher materials such as steel shot. garnet, metal chips and more.



















## EasySwitch Wet-Dry Vac



# EasySwitch® Wet-Dry Vac

## Make the seamless transition from a dry material vacuum to liquids with ease!

#### What is the EasySwitch Vacuum?

EXAIR's patent-pending EasySwitch vacuum simplifies the filter change process when switching from vacuuming a dry material to a liquid or vice versa. Utilizing minimal compressed air, the EasySwitch is a powerful pneumatic vacuum that is ideal for any application - wet, dry, light and heavy.

The EasySwitch is designed to handle the toughest of industrial cleanup jobs with ease. EXAIR's EasySwitch vacuum uses a standard or HEPA certified filter when vacuuming dry material. The fast and simple conversion to vacuuming



liquids is done by releasing one latch and simply removing the filter element. Using only compressed air, the EasySwitch vacuum creates a powerful vacuum without the need for electricity. Because the vacuum generator has no moving parts and uses no electricity, there is little concern for failed parts, motor failure or personnel safety associated with using electric vacuums for liquids.

#### Why the EasySwitch Vacuum?

The EasySwitch vacuum is an all-purpose pneumatic vacuum with the capability of handling any job dry or wet. Switching between vacuuming liquids or solids is as easy as removing the pleated filter when vacuuming liquids, and reinstalling directly into the open filter hatch when working with dry material. Like most of EXAIR's Intelligent Compressed Air" products, this compressed air-driven vacuum functions at a quiet 79 decibels without purchasing additional noise muffling accessories. This quiet operation feature protects operator hearing. In addition, the EasySwitch vacuum generally uses less compressed air to produce better or similar performance than other pneumatic competition. The EasySwitch vacuum also features accessory options of both a standard and anti-static vacuum hose, drum dolly for convenient movement, premium metal attachments and tool holder. Providing customers with an effective and adaptable method of cleanup, the EasySwitch vacuum is your allencompassing solution to industrial housekeeping.

#### **Applications**

- Coolant
- Chips
- Floor Cleanup
- Drains
- Shavings
- Sawdust
- Absorbent
- · Mold and allergen removal

#### Advantages

- · Easy to switch from liquid to dry material
- · High performance with minimal air requirements
- · Low sound level
- · Maintenance free
- · Safe no electricity
- · Spill free auto safety shutoff
- · No motors to clog or wear out
- · Continuous duty

Do Not Use With Combustible Dust

PRODUC

Do Not Use With Any Material With A Low Flash Point Or With Flammable Liquids Such As Fuel Oil, Alcohol, Mineral Spirits, Gasoline



## EasySwitch Wet-Dry Vac



#### **How The EasySwitch Wet-Dry Vac Works**

The EasySwitch vacuum utilizes a filter hatch, secured by one simple latch, for easy installation and replacement of filters. It does not require any additional springs, clips or closures. A rubber handle (1) is connected to the filter latch (2). Unlatching the handle from the drum lid will allow the hatch to be raised. When the hatch is raised, the filter (3) can be installed or uninstalled easily. The filter simply lifts out of the filter hatch hole, and be can reinstalled by placing the filter on top of edge gasket (4) on the filter hatch hole. For operation, close the hatch and secure the rubber handle (1). When the filter is installed, the vacuum will work with dry media and, when it is uninstalled. it will work with liquids. When the drum is filled with liquid, the vacuum is automatically turned off by a float shutoff.



Wet: Do not use with any material with a low flash point or with flammable liquids such as fuel oil, alcohol, mineral spirits, gasoline or

Dry: Do not use with combustible dust.

#### **EasySwitch Wet-Dry Vac Specifications**

Pressure Supply			ir mption			Vacuum Flow		Sound Level	
PSIG	BAR	SCFM	SLPM	"H <sub>2</sub> O	mm Hg	CFM	LPM	dBA	
80	5.5	53	1,500	168	314	90	2,548	79	
90	6.2	59	1,670	190	355	92	2,605	80	
100	6.9	65	1,840	210	392	94	2,661	82	

#### **Conveying Rate Comparison** for EasySwitch Wet-Dry Vac

Pressure Supply		Wa		Plastic To Me	umbling dia	Steel Shot		
PSIG	BAR	GPM	LPM	Lbs/min	kg/min	Lbs/min	kg/mir	
80	5.5	36	136	68	31	54	24	

The Model 6101 EasySwitch Vac System includes a standard filter. 10' (3m) hose, 20' (6.1m) compressed air hose, plastic tools, shutoff valve and gauge. HEPA version also available.



The Model 6201 Deluxe EasySwitch Vac System comes complete with standard filter, 10' (3m) static resistant hose, 20' (6.1m) compressed air hose, shutoff valve, gauge, heavy duty tools, tool holder and drum dolly. HEPA version also available.

Premium EasySwitch Vac Systems add a 55 gallon drum.


	EasySwitch Wet-Dry Vac Systems
Model #	Description
6101	55 Gallon EasySwitch Wet-Dry Vac System includes the EasySwitch Vac unit, EasySwitch drum lid, standard filter, pre-filter, 1/2" compressed air hose assembly, pressure gauge, 10" of 1.5" vacuum hose, crevice tool, 19" straight wand, skimmer tool and dust brush. (drum not included)
6201	55 Gallon Deluxe EasySwitch Wet-Dry Vac System - same as Model 6101 and adds a drum dolly, an upgrade to 10 feet of 1.5' antistatic hose, spill recovery kit, extension wand, round dust brush, 24' and 11' crevice tools, 12" wide floor tool and tool holder. (drum not included)
6301	55 Gallon Premium EasySwitch Wet-Dry Vac System - same as Model 6201 and adds a 55 gallon drum.
6103	SS Gallon HEPA EasySwitch Wet-Dry Vac System includes the EasySwitch Vac unit, EasySwitch drum lid, HEPA filter and pre-filter, 1/2° compressed air hose assembly, pressure gauge, 10° of 1.5° vacuum hose, crevice tool, 19° straight wand, skimmer tool and dust brush. (drum not included)
6203	55 Gallon Deluxe HEPA EasySwitch Wet-Dry Vac System - same as Model 6103 and adds a drum dolly, an upgrade to 10 feet of 1.5" antistatic hose, spill recover kit, extension wand, round dust brush, 24" and 11" crevice tools, 12" wide floor tool and tool holder. (drum not included)
6303	55 Gallon Premium HEPA EasySwitch Wet-Dry Vac System - same as Model 6203 and adds a 55 gallon drum.

Accessories							
Model#	Description	Model #	Description				
902100	Standard Filter for EasySwitch Vac	902032	Replacement EasySwitch Vacuum Unit Gasket				
902200	HEPA Filter	902184	Replacement Filter Port Gasket				
902146	Pre-Filter for EasySwitch Vac	901176	Magnetic Tool Holder				
902176	Replacement Muffler Material	902187	Latch Repair Kit				
902031	Replacement Drum Lid Gasket	902190	Replacement E-Clip for Hinge				

















# Reversible Drum Vac™

## Pump 55 gallons in 90 seconds! Two-way pumping action!

Waste water

#### What Is The Reversible Drum Vac?

A safe, maintenance free way to recover:

- Sludge and chips Coolant
- Hydraulic oils · Tramp oil

· Liquid spills

#### Why The Reversible Drum Vac?

EXAIR's compressed air operated Reversible Drum Vac System attaches quickly to any closed head 30, 55 or 110 gallon drum. Its high powered vacuum fills a 55 gallon drum in less than two minutes. With the simple turn of a knob, the same stainless steel pump quickly empties the drum. Coolant sumps can be easily refilled, floor spills vacuumed, or contaminated liquids transferred to filtration tanks in minutes. The flow rate in and out of the drum can be controlled with the knob, making it ideal for dispensing liquids.



EXAIR's Mini Reversible Drum Vac System delivers the same two-way action for small jobs. It comes complete with a 5 gallon drum and all the tools.


Electrically operated "all purpose" vacuums aren't designed for use in industrial environments. As a result, motors wear out quickly and impellers clog. The Reversible Drum Vac does not use electricity and has no moving parts, assuring maintenance free operation. An automatic safety shutoff valve prevents spills or overfilling.



ws for quick and easy clear

Product

the Mini Reversible Drum Vac provides fast



**Applications** 

Food processing

Floor cleanup

EDM machines

· Machining centers

Lathes

· Pits Screw machines

Tanks


#### **Advantages**

- Coolant sumps · No moving parts
  - · Maintenance free
    - · Stainless steel construction
    - · Safe no electricity
    - · Built-in pressure/vacuum relief
    - · Compact and portable
    - · Installs quickly
    - · Spill free auto safety shutoff
    - · Fits standard closed head drums





**Reversible Drum Vac** 





## EXAIR

#### Reversible Drum Vac

## **How The Reversible Drum Vac Works**



The flex hose (1) is attached to the barbed connection (2) on the Reversible Drum Vac system. The knob (3) on the Reversible Drum Vac pump is set to the "fill" position. The air supply valve (4) is opened to permit compressed air at 80-100 PSIG (5.5 - 6.9 BAR) to flow through the Reversible Drum Vac pump which pulls liquid through the flex hose and into the drum. When all liquid is in the drum, the air supply is turned off. If liquid exceeds the drum capacity, the safety shut-off valve (5) will prevent overfilling. The liquid can then be pumped back out of the flex hose (1) by setting the knob (3) on the Reversible Drum Vac pump to the "empty" position and opening the air supply valve.

Warning: Do not use with any material with a low flash point or with flammable liquids such as fuel oil, alcohol, mineral spirits, gasoline or kerosene.

#### **Reversible Drum Vac System Specifications**

Pressure Supply 80 PSIG (5.5 BAR)	Consu	ir nption				ter Rate	Sound Level
DESCRIPTION	SCFM	SLPM	"H2O	mm Hg	GPM	LPM	86
REVERSIBLE DRUM VAC	19	538	96	179	30	114	dBA



The Model 6196, Model 6196-30 and Model 6196-110 Reversible Drum Vac Systems include a vacuum hose and an aluminum wand.



Model 6196-5 Mini Reversible Drum Vac System includes a 5 gallon drum w/lid, ABS spill recovery kit, vacuum hose and all tools



Model 6296 and Model 6296-30 Deluxe Reversible Drum Vac Systems include a drum dolly, ABS spill recovery kit, vacuum hose, tool holder and all tools.



Premium Reversible Drum Vac Systems include the drum, drum dolly, an upgrade to heavy duty aluminum tools, ABS spill recovery kit, tool holder and air hose.

Reversible Drum Vac Systems						
Model #	Description					
6196	55 Gallon Reversible Drum Vac System includes two-way pump assembly (1/4 NPT), shutoff valve, 10' (3m) flexible vacuum hose (1-1/2'/38mm i.D.) with 90' quic release elbow connection, (1) aluminum wand (drum not included).					
6196-30	30 Gallon Reversible Drum Vac System - same as Model 6196 except fits a 30 gallon drum (drum not included).					
6196-110	110 Gallon Reversible Drum Vac System - same as Model 6196 except fits a 110 gallon drum (drum not included).					
6196-5	5 Gallon Mini Reversible Drum Vac System includes two-way pump assembly (1/4 NPT), shutoff valve, 5 gallon container with Ild and lock ring, 10' (3m) flexible vacuum hose (1-1/2'/38mm I.D.) with 90" quick release elbow connection, aluminum wand, ABS spill recovery kit, (2) extension wands, crevice tool and skimmer to					
6296	55 Gallon Deluxe Reversible Drum Vac System - same as Model 6196 and adds drum dolly, ABS spill recovery kit, (2) extension wands, crevice tool, skimmer tool and tool holder (drum not included).					
6296-30	30 Gallon Deluxe Reversible Drum Vac System - same as Model 6296 except fits 30 gallon drum (drum not included).					
6296-5	5 Gallon Deluxe Mini Reversible Drum Vac System - same as Model 6196-5 and adds drum dolly.					
6396	55 Gallon Premium Reversible Drum Vac System - same as Model 6196 and adds the 55 gallon drum with lock ring and lid, drum dolly, ABS spill recovery kit, 11" (279mm) and 24" (610mm) aluminum crevice tools, skimmer tool, tool holder and 20" (6.1m) air hose.					
6396-30	30 Gallon Premium Reversible Drum Vac System - same as Model 6396 except includes a 30 gallon drum.					
6396-110	110 Gallon Premium Reversible Drum Vac System - same as Model 6396 except includes a 110 gallon drum.					
6091	Reversible Drum Vac Only - included in all systems listed above.					

Accessories							
Model #	Description	Model #	Description				
9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)	901071	Heavy Duty Aluminum Tools plus Tool Holder				
9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)	9041-5	5 Gallon Drum Dolly				
901067-5	5 Gallon Drum with lock ring and lid	9041-30	30 Gallon Drum Dolly				
901067-30	30 Gallon Drum with lock ring and lid	9041	55 Gallon Drum Dolly				
901067	55 Gallon Drum with lock ring and lid	9041-110	110 Gallon Drum Dolly				
901067-110	110 Gallon Drum with lock ring and lid	6901	Spill Recovery Kit includes a one-piece 54" (1372mm) AB5 wand and 14" (356mm) double blade squeegee tool.				
6569-20	20' (6.1m) Flexible Vacuum Hose (1-1/2"/38mm I.D.)	901176	Magnetic Tool Holder				













## High Lift Reversible Drum Vac COMPRESSED AIR

# **High Lift Reversible** Drum Vac™

Two-way pump provides maximum lift (up to 15 feet)!

Move thick liquids (up to 1400 cP) through 20' of hose!

#### What Is The High Lift Reversible **Drum Vac?**

A safe, powerful, and maintenance free way to recover:

- · Coolant
- · Sludge and chips
- · Hydraulic oils
- · Tramp oil
- · Liquid spills
- · Waste water



EXAIR's compressed air operated High Lift Reversible Drum Vac System attaches quickly to any closed head 30, 55 or 110 gallon drum. Its high powered vacuum is able to lift liquids up to 15 feet and fill a 55 gallon drum in less than 85 seconds. With the simple turn of a knob, the same stainless steel pump quickly empties the drum. The High Lift Reversible Drum Vac has the extra power you need to move liquids from below grade work areas, sumps or tanks up to 15 feet deep!

Like all of EXAIR's industrial vacuums, the High Lift Reversible Drum Vac uses no electricity and has no moving parts which assures maintenance free operation. It is designed for continuous and heavy duty applications where electric vacuums fail due to motor wear or clogged impellers. This vacuum efficiently and safely uses the compressed air in your facility. An automatic safety shutoff valve prevents overfilling.

#### **Applications**

- · Below grade coolant sumps
- Deep wells
- · Underground storage tanks
- · Pits
- Drains
- · Deep hole broaching
- Bulk storage tanks
- Cisterns



#### Advantages

- No moving parts
- · Maintenance free
- · Stainless steel construction
- · Safe no electricity
- · Built-in pressure/vacuum relief
- · Compact and portable
- · Installs quickly
- · Spill free auto safety shutoff · Fits standard closed head drums

# **Pump Farther Pump Higher Pump Thicker** Liquids

If you need assistance choosing the right High Lift Reversible Drum Vac System, please contact an **Application Engineer to** discuss your application.

15 Feet

# **High Lift Reversible Drum Vac**

# **How The High Lift Reversible Drum Vac Works**



The flex hose (1) is attached to the barbed connection (2) on the Reversible Drum Vac system. The knob (3) on the High Lift Reversible Drum Vac pump is set to the "fill" position. The air supply valve (4) is opened to permit compressed air at 80-100 PSIG (5.5 - 6.9 BAR) to flow through the High Lift Reversible Drum Vac pump which pulls liquid through the flex hose and into the drum. When all liquid is in the drum, the air supply is turned off. If liquid exceeds the drum capacity, the safety shut-off valve (5) will prevent overfilling. The liquid can then be pumped back out of the flex hose (1) by setting the knob (3) on the High Lift Reversible Drum Vac pump to the "empty" position and opening the air supply valve.

Warning: Do not use with any material with a low flash point or with flammable liquids such as fuel oil, alcohol, mineral spirits, gasoline

Pressure Supply 80 PSIG (5.5 BAR)	Air Consumption				Water Flow Rate		Sound Level	
DESCRIPTION	SCFM	SLPM	"H <sub>2</sub> O	mm Hg	GPM	LPM	83	
HIGH LIFT REVERSIBLE DRUM VAC	43	1,218	180	336	30	114	dBA	

High Lift Reversible Drum Vac Only - included in all systems listed above



Model 6195, Model 6195-30 and Model 6195-110 **High Lift Reversible** Drum Vac Systems include a vacuum hose and an aluminum wand.



Model 6295 and Model 6295-30 Deluxe High Lift Reversible Drum Vac Systems include a drum dolly, ABS spill recovery kit, vacuum hose, tool holder and all tools.



Premium High Lift Reversible Drum Vac Systems include the drum, drum dolly, an upgrade to heavy duty aluminum tools, ABS spill recovery kit, tool holder and air hose.

## **High Lift Reversible Drum Vac System Specifications**








Deluxe and Premium High Lift Drum Vac Systems include a drum dolly.

	High Lift Reversible Drum Vac Systems
Model #	Description
6195	55 Gallon High Lift Reversible Drum Vac System includes two-way pump assembly (1/4 NPT), shutoff valve, 20' (6.1m) flexible vacuum hose (1-1/2'/38mm I.D.) with 90° quick release elbow connection, (1) aluminum wand (drum not included).
6195-30	30 Gallon High Lift Reversible Drum Vac System - same as Model 6195 except fits a 30 gallon drum (drum not included).
6195-110	110 Gallon High Lift Reversible Drum Vac System - same as Model 6195 except fits a 110 gallon drum (drum not included).
6295	55 Gallon Deluxe High Lift Reversible Drum Vac System - same as Model 6195 and adds drum dolly, ABS spill recovery kit, (2) extension wands, crevice tool, skimmer tool and tool holder (drum not included).
6295-30	30 Gallon Deluxe High Lift Reversible Drum Vac System - same as Model 6295 except fits 30 gallon drum (drum not included).
6395	55 Gallon Premium High Lift Reversible Drum Vac System - same as Model 6195 and adds the 55 gallon drum with lock ring and lid, drum dolly, ABS spill recovery kit, 11* (279mm) and 24* (610mm) aluminum crevice tools, skimmer tool, tool holder and 20* (6.1m) air hose.
6395-30	30 Gallon Premium High Lift Reversible Drum Vac System - same as Model 6395 except includes a 30 gallon drum.
6395-110	110 Gallon Premium High Lift Reversible Drum Vac System - same as Model 6395 except includes a 110 gallon drum.

Accessories					
Model#	Description	Model #	Description		
9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)	901071	Heavy Duty Aluminum Tools plus Tool Holder		
9006	Oil Removal Filter, 3/4 NPT, 50-150 SCFM (1,416-4,248 SLPM)	9041-30	30 Gallon Drum Dolly		
901067-30	30 Gallon Drum with lock ring and lid	9041	55 Gallon Drum Dolly		
901067	55 Gallon Drum with lock ring and lid	9041-110	110 Gallon Drum Dolly		
901067-110	110 Gallon Drum with lock ring and lid	6901	Spill Recovery Kit includes a one-piece 54" (1372mm) ABS wand and 14" (356mm) double blade squeegee tool.		
6569-20	20' (6.1m) Flexible Vacuum Hose (1-1/2"/38mm I.D.)	901176	Magnetic Tool Holder		













11510 Goldcoast Drive • Cincinnati. OH 45249-1621 • Phone (513) 671-3322 FAX (513) 671-3363 \* E-mail: techelp@exair.com \* www.exair.com



## **Chip Trapper**



YEAR

# Chip Trapper™

## Filter the chips out of your used coolant and cutting oils!

## Vacuums in the liquid with solids, pumps out only the liquid!

#### What Is The Chip Trapper?

The patented\* Chip Trapper offers a fast, easy way to clean chips, swarf and shavings out of used coolants and other liquids. The Chip Trapper vacuums the coolant or liquid that is filled with debris and traps all the solids in a reusable filter bag. Only the liquid pumps back out. It is ideal for use on machines with sumps, parts washers, tanks and storage containers of contaminated liquids.

The Chip Trapper uses EXAIR's compressed air powered Reversible Drum Vac (included) that can fill or empty a 55 gallon drum in less than two minutes. Simply



set the Reversible Drum Vac pump and directional flow control valve on top of the drum to "fill" for it to quickly vacuum the liquid with solids. Once the sump, pit or tank is empty, set the pump and directional valve to "empty" for it to pump out clean coolant/liquid. All the chips and other solids are trapped inside the reusable filter bag of the Chip Trapper.

#### Why The Chip Trapper?

A sudden lack of coolant flow in a machining operation will likely damage the part and expensive tooling. Machine tools commonly discharge some chips and shavings into the coolant sump. As the chips accumulate and mound up, the coolant flow used to flood the part and tooling becomes restricted. Some high pressure coolant systems sound an audible alarm and abruptly shut down the machine when low coolant flow occurs. This results in downtime to fix the problem and clear the alarm. That isn't the case with standard machines where immediate damage can occur if the operator fails to spot the lack of coolant. Regular cleaning of the coolant sump with the Chip Trapper can quickly eliminate this very costly problem.


#### **Applications**

- · CNC's
- Lathes
- Saws
- · Mills Drills
- Parts washers
- · Pits
- Tanks
- Containers
- Grinders

#### \*Patent #8153001 and #8268179

#### Advantages

- · Removes unwanted solids from liquid
- Recycles coolants
- No moving parts
- · No motors to clog or wear out
- · Self priming stainless steel pump
- Safe no electricity
- · Built-in pressure/vacuum relief
- Drum is included
- · Spill free auto safety shutoff
- Quiet





Chip Trapper filters out solids from parts

The Chip Trapper vacuums dirty coolant

The Chip Trapper pumps the coolant back

into the sump - free of chips and debris.

and chips into the drum.

## Chip Trapper

# **How The Chip Trapper Works**

The vacuum hose (1) is attached to the barbed connection of the Chip Trapper (2). The directional flow control valve on top of the drum (3) and knob on the pump (4) are set to the "fill" position. The air supply valve is opened to permit compressed air at 80-100 PSIG (5.5 - 6.9 BAR) to flow through the pump which pulls the liquid through the hose, then into the reusable filter bag (5). When all liquid is in the drum, the air supply is automatically turned off. The filtered liquid can then be pumped out by setting the directional flow control valve on top of the drum and the knob on the pump to the "empty" position. Once the air supply valve is opened, the air pushes the liquid back through the hose while all solids remain in the reusable filter bag.

Warning: Do not use with any material with a low flash point or with flammable liquids such as fuel oil, alcohol, mineral spirits, gasoline or kerosene

#### **Chip Trapper System Specifications**

Pressure Supply 80 PSIG (5.5 BAR)		ir mption	Wa Flow		
DESCRIPTION	SCFM	SLPM	GPM	LPM	86
CHIP TRAPPER	19	538	30	114	dBA

The filter han included with the system provides 5 micron filtration

#### **Built To Last**

The stainless steel pump has no motors or impellers to clog or wear out and there is no electricity or shock hazard! Safe operation is assured with a built-in pressure/vacuum relief and an automatic safety shutoff valve that prevents spills or overfilling.




The Chip Trapper includes the pump assembly with directional flow valve, a 30, 55 or 110 gallon drum, 10' (3m) chemical resistant hose, 20' (6.1m) compressed air hose, aluminum chip wand, (2) reusable 5 micron filter bags and drum dolly.



	Chip Trapper Systems
Model #	Description
6198	55 Gallon Chip Trapper System includes the Reversible Drum Vac pump assembly, directional flow valve, 55 gallon drum, lever lock drum lid, shutoff valve, 10' (3m) flexible vacuum hose (1-1/2"/38mm I.D.), 20' (6.1m) compressed air hose, chip wand, (2) filter bags and drum dolly.
6198-30	30 Gallon Chip Trapper System - same as Model 6198 except includes a 30 gallon drum
198-110	110 Gallon Chip Trapper - same as Model 6198 except includes a 110 gallon drum.
6091	Reversible Drum Vac Only - included in all systems listed above.

Accessories					
Model #	Description	Model #	Description		
901060-1	Replacement Filter Bag, 1 micron	901060-200	Replacement Filter Bag, 200 micron		
901060	Replacement Filter Bag, 5 micron	901060-SP	Filter Bag Sample Pack-Includes one each 1, 25, 50, 100 & 200 micron bags		
901060-25	Replacement Filter Bag, 25 micron		Spill Recovery Kit includes a one-piece 54" (1372mm) ABS wand and		
901060-50	Replacement Filter Bag, 50 micron	6901 Spill recovery for includes a one piece 34 (15) Ziriling Abs Wal			
901060-100	Replacement Filter Bag, 100 micron	9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)		















## High Lift Chip Trapper



# **High Lift Chip Trapper™**

Filter chips and solids out of used coolant and liquids from below grade sumps or elevated tanks!

Vacuum in liquid with solids and pump out only the liquid, with 15 feet of lift!

#### What Is The High Lift Chip Trapper?

The patented\* High Lift Chip Trapper offers a fast, easy way to clean chips, swarf and shavings out of used coolants and other liquids. The High Lift Chip Trapper vacuums the coolant or liquid that is filled with debris and traps all the solids in a reusable filter bag. Only the liquid pumps back out. It is ideal for use on pits, wells, below grade sumps, tanks and storage containers of contaminated liquids.

#### Why The High Lift Chip Trapper?

EXAIR's compressed air operated High Lift Chip Trapper System attaches quickly to the included 30, 55 or 110 gallon drum lid. Its high powered vacuum is able to lift liquids up to 15 feet or pump liquids from as far as 20 feet and fill a 55 gallon drum in less than 85 seconds. With the simple turn of a knob, the same stainless steel pump quickly empties the drum. The High Lift Chip Trapper has the extra power you need to move liquids from below grade work areas, sumps or tanks.

Wells, pits, below grade or elevated tanks can accumulate debris. This debris can cause problems when the liquid is transferred into a machine or process. Waste oil for heating or recycled lubricants which are suitable for dirtier jobs can be used without worry of solids damaging equipment. The heavy duty power of the High Lift Chip Trapper is capable of moving high viscosity liquids up to 1400 centipoise.

#### **Applications**

- · Below grade coolant sumps
- · Deep wells
- · Underground storage tanks
- · Pits
- Drains
- · Deep hole broaching
- · Bulk storage tanks
- Cisterns

\*Patent #8153001 and #8268179



#### **Advantages**

- · Removes unwanted solids from liquid
- Recycles coolants
- No moving parts
- · No motors to clog or wear out
- · Self priming stainless steel pump
- · Safe no electricity
- · Built-in pressure/vacuum relief
- · Spill free auto safety shutoff
- Quiet

FAX (513) 671-3363 \* E-mail: techelp@exair.com \* www.exair.com

## **Pump Farther Pump Higher**

**Pump Thicker** Liquids

If you need assistance choosing the right High Lift Chip Trapper System, please contact an **Application Engineer** to discuss your application.

## **High Lift Chip Trapper**

# **How The High Lift Chip Trapper Works**



The vacuum hose (1) is attached to the barbed connection of the High Lift Chip Trapper (2). The directional flow control valve on top of the drum (3) and knob on the pump (4) are set to the "fill" position. The air supply valve is opened to permit compressed air at 80-100 PSIG (5.5 - 6.9 BAR) to flow through the pump which pulls the liquid through the hose, then into the reusable filter bag (5). When all liquid is in the drum, the air supply is turned off. The filtered liquid can then be pumped out by setting the directional flow control valve on top of the drum and the knob on the pump to the "empty" position. Once the air supply valve is opened, the air pushes the liquid back through the hose while all solids remain in the reusable filter bag.

Warning: Do not use with any material with a low flash point or with flammable liquids such as fuel oil, alcohol, mineral spirits, gasoline or kerosene.

#### **High Lift Chip Trapper System Specifications**

Pressure Supply 80 PSIG (5.5 BAR)	Air Consumption				Wa Flow	ter Rate	Sound Level
DESCRIPTION	SCFM	SLPM	*H2O	mm Hg	GPM	LPM	
HIGH LIFT CHIP TRAPPER	43	1,218	180	336	30	114	dBA

#### **Built To Last**

The stainless steel pump has no motors or impellers to clog or wear out and there is no electricity or shock hazard! Safe operation is assured with a built-in pressure/vacuum relief and an automatic safety shutoff valve that prevents spills or overfilling.





The High Lift Chip Trapper includes the pump assembly with directional flow valve, a 30, 55 or 110 gallon drum, 20' (6.1m) chemical resistant hose, 20' (6.1m) compressed air hose, aluminum chip wand, (2) reusable 5 micron filter bags and drum dolly.



The 5 micron filter bag traps all the chips so no solids get pumped back out of the drum.

	A STATE OF THE STA
Model #	Description
6190	55 Gallon High Lift Chip Trapper System includes the High Lift Reversible Drum Vac pump assembly, directional flow valve, 55 gallon drum, lever lock drum lid, shutoff valve, 20' (6.1m) flexible vacuum hose (1-1/2'/38mm1.D.), 20' (6.1m) compressed air hose, chip wand, (2) filter bags and drum dolly.
6190-30	30 Gallon High Lift Chip Trapper System - same as Model 6190 except includes a 30 gallon drum.
6190-110	110 Gallon High Lift Chip Trapper - same as Model 6190 except includes a 110 gallon drum.
****	High Life Reversible Day on Vac Only, Included in all systems listed above

Accessories					
Model #	Description	Model #	Description		
901060-1	Replacement Filter Bag, 1 micron	901060-200	Replacement Filter Bag, 200 micron		
901060	Replacement Filter Bag, 5 micron	901060-SP	Filter Bag Sample Pack- Includes one each 1, 25, 50, 100 & 200 micron bags		
901060-25	Replacement Filter Bag, 25 micron	6901	Spill Recovery Kit includes a one-piece 54* (1372mm) ABS wand and		
901060-50	Replacement Filter Bag, 50 micron	6901	14" (356mm) double blade squeegee tool		
901060-100	Replacement Filter Bag, 100 micron	9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)		




For Technical Assistance, Call An EXAIR Application Engineer 1-800-903-9247 Toll Free FAX (866) 329-3924 · E-mail: techelp@exair.com · www.exair.com



















# Chip Vac™

## Vacuums chips directly into an open-top drum with no moving parts!

#### What Is The Chip Vac?



EXAIR's Chip Vac picks up dry or wet chips and delivers them directly to an ordinary open-top drum. The Chip Vac is used to clean chips from fixtures, floors and work surfaces of machining centers, lathes, saws, mills and other industrial equipment. The powerful suction is ideal for fast and efficient cleaning.

EXAIR's Mini Chip Vac System delivers the same cleaning power for small jobs. It comes complete with a 5 gallon drum and all the tools.

#### Why The Chip Vac?

The compressed air operated Chip Vac is an industrial duty vacuum designed specifically for vacuuming chips. It creates a powerful direct flow action that vacuums metal, wood or plastic chips into an ordinary drum. Designed for occasional use with dusty materials, the included filter bag keeps the surrounding air clean.

Electrically operated "all purpose" vacuums aren't designed for use in industrial environments. As a result, motors wear out quickly and impellers clog. The Chip Vac has no moving parts to wear out or break which ensures long life. Sound level is half that of electric vacs.

The Chip Vac Systems include a drum lid with a locking ring that fits an open top drum. In less than a minute, the Chip Vac can be removed and easily placed onto another drum to keep different materials separate for recycling. Constant heavy lifting and dumping of the vacuum cleaner tanks is eliminated since all chips are vacuumed directly into the drum.

#### **Applications**

- · CNC's
- Lathes
- Saws
- · Mills
- Drills
- Grinders
- Routers
- Molding machines
- Absorbent pick-up

#### Advantages

- No moving parts
- Low cost
- · No motors to clog or wear out
- · No electricity
- · Chips go directly into a drum
- · Powerful direct flow action
- Includes accessories
- 50% guieter than electric vacs





The Chip Vac removes abrasive stainless steel chips from a CNC.




110 Gallon Chip Vac offers maximum capacity cleanup on a large machining



The Mini Chip Vac allows for easy clean up








#### Chip Vac

#### **How The Chip Vac Works**



Compressed air, normally 80-100 PSIG (5.5 - 6.9 BAR), flows through the inlet (1) into an annular plenum chamber (2). It is then injected into the throat through directed nozzles (3). These jets of air create a vacuum at the intake (4) which draws material in, accelerates it through the unit (5), and directs it to the bottom of the drum. The airflow exhausts through the port in the drum lid. Airborne particles are trapped by the filter bag (6).

#### Warning: Do not use with combustible dust.

The Chip Vac System can be used with an open head steel. fiber or plastic drum that is in good condition (ANSI Standard #MH2-2004). To prevent material contamination, a poly drum liner can be inserted into the drum.







Deluxe and Premium Chip Vac Systems include a drum dolly.

Chip Vac Only - included in all 30 gallon through 110 gallon systems listed above

6093-5 Mini Chip Vac Only - included with 6193-5 and 6293-5 5 gallon systems.

#### **Chip Vac System Specifications**

	Pressure Supply			umption		Sound
Size		BAR		SLPM	INLET	
110, 55 & 30 Gallon	80	5.5	40	1,132	3/8 NPT	77 dBA
5 Gallon	80	5.5	33	934	3/8 NPT	

Air consumption has been minimized by using the appropriate amount of air required for vacuuming chips.



The Model 6193 Chip Vac System includes a vacuum hose, chip wand and plastic tools.



The Model 6193-5 Mini Chip Vac System includes a vacuum hose, 5 gallon drum, chip wand and plastic tools.



Premium Chip Vac Systems include the drum, drum dolly, an upgrade to static resistant hose, heavy duty aluminum tools, tool holder, air hose and quick connects fittings. (Model 6393 shown.)

	Chip Vac Systems			
Nodel #	Description			
6193	55 Gallon Chip Vac System includes the Chip Vac, lever lock drum lid, shutoff valve, filter bag, 10' (3m) flexible vacuum hose (1-1/2'738mm I.D.), chip wand, (2) extension wands, crevice tool, brush, skimmer tool (drum not included).			
193-30	30 Gallon Chip Vac System - same as Model 6193 except fits a 30 gallon drum (drum not included).			
	5 Gallon Mini Chin Vac System - includes the Chin Vac (3/8 NDT) shutoff value filter has 5 gallon container with list and lock sine 10' (3m) flevible vacuum h			

6193-5	(1-1/2"/38mm I.D.), aluminum chip wand, (2) extension wands, crevice tool, brush, skimmer tool.
6293	55 Gallon Deluxe Chip Vac System - same as Model 6193 and adds drum dolly and tool holder (drum not included).
6293-30	30 Gallon Deluxe Chip Vac System - same as Model 6293 except fits 30 gallon drum (drum not included).
6293-5	5 Gallon Deluxe Chip Vac System - same as Model 6193-5 and adds drum dolly.
6393	55 Gallon Premium Chip Vac System - same as Model 6193 and adds a 55 gallon drum, drum dolly, an upgrade to static resistant hose, an upgrade to heavy duty aluminum tools, 20' (6.1m) air hose, tool holder and quick connects fittings.
6393-30	30 Gallon Premium Chip Vac System - same as Model 6393 except includes 30 gallon drum.
6393-110	110 Gallon Premium Chip Vac System - same as Model 6393 except includes a 110 gallon drum.

Accessories					
Model #	Description	Model #	Description		
6804	Replacement Filter Bag	9041-5	5 Gallon Drum Dolly		
901176	Magnetic Tool Holder	9041-30	30 Gallon Drum Dolly		
901071	Heavy Duty Aluminum Tools plus Tool Holder	9041	55 Gallon Drum Dolly		
4540.30	20' (6.1m) Elevible Vacuum Hore (1.1/2" / 28mm (D.)	9041-110	110 Gallon Drum Dolly		









## Heavy Duty Dry Vac

only



# Heavy Duty Dry Vac™

## Vacuum more material in less time! Industrial duty vacuum has a rugged construction to resist wear!

#### What Is The Heavy Duty Dry Vac?

EXAIR's Heavy Duty Dry Vac attaches to an ordinary 30, 55 or 110 gallon open-top drum to turn it into a powerful, industrial duty vacuum cleaner. The Heavy Duty Dry Vac has been engineered to vacuum more dry materials in less time with less wear.



Designed for tough industrial environments, the hardened alloy construction resists premature wear while the increased power handles difficult jobs and harsh conditions. The quiet operation makes it suitable for a wide variety of applications including the clean up of abrasive materials like steel shot, garnet, metal chips and sand while also useful for general purpose applications like vacuuming floors, machines, work stations, industrial machinery and equipment.

#### Why The Heavy Duty Dry Vac?

Electrically operated vacuums have motors and impellers that clog and wear out quickly. There's also a potential shock hazard when electric vacs are used in standing liquids. The Heavy Duty Dry Vac is compressed air powered, which eliminates the shock hazard. It has no moving parts to wear out or break, to assure long life. It is quiet with a sound level that is half that of electric vacs. A static resistant hose prevents painful shocks when vacuuming dry materials.

	Va	Vacuuming Rate Comparison						
	1/4 NPT Pipe Plugs bulk density is 250 lb/ft <sup>2</sup> (4005 kg/m <sup>2</sup> )	Plastic Pellets (tumbling media) bulk density is 69.3 lb/ft <sup>3</sup> (1110 kg/m <sup>3</sup> )	Steel Shot (blasting media) bulk density is 317.7 lb/ft² (5089 kg/m²)					
Standard Chip Vac	11.1 lbs/min (5 kg/min)	27.4 lbs/min (12.4 kg/min)	13 lbs/min (5.9 kg/min)					
HD Dry Vac	26.9 lbs/min (12.2 kg/min)	51.6 lbs/min (23.4 kg/min)	32 lbs/min (14.5 kg/min)					
% Increase	142%	88%	146%					

#### **Applications**

- Work surfaces
- · Abrasive tumbling media
- · Industrial machinery
- · Shop floors
- · Sand blasting equipment
- Grinders
- Punch presses
- Absorbent pick-up
- · Building maintenance/remodeling
- Saws
- Gravel

#### **Advantages**

- · Moves more material in less time
- · Hardened construction resists wear
- No moving parts maintenance free
- · No motors to clog or wear out
- No electricity
- · Continuous duty with high capacity
- · Static resistant hose
- Ouiet
- · Powerful direct flow action
- · Heavy duty accessories





The Heavy Duty Dry Vac cleans up a spill of tumbling media.




110 Gallon Heavy Duty Dry Vac provides maximum capacity cleanup for a large, dusty walnut shell blasting application.



Sand that covers the floor around a sand blaster is guickly vacuumed into the drum using the rugged floor tool.

## EXAVA





## **Heavy Duty Dry Vac**

#### **How The Heavy Duty Dry Vac Works**



Compressed air, normally 80-100 PSIG (5.5 - 6.9 BAR), flows through the inlet (1) into an annular plenum chamber (2). It is then injected into the throat through directed nozzles (3). These jets of air create a vacuum at the intake (4) which draws material in, accelerates it through the unit (5), and directs it to the bottom of the drum. The airflow exhausts through the port in the drum lid. Airborne particles are trapped by the filter bag (6). The Heavy Duty Dry Vac unit (5) and vacuum tools (7) are built to withstand rugged use.

#### Warning: Do not use with combustible dust.

The Heavy Duty Dry Vac's lever lock drum lid fits any open top drum. Moving it from one drum to another can be done quickly, making it easy to keep different materials separate for recycling. All materials are vacuumed directly into the drum, eliminating the heavy lifting that is common with electrically powered vacuums. The Heavy Duty Dry Vac can be used with an open head steel, fiber or plastic drum that is in good condition (ANSI Standard #MH2-2004). To prevent material contamination, a poly drum liner can be inserted into the drum

#### **Heavy Duty Dry Vac System Specifications**

1	Model	Pressure	Supply			DUCT	Sound Level
L	model	PSIG	BAR	SCFM	SLPM	INLET	Sound Leves
	ALL	80	5.5	68	1,924	3/8 NPT	82 dBA



The Model 6197 Heavy Duty Dry Vac System includes 10' (3m) static resistant hose, 20' (6.1m) compressed air hose, filter bag, aluminum chip wand, shutoff valve and gauge



The Model 6297 Deluxe Heavy Duty Dry Vac System comes complete with a 10' (3m) static resistant hose, 20' (6.1m) compressed air hose, filter bag, shutoff valve, gauge, heavy duty tools, tool holder and drum dolly.

Premium Heavy Duty Dry Vac Systems are the same as Model 6297 and add either a 30, 55 or 110 gallon drum

into the di	ann.
	Heavy Duty Dry Vac Systems
Model #	Description
6197	55 Gallon Heavy Duty Dry Vac System includes the Heavy Duty Dry Vac, lever lock drum lid, shutoff valve, filter bag, 10' (3m) polyethylene static resistant hose (1-12'38mm I.D.), hose hanger, 1/2 NPT quick connect couplings, 20' (6.1m) air hose with swivel fitting, pressure gauge, and aluminum chip wand (drum not included).
6197-30	30 Gallon Heavy Duty Dry Vac System - same as the Model 6197 except fits a 30 gallon drum (drum not included).
6297	55 Gallon Deluxe Heavy Duty Dry Vac System-same as Model 6197 plus drum dolly and heavy duty aluminium tools. Additional tools include 2 piece double bend wand, 12*(365mm) floor tool, 11*(279mm) crevice tool, 24*(610mm) crevice tool, skimmer tool with detachable brush, tool holder, and a 3-1/2* (89mm) diameter dusts brush with conductive bristles (drum not included).
6297-30	30 Gallon Deluxe Heavy Duty Dry Vac System - same as the Model 6297 except fits a 30 gallon drum (drum not included).
6397	55 Gallon Premium Heavy Duty Dry Vac System - same as the Model 6297 and adds a 55 gallon drum.
6397-30	30 Gallon Premium Heavy Duty Dry Vac System - same as the Model 6397 except includes a 30 gallon drum.
6397-110	110 Gallon Premium Heavy Duty Dry Vac System - same as the Model 6397 except includes a 110 gallon drum.
6097	Heavy Duty Dry Vac only - included in all systems listed above.

Accessories							
Model #	Description	Model #	Description				
6804	Replacement Filter Bag	9041-30	30 Gallon Drum Dolly				
901176	Magnetic Tool Holder	9041-110	110 Gallon Drum Dolly				
901071	Heavy Duty Aluminum Tools plus Tool Holder	901069	55 Gallon Drum Only				
6580-20	20' (6.1m) Static Resistant Vacuum Hose	901069-30	30 Gallon Drum Only				
9041	55 Gallon Drum Dolly	901069-110	110 Gallon Drum Only				











## Heavy Duty HEPA Vac



A clogged filtering system for a buffing

service using the Heavy Duty HEPA Vac.

A technician uses a Heavy Duty HEPA Vac

to perform scheduled maintenance on a

booth is quickly cleaned and put back into

# Heavy Duty HEPA Vac™

## A rugged HEPA quality vacuum! High capacity cleaning for dusty environments!



EXAIR's compressed air operated Heavy Duty HEPA Vac attaches to an ordinary 30, 55, or 110 gallon open top drum to turn it into a powerful, HEPA (High Efficiency Particulate Air) quality, industrial vacuum cleaner. Like the Heavy Duty Dry Vac, it's powerfully designed to move more material with less wear. In addition, the Heavy Duty HEPA Vac has been engineered to filter contaminants to HEPA requirements in dusty environments requiring frequent cleaning.

#### Why The Heavy Duty HEPA Vac?



Engineered for dusty environments that require regular cleaning, the HEPA filter is designed with high capacity in mind. Ordinary vacuums can clog up quickly in environments with an abundance of dust or particulates. An economical, easily maintained pre-filter stops larger particles of debris while the HEPA filter handles smaller matter. All of EXAIR's filters are 100% tested in strict accordance to IEST-RP-CC-007 for

minimum 99.97% Filtration at the 0.3 micron level to meet HEPA standards. An optional filter protector is available to extend the life of the HEPA filter.

The Heavy Duty HEPA Vac does not use electricity and has no moving parts, assuring maintenance free operation. This eliminates the risk of electric shock often associated with electric shop vacs. Static resistant hose prevents painful shocks when vacuuming dry, dusty materials.

#### **Applications**

- · Critical dust removal
- Clean up around grit and dust producing equipment
- · Abrasive media
- · Shop floors
- · Drywall refinishing
- · Industrial contaminants
- · Mold and allergen removal Trapping dust and airborne irritants
- · Eliminate exhaust debris

- No electricity

- · For frequent use in dusty environments
- · Hardened construction resists wear
- · No moving parts maintenance free

- · Includes accessories
- · Quiet

#### Advantages



- · Static resistant hose
- · Dust free operation
- · Reduces exposure to airborne particulates

#### **How The Heavy Duty HEPA Vac Works**

**Heavy Duty HEPA Vac** 



Compressed air, normally 80-100 PSIG (5.5 - 6.9 BAR), flows through the inlet (1) into an annular plenum chamber (2). It is then injected into the throat through directed nozzles (3). These jets of air create a vacuum at the intake (4) which draws material in, accelerates it through the unit (5), and directs it to the bottom of the drum. The airflow passes first through the pre-filter and then through the 0.3 micron HEPA filter, trapping airborne particles. It then exhausts through the vent in the drum lid (6). The Heavy Duty Dry Vac unit (5) and vacuum tools (7) are built to resist wear.

#### Warning: Do not use with combustible dust.

The Heavy Duty HEPA Vac's lever lock drum lid fits any open top 30, 55 or 110 gallon drum. Moving it from one drum to another can be done quickly, making it easy to keep different materials separate for recycling. All materials are vacuumed directly into the drum, eliminating the heavy lifting that is common with electrically powered vacuums. The Heavy Duty HEPA Vac can be used with an open head steel, fiber or plastic drum that is in good condition (ANSI Standard #MH2-2004). To prevent material contamination, a poly drum liner can be inserted into the drum.

#### **Heavy Duty HEPA Vac System Specifications**

Model		Supply		umption			
Model				SLPM			
ALL	80	5.5	68	1,924	3/8 NPT	82 dBA	



The Model 6199 Heavy Duty HEPA Vac System includes HEPA filter, pre-filter, 10' (3m) static resistant hose, 20' (6.1m) compressed air hose, aluminum chip wand, shutoff valve and gauge.



The Model 6299 Deluxe Heavy Duty HEPA Vac System comes complete with HEPA filter, pre-filter, 10' (3m) static resistant hose, 20' (6.1m) compressed air hose, shutoff valve, gauge, heavy duty tools, tool holder and drum dolly.

Premium Heavy Duty HEPA Vac Systems are the same as Model 6299 and add either a 30, 55 or 110 gallon drum.

Heavy Duty HEPA Vac Systems							
Model #	Description						
6199	55 Gallon Heavy Duty HEPA Vac System includes Heavy Duty Dry Vac, lever lock drum lid, shutoff valve, pre-filter, HEPA filter, 10' (3m) polyethylene static resistant hose (1-12/738mm LD.), hose hanger, 12' NPT quick connects coupling, 20' (6.1m) air hose with swivel fitting, pressure gauge, and aluminum chip wand (drum not included)						
6199-30	30 Gallon Heavy Duty HEPA Vac System – same as Model 6199 except fits a 30 gallon drum (drum not included).						
6299	55 Gallon Deluxe Heavy Duty HEPA Vac System- same as Model 6199 plus drum dolly and heavy duty aluminium tools. Additional tools include 2 piece double bend wand, 12° (305mm) floor tool, 11° (279mm) crevice tool, 24° (610mm) crevice tool, skimmer tool with detachable brush, tool holder, and a 3-172′ (899mm) diameter dust brush with conductive bristles (drum not included).						
6299-30	30 Gallon Deluxe Heavy Duty HEPA Vac System - same as Model 6299 except fits a 30 gallon drum (drum not included).						
6399	55 Gallon Premium Heavy Duty HEPA Vac System - same as the Model 6299 and adds a 55 gallon drum.						
6399-30	30 Gallon Premium Heavy Duty HEPA Vac System - same as Model 6399 except includes a 30 gallon drum.						
6399-110	110 Gallon Premium Heavy Duty HEPA Vac System - same as Model 6399 except includes a 110 gallon drum.						
6097	Heavy Duty Dry Vac only - included in all systems listed above.						


	Accessories							
Model #	Description	Model #	Description					
901356	Replacement Pre-filter	9041	55 Gallon Drum Dolly					
901357	Replacement HEPA Filter	9041-30	30 Gallon Drum Dolly					
901373	Optional Filter Protector	901176	Magnetic Tool Holder					
901071	Heavy Duty Aluminum Tools plus Tool Holder	901069	55 Gallon Drum Only					
6580-20	20' (6.1m) Static Resistant Vacuum Hose	901069-30	30 Gallon Drum Only					

























## Vac-u-Gun™

## Vacuum, blow and transfer with no moving parts!

## Rugged die cast construction for industrial use!





A low cost solution to a wide variety of industrial housekeeping problems. The Vac-u-Gun is a vacuum gun, a blow gun and a transfer tool all in one. Lightweight and easy to use, the Vac-u-Gun has durable die cast construction with no moving parts to wear out.

#### Why The Vac-u-Gun?

The Vac-u-Gun uses less compressed air than an ordinary blow gun. It injects a small amount of compressed air through directed nozzles to produce a vacuum on one end and a high output flow on the other. The amplified output flow is 12 times the air consumption rate.

The Vac-u-Gun offers a more efficient way to blowoff, cool, dry and clean. In vacuum mode, work surfaces can be easily cleaned by vacuuming the debris away instead of blowing it off the surface only to sweep it up later. In blow mode, more surface area can be cleared in less time compared to ordinary air guns. Transferring materials over long distance is also possible using the smooth bore vacuum hose. Three Vac-u-Gun Systems are available.

#### **Applications**

- Vacuum shavings
- Vacuum absorbent
- Vacuum sawdust
- Vacuum spills
- · Transfer small parts
- Transfer pellets
- Transfer trim
- · Blow chips
- Blow water
- · Blow coolant
- · Blow scrap

#### **Advantages**

- Low cost
- · No moving parts maintenance free
- · Durable die cast construction
- · Switch from vacuum to blow mode in seconds
- · Safe no electricity
- · Meets OSHA pressure requirements
- · Vacuum or blowoff
- · Lightweight and portable

# Model 6392 Vac-u-Gun All Purpose System removes plastic shavings from a saw.

Model 6192 Vac-u-Gun Collection System

Model 6292 Vac-u-Gun Transfer System carries dust away from sensitive electronic

vacuums absorbent and chips.


- Versatile
- Quiet

#### Vac-u-Gun Specifications

Vac-u-Gun

Pres Sup	sure		umption						Soun
PSIG	BAR	SCFM	SLPM	"H2O	kPa	Ozs	Grams	Inlet	84
80	5.5	13	368	-29.5	-7	9	255	1/4 NPT	dBA*

\* Tested in "vacuum" mode with bag attached.



Reverse the direction of the nozzle insert to change from vacuum to blowoff

#### Versatile

In seconds, the Vac-u-Gun can be transformed from a powerful vacuum gun into an efficient blow gun or into a transfer tool for lightweight materials. Each Vac-u-Gun System comes complete with a set of attachments to suit numerous industrial applications.

Warning: Do not use with combustible dust.



In blow mode, the Vac-u-Gun consumes less air than ordinary blow guns.

#### Vac-u-Gun Systems



**Model 6192 Collection System** includes Vac-u-Gun, reusable bag, brush, crevice tool, skimmer tool and (2) extension wands.



Model 6292 Transfer System includes Vac-u-Gun, 10' (3m) vacuum hose, brush, crevice tool, skimmer tool and (2) extension wands.



Model 6392 All Purpose System includes Vac-u-Gun, reusable bag, 10' (3m) vacuum hose, brush, crevice tool, skimmer tool and (2) extension wands.




























## Deep Hole Vac-u-Gun



# Deep Hole Vac-u-Gun™

## Blow chips loose and vacuum them away in one step!

## Ideal for cleaning cavities and drilled holes!



#### What Is The Deep Hole Vac-u-Gun?



A low cost solution to quickly remove chips and contaminants from grooves, containers and drilled holes. The Deep Hole Vac-u-Gun is ideal for extracting chips/contaminants from grooves, containers and drilled holes where blow guns could create potentially hazardous flying debris. Simply position the Deep Hole Vac-u-Gun over the hole and press the trigger.

A small blow tube dislodges and lifts the chips while the large suction tube vacuums them away. The operator is protected from flying debris since all contaminants are contained within the clear suction tube. It is perfect for cleaning holes up to 1-1/4" (32mm) diameter at a depth of 18" (457mm).

#### Why The Deep Hole Vac-u-Gun?

The Deep Hole Vac-u-Gun uses less compressed air than an ordinary blow gun. It injects a small amount of compressed air through directed nozzles to produce a vacuum on one end and a high output flow on the other. The amplified output flow is 12 times the air consumption rate.

Lightweight and easy to use, the Deep Hole Vac-u-Gun has a durable die cast construction with no moving parts to wear out. A hanger is provided for easy storage or for mounting on a tool balancer.

#### **Applications**

#### Holes in fixtures

- Drilled plastics
- · T-slots groove cleaning
- · Coolant evacuation from parts
- Woodworking
- Container cleaning
- Tapped holes
- Cupped surfaces
- · Cavity evacuation
- · Bottle cleaning
- · Punch press tables

#### **Advantages** Low cost

- No moving parts maintenance free
- · Durable die cast construction
- · Eliminates shock hazard no electricity
- · Meets OSHA pressure and chip guard requirements
- · Safe operation no flying chips
- · Lightweight and portable
- Quiet
- · Low air consumption



Model 6394 Deep Hole Vac-u-Gun All Purpose System removes the chips from a drilled plastic part.



The Model 6194 Deep Hole Vac-u-Gun cleans the t-slots on a milling machine.



# EXAM



# Deep Hole Vac-u-Gun

# How The Deep Hole Vac-u-Gun Works

Compressed air, normally 80-100 PSIG (5.5 - 6.9 BAR), flows through the inlet (1) into an annular plenum chamber (2) when the trigger is depressed. A small amount of air is injected into the blow

tube (3) to provide lift for the chips or debris. The larger airflow is injected into the throat of the gun through directed nozzles (4). These jets of air create a vacuum at the intake (5) which draws

material in and accelerates it through the unit. The chips, debris or other particulates can then be exhausted into a filter bag or hose attached to the Deep Hole Vac-u-Gun System.

#### **Deep Hole Vac-u-Gun Specifications**


Sound Level	ium	Vacu	umption	Air Cons	Supply	Pressure Supply	
84	kPa	"H2O	SLPM	SCFM	BAR	PSIG	
dBA*	-8	-32	425	15	5.5	80	

"Tested in "vacuum" mode with bag attached

The Deep Hole Vac-u-Gun should not be operated without a filter bag or vacuum hose attached to the exhaust. Vacuum tools cannot be used with this product.

Warning: Do not use with combustible dust.

#### **Deep Hole Vac-u-Gun Systems**



Model 6094 Deep Hole Vac-u-Gun Only



Model 6194 Deep Hole Vac-u-Gun with Bag includes Deep Hole Vac-u-Gun and reusable bag.



Model 6394 Deep Hole Vac-u-Gun All Purpose System includes Deep Hole Vac-u-Gun, reusable bag and 10' (3m) vacuum hose.





















# Cold air to -50°F (-46°C) from your compressed air supply with no moving parts!



#### What Is A Vortex Tube?

A low cost, reliable, maintenance free solution to a variety of industrial spot cooling problems. Using an ordinary supply of compressed air as a power source, vortex tubes create two streams of air, one hot and one cold, with no moving parts. Vortex tubes can produce:

- Temperatures from -50° to +260°F (-46° to +127°C)
- Flow rates from 1 to 150 SCFM (28 to 4,248 SLPM)
- · Refrigeration up to 10,200 Btu/hr. (2,989 Watts)

Temperatures, flows and cooling power are adjustable over a wide range using the control valve on the hot end exhaust.

#### Why EXAIR Vortex Tubes?

EXAIR Vortex Tubes are constructed of stainless steel. The wear resistance of stainless steel, as well as its resistance to corrosion and oxidation, assures that EXAIR Vortex Tubes will provide years of reliable, maintenance-free operation.





A 1/4 ton of refrigeration in the palm of your hand!

- No moving parts
- · No electricity or chemicals
- · Small, lightweight
- Low cost
- Instant cold air
- · Durable stainless steel
- Adjustable temperature

#### Advantages

- Maintenance free

- · Interchangeable generators



A Model 3225 Vortex Tube keeps plastic

dishwasher arms cool during ultrasonic

Special high temperature vortex tubes

into a 1200°F (650°C) boiler porthole.


keep a boroscope lens cool while inserted

A pair of medium vortex tubes cool a solenoid coil after a welding operation.




#### **Vortex Tubes**

#### **How A Vortex Tube Works**



Compressed air, normally 80-100 PSIG (5.5 - 6.9 BAR), is ejected tangentially (1) through a generator into the vortex spin chamber (2). At up to 1,000,000 RPM, this air stream revolves toward the hot end (3) where some escapes through the control valve (4). The remaining air, still spinning, is forced back through the center of this outer vortex. The inner stream gives off kinetic energy in the form of heat to the outer stream and exits the vortex tube as cold air (5). The outer stream exits the opposite end as hot air (6). There is a detailed discussion of vortex tube history and theory later on page 205 in this section.

(4) Model 3250 Vortex Tubes cool the cutting knives in this pelletizer to prevent irregular shapes.



#### **Controlling Temperature** And Flow In A Vortex Tube

Cold airflow and temperature are easily controlled by adjusting the slotted valve in the hot air outlet. Opening the valve reduces the cold airflow and the cold air temperature. Closing the valve increases the cold airflow and the cold air temperature. The percentage of air directed to the cold outlet of the vortex tube is called the "cold fraction". In most applications, a cold fraction of 80% produces a combination of cold flow rate and temperature drop that maximizes refrigeration, or Btu/hr. (Watts), output of a vortex tube. While low cold fractions (less than 50%) produce lowest temperatures, cold airflow volume is sacrificed to achieve them.

Most industrial applications (i.e., process cooling, part cooling, chamber cooling) require maximum refrigeration and utilize the 32XX series Vortex Tube. Certain "cryogenic" applications (i.e., cooling lab samples, circuit testing) are best served by the 34XX series Vortex Tube.

Setting a vortex tube is easy. Simply insert a thermometer in the cold air exhaust and set the temperature by adjusting the valve at the hot end. Maximum refrigeration (80% cold fraction) is achieved when cold air temperature is 50°F (28°C) below compressed air temperature.



Model 3930 EXAIR Cooling Kit

If you are unsure of your flow and temperature requirements, EXAIR recommends the purchase of an EXAIR Cooling Kit. It contains a vortex tube, cold air muffler, compressed air filter and all generators required to experiment with the full range of airflows and temperatures.











Electronic component cooling

**Applications** 

Cooling electronic controls

Cooling CCTV cameras

Cooling soldered parts

Cooling gas samples

Cooling heat seals


Setting hot melts

Cooling machining operations

#### Selecting The Right Vortex Tube

EXAIR Vortex Tubes are available in three sizes. Each size can produce a number of flow rates, as determined by a small internal part called a generator. If Btu/hr. (Watts) requirements, or flow and temperature requirements are known, simply select the appropriate vortex tube according to the specification information shown below or the performance tables shown on the following page. Keep in mind that the vortex generators are interchangeable. If, for example, a Model 3215 Vortex Tube does not provide sufficient cooling, you need only change generators within the vortex tube to upgrade the flow rate from 15 to 25, 30 or 40 SCFM (425 to 708, 850 or 1,133 SLPM). Generator part numbers are shown in the "Accessories" listing on page 206.

#### **Vortex Tube Dimensions**



#### **Vortex Tube Specifications**

32XX series Vortex Tubes optimize temperature drop and airflow to produce maximum cooling power or Btu/ hr. (Watts). Specify 32XX series Vortex Tubes for most general cooling applications.

34XX series Vortex Tubes provide lowest cold air temperatures, but at low cold airflow (when less than a 50% cold fraction is used). Specify 34XX series Vortex Tubes only where temperatures below 0°F (-18°C) are desired.

	32XX	Series Vo	ortex Tube	Specifica	tions		34XX Series Vortex Tube Specifications						
Model	SCFM*	SLPM*	Btu/hr.**	Watts**	SIZE	dBA***	Model	SCFM*	SLPM*	Btu/hr.**	Watts**	SIZE	dBA**
3202	2	57	135	40	Small	68	3402	2	57			Small	67
3204	4	113	275	80	Small	70	3404	4	113	*****	*****	Small	69
3208	8	227	550	162	Small	76	3408	8	227	*****	*****	Small	75
3210	10	283	650	191	Medium	80	3410	10	283		*****	Medium	78
3215	15	425	1,000	293	Medium	81	3415	15	425	****	*****	Medium	80
3225	25	708	1,700	498	Medium	82	3425	25	708		*****	Medium	82
3230	30	850	2,000	586	Medium	84	3430	30	850		****	Medium	84
3240	40	1,133	2,800	821	Medium	88	3440	40	1,133	*****	*****	Medium	87
3250	50	1,416	3,400	997	Large	94	3450	50	1,416	*****	****	Large	93
3275	75	2,124	5,100	1,494	Large	96	3475	75	2,124	*****	****	Large	96
3298	100	2,832	6,800	1,993	Large	96	3498	100	2,832	****	*****	Large	96
3299	150	4,248	10,200	2,989	Large	97	3499	150	4,248	*****	*****	Large	96

- SCFM (SLPM) at 100 PSIG (6.9 BAR) Inlet Pressure

  \* Btu/hr. (Watts) Cooling Capacity at 100 PSIG (6.9 BAR)

  \*\* Noise levels taken with hot and cold mufflers installer

- SCFM (SLPM) at 100 PSIG (6.9 BAR) Inlet Pressure
  Not Applicable, 34XX series Vortex Tubes are not normally used in air conditioning applications.
  Noise levels taken with but and cold multiples installed.





#### **Vortex Tubes**

#### **Vortex Tube Performance**

The Vortex Tube Performance Tables below give approximate temperature drops (and rises) from inlet air temperature produced by a vortex tube set at each cold fraction. Assuming no fluctuation of inlet temperature or pressure, a vortex tube will reliably maintain temperature within ±1°F.

ressure Supply			Col	d Fraction	n %		
PSIG	20	30	40	50	60	70	80
20	62	60	56	51	44	36	28
20	15	25	36	50	64	83	107
40	88	85	80	73	63	52	38
40	21	35	52	71	92	117	147
60	104	100	93	84	73	60	46
60	24	40	59	80	104	132	166
	115	110	102	92	80	66	50
80	25	43	63	86	113	143	180
	123	118	110	100	86	71	54
100	26	45	67	90	119	151	191
120	129	124	116	104	91	74	55
120	26	46	69	94	123	156	195

Pressure Supply	Cold Fraction % (METRIC)								
BAR	20	30	40	50	60	70	80		
1.4	34.4	33.3	31.1	28.3	24.4	20.0	15.6		
1.4	8.3	13.9	20.0	28.3	35.6	46.1	59.4		
2	40.9	39.6	37.1	33.8	29.2	24.0	18.1		
4	9.8	16.4	24.0	33.3	42.6	54.6	69.5		
3	50.4	48.7	45.7	41.6	36.0	29.7	21.9		
•	12.0	19.9	29.6	40.3	52.3	66.5	83.5		
4	56.9	54.7	50.9	46.1	40.0	32.9	25.1		
7.	13.2	21.9	32.4	43.9	57.1	72.5	91.2		
5	61.6	59.0	54.8	49.4	43.0	35.4	26.9		
1	13.7	23.3	34.2	46.5	60.9	77.2	97.1		
6	65.4	62.7	58.2	52.7	45.6	37.6	28.6		
0	14.1	24.3	35.8	48.6	63.9	81.0	102.		
7	68.6	65.8	61.4	55.7	48.0	39.6	30.0		
	14.4	25.1	37.3	50.2	66.3	84.2	106.		
8	71.1	68.2	63.8	57.3	50,0	40.8	30.4		
	14.4	25.4	38.1	51.8	67.9	86.1	107.5		

Numbers in white area give temperature rise of hot air, 'F.

Back Pressure: The performance of a vortex tube deteriorates with back pressure on the cold air exhaust. Low back pressure, up to 2 PSIG (.1 BAR), will not change performance. 5 PSIG (.3 BAR) will change performance by approximately 5°F (2.8°C).

Filtration: The use of clean air is essential, and filtration of 25 microns or less is recommended. EXAIR filters contain a 5 micron element and are properly sized for flow.

Inlet Air Temperature: A vortex tube provides a temperature drop from supply air temperature (see Performance Charts above). Elevated inlet temperatures will produce a corresponding rise in cold air temperatures.

Noise Muffling: EXAIR offers mufflers for both the hot and cold air discharge. Normally, muffling is not required if the cold air is ducted.

Regulation: For best performance, use line pressures of 80 to 110 PSIG (5.5 to 7.6 BAR). Maximum pressure rating is 250 PSIG (17.2 BAR), minimum 20 PSIG (1.4 BAR).

#### **EXAIR Products Using Vortex Tubes**

Over the years, the basic vortex tube has been used in virtually hundreds of industrial cooling applications. A few have become so popular as to warrant the development

of an "applied product" designed to suit the specific application. These products include the Adjustable Spot Cooler, Mini Cooler, Cold Gun and Cabinet Coolers that can be found in this catalog.



#### **High Temperatures**

High temperature vortex tubes for ambient temperatures up to 200°F (93°C) are available. Standard vortex tubes are for ambient temperatures up to 125°F (52°C). Contact an Application Engineer at 1-800-903-9247 for details.

#### **Preset Vortex Tubes**

EXAIR can provide vortex tubes preset to any combination of flow and temperature desired. To prevent tampering with the desired setting, a drilled orifice that replaces the adjustable hot valve is available. For more information, please contact an Application Engineer.












#### **Cooling Vacuum Formed Parts**



The Problem: A manufacturer of major appliances vacuum forms the plastic interior shell of refrigerators. The deep draw of the plastic and complex geometry left the four corners unacceptably thin. The corners would tear during assembly or bulge when insulation was inserted between the shell and exterior housing, resulting in a high rejection rate.

The Solution: (4) Model 3225 Vortex Tubes were positioned to cool the critical corner areas just prior to forming the plastic sheet. By cooling these areas, less stretching of the plastic occurred which resulted in thicker corners.

Comment: Rejected parts become very costly, especially when expensive materials and slow process times are involved. The cold air from the vortex tube is just the solution for big problems like this one. It can supply "instant" cold air down to -50°F (-46°C) from an ordinary compressed air supply. Along with cooling other vacuum formed parts such as spas, bathtubs, tote pans and waste cans, it is ideal for cooling hot melts, ultrasonic welders, environmental chambers, etc.


This is an ideal application for EXAIR's EFC, an electronic flow control for compressed air, shown on page 7. It reduces air consumption by turning on the compressed air for a preset length of time, when sensing the plastic sheet is in position.

#### Cooling An Ultrasonic Weld

The Problem: A manufacturer of toothpaste seals the ends of plastic tubes with an ultrasonic welder prior to filling. As heat built up at the sealing jaw of the welder, release of the tubes was delayed. Tubes that were too hot would not seal resulting in a high rate of rejection.


The Solution: A Model 3215 Vortex Tube was used to direct cold air at the jaw of the welder. The cooling was transferred through the metal jaw to the tube seam while in the clamped position. Process time was reduced and rejected tubes were eliminated.

Comment: It amazes most people that the cooling from a small vortex tube can dramatically improve quality and throughput. The vortex tube is the low cost solution for cooling parts, chambers, heat seals and various processes. They're easy to use, can be adjusted to produce cold air down to -50°F (-46°C) and have no moving parts to wear out.



#### **Vortex Tubes**

#### **Cooling Blow Molded Fuel Tanks**




The Problem: Automobile fuel tanks are blow molded. then clamped to a fixture to prevent distortion during the cooling cycle. The cooling time of over 3 minutes required for each tank created a bottleneck in the production process.

The Solution: (2) Model 3250 Vortex Tubes were mounted to the cooling rack and connected to a compressed air line. Cold air produced by the vortex tubes was circulated inside the fuel tanks. Cooling time was reduced from three minutes to two minutes for each tank, improving productivity by 33%.

Comment: It's hard to imagine an application better suited to vortex cooling than this one. The vortex tubes' small size and light weight simplified mounting to the cooling rack. No moving parts assured reliability and maintenance-free operation in a hostile environment. Finally, the cold airstream was easily channeled to the fuel tank via the threaded cold air outlet. When the cooling problem includes the need for simplicity, reliability and compact design, a vortex tube is very often the best choice.

#### **Cooling Small Parts After Brazing**



The Problem: Air conditioner parts assembled on an automatic brazing machine must be cooled to handling temperature prior to removal. The machine was capable of brazing up to four hundred pieces per hour. However, the time required for the parts to cool severely limited the production rate. Water cooling was unacceptable from the standpoint of both housekeeping and part contamination.

The Solution: (2) Model 3230 Vortex Tubes (with cold air mufflers installed) were used to blow cold air on the parts after the brazing cycle. The vortex tubes were set at an 80% cold airflow (cold fraction) to produce maximum refrigeration. The parts were cooled from a brazing temperature of 1,450°F (788°C) to a handling temperature of 120°F (49°C) within 20 seconds, allowing the machine to operate at its maximum production rate.


Comment: Compared to conventional refrigeration or water cooling, vortex tubes offer a number of advantages: low cost, compact design, inherent reliability and cleanliness. These attributes make vortex tubes the cost effective choice for many small part cooling operations.



















#### A Phenomenon of Physics

The two questions we're most often asked about the vortex tube are, "How long has it been around?" and "How does the thing work?". Following is a brief history and theory of the vortex tube.

The vortex tube was invented quite by accident in 1928. George Ranque, a French physics student, was experimenting with a vortex-type pump he had developed when he noticed warm air exhausting from one end, and cold air from the other. Ranque soon forgot about his pump and started a small firm to exploit the commercial potential for this strange device that produced hot and cold air with no moving parts. However, it soon failed and the vortex tube slipped into obscurity until 1945 when Rudolph Hilsch, a German physicist, published a widely read scientific paper on the device.

Much earlier, the great nineteenth century physicist, James Clerk Maxwell, postulated that since heat involves the movement of molecules, we might someday be able to get hot and cold air from the same device with the help of a "friendly little demon" who would sort out and separate the hot and cold molecules of air.

Thus, the vortex tube has been variously known as the "Ranque Vortex Tube", the "Hilsch Tube", the "Ranque-Hilsch Tube", and "Maxwell's Demon". By any name, it has in recent years gained acceptance as a simple, reliable and low cost answer to a wide variety of industrial spot cooling problems.

A vortex tube uses compressed air as a power source, has no moving parts, and produces hot air from one end and cold air from the other. The volume and temperature of these two airstreams are adjustable with a valve built into the hot air exhaust. Temperatures as low as -50°F (-46°C) and as high as 260°F (127°C) are possible.

#### Theories abound regarding the dynamics of a vortex tube. Here is one widely accepted explanation of the phenomenon:

Compressed air is supplied to the vortex tube and passes through nozzles that are tangential to an internal counterbore. These nozzles set the air in a vortex motion. This spinning stream of air turns 90° and passes down the hot tube in the form of a spinning shell, similar to a tornado. A valve at one end of the tube allows some of the warmed air to escape. What does not escape, heads back down the tube as a second vortex inside the low-pressure area of the larger vortex. This inner vortex loses heat and exhausts through the other end as cold air.

While one airstream moves up the tube and the other down it, both rotate in the same direction at the same

angular velocity. That is, a particle in the inner stream completes one rotation in the same amount of time as a particle in the outer stream. However, because of the principle of conservation of angular momentum, the rotational speed of the smaller vortex might be expected by spinning skaters who can slow or speed up their spin by extending or drawing in their arms.) But in the vortex Angular momentum has been lost from the inner vortex. The energy that is lost shows up as heat in the outer vortex. Thus the outer vortex becomes warm, and the

to increase. (The conservation principle is demonstrated tube, the speed of the inner vortex remains the same. inner vortex is cooled.

#### **Vortex Tubes**

#### **EXAIR Cooling Kits** EXAIR Cooling Kits include a vortex tube, all generators, cold muffler, fitting, tubing and clips to duct cold air, and filter separator 3908 Cooling Kit up to 550 Btu/hr. (162 Watts), Small Size Cooling Kit up to 2,800 Btu/hr. (821 Watts), Medium Size

Cooling Kit up to 10:200 Btu/hr. (2.989 Watts), Large Size

	Vortex Tubes
Model #	Description
3202	Vortex Tube, 2 SCFM (57 SLPM), for max. refrigeration, 135 Btu/hr. (40 Watts), Small Size
3204	Vortex Tube, 4 SCFM (113 SLPM), for max. refrigeration, 275 Btu/hr. (80 Watts), Small Size
3208	Vortex Tube, 8 SCFM (227 SLPM), for max. refrigeration, 550 Btu/hr. (162 Watts), Small Size
3210	Vortex Tube, 10 SCFM (283 SLPM), for max. refrigeration, 650 Btu/hr. (191 Watts), Medium Size
3215	Vortex Tube, 15 SCFM (425 SLPM), for max. refrigeration, 1,000 Btu/hr. (293 Watts), Medium Size
3225	Vortex Tube, 25 SCFM (708 SLPM), for max. refrigeration, 1,700 Btu/hr. (498 Watts), Medium Size
3230	Vortex Tube, 30 SCFM (850 SLPM), for max. refrigeration, 2,000 Btu/hr. (586 Watts), Medium Size
3240	Vortex Tube, 40 SCFM (1,133 SLPM), for max. refrigeration, 2,800 Btu/hr. (821 Watts), Medium Size
3250	Vortex Tube, 50 SCFM (1,416 SLPM), for max. refrigeration, 3,400 Btu/hr. (997 Watts), Large Size
3275	Vortex Tube, 75 SCFM (2,124 SLPM), for max. refrigeration, 5,100 Btu/hr. (1,494 Watts), Large Size
3298	Vortex Tube, 100 SCFM (2,832 SLPM), for max. refrigeration, 6,800 Btu/hr. (1,993 Watts), Large Size
3299	Vortex Tube, 150 SCFM (4,248 SLPM), for max. refrigeration, 10,200 Btu/hr. (2,989 Watts), Large Size
3402	Vortex Tube, 2 SCFM (57 SLPM), for max. cold temperature, Small Size
3404	Vortex Tube, 4 SCFM (113 SLPM), for max. cold temperature, Small Size
3408	Vortex Tube, 8 SCFM (227 SLPM), for max. cold temperature, Small Size
3410	Vortex Tube, 10 SCFM (283 SLPM), for max. cold temperature, Medium Size
3415	Vortex Tube, 15 SCFM (425 SLPM), for max. cold temperature, Medium Size
3425	Vortex Tube, 25 SCFM (708 SLPM), for max. cold temperature, Medium Size
3430	Vortex Tube, 30 SCFM (850 SLPM), for max. cold temperature, Medium Size
3440	Vortex Tube, 40 SCFM (1,133 SLPM), for max. cold temperature, Medium Size
3450	Vortex Tube, 50 SCFM (1,416 SLPM), for max. cold temperature, Large Size
3475	Vortex Tube, 75 SCFM (2,124 SLPM), for max. cold temperature, Large Size
3498	Vortex Tube, 100 SCFM (2,832 SLPM), for max. cold temperature, Large Size
3499	Vortex Tube, 150 SCFM (4,248 SLPM), for max. cold temperature, Large Size

	Vortex Tube Accessories and Components
Model #	Description
3905	Cold Muffler for 2 through 8 SCFM (S7-227 SLPM) Vortex Tube, Small Size
3901	Cold Muffler for 10 through 40 SCFM (283-1,133 SLPM) Vortex Tube, Medium Size
3906	Cold Muffler for 50 through 150 SCFM (1,416 -4,248 SLPM) Vortex Tube Large Size
3903	Hot Muffler for 2 through 40 SCFM (57-1,133 SLPM) Vortex Tube, Small & Medium Size
3907	Hot Muffler for 50 through 150 SCFM (1,416-4,248 SLPM) Vortex Tube, Large Size
3909	Generator Kit for 2 through 8 SCFM (57-227 SLPM) Vortex Tube, Small Size
3902	Generator Kit for 10 through 40 SCFM (283-1,133 SLPM) Vortex Tube, Medium Size
3910	Generator Kit for 50 through 150 SCFM (1,416-4,248 SLPM) Vortex Tube, Large Size

Generator Kits ordered with a vortex tube include all generators for the specified tube. Permits setting the vortex tube for all capacities and styles.

Generator Only —Specify capacity (SCFM) and style ("R" for max. refrigeration, "C" for max. cold tempera

Example: 15-R = 15 SCFM Generator for max. refrigeration

	Accessories
Model #	Description
9001	Automatic Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)
9032	Automatic Drain Filter Separator, 1/2 NPT, 90 SCFM (2,549 SLPM)
9002	Automatic Drain Filter Separator, 3/4 NPT, 220 SCFM (6,230 SLPM)
9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)
9006	Oil Removal Filter, 3/4 NPT, 50-150 SCFM (1,416-4,248 SLPM)
9015	Valve and Thermostat Kit, 120V, 50/60Hz, 1/4 NPT, 40 SCFM (1,133 SLPM)

Other solenoid valves and thermostats available. Contact factory.

Note: Flow ratings shown (SCFM/SLPM) assume 100 PSIG (6.9 BAR) inlet pressure.

At other pressures, flow is proportional to absolute inlet pressure.





**Dual Vortex Tubes rapidly cooling milk** chocolate on a production line.





Order Direct

We Ship From Stock

ww.exair.com techelp@exair.com















## Adjustable Spot Cooler



# **Adjustable Spot Cooler**

## Cold air to -30°F (-34°C) from your compressed air supply for spot cooling!



#### What Is The Adjustable Spot Cooler?

A low cost, reliable, maintenance-free solution to a variety of industrial spot cooling problems. With the turn of a knob, you can select the temperature best suited to your application. The Adjustable Spot Cooler provides a precise temperature setting from -30°F (-34°C) to room temperature.

The Adjustable Spot Cooler incorporates a vortex tube that converts an ordinary supply of compressed air into cold air.

- It can produce temperatures from -30° to +70°F (-34° to +21°C)
- Parts included for flow rates of 15, 25, and 30 SCFM (425, 708 and 850 SLPM). 25 SCFM (708 SLPM) generator is factory installed.
- It can produce refrigeration up to 2,000 Btu/hr. (586 Watts)

A swivel magnetic base provides easy mounting and portability. Flexible tubing that holds its position directs the cold air. No moving parts or CFC's assures maintenance free operation.

#### Why The Adjustable Spot Cooler?

The Adjustable Spot Cooler is quiet (less than 75 dBA), easily set with a thermometer that will hold the temperature setting. It's ideal for applications where mist or liquid cooling cannot be used due to part contamination or cost. Tolerances, product finish and production rates can improve dramatically.

The Adjustable Spot Cooler is available with either a single point or dual point hose kit. The single point system (Model 3825) is recommended for cooling a small surface like solder joints, hot melts or drilled plastics. The dual point system (Model 3925) is recommended when heat is generated over a larger surface area.

#### **Applications**

- Adjusting thermostats
- Cooling solder
- Cooling machined plastics
- Setting hot melts
- Cooling welding horns
- Cooling molded plastics
- Electronic component cooling
- Cooling gas samples
- Cooling environmental chambers

EXAM

#### **Advantages**

- · No moving parts
- · No electricity or chemicals
- · Small, lightweight
- Low cost
- Maintenance free
- · Instant cold air
- · Quiet less than 75 dBA
- Swivel magnetic base
- · Interchangeable generators



PVC hose is cooled at the exit of an extruder so it can be coiled immediately.




The Adjustable Spot Cooler replaces flood coolant and eliminates hours of cleanup on a cast iron machining operation.



The Adjustable Spot Cooler maintains critical tolerances on machined plastic parts.





**How The Adjustable Spot Cooler Works** 

The Adjustable Spot Cooler incorporates a vortex tube to convert an ordinary supply of compressed air (1) into two low pressure streams, one hot and one cold. (For complete information on vortex tube operation, see page 200.) With the turn of a knob. the temperature control valve (2) allows some hot air to flow through a muffling sleeve and out the hot air exhaust (3). The opposite end provides a cold airstream (4) that is muffled and discharged through the flexible hose, which directs it to the point of use. The swivel magnetic base (5) provides easy mounting and portability.

#### **Specifications**

Pressure	Supply	Consu	ir mption	Sound Level
PSIG	BAR	SCFM	SLPM	dBA
100	6.9	15	425	72
100	6.9	25*	708	73
100	6.9	30	850	74

**Adjustable Spot Cooler** 

\* 25 SCFM (708 SLPM) generator is factory installed




The Model 3825 Adjustable Spot Cooler can produce temperatures from -30° to +70°F (-34° to +21°C).



Electronic components stay cool during a soldering operation.

#### **Dimensions**



#### Adjusting the Spot Cooler

The Adjustable Spot Cooler System can produce a full range of airflows and temperatures as determined by the knob setting and a small internal part called a generator. The generators control the SCFM (SLPM) of air consumption and are easily interchangeable.

The Adjustable Spot Cooler has a 25 SCFM (708 SLPM) generator installed that produces up to 1,700 Btu/hr. (498 Watts). If less cooling is desired, the 15 SCFM (425 SLPM) generator, which delivers 1,000 Btu/hr. (293 Watts), can be installed. If more cooling is needed, the 30 SCFM (850 SLPM) generator can be installed for up to 2,000 Btu/hr. (586 Watts).


#### Controlling the Cold Air

The Adjustable Spot Cooler gives instant cold air when filtered compressed air is supplied to it. Cycling on and off is a good way to save air. For on and off control, use a Model 9012 Manual Shutoff Valve. To turn the Adjustable Spot Cooler on with the machine, the Model 9020 Solenoid Valve may be used and wired through the machine control switch. The EFC electronic flow control shown on page 7 can also be used.



















## **Adjustable Spot Cooler**

#### **Testing Heat Tape Thermostats**



The Problem: A manufacturer of electrical heat tapes had a problem testing thermostats for accuracy. The heat tape is supposed to switch on when the outdoor temperature dips below 40°F to prevent pipes from freezing or ice from building up on a roof's edge. The liquid-tight thermostat of every tape had to be dipped into a bowl of ice water (thermometer checked at 36°F (2°C)) to make sure the indicator light

came on and the tape got warm. Summertime heat caused the water to heat up so quickly that more time was spent regulating the water temperature than testing thermostats.

The Solution: The water bath was replaced with a Model 3825 Adjustable Spot Cooler. Once set to their desired temperature of 36°F (2°C), it provided a stable temperature all day long without adjustment. Drying each heat tape was no longer required and testing was over in seconds.

Comment: The Adjustable Spot Cooler paid for itself in no time as a result of the increased productivity. In this case, the company used the included 15 SCFM (425 SLPM) generator which minimized the compressed air use, costing only 23 cents per hour of continuous use! When testing thermostats, cooling machined plastics, setting hot melts or controlling tolerances, the Adjustable Spot Cooler is the best choice.

#### **Adjustable Spot Cooler Systems**



Model 3825 Adjustable Spot Cooler System includes the Adjustable Spot Cooler, single point hose kit with cone and fan nozzle, swivel magnetic base, filter separator, 15 and 30 SCFM (425 and 850 SLPM) generators. (25 SCFM/708 SLPM generator installed.)

	Accessories and Components
Model #	Description
5901	Single Point Hose Kit (Included with 3825)
5902	Dual Point Hose Kit (Included with 3925)
9004	Auto Drain Filter Separator, 1/4 NPT, 43 SCFM (1,359 SLPM) (Included with 3825 and 3925)
9005	Oil Removal Filter, 3/8 NPT, 15 - 37 SCFM (425 - 1,048 SLPM)
9012	Manual Shutoff Valve, 1/4 NPT
9020	Solenoid Valve, 120V, 50/60Hz, 1/4 NPT, 40 SCFM (1,133 SLPM)



Model 3925 Adjustable Spot Cooler System includes the Adjustable Spot Cooler, dual point hose kit with cone and fan nozzles, swivel magnetic base, filter separator, 15 and 30 SCFM (425 and 850 SLPM) generators. (25 SCFM/708 SLPM generator installed.)

(Adjustable Spot Cooler with dual point hose kit is recommended when heat is generated over a larger surface area.)









# Mini Cooler

# Product Mini Cooler™

An INTELLIGENT

## Cool small parts and tools with clean, cold air!

## Prevent burning, melting or breakage!

#### What Is The Mini Cooler?

A proven way to reduce downtime and increase productivity on a variety of operations involving small parts where heat is a problem. EXAIR's Mini Cooler produces a stream of 20°F (-7°C) cold air to prevent heat build-up. The Mini Cooler is particularly effective on high speed operations to prevent burning, melting and heat related breakage. Operation is quiet (76 dBA) and there are no moving parts to wear out.

#### **Applications**

- · Small tool cooling
- Needle cooling
- Blade cooling
- Lens grinding

#### Advantages

- Low cost
- Increases production rates
- Improves tolerances
- · Quiet, compact

#### **Mini Cooler Systems**



#### **Model 3808** Mini Cooler System one cold outlet)

ncludes Mini Cooler, Single Point Hose Kit, Swivel Magnetic Base and Manual Drain Filter Separator with Mounting Bracket.



#### Model 3308 Mini Cooler System (two cold outlets)

includes Mini Cooler, Dual Point Hose Kit, Swivel Magnetic Base and Manual Drain Filter Separator with Mounting Bracket.

	Mini Cooler
	Mini Cooler
Model#	Description
3808	Mini Cooler System (one cold outlet) includes the Mini Cooler, swivel magnetic base, mini single point hose kit and manual drain filter with mounting bracket
3308	Mini Cooler System (two cold outlets) includes the Mini Cooler, swivel magnetic base, mini dual point hose kit and manual drain filter with mounting bracket



#### **Mini Cooler Specifications**


	ir mption		rature ut	Sound @ 3' (914mm)	
SCFM	SLPM	°F	°c	dBA	INLET
8	227	20	-7	76	1/4 NPT

Supply air at 100 PSIG (6.9 BAR) & 70°F (21°C)



The Mini Cooler incorporates a vortex tube to convert a small amount of compressed air into two low pressure streams, one moving within the other in opposite directions (see page 200). The two airstreams exchange heat, producing cold air from one end of the tube and hot air from the other. A flexible hose directs the cold airstream at the surface to be cooled.

#### **Dimensions**



	Accessories
Model #	Description
5904	Mini Cooler Single Point Hose Kit (Included with 3808)
5905	Mini Cooler Dual Point Hose Kit (Included with 3308)
9003	Manual Drain Filter Separator, 1/4 NPT (Included with 3808 and 3308)
9012	Manual Shutoff Valve, 1/4 NPT
9027	Oil Removal Filter, 1/4 NPT, 24 SCFM (680 SLPM)











# Cold Gun Aircoolant System COMPRESSED AIR Product

# **Cold Gun Aircoolant System™**



Replace messy mist systems - improve dry machining with clean, cold air!

#### What Is The Cold Gun Aircoolant System?



A new solution to an old problem. Heat build up on dry machining operations reduces tool life and machining rates. The Cold Gun Aircoolant System produces a stream of clean, cold air at 50°F (28°C) below supply air temperature. Operation is quiet and there are no moving parts to wear out. It will remove heat to prolong tool life and increase productivity on machining operations when liquid coolants cannot be used.

The Cold Gun is also an alternative to expensive mist systems. It eliminates the costs associated with the purchase and disposal of cutting fluids and worker related health problems from breathing airborne coolants or slipping on wet floors.

EXAIR's Cold Gun is non-adjustable to prevent freeze-up during use. Cold airflow and temperature drop are factory set to optimize the gun's cooling capability.

#### **Applications**

- Tool sharpening
- · Drill and cutter grinding
- · Routing
- · Plunge and form grinding
- Milling
- Surface grinding
- Drilling
- · Tire grinding
- Band sawing
- · Plastic machining
- Laser cutting
- · Chill rolls · Setting hot melt adhesives

#### **Advantages**

- Improves production rates
- · Prevents burning
- · Extends tool life reduces breakage
- · Improves tolerance control
- · Prevents smearing of metal or plastics
- · Finished part is dry
- · Eliminates wheel loading
- Low cost
- · Compact, lightweight, portable
- · No moving parts maintenance free Quiet
- No coolant cost
- · No electricity

# life by 50%.



The Model 5215 Cold Gun keeps the part cool to the touch and prevents discoloration.



Cold air eliminates heat cracking of the carbide tool during sharpening.



The Model 5315 Cold Gun cools a two flute 3/8" carbide cutter on a CNC, increasing tool

## **Cold Gun Aircoolant System**

#### **Applications**



Model 5215 Cold Gun System

#### **Tool Grinding**

Cold air eliminates heat cracking of carbide and tool edge burning during grinding and sharpening operations. Increased tool life between regrinds is the result.



Model 5215 Cold Gun System

#### Milling & Drilling

Fly cutters up to 460mm in diameter have been cooled with the Cold Gun. Dissipating heat with cold air extends tool life, increases speeds and feeds, and improves finishes.



Model 5315 Cold Gun System

#### **Chill Roll**

Cooling a roll with 20°F (-7°C) air keeps the material on the surface from bunching up, jamming or tearing. The metal surface transfers the cold temperature to the product.



Model 5230 High Power Cold Gun System

#### **Laser Cutting**


Cold air cools a laser cut part so it can be handled seconds later. The High Power Cold Gun has twice the cooling capacity of the standard Cold Gun, cooling the part in less time.



















## **Cold Gun Aircoolant System**




The standard Cold Gun and High Power Cold Gun incorporate a vortex tube to convert an ordinary supply of compressed air (1) into two low pressure streams, one hot and one cold. (For complete information on vortex tube operation, see page 200 of this catalog.) Secondary air is drawn in (2). The Cold Gun's hot airstream is muffled and discharged through the hot air exhaust (3). The cold air (4) is muffled and discharged through the flexible hose (5), which directs it to the point of use. Easy mounting and portability are provided through the use of an attached magnetic base (6).

#### Specifications

	Pressure	Supply	Air Cons	umption	Sound Level
Model #	PSIG	BAR	SCFM	SLPM	dBA
Cold Gun 5215, 5315	100	6.9	15	425	70
High Power Cold Gun 5230, 5330	100	6.9	30	850	82

#### **Cold Gun Dimensions**



#### Controlling the Cold Air

The EXAIR Cold Gun gives instant cold air when filtered compressed air is supplied to it. Cycling on and off is a good way to save air. For on and off control, use a Model 9012 Manual Shutoff Valve. To turn the Cold Gun on with the machine, a solenoid valve may be used and wired through the machine control switch. This method is ideal for hand grinders and drill sharpeners.

#### The Compressed Air Supply

The Cold Gun is designed to use full line pressure of 80-100 PSIG (5.5-6.9 BAR). Temperature drop and flow are reduced when lower input pressures are applied. The use of clean, filtered air is essential to the operation of the Cold Gun. A filter separator that removes moisture, dirt and other particulates from the compressed air is included with each Cold Gun System. An optional Oil Removal Filter is also available. (See page 231 for details.)

#### Selecting The Right Model

Cold Gun Aircoolant Systems are available with either a Single Point or Dual Point Hose Kit.



the Model 5315 Cold Gun and Model 5330 High Power Cold Gun) is recommended for applications where the heat is generated over a larger surface area such as band sawing, milling, chill rolls and hot melt adhesives.

A Cold Gun System with the Model 5901 Single Point Hose Kit can be easily converted to a "dual point" system with the purchase of the Model 5902 Dual Point Hose Kit.

#### **Need More Cooling?**

EXAIR's High Power Cold Gun Aircoolant System™ produces twice the airflow of the standard Cold Gun, doubling the cooling capability. It produces cold air at 50°F (28°C) below the supply air temperature so the air is as cold as possible without freezing up. Two systems are available: the Model 5230 High Power Cold Gun with Single Point Hose Kit and Model 5330 High Power Cold Gun with Dual Point Hose Kit.





#### **Cold Gun Aircoolant System**

#### **Purdue University Study Confirms Benefits** Of The EXAIR Cold Gun

Tooling costs a lot of money to replace. That's only part of the problem. As the tools wear out, you can expect:

- · Slowed production and downtime to change out the tooling
- · Poor tolerances and decreased dimensional accuracy due to increased temperature
- · Increased cutting force is required (generates more heat and uses more electricity)

If you could just make the tooling last longer, you'd not only cut the tool cost but could increase profits by reducing scrapped parts and downtime.


A long term study on the effect of refrigerated air on tool wear in wood machining was conducted at the Forestry Products Department of Purdue University by Ms. Judith Gisip. The project was under the direction of Dr. Rado Gazo (department professor) and Harold Stewart



turns (22) 4'x8'







Cold air from EXAIR's Model 5315 Cold Gun System keeps the tooling cool.

(professor at North Carolina State University with 35 years in wood machining research). Wood is brutal on tooling. In metalworking, most of the heat goes away with the machined chip. Wood is an excellent insulator and doesn't conduct the heat away, which keeps it all there at the tool. Temperatures can exceed 1472°F (800°C)!

The extensive tests at Purdue were conducted in a 70°F climate controlled room. They tested (4) 1/2" (12.7mm) two-flute cutters on a CNC router at 16,000 rpm. (22) sheets of 3/4" thick MDF (medium density fiberboard) were fed one at a time, cutting away 1/4" (6mm) depth of cut on each pass. Power consumption of the CNC was recorded (current draw increases as the tool starts to dull). When finished, the surface of the tools was examined using a scanning electron microscope. Machining with the Cold Gun's 20°F air reduced tool wear by over 21% compared to the results with no cooling.

For complete details of the Purdue study, visit our web site at www.exair.com/purdue.htm.

#### How Much Can You Save?

- · A 1/2" two flute router bit for wood is approximately \$67.
- · The 21% reduction in tool wear when using a Cold Gun is  $$67 \times 0.21 = $14.07$  savings per bit.
- · If you use (1) router bit per working day, the savings is \$14.07 x 5 working days = \$70.35 per week / \$3,658 per year

#### **Cold Gun Aircoolant Systems**





includes Cold Gun, Single Point Hose Kit, 3/8" (10mm) Cone Nozzle, 1-1/4" (32mm) Fan Nozzle, Manual Drain Filter Separator



Model 5315 **Cold Gun System** (two cold outlets)

includes Cold Gun, Dual Point Hose Kit, (2) 1/4" (6mm) Cone Nozzles, (2) 1" (25mm) Fan Nozzles, Manual Drain Filter Separator.



Cold Gun System (one cold outlet) includes High Power Cold Gun. Single Point Hose Kit, 3/8" 10mm) Cone Nozzle, 1-1/4" (32mm) Fan Nozzle, Automatic Drain Filter Separator.

Model 5230 High Power



Model 5330 High Power **Cold Gun System** (two cold outlets) includes High Power Cold Gun, Dual Point Hose Kit, (2) 1/4" (6mm) Cone Nozzles, (2) 1" (25mm) Fan Nozzles, Automatic Drain Filter Separator.

#### A Dual Point Hose Kit is recommended when heat is generated over a larger surface area.

	Accessories	and Compon	ents
Model#	Description	Model #	Description
5015	Cold Gun Only	9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)
5030	High Power Cold Gun Only	9012	Manual Shutoff Valve, 1/4 NPT
5901	Single Point Hose Kit (Included with 5215 and 5230)	9020	Solenoid Valve, 120V, 50/60Hz, 1/4 NPT, 40 SCFM (1,133 SLPM)
5902	Dual Point Hose Kit (Included with 5315 and 5330)	9021	Solenoid Valve, 200-240V, 50/60Hz, 1/4 NPT, 40 SCFM (1,133 SLPM)
9003	Manual Drain Filter Separator, 1/4 NPT, 27 SCFM (765 SLPM)	9031	NEMA 4/4X Solenoid Valve, 24VDC, 1/4 NPT, 40 SCFM (1,133 SLPM)
9004	Automatic Drain Filter Separator, 1/4 NPT, 43 SCFM (1,359 SLPM)		











# Cabinet Cooler® Systems CompressED Air Product



# **Cabinet Cooler® Systems**

Stop electronic control downtime due to heat, dirt, and moisture!

Cabinet Coolers maintain NEMA 4, 4X, and 12 integrity.

All Cabinet Coolers are LISTED , CULJUS and/or ( compliant!

#### What is an EXAIR Cabinet Cooler System?



A low cost, reliable way to cool and purge electronic control panels. **EXAIR Cabinet Coolers incorporate** a vortex tube to produce cold air from compressed air - with no moving parts. The compact Cabinet Cooler can be installed in minutes through a standard electrical

knockout. NEMA 12, 4, and 4X (IP54 and IP66) Cabinet Coolers that match the NEMA rating of the enclosure are available in many cooling capacities for large and small control panels.

#### Why EXAIR Cabinet Cooler Systems?

The vortex tubes incorporated in the EXAIR Cabinet Coolers are constructed of stainless steel. The wear, corrosion and oxidation resistance of stainless steel assures long life and maintenance free operation. All Cabinet Coolers are UL Listed, UL Classified and/ or CE compliant.

#### **Applications**

- Programmable controllers
- Line control cabinets
- Motor control centers
- Relay panels
- NC/CNC systems
- Modular control centers
- CCTV cameras
- Computer cabinets
- Laser housings
- Electronic scales
- Food service equipment

EXAIR

#### Advantages

- Low cost
- Compact
- Cooling capacities to 5,600 Btu/hr. (1,641 Watts)
- Quiet
- · Install in minutes
- · Maintain NEMA 12, 4 and 4X integrity (IP54 and IP66)
- · Stabilize enclosure temperature and humidity
- · No CFC's
- · No moving parts-maintenance free
- · Mount in standard electrical knockout

Stop nuisance tripping

DON'T DO THIS

It is an OSHA violation that

presents a shock hazard to

The fan blows hot, humid,

dirty air at the electronics

personnel

- Stop heat damage
- · Eliminate fans and filters
- Eliminate lost production
- · Stop circuit drift
- · Stop dirt contamination
- · Provide washdown protection

#### **Special Cabinet Coolers**

- · High temp. models for ambients up to 200°F (93°C) available
- · Type 316 stainless steel available
- Purge models for non-hazardous locations available

# **Cabinet Cooler® Systems**

#### **How The Cabinet Cooler Works**



Compressed air enters the vortex tube powered Cabinet Cooler and is converted into two streams, one hot and one cold. (For more information on vortex tube operation, see page 200.) Hot air from the vortex tube is muffled and exhausted through the vortex tube exhaust. The cold air is discharged into the control cabinet through the cold air distribution kit. The displaced hot air in the cabinet rises and exhausts to atmosphere through the cabinet air exhaust at a slight positive pressure. Thus, the control cabinet is both cooled and purged with cool, clean air. Outside air is never allowed to enter the control panel.

## Selecting The Right Model - Know Your System Options

Each different NEMA rated Cabinet Cooler system is available with a thermostat control or as a continuous operation system. Each of these systems will include a water-dirt filter separator to prevent water condensate and dirt from entering your enclosure, and a cold air distribution kit used to direct the air for circulation or on to hot spots. EXAIR also manufactures Cabinet Cooler systems for difficult environments. We have provided additional information on our Cabinet Cooler systems suitable for high temperature environments, Non-Hazardous purge environments, Type 316SS material coolers for highly corrosive environments, Hazardous Location and ATEX environments.

# Mounting

The Cabinet Cooler mounts to the enclosure through a drilled hole or electrical knockout. The NEMA 12 (IP54) Cabinet Coolers may be mounted on the top or side of the panel. NEMA 4 and 4X (IP66) Cabinet Coolers must be mounted on the top of the panel or on the side of the panel using one of our Side Mount Kits (See page 225).



**Cabinet Cooler** Systems with **ETC** provide temperature control.

#### **NEMA Rating**

The first step to solving your overheating problem is to identify the NEMA integrity your enclosure will require. At right is an explanation to help you determine which NEMA integrity Cabinet Cooler system we should ship to you.

#### Thermostat Control

The thermostat control systems are the most efficient way to operate a Cabinet Cooler. They save air by activating the cooler only when internal temperatures approach critical levels. Thermostat controlled cooler systems are the best option when experiencing fluctuating heat loads caused by environment or seasonal changes. The standard thermostat control systems include an adjustable thermostat factory set at 95°F (35°C).

#### **Environmental Considerations**


NEMA 12 (IP54) Cabinet Coolers (dust-tight, oil-tight) are ideal for general industrial environments where no liquids or corrosives are present.

NEMA 4 (IP66) Cabinet Coolers (dust-tight, oil-tight, splash resistant, indoor/outdoor service) incorporate a low pressure relief valve for both the vortex tube and cabinet air exhaust. This valve closes and seals when the cooler is not operating to maintain the integrity of a NEMA 4 enclosure.

NEMA 4X (IP66) Cabinet Coolers offer the same protection as NEMA 4 but are constructed of stainless steel for food service and corrosive



Systems with thermostat control include a Cabinet Cooler, thermostat, solenoid valve, cold air distribution kit and filter.


















#### Selecting The Right Model - Know Your System Options (continued)

#### **ETC™ Electronic Temperature Control**

EXAIR's digital ETC (Electronic Temperature Control) provides precise temperature control for your electrical enclosure. It can accurately maintain a constant temperature that is slightly under the maximum rating of the electronics, permitting just enough cooling for the electronics without going so cold as to waste compressed air. The LED readout of the ETC displays the internal temperature of the

electrical enclosure (°F or °C) that is constantly being monitored by a quick response thermocouple. The control activates the solenoid valve (included) when the temperature setting is exceeded. The polycarbonate plastic enclosure of the ETC is suitable for NEMA 12, 4 and 4X environments. (Cabinet Cooler not included.)

Model	Voltage	Sample Rate	Max Temp	Solenoid Valve	Setting Temp	Supply Current	Sensor
9238	120VAC, 50-60 Hz	1/sec.	158°F (70°C)	¼ NPT	Push Button	250 mA max	Type J Thermocouple
9258	120VAC, 50/60 Hz	1/sec.	158°F (70°C)	1/2 NPT	Push Button	325 mA max	Type J Thermocouple
9239	240VAC, 50/60 Hz	1/sec.	158°F (70°C)	14 NPT	Push Button	165 mA max	Type J Thermocouple
9259	240VAC, 50/60 Hz	1/sec.	158°F (70°C)	1/2 NPT	Push Button	215 mA max	Type J Thermocouple

ETC controls are available within Cabinet Cooler Systems (see pages 222-224) or separately for retrofitting on existing coolers. All ETC enclosures are NEMA 4X (IP66), UL508 and UL94-5V. ETCs are RoHS and CE compliant.



ETC (Electronic Temperature Control) units are available in four different models, See

#### **Continuous Operation**

Also available in any of our NEMA ratings, continuous operation Cabinet Cooler systems are recommended when constant cooling and constant positive purge are desirable.



HT

Systems for continuous operation include a Cabinet Cooler, cold air distribution kit and filter.

#### **Special Cabinet Coolers**

EXAIR manufactures special NEMA 12 (IP54), 4 (IP66) and 4X (IP66) Cabinet Coolers suited to specific environmental requirements:

High Temperature Cabinet Coolers (shown top right) for ambient temperatures of 125° to 200°F (52° to 93°C) are available. Internal components can withstand high temperatures (like those near furnaces, ovens, etc.).

Non-Hazardous Purge Cabinet Cooler Systems (shown middle right) are ideal for dirty areas where contaminants might normally pass through small holes or conduits. Under normal conditions, the NHP Cabinet Cooler Systems provide a slight positive pressure in the enclosure by passing 1 SCFM (28 SLPM) of air through the cooler, when the solenoid valve is in the closed position. When the thermostat detects high temperature, it energizes the solenoid valve to pass full line pressure and volume of compressed air to the Cabinet Cooler, giving it full cooling capability.

Type 316 Stainless Steel NEMA 4X Cabinet Coolers (shown bottom right) are suitable for food service, pharmaceutical, harsh and corrosive environments, and other applications where 316SS is preferred. Capacities from 275 to 5,600 Btu/ hr. (80 to 1.641 Watts) are available.

EXAIR High Temperature Cabinet Coolers, Non-Hazardous Purge Cabinet Coolers and Type 316 Cabinet Coolers are now available from stock.









## **Cabinet Cooler® Systems**

Filtration: EXAIR Cabinet Cooler Systems include a 5 micron automatic drain water and dirt filter. This filter is critical for protection of electronics from water and dirt in the compressed air line. If oil is present in the compressed air, a coalescing (oil removal) filter, such as EXAIR Model 9005 is recommended. (See page 231)

Inlet Air Temperature: Cabinet Cooler Systems provide a 50°F (28°C) temperature drop from supply air temperature when the inlet pressure is 80 PSIG (5.5 BAR). Elevated inlet temperature will produce a corresponding rise in cold air temperature and reduction in cooling capacity. Low air pressures will also reduce the cooling capacity.

Humidity: For a continuous operating Cabinet Cooler System, relative humidity inside the enclosure stabilizes at 45%. No moisture condenses inside the enclosure. (The enclosure must be sealed to prevent condensation.)



#### Cold Air Distribution Kit:

The kit includes a length of flexible vinyl tubing used to direct the cold air for circulation, or to hot spots. Tubing connectors and adhesive backed clips to hold the tubing in place are provided.



#### Solenoid Valve and Thermostat:

Cabinet Cooler Systems with thermostat control include a solenoid valve and thermostat that limit the flow of compressed air to only cool when needed. The thermostat is factory set at 95°F (35°C). It will normally hold ±2°F (1°C) inside the cabinet. Solenoid valves are available in 120V, 60Hz; 110V, 50Hz; 240V. 50/60Hz and 24VDC. All solenoids are CSA Certified and UL Listed or Recognized.







#### **Heat Can Stop Your Machines**

When hot weather causes the electronics inside a control cabinet to fail, there is a panic to get the machinery up and running again. There are several cooling options out there and it's important to know the facts.



#### A. Heat Exchangers and Heat Pipes

These have serious limitations. On hot summer days when the temperatures of the room and inside of the enclosure are about equal, there's not enough difference for effective heat exchange.

- · They fail when dust and dirt clog the filter
- · The cooling capacity is limited due to ambient conditions



These coolers are prone to failure in dirty, industrial environments when dust and dirt clog the filter.

- · It takes almost a day to install
- · Vibration from machinery causes refrigerant leaks and component failures



#### **EXAIR Cabinet Cooler® Systems**

EXAIR has a complete line of Cabinet Cooler Systems to dependably cool and purge your electrical enclosures. They convert an ordinary supply of compressed air into clean, cold 20°F (-7°C) air. They mount in minutes through an ordinary electrical knockout and have no moving parts to wear out. The compressed air filtration that is provided keeps water, oil and other contaminants out of the enclosure.

- · There is no room air filter to clog
- An accurate electrical thermostat control minimizes compressed air use
- · All Cabinet Coolers are UL Listed, UL Classified and/or **CE Compliant**
- They are the only compressed air powered coolers that are **CE** compliant







#### Sizing Guide - Let us do the work

On the following page, EXAIR provides a simple guide to fill in and send to us so we may do the heat load calculations for you and specify a Cabinet Cooler system. You may e-mail the information to techelp@exair.com, call 1-800-903-9247, fill out an online form at exair.com/sizing, use our new calculator at https://exair.co/cccalc\_ca or fax the information to 1-866-329-3924.

#### **How To Calculate Heat Load for Your Enclosure**

If you would like to determine the correct model for your enclosure without our assistance, it is first necessary to determine the total heat load to which the control panel is subjected. This total heat load is the combination of two factors — heat dissipated within the enclosure and heat transfer from outside the enclosure.

#### To Calculate Btu/hr.:

- 1. First, determine the approximate Watts of heat generated within the enclosure. Watts x 3.41 = Btu/hr.
- 2. Then, calculate outside heat transfer as follows:
  - a. Determine the area in square feet exposed to the air, ignoring the top of the cabinet.
  - b. Determine the temperature differential between maximum surrounding temperature and desired internal temperature. Then, using the Temperature Conversion Table (below), determine the Btu/hr./ft.² for that differential. Multiplying the cabinet surface area times Btu/hr./ft.² provides external heat transfer in Btu/hr.
- 3. Add internal and external heat loads for total heat load.

Temperature Differential °F	Btu/hr./ft.2
5	1.5
10	3.3
15	5.1
20	7.1
25	9.1
30	11.3
35	13.8
40	16.2

After picking which NEMA integrity you need, choosing your options and calculating your heat load -go to page 222-224 to specify a model number.

See page 226 for HazLoc Cabinet Coolers. See page 228 for ATEX Cabinet Coolers.

OR Cor

Contact EXAIR and we'll walk you right through it.

#### To Calculate Watts:

- 1. First, determine the approximate Watts of heat generated within the enclosure.
- 2. Then, calculate outside heat transfer as follows:
  - a. Determine the area in square meters exposed to the air, ignoring the top of the cabinet.
  - b. Determine the temperature differential between maximum surrounding temperature and desired internal temperature. Then, using the Metric Temperature Conversion Table (below), determine the Watts/m² for that differential. Multiplying the cabinet surface area times Watts/m² provides external heat transfer in Watts.
- 3. Add internal and external heat loads for total heat load.

Temperature Conversion Table (METRIC)					
Temperature Differential °C	Watts/m²				
3	5.2				
6	11.3				
9	17.6				
12	24.4				
15	31.4				
18	39.5				
21	47.7				

#### Example:

Internal heat dissipation: 471 Watts or 1,606 Btu/hr. Cabinet area: 40 ft.<sup>2</sup>

Maximum outside temperature: 110°F Desired internal temperature: 95°F

The conversion table (above) shows that a 15°F temperature differential inputs 5.1 Btu/hr./ft.²

40 ft.2 x 5.1 Btu/hr./ft.2 = 204 Btu/hr. external heat load.

Therefore, 204 Btu/hr. external heat load plus 1,606 Btu/hr. internal heat load = 1,810 Btu/hr. total heat load or Btu/hr. refrigeration required to maintain desired temperature.

In this example, the correct choice is a 2,000 Btu/hr. Cabinet Cooler System. Choose a Cabinet Cooler model by determining the NEMA rating of the enclosure (type of environment), and with or without thermostat control.

#### Evample

Internal heat dissipation: 471 Watts Cabinet area: 3.7m<sup>2</sup>

Maximum outside temperature: 44°C Desired internal temperature: 35°C

The conversion table (above) shows that a 9°C temperature differential inputs 17.6 Watts/m².

3.7m<sup>2</sup> x 17.6 Watts/m<sup>2</sup> = 65.1 Watts external heat load.

Therefore, 65.1 Watts external heat load plus 471 Watts internal heat load = 536.1 Watts total heat load or Watts of refrigeration required to maintain desired temperature.

In this example, the correct choice is a 586 Watt Cabinet Cooler System. Choose a Cabinet Cooler model by determining the NEMA rating of the enclosure (type of environment), and with or without thermostat control.

# Cabine







# **EXAMP** Cabinet Cooler System Sizing Guide

#### Deliver your Data - Receive a Quote

Use this form to gather the information necessary to specify a Cabinet Cooler System and choose a delivery method below.













www.exair.com/sizing.htm

https://exair.co/qr-pro-ccsg

Online chat with us at csg www.exair.com Calculate Yourself https://exair.co/04-CCcalc

Send Us The Facts!

# **Cabinet Cooler Sizing Guide**

From:	Name	In a hurry? For help NOW, call
rion.	) (1) (1) (1) (1) (1) (1) (1) (1) (1) (1	our Application Engineering Department at 1-800-903-9247
		You can fill this form out online at:
	Phone number	Ext.# www.exair.com/sizing.htm
	E-mail	
T	D	1. Height (H) 2. Width (W) 3. Depth (D)
		4. *External air temperature now?°F or °C
н		5. *Internal air temperature now?°F or °C
ï	11	6. Maximum external air temperature possible?°F or °C
		7. Maximum internal air temperature desired?°F or °C
		8. My cabinet rating is: NEMA 12 NEMA 4 NEMA 4X
	w	Other (explain)
		9. My cabinet is in an area with a hazardous classification: YES NO
	1-800-903-9247	10. My cabinet is in an explosive environment: YES NO
	OIREC	11. My cabinet is (check all that apply):   Vented - outside air circulates through the enclosure
	Using a "Temperature Gun" or infrared	Not Vented - outside air does not circulate through the enclosure
	hermometer will result in measuring urface temperatures.	Wall mounted
A cr th	ir temperatures are needed for the cabinet coling calculations. Please use a standard hermometer or thermocouple to measure he air temperature.	Fan(s)/Vent(s) - Indicate diameter or SCFM Number of fans/vents
- 1	ie an temperature.	12. Available voltage for thermostat control: 24 VDC 110 VAC 240 VAC
	man and a second	







#### Cabinet Coolers Keep Working at Full Capacity After Seven Years of Near Constant Operation

The Problem: A manufacturer of automotive radiators had a problem relating to an overheated motor drive which caused one of their two production lines to come to a stop. They used a refrigerant based air conditioner set on the panel, but the air conditioner began leaking water into the panel. The water got into the motor drive, shorted it out and caused the production line to go down. Not only was production down for 1 month, but the motor drive cost them \$20,000 to replace by the time they purchased, had it shipped and got it installed.



The Solution: The manufacturer was unsure of what they were going to use for an air conditioning unit because the motor drives had to stay cool. They purchased EXAIR's Model 4330 NEMA 12 2.000 Btu/hr. (586 Watts) Cabinet Cooler System with thermostat control for the panel. The Cabinet Cooler System worked perfectly at solving the cooling problem.

Seven years later, this manufacturer contacted EXAIR for another application. They mentioned the old EXAIR Cabinet Cooler system still on the motor drive panel,

cranking out cold air. No maintenance had been performed on the Cabinet Cooler System in that time (as none was necessary) even though the environment was quite dirty. It was still working perfectly!



Comment: When we talk to customers about the EXAIR Cabinet Cooler Systems, one of their initial concerns is how long they last. With a source of clean/dry compressed air, the life span of a Cabinet Cooler can easily be in the range of 20 years or more, since there are no moving parts to wear out. In that time frame, you could have to purchase four refrigerant based units, pay to have them changed out and pay for them to be maintained 2 - 4 times per year, changing filters, replacing compressors, and re-charging refrigerant. Not only does the Cabinet Cooler last a long time, but when it is operating, it produces a positive pressure inside the panel which keeps dust and debris from getting inside your cabinet over time.

#### Cooling in a Hostile Environment



The Problem: A traditional refrigerant based air conditioner was installed on wastewater clarifier controls but could not withstand the harsh chemical environment of the wastewater industry. Controls on a wastewater clarifier process were mounted outdoors and experienced weather related overheating problems in the hotter months of the year. Not only did higher temperatures compromise the performance of the traditional refrigerant based air conditioner. the corrosive environment from the many different wastewater chemicals, acids and bases prematurely wore the critical moving parts of the air conditioner.

The Solution: A Model 4850SS-316 Cabinet Cooler System provided 3,400 Btu/hr, (997 Watts) of cooling for the clarifier controls and kept them running efficiently. The Cabinet Cooler is resistant to seasonal temperature fluctuations because it operates from a source of compressed air and not ambient air. The 316SS construction also provided high corrosion resistance to the chemical environment. Since EXAIR Cabinet Coolers have no moving parts, another maintenance concern was eliminated.

Comment: The inherent reliability of the vortex tube operated Cabinet Cooler System is another important advantage in this application. Because they have no moving parts, EXAIR Cabinet Coolers are virtually impervious to hostile environments. Wastewater treatment, chemical processing, paper manufacturing, steel mills and power generation are just a few of the facilities benefitting from this simple, yet effective technology.

#### **Cabinet Cooler® Systems**

#### NEMA 12 (IP54) Cabinet Cooler Systems

	120V Thermostat Control	ETC 120V Thermostat Control Model #	ETC 240V Thermostat Control Model #	High Temp Thermostat Control Model #	Non-Hazardous Purge Thermostat Control	Capa	icity*	Sound level dBA
	Model #	Control Model #	Control Model #	Control Model #	Model #	Btu/Hr	Watts	ievel dbA
	4304	4304-ETC120	4304-ETC240	N/A	NHP4304	275	80	59**
	4308	4308-ETC120	4308-ETC240	N/A	NHP4308	550	162	67**
	4315	4315-ETC120	4315-ETC240	HT4315	NHP4315	1,000	293	73**
NEMA 12	4325	4325-ETC120	4325-ETC240	HT4325	NHP4325	1,700	498	74**
(IP54)	4330	4330-ETC120	4330-ETC240	HT4330	NHP4330	2,000	586	74**
(Dust, Oil	4340	4340-ETC120	4340-ETC240	HT4340	NHP4340	2,800	821	78**
Resistant)	4350	4350-ETC120	4350-ETC240	HT4350	NHP4350	3,400	997	75**
	4360	4360-ETC120	4360-ETC240	HT4360	NHP4360	4,000	1,171	77**
	4370	4370-ETC120	4370-ETC240	HT4370	NHP4370	4,800	1,406	77**
	4380	4380-ETC120	4380-ETC240	HT4380	NHP4380	5,600	1,641	79**

	Cabinet Cooler Only Model #	Continuous Operation Model #	High Temp Continuous Operation Model #	Capa Btu/Hr	city* Watts	Sound level dBA
	4004	4204	N/A	275	80	59**
	4008	4208	N/A	550	162	67**
	4015	4215	HT4215	1,000	293	73**
NESS 13	4025	4225	HT4225	1,700	498	74**
NEMA 12 (IP54)	4030	4230	HT4230	2,000	586	74**
(Dust, Oil	4040	4240	HT4240	2,800	821	78**
Resistant)	N/A	4250	HT4250	3,400	997	75**
	N/A	4260	HT4260	4,000	1,171	77**
	N/A	4270	HT4270	4,800	1,406	77**
	N/A	4280	HT4280	5,600	1,641	79**

<sup>\*</sup>Cooling capacity at 100 PSIG (6.9 BAR) supply pressure. \*\*With optional cold muffler installed.

NEMA 12 (IP54) Cabinet Cooler systems are dust and oil tight. They are ideal for general industrial environments where no liquids or corrosives are present.

Thermostat control systems (Models 4304-4380) are the most efficient cabinet cooler system because it will turn itself on and off as needed to cool your enclosure. Includes cooler, solenoid valve, thermostat, filter separator and cold air distribution kit. Models are available in 120VAC, 240VAC and 24VDC.

Continuous operation systems (Models 4204-4280) include the cooler, a filter separator and cold air distribution kit.


ETC Thermostat control systems provide on the fly temperature adjustment and display internal temperature in real time.

High Temperature Cabinet Cooler systems should be used when ambient temperatures reach 125°F to 200°F (52°C to 93°C).

Non-Hazardous Purge (NHP) models provide a continuous positive purge within the enclosure to prevent contaminants from entering. They are suited for extremely dirty and dusty environments.


Dual Cabinet Cooler systems (Models (##50-##80) provide for additional cooling.

#### **Dimensions**






#### **Dimensions**





















#### **NEMA 4 (IP66) Cabinet Cooler Systems**

	120V Thermostat Control Model#	ETC 120V Thermostat Control Model#	ETC 240V Thermostat Control Model#	High Temp Thermostat Control Model#	Non-Hazardous Purge Thermostat Control Model#	Capa Btu/Hr	city* Watts	Sound level dBA
	4804	4804-ETC120	4804-ETC240	N/A	NHP4804	275	80	59**
	4808	4808-ETC120	4808-ETC240	N/A	NHP4808	550	162	67**
	4815	4815-ETC120	4815-ETC240	HT4815	NHP4815	1,000	293	73
NEMA 4	4825	4825-ETC120	4825-ETC240	HT4825	NHP4825	1,700	498	80
(IP66)	4830	4830-ETC120	4830-ETC240	HT4830	NHP4830	2,000	586	80
(Splash	4840	4840-ETC120	4840-ETC240	HT4840	NHP4840	2,800	821	82
Resistant)	4850	4850-ETC120	4850-ETC240	HT4850	NHP4850	3,400	997	84
	4860	4860-ETC120	4860-ETC240	HT4860	NHP4860	4,000	1,171	84
	4870	4870-ETC120	4870-ETC240	HT4870	NHP4870	4,800	1,406	84
	4880	4880-ETC120	4880-ETC240	HT4880	NHP4880	5,600	1,641	85

	Cabinet Cooler Only Model#	Continuous Operation Model#	High Temp Continuous Operation Model#	Capa Btu/Hr	icity* Watts	Sound level dBA
	4604	4704	N/A	275	80	59**
	4608	4708	N/A	550	162	67**
	4615	4715	HT4715	1,000	293	73 80
NEMA 4	4625	4725	HT4725	1,700	498	80
(IP66)	4630	4730	HT4730	2,000	586	80
(Splash	4640	4740	HT4740	2,800	821	82
Resistant)	N/A	4750	HT4750	3,400	997	84
	N/A	4760	HT4760	4,000	1,171	84
	N/A	4770	HT4770	4,800	1,406	84
	N/A	4780	HT4780	5,600	1,641	85

\*Cooling capacity at 100 PSIG (6.9 BAR) supply pressure. \*\*With optional cold muffler installed.

NEMA 4 (IP66) Cabinet Cooler systems are dust and oil tight, splash resistant and indoor/outdoor capable. By incorporating a low pressure valve for all air exhaust, the valve closes and seals when not operating to maintain NEMA 4 enclosure integrity.

Thermostat control systems (Models 4804-4880) are the most efficient system because it will turn itself on and off as needed to cool your enclosure. Includes cooler, solenoid valve and thermostat, filter separator and cold air distribution kit. Models are available in 120VAC, 240VAC and 24VDC.

Continuous operation systems (Models 4704-4780) include the cooler, a filter separator and cold air distribution kit.

ETC Thermostat control systems provide on the fly temperature adjustment and display internal temperature in real time.


High Temperature Cabinet Cooler systems should be used when ambient temperatures reach 125°F to 200°F (52°C to 93°C).


Non-Hazardous Purge (NHP) models provide a continuous positive purge within the enclosure to prevent contaminants from entering. They are suited for extremely dirty and dusty environments.

Dual Cabinet Cooler systems (Models (##50-##80) provide for additional cooling.

EXAIR

## **Dimensions**





# 11510 Goldcoast Drive • Cincinnati, OH 45249-1621 • Phone (513) 671-3322



## **Cabinet Cooler® Systems**

#### NEMA 4X (IP66) Cabinet Cooler Systems

	120V Thermostat Control Model#	ETC 120V Thermostat Control Model#	ETC 240V Thermostat Control Model#	High Temp Thermostat Control Model#	Non-Hazardous Purge Thermostat Control Model#	Capa Btu/Hr	city* Watts	Sound level dBA
	480455	4804SS-ETC120	48045S-ETC240	N/A	NHP4804SS	275	80	59**
	480855	4808SS-ETC120	48085S-ETC240	N/A	NHP48085S	550	162	67**
1	4815SS	4815SS-ETC120	48155S-ETC240	HT4815SS	NHP4815SS	1,000	293	73
NEMA 4X	482555	4825SS-ETC120	48255S-ETC240	HT4825SS	NHP4825SS	1,700	498	80
(IP66)	4830SS	4830SS-ETC120	4830SS-ETC240	HT4830SS	NHP4830SS	2,000	586	80
CorrosionRe-	484055	4840SS-ETC120	4840SS-ETC240	HT4840SS	NHP4840SS	2,800	821	82
sistant)	485055	4850SS-ETC120	48505S-ETC240	HT4850SS	NHP4850SS	3,400	997	84
	486055	486055-ETC120	486055-ETC240	HT486055	NHP486055	4,000	1,171	84
	487055	4870SS-ETC120	48705S-ETC240	HT4870SS	NHP4870SS	4,800	1,406	84
	488055	4880SS-ETC120	488055-ETC240	HT488055	NHP488055	5,600	1,641	85

	Cabinet Cooler Only Model#	Continuous Operation Model#	High Temp Continuous Operation Model#	Capa	city*	Sound
				Btu/Hr	Watts	dBA
	460455	470455	N/A	275	80	59**
	4608SS	470855	N/A	550	162	67**
	461555	4715SS	HT4715SS	1,000	293	73
NEMA 4X	462555	472555	HT4725S5	1,700	498	80
(IP66)	4630SS	4730SS	HT4730SS	2,000	586	80
(Corrosion	4640SS	4740SS	HT4740SS	2,800	821	82
Resistant)	N/A	4750SS	HT4750SS	3,400	997	84
	N/A	4760SS	HT4760SS	4,000	1,171	84
	N/A	4770SS	HT4770SS	4,800	1,406	84
	N/A	478055	HT4780SS	5,600	1,641	85

\*Cooling capacity at 100 PSIG (6.9 BAR) supply pressure. \*\*With optional cold muffler installed.

NEMA 4X (IP66) Cabinet Cooler systems are made from 303 stainless steel, dust and oil tight, splash resistant, indoor/outdoor capable and corrosion resistant. By incorporating a low pressure valve for all air exhaust, the valve closes and seals when not operating to maintain NEMA 4X enclosure integrity.

Thermostat control systems (Models 4804SS-4880SS) are the most efficient system because it will turn itself on and off as needed to cool your enclosure. Includes cooler, solenoid valve and thermostat, filter separator and cold air distribution kit. Models are available in 120VAC, 240VAC and 24VDC.

Continuous operation systems (Models 4704SS-4780SS) include the cooler, a filter separator and cold air distribution kit.

ETC Thermostat control systems provide on the fly temperature adjustment and display internal temperature in real time.

High Temperature Cabinet Cooler systems should be used when ambient temperatures reach 125°F to 200°F (52°C to 93°C).

Non-Hazardous Purge (NHP) models provide a continuous positive purge within the enclosure to prevent contaminants from entering. They are suited for extremely dirty and dusty environments.

Dual Cabinet Cooler systems (Models (##50SS-##80SS) provide for additional cooling.

462555

463055

464055

471555 472555

473055


474055


482555

483055

















	Accessories	and Comp	onents
Model#	Description	Model #	Description
4902	Cold Muffler only	9044	Valve and Thermostat Kit, 240V, 50/60 Hz
4904	Cold Air Distribution Kit (For all Cabinet Coolers 650 Btu/hr. and higher)	9016	NEMA 4-4X Valve and Thermostat Kit, 120V, 50/60 Hz
4905	Cold Air Distribution Kit (For Cabinet Coolers up to 550 8tu/hr.)	9045	NEMA 4-4X Valve and Thermostat Kit, 240V, 50/60 Hz
9004	Automatic Drain Filter Separator, 1/4 NPT, 43 SCFM (1,359 SLPM)	9017	Thermostat Only, 24V-240V, 50/60Hz
9027	Oil Removal Filter (For Cabinet Coolers with 550 Btu/hr. output), 1/4 NPT, 7-24 SCFM (198-680 SLPM)	9018	NEMA 4-4X Solenoid Valve Only, 120V, 50/60 Hz, 1/4 NPT, 40 SCFM (1,133 SLPM)
9005	Oil Removal Filter (For all Cabinet Coolers except 550 Btu/hr. output), 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)	9024	NEMA 4-4X Solenoid Valve Only, 240V, 50/60 Hz, 1/4 NPT, 40 SCFM (1,133 SLPM)
9006	Oil Removal Filter, 3/4 NPT, 50-150 SCFM (1,416-4,248 SLPM)	9020	Solenoid Valve Only, 120V, 50/60 Hz, 1/4 NPT, 40 SCFM (1,133 SLPM)
9008	Pressure Regulator with Gauge, 1/4 NPT, 50 SCFM (1,416 SLPM)	9021	Solenoid Valve Only, 200-240V, 50/60 Hz, 1/4 NPT, 40 SCFM (1,133 SLPM)
9238	ETC - Electronic Temperature Control, 120V, 50/60 Hz, 1/4 NPT	9031	NEMA 4-4X Solenoid Valve Only, 24VDC, 1/4 NPT, 40 SCFM (1,133 SLPM)
9239	ETC - Electronic Temperature Control, 240V, 50/60 Hz, 1/4 NPT	9034	NEMA 4-4X Solenoid Valve Only, 120V, 50/60 Hz, 1/2 NPT, 100 SCFM (2,832 SLPM)
9258	ETC - Electronic Temperature Control, 120V, 50/60 Hz, 1/2 NPT	9058	NEMA 4-4X Solenoid Valve Only, 24VDC, 1/2 NPT, 100 SCFM (2,832 SLPM)
9259	ETC - Electronic Temperature Control, 240V, 50/60 Hz, 1/2 NPT		EXAIR's Side Mount Kits for
0015	Malana de de la companya de la compa		NEMA 12, 4 and 4X Cabinet

#### **Side Mount Kits**

9015 Valve and Thermostat Kit, 120V, 50/60 Hz

EXAIR's Side Mount Kits make mounting on the side of an electrical enclosure possible when there is limited space on the top or side. (NEMA 4 and 4X Cabinet Cooler Systems must be mounted vertically.) The Side Mount Kits maintain the NEMA rating of large and small NEMA Type 12, 4 and 4X enclosures. They mount in a standard electrical knockout (1-1/2 NPS). Side Mount Kits for NEMA 12 Cabinet Cooler Systems have an aluminum construction. Those for NEMA 4 and 4X Cabinet Cooler Systems are Type 303 or Type 316 stainless steel.

	Accessories and Components	
Model #	Description	
4909	Side Mount Kit for NEMA 12 Cabinet Coolers up to 550 Btu/hr. (162 Watts)	
4910	Side Mount Kit for NEMA 12 Cabinet Coolers, 650 Btu/hr. (192 Watts) and higher	
4906	Side Mount Kit for NEMA 4 and 4X Cabinet Coolers up to 550 Btu/hr. (162 Watts)	
4907	Side Mount Kit for NEMA 4 and 4X Cabinet Coolers, 650 Btu/hr. (192 Watts) and higher	
4906-316	Type 316 Stainless Steel Side Mount Kit for NEMA 4 and 4X Cabinet Coolers, up to 550 Btu/hr. (162 Watts)	
4907-316	Type 316 Stainless Steel Side Mount Kit for NEMA 4 and 4X Cabinet Coolers, 650 Btu/hr. (192 Watts) and higher	

		90	Degree	Side Mot	ınt Kit Di	mensior	15	,
Model		A	В	C	D	E	F	G
4906	in.	2.50	2.50	1.50	3.50	3.03	3.4100	1-1/2 NP5
4906	mm	64	64	38	89	77	1 NPS	1-1/2 NP3
****	in	2.50	2.50	1.50	3.50	3.03		1-1/2 NPS
4907	mm	64	64	38	89	77	1-1/2 NPS	
	in	2.50	2.50	1.50	2.19	1.73	LINE	
4909	mm	64	64	38	56	44	1/2 NPS	1-1/2 NPS
in	in	2.50	2.50	1.50	2.19	1.73	3/4 NPS	4 4 10 4 10 6
4910	mm	64	64	38	56	44	3/4 NPS	1-1/2 NPS

#### **Side Mount Kit Dimensions**

Coolers offer convenient

mounting to the side of an electrical enclosure.







#### An INTELLIGENT OMPRESSED AIR Product **Cabinet Cooler® Systems**









# **Hazardous Location Cabinet Cooler® Systems**



# For use with classified enclosure purge and pressurization systems

- Class I Div 1, Groups A, B, C and D
- Class II Div 1, Groups E, F and G
- Class III

HazLoc Cabinet Coolers maintain NEMA 4/4X integrity and are C∈ compliant!



#### What is an EXAIR HazLoc **Cabinet Cooler System?**

These Cabinet Cooler Systems are engineered and approved for use upon purged electrical enclosures (not included) found within classified areas. The areas approved are Class I Div 1, Groups A, B, C and D - Class II Div 1 Groups E, F and G - and Class III. EXAIR's HazLoc Cabinet Cooler Systems have been tested by UL and meet the stringent UL requirements for these areas. Cabinet Cooler systems are a low cost and reliable way to cool purged electric control panels found within these environments. They utilize vortex tube technology to produce up to 5,600 Btu/Hr, with no moving parts, which additionally creates a low maintenance solution for cooling your HazLoc purged cabinets.

#### Advantages

- Rated for Div I Hazardous Locations
- UL Classified
- Available in 8 different cooling capacities
- No moving parts, low maintenance
- Thermostat control reduces operating cost
- Large range of cooling capacities up to 5,600 Btu/Hr
- 5 Year warranty
- Low cost

#### Why EXAIR HazLoc Cabinet Cooler Systems?

EXAIR's HazLoc Cabinet Cooler Systems have been set apart from the competition by achieving the UL classified designation for Div I environments. Thermostatically controlled systems are recommended for the highest efficiency and include UL listed solenoids, also for hazardous environments. EXAIR Cabinet Cooler systems will install on your purged enclosure in minutes, require little to no maintenance and operate under the toughest of industrial conditions. If you require low cost, ease of use and/or reliability - a HazLoc Cabinet Cooler system will meet your needs.

EXAIR Hazardous Location Cabinet Cooler Systems are available in 8 different cooling capacities from 1,000 Btu/Hr. to 5,600 Btu/Hr. This range of cooling allows for choosing the best fit for your cooling needs without wasting compressed air.

Cabinet Cooler Systems protect your electronics from heat, dirt and moisture and keep your processes running. They are the low-cost solution to messy, high maintenance coolant-based air conditioners with simple installation. With modern technology comes an increased number of small electronic components packed into smaller electronic cabinets. This creates a high internal heat load which increases failures due to heat. Components will fail, sensors will misread, controls can drift and displays become inaccurate. EXAIR HazLoc Cabinet Coolers can solve these problems and prevent lost productivity, shutdown and the expense of new components.















#### **Thermostat Control**


Each EXAIR HazLoc Cabinet Cooler System is available with a thermostat control or as a continuous operation system. Each of these systems will include a water-dirt filter separator to prevent water condensate and dirt from entering your enclosure and a cold air distribution kit used to direct the air for circulation or onto hot spots.


HazLoc Cabinet Cooler Systems are also available in Type 316SS for highly corrosive environments.

Any control systems and accessories not rated for the hazardous location need to be moved outside of the hazardous area or inside a properly purged and pressurized enclosure which is suitable for the hazardous area.

#### Safety

EXAIR's HazLoc Cabinet Cooler Systems are not purged and pressurized control systems and should not be relied upon nor used in place of a purged and pressurized controller. They are meant for use in conjunction with a purged and pressurized control system.





#### NEMA 4 (IP66) Hazardous Location Cabinet Cooler Systems

Cabinet Cooler Only Model #	Continuous Operation Model #	120V Thermostat Control Model #	240V Thermostat Control Model #	24VDC Thermostat Control Model #	Capa Btu/Hr	city* Watts	Sound level dBA
Management of the last of the	THE RESERVE	(3/00/00/00/00/00/00/00/00/00/00/00/00/00			-		- Control of
HZ4615	HZ4715	HZ4815	HZ4815-240	HZ4815-24VDC	1,000	293	73
HZ4625	HZ4725	HZ4825	HZ4825-240	HZ4825-24VDC	1,700	498	80
HZ4630	HZ4730	HZ4830	HZ4830-240	HZ4830-24VDC	2,000	586	80
HZ4640	HZ4740	HZ4840	HZ4840-240	HZ4840-24VDC	2,800	821	82
N/A	HZ4750	HZ4850	HZ4850-240	HZ4850-24VDC	3,400	997	84
N/A	HZ4760	HZ4860	HZ4860-240	HZ4860-24VDC	4,000	1,171	84
N/A	HZ4770	HZ4870	HZ4870-240	HZ4870-24VDC	4,800	1,406	84
N/A	HZ4780	HZ4880	HZ4880-240	HZ4880-24VDC	5,600	1,641	85

#### NEMA 4X Hazardous Location Cabinet Cooler Systems

Cabinet Cooler Only	Continuous Operation	120V 240V Thermostat Control Thermostat Con		24VDC Thermostat Control	Capa	Sound level		
Model #	Model #	Model #	Model #	Model #	Btu/Hr	Watts	dBA	
HZ461555	HZ4715SS	HZ4815SS	HZ48155S-240	HZ4815SS-24VDC	1,000	293	73	
HZ4625SS	HZ472555	HZ482555	HZ48255S-240	HZ4825SS-24VDC	1,700	498	80	
HZ4630SS	HZ4730SS	HZ4830SS	HZ4830SS-240	HZ4830SS-24VDC	2,000	586	80	
HZ4640SS	HZ4740SS	HZ4840SS	HZ4840SS-240	HZ4840SS-24VDC	2,800	821	82	
N/A	HZ4750SS	HZ4850SS	HZ4850SS-240	HZ4850SS-24VDC	3,400	997	84	
N/A	HZ4760SS	HZ48605S	HZ48605S-240	HZ4860SS-24VDC	4,000	1,171	84	
N/A	HZ4770SS HZ4870SS HZ4870SS-24VDC 4,8		4,800	1,406	84			
N/A	HZ478055	HZ4880SS	HZ4880SS-240	HZ48805S-24VDC	5,600	1,641	85	

Model#	Description
902019	Hazloc Solenoid NEMA Type 4X/7/9, 1/4 NPT, 120V/60HZ
902020	Hazloc Solenoid NEMA Type 4X/7/9, 1/4 NPT, 240V/60HZ
902021	Hazloc Solenoid NEMA Type 4X/7/9, 1/4 NPT, 24VDC
9017	Thermostat only 24V-240V, 50/60 Hz
9004	Automatic Drain Filter Separator, 1/4 NPT, 43 SCFM (1,359 SLPM)
9027	Oil Removal Filter for all HazLoc Systems, 7-24 SCFM (198-680 SLPM), 1/4 NPT
9005	Oil Removal Filter for all HazLoc Systems, 15-37 SCFM (425-1,048 SLPM), 3/8 NPT
9006	Oil Removal Filter for all HazLoc Systems, 50-150 SCFM (1,416- 4,248 SLPM), 3/4 NPT

Accessories and

\*Cooling capacity at 100 PSIG (6.9 BAR) supply pressure





## For Technical Assistance, Call An EXAIR Application Engineer 1-800-903-9247













**ATEX Cabinet Cooler® Systems** 

**Cabinet Cooler® Systems** 



An INTELLIGENT OMPRESSED AIR Product

For use with classified enclosure purge and pressurization systems

#### Zones 2 and 22

- € II 3 G ExhIIC T3 Gc
- (Ex II 3 D Ex h IIIC T200°C Dc



#### What is an ATEX Cabinet Cooler System?

ATEX Cabinet Cooler Systems are engineered and approved for use upon purged electrical enclosures (not included) found within ATEX zoned areas. The areas approved are Zone 2 and 22. EXAIR's ATEX Cabinet Cooler Systems have been tested by UL and meet the stringent ATEX requirements for these areas. Cabinet Cooler systems are a low cost and reliable way to cool purged electric control panels found within these environments. They utilize vortex tube technology to produce up to 5,600 Btu/Hr, with no moving parts, which additionally creates a low maintenance solution for cooling your ATEX purged cabinets.

The compact Cabinet Cooler is an easy-to-use air conditioner that can be installed in minutes through a standard electrical knockout. Aluminum and Stainless Steel ATEX Cabinet Coolers that match the NEMA rating of the enclosure are available in many cooling capacities for large and small control panels.

#### Advantages

- Rated for Zones 2 and 22
- Available in 8 different cooling capacities
- No moving parts, low maintenance
- Thermostat control reduces operating cost
- Large range of cooling capacities up to 5,600 Btu/hr
- 5 Year warranty
- Low cost

#### Why EXAIR ATEX Cabinet Coolers?

EXAIR's ATEX Cabinet Cooler Systems have been set apart from the competition by being certified for Zone 2 and 22 environments. Thermostatically controlled systems are recommended for the highest efficiency and include ATEX approved solenoids, also for hazardous environments. EXAIR Cabinet Cooler Systems will install upon your purged enclosure in minutes, require little to no maintenance and operate under the toughest of industrial conditions. If you require low cost, ease of use and/or reliability - an ATEX Cabinet Cooler System will meet your needs.

EXAIR ATEX Cabinet Cooler Systems are available in 8 different cooling capacities from 1,000 Btu/hr. to 5,600 Btu/hr. This range of cooling allows for choosing the best fit for your cooling needs without wasting compressed air.

Cabinet Cooler Systems protect your electronics from heat, dirt and moisture and keep your processes running. They are the low-cost solution to messy, high maintenance coolant-based air conditioners with simple installation. With modern technology comes an increased number of small electronic components packed into smaller electronic cabinets. This creates a high internal heat load which increases failures due to heat. Components will fail, sensors will misread, controls can drift and displays become inaccurate. EXAIR ATEX Cabinet Coolers can solve these problems and prevent lost productivity, shutdown and the expense of new components.

#### **Thermostat Control**


Each EXAIR ATEX Cabinet Cooler System is available with a thermostat control or as a continuous operation system. Each of these systems will include a water-dirt filter separator to prevent water condensate and dirt from entering your enclosure and cold air distribution kit used to direct the air for circulation and onto hot spots. ATEX Cabinet Cooler Systems are also available in Type 303 and Type 316SS for highly corrosive environments.

Any control systems and accessories not rated for the ATEX zone need to be moved outside of the ATEX zone or inside a properly purged and pressurized enclosure which is suitable for the ATEX zone.

#### Safety

EXAIR's ATEX Cabinet Cooler Systems are not purged and pressurized control systems and should not be relied upon nor used in place of a purged and pressurized controller. They are meant for use in conjunction with a purged and pressurized control system.

Model #'s Aluminum	Model #'s St. Steel
ATEX4615	ATEX4615SS
ATEX4625	ATEX4625SS
ATEX4630	ATEX4630SS
ATEX4640	ATEX4640SS
ATEX4715	ATEX4715SS
ATEX4725	ATEX4725SS
ATEX4730	ATEX4730SS
ATEX4740	ATEX4740SS
ATEX4815	ATEX4815SS
ATEX4825	ATEX4825SS
ATEX4830	ATEX4830SS
ATEX4840	ATEX484055



#### Aluminum ATEX Cabinet Cooler Systems (maintain NEMA 4 integrity)

Cabinet Cooler Only	Continuous Operation	120V Thermostat Control	240V I Thermostat Control	24VDC Thermostat Control	Capi	Sound	
Model #	Model #	Model #	Model #	Model #	Btu/Hr	Watts	dBA
ATEX4815	ATEX4815	ATEX4815	ATEX4815-240	ATEX4815-24VDC	1,000	293	73
ATEX4825	ATEX4825	ATEX4825	ATEX4825-240	ATEX4825-24VDC	1,700	498	80
ATEX4830	TEX4830 ATEX4830		ATEX4830-240	ATEX4830-24VDC	2,000	586	80
ATEX4840	X4840 ATEX4840 ATEX484		ATEX4840-240	ATEX4840-24VDC	2,800	821	82
N/A	ATEX4850	ATEX4850	ATEX4850-240	ATEX4850-24VDC	3,400	997	84
N/A	ATEX4860	ATEX4860	ATEX4860-240	ATEX4860-24VDC	4,000	1,171	84
N/A	ATEX4870	ATEX4870	ATEX4870-240	ATEX4870-24VDC	4,800	1,406	84
N/A	ATEX4880	ATEX4880	ATEX4880-240	ATEX4880-24VDC	5,600	1,641	85

#### Stainless Steel ATEX Cabinet Cooler Systems (maintain NEMA 4X integrity)

Cabinet Cooler Only	Continuous Operation	120V Thermostat Control	240V Thermostat Control	24VDC Thermostat Control	Capacity*		Sound	
Model #	Model #	Model #	Model #	Model #	Btu/Hr	Watts		
ATEX4615SS	ATEX4715SS	ATEX4815SS	ATEX481555-240	ATEX4815SS-24VDC	1,000	293	73	
ATEX4625SS	ATEX4725SS	ATEX4825SS	ATEX4825SS-240	ATEX4825SS-24VDC	1,700	498	80	
ATEX4630SS ATEX4730		ATEX4830SS	ATEX4830SS-240	ATEX4830SS-24VDC	2,000	586	80	
ATEX4640SS	ATEX4740SS	ATEX4840SS	ATEX4840SS-240	ATEX4840SS-24VDC	2,800	821	82	
N/A ATEX4750SS		ATEX4850SS	ATEX485055-240 ATE	ATEX4850SS-24VDC	3,400	997	84	
N/A	ATEX4760SS	ATEX4860SS	ATEX4860SS-240	ATEX4860SS-24VDC	4,000	1,171	84	
N/A	ATEX4770SS	ATEX4870SS	ATEX4870SS-240	ATEX4870SS-24VDC	4,800	1,406	84	
N/A	ATEX4780SS	ATEX4880SS	ATEX4880SS-240	ATEX4880SS-24VDC	5,600	1,641	85	
N/A	ATEX4780SS	ATEX4880SS	ATEX4880SS-240	ATEX4880SS-24VDC	5,600	1,64	1	

\*Cooling capacity at 100 PSIG (6.9 BAR) supply pressure

#### 11510 Goldcoast Drive • Cincinnati, OH 45249-1621 • Phone (513) 671-3322 EXAIR FAX (513) 671-3363 \* E-mail: techelp@exair.com \* www.exair.com

Accessories and

902380 ATEX Solenoid, IP65, 1/4 NPT, 120V/60HZ

ATEX Solenoid, IP65, 1/4 NPT, 240V/60HZ

Thermostat only 24V-240V, 50/60 Hz

Automatic Drain Filter Separator, 1/4 NPT, 43 SCFM (1,359 SLPM) Oil Removal Filter for all ATEX Systems, 7-24 SCFM (198-680 SLPM), 1/4 NPT Oil Removal Filter for all ATEX Systems, 15-37 SCFM (425-1,048 SLPM), Oil Removal Filter for all ATEX Systems, 50-150 SCFM (1,416-4,248 SLPM), 3/4 NPT

# **EXAIR** White Papers



# Cabinet Coolers **End Costly** Shutdowns

Save Your Bottom Line -Download Now!



See our customer's success story. They were experiencing the very common circumstance of seasonal summertime control failures due to the elevated temperatures.

Soon the heat took its toll on the electrical enclosure of their laser cutting machine... The main circuit board failed and required repairs in Australia.

As the machine remained shut down, the urgency to keep their good reputation and meet delivery times made finding the proper cooling product their top priority.

After comparing other options for cooling, it became clear an EXAIR Cabinet Cooler would provide the long-term solution they needed.

There were numerous features that made EXAIR's Cabinet Cooler the best choice for this customer. It was easy to install, compact, requires no maintenance and maintains the integrity of their enclosure.

It's hard to believe you can get so much cooling out of such a compact product.

The customer now considers EXAIR Cabinet Coolers to be a good insurance policy against summertime heat conditions that had just cost them a significant amount of money.

EXAIR's White Paper will help you learn more about how you can stop costly shutdowns in your plant with the compact, low-cost Cabinet Cooler.




**Download Cabinet Coolers** End Costly Shutdowns now at https://exair.co/ccecs04









EXAIR's Filter Separators remove water, dirt and rust from your compressed air system. They prevent these contaminants from plugging or damaging the compressed air products. A Filter Separator should be installed prior to an Oil Removal Filter, pressure regulator or valve.


Model #	Description	Max Pres.	Max Temp
9003	Manual Drain Filter Separator, 1/4 NPT, 27 SCFM (765 SLPM)	150 PSIG	125°F (52°C
9004	Automatic Drain Filter Separator, 1/4 NPT, 43 SCFM (1,218 SLPM)	150 PSIG	125°F (52°C)
9001	Automatic Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)	175 PSIG	120°F (49°C)
9032	Automatic Drain Filter Separator, 1/2 NPT, 90 SCFM (2,549 SLPM)	175 PSIG	120°F (49°C)
9002	Automatic Drain Filter Separator, 3/4 NPT, 220 SCFM (6,230 SLPM)	175 PSIG	120°F (49°C)
9066	Automatic Drain Filter Separator, 1-1/4 NPT, 400 SCFM (11,327 SLPM)	175 PSIG	120°F (49°C)

The Model 9003 Manual Drain Filter has a polycarbonate bowl and a 20 micron filter element. A manual drain is used to empty the filter. Model 9001, 9002, 9004, 9032, and 9066 Automatic Drain Filter Separators have a metal bowl and a 5 micron filter element (Model 9004 has a polycarbonate bowl with a metal guard). An internal float automatically activates the drain to remove liquid condensate when the bowl becomes full.


# Oil Removal Filters Model 9027 Model 9005


EXAIR's Model 9027, 9005, 9006, and 9010 Oil Removal Filters remove oil and solid particulate that is typical in many compressed air systems.

A 0.03 micron element is used to trap submicron particles. An internal float automatically activates the drain when full.



Model #	Description	Max Pres.	Max Temp.
9027	Oil Removal Filter, 1/4 NPT, 24 SCFM (680 SLPM)	175 PSIG	120°F (49°C)
9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)	175 PSIG	120°F (49°C)
9006	Oil Removal Filter, 3/4 NPT, 50-150 SCFM (1,416-4,248 SLPM)	175 PSIG	120°F (49°C)
9010	Oil Removal Filter, 1-1/2 NPT, 130-310 SCFM (3,679-8,773 SLPM)	175 PSIG	120°F (49°C)








Model 900394

# Toll Free FAX (866) 329-3924 - E-mail: techelp@exair.com - www.exair.com


#### Accessories



EXAIR's Model 9008, 9033, 9009 and 9067 Pressure Regulators permit easy selection of the operating pressure. A pressure gauge is included.

1	Model#	Description	Max Pres.	Max Temp.
1	9008	Pressure Regulator with Gauge, 1/4 NPT, 50 SCFM (1,416 SLPM)	250 PSIG	120°F (49°C)
I	9033	Pressure Regulator with Gauge, 1/2 NPT, 100 SCFM (2,832 SLPM)	250 PSIG	120°F (49°C)
1	9009	Pressure Regulator with Gauge, 3/4 NPT, 220 SCFM (6,230 SLPM)	250 PSIG	120°F (49°C)
I	9067	Pressure Regulator with Gauge, 1-1/4 NPT, 700 SCFM (19,822 SLPM)	250 PSIG	120°F (49°C)
1	9011	Pressure Gauge Only, 1/4 NPT, 0-160 PSI (0-11 BAR)	250 PSIG	120°F (49°C)

#### **Pressure Regulator Mtg Brackets**



This optional mounting bracket fits Models 9008, 9033 and 9009 Pressure Regulators and includes a locking ring.

Model #	Description	
900398	Mounting Bracket for Model 9008, 9033 and 9009	

#### Mounting and Coupling Kits





Model #	Description
9046	Mounting and Coupling Kit for Model 9001 Filter/Model 9008 Regulator and Model 9032 Filter/ Model 9033 Regulator
9047	Mounting and Coupling Kit for Model 9002 Filter/Model 9009 Regulator
9048	Mounting and Coupling Kit for Model 9004 Filter/Model 9005 Oil Removal Filter

EXAIR's Coupling Kits are interlocking slides that couple the modular filters and pressure regulators together.

Model #	Description
900394	Fits auto drain filters and regulators with 1/4 NPT, 3/8 NPT and 1/2 NPT threads
900552	Fits auto drain filters and regulators with 3/4 NPT threads













Model 9011

# Silencing Mufflers

EXAIR Silencing Mufflers help to reduce work area noise produced by air exhausting from cylinders, valves and other air powered equipment. Per OSHA Standard 1910.95(a), a worker must not be exposed to sound levels above 90 dBA for any eight hour shift of a 40 hour work week. Silencing Mufflers help plants meet this OSHA requirement by reducing the sound to safe levels below 90 dBA. They also eliminate harmful dead end pressures. Each style of Silencing Muffler shown has a high airflow capacity, with low back pressure. Popular NPT sizes are ideal for new and existing installations.

Model 9070

Model 9071

Model 9072

Model 9073

Model 9074

Model 9075

Muffler Needed To Exhaust

Charged To 100 PSIG

Contact an Application Engineer for more

#### Reclassifying Mufflers

Reclassifying Mufflers are an upgrade from Sintered Bronze Mufflers (see next page). They offer the best noise reduction - up to 35 dB. Available from 1/8 NPT through 1 NPT, Reclassifying Mufflers eliminate oil mist. Exhaust air from cylinders and valves often contain oil mists that can contaminate the workers' breathing air, affecting their health. Per OSHA Standard 29 CFR 1910,1000, a worker's cumulative exposure to oil mist must not exceed 5mg/m3 by volume in any eight hour shift of a 40 hour work week.

The patented wrap design of the removable element separates oil from the exhausted air so virtually no oil is released into the environment. Based on an intake of 50 PPM at 100 PSIG, the Reclassifying Mufflers reclassify and reduce the exhausted oil mist to 0.015 PPM. A reservoir where oil accumulates at the bottom can be drained by attaching a 1/4" tube.

Each Reclassifying Muffler passes a certain volume of air with minimal back pressure restriction so it doesn't interfere with the operation of the cylinder or valve. When used with cylinders, the "Muffler Quick Pick" table (right) helps you select the appropriate model based on the actual bore and stroke of the cylinder.





#### **Muffler Quick Pick**

	Bore (in.)				St	rok	e (i	n.)			
	(in.)	3	6	9	12	18	24	30	36	42	48
	0.5										
	1.0										
	1.5										
	2.0										
	2.5										
	3.0										
	3.5										
1	4.0								7		
	4.5										
	5.0										
	5.5										
	6.0										

Model #	Description	on	Α	В		Replacement Element #
	Reclassifying	in	3.13	1.63	1/8	
9070	Muffler	mm	80	41	NPT	
	Reclassifying	in	3.13	1.63	1/4	900553
9071	Muffler	mm	80	41	NPT	
9072	Reclassifying Muffler	in	4.75	2.44	3/8 NPT	900554
90/2		mm	121	62		
9073	Reclassifying Muffler	in	4.75	2.44	1/2	
90/3		mm	121	62	NPT	
	Reclassifying	in	6.25	3.31	3/4 NPT	
9074	Muffler	mm	159	84		
0075	Reclassifying	in	6.25	3.31	1	900555
9075	Muffler	mm	159	84	NPT	

#### Accessories

#### Sintered Bronze Mufflers

EXAIR's low cost Sintered Bronze Mufflers are easy to install in new and existing exhaust ports of valves, cylinders and other air powered equipment. Each Sintered Bronze Muffler is capable of passing a certain volume of air with minimal back pressure restriction so it doesn't interfere with the operation of the cylinder or valve. When used with cylinders, the "Muffler Quick Pick" table helps you select the appropriate model based on the actual bore and stroke of the cylinder. (Note: Model 9089 has a 1/2"-20 UNF straight thread to fit most solenoid valves.)



#### 0.72 9080 18 8 1.13 0.44 9081 11 29 1.38 0.56 14 1.50 0.69 9083 18 1.88 0.88 48 22 2.25 1.06 57 27 2.91 1.31 1 NOT 74 33 3.25 1.69 -1/4 NPT 43 3.69 2 9088 -1/2 NPT 94 51 1.19 0.63

#### Muffler Quick Pick Stroke (in.) 6 9 12 18 24 30 36 42 48 Model 9080 Model 9085 3.0 Model 9081 Model 9086 3.5 Model 9082 Model 9087 4.0 Model 9083 Model 9088 4.5 Model 9084 Contact an Muffler will exhaust cylinder in 1/2 second for a cylinder charged to 100 PSIG

## Straight-Through Mufflers



Straight-Through Silencing Mufflers feature a corrosionresistant aluminum outer shell lined with sound absorbing foam for better noise reduction. The typical noise reduction is up to 20 dB.

Model #	Description		Α	В		D	Rated Flow
2014	Straight-Through	in	4	1.50	1/4	1/4	22 SCFM
3914 Straigh	Muffler	mm	102	38	MNPT	FNPT	623 SLPM
2011	Straight-Through	in	4.13	1.50		3/8	50 SCFM
	Muffler	mm	105	38		FNPT	1,416 SLPM
	Straight-Through	in	9.75	2	3/4	3/4	73 SCFM
3913	Muffler	mm	248	51	MNPT	FNPT	2.066 SLPM

3903

Caution: Operations approaching 32°F (0°C) or below could result in freeze-up due to moisture in the compressed air line.

#### **Heavy Duty Mufflers**



Heavy Duty Silencing Mufflers feature a corrosion-resistant aluminum outer shell with an internal stainless steel screen that protects valves and cylinders from contamination that could enter through the exhaust ports. This also keeps contaminants such as rust from being ejected at high speed from the exhaust port. The typical noise reduction is up to 14 dB.

Caution: Operations approaching 32°F (0°C) or below could result in freeze-up due to moisture in the compressed air line.













mm 46 21 16

in 4.50 2 1.50





1/2"-20

FEMALE

#### Solenoid Valves




Solenoid Valves are available in a variety of flow rates and voltages. All models are UL Listed and are CE and RoHS compliant.













Model #	Description
9012	Manual Valve, 1/4 NPT
900340	Manual Valve, 3/8 NPT
900343	Manual Valve, 1/2 NPT
900743	Manual Valve, 3/4 NPT
900346	Manual Valve, 1 NPT
900744	Manual Valve, 1-1/4 NPT

#### **Swivel Fittings**



EXAIR's Swivel Fittings make it easy to adjust the position of the Air Nozzles, Air Jets, and Air Amplifiers. Swivel Fittings permit a movement of 25 degrees from the center axis for a total movement of 50 degrees. Type 303 and 316 stainless steel.

Model #	Description
9201	M4 x 0.5mm female x 1/8 MNPT Swivel Fitting, 316 SS
9202	M5 x 0.5mm female x 1/8 MNPT Swivel Fitting, 316 SS
9203	M6 x 0.75mm female x 1/8 MNPT Swivel Fitting, 316 SS
9052	1/8 NPT Swivel Fitting, 303 SS
9053	1/4 NPT Swivel Fitting, 303 SS
9068	3/8 NPT Swivel Fitting, 303 SS
9069	1/2 NPT Swivel Fitting, 303 SS
9023	3/4 NPT Swivel Fitting, 303 SS
9204	1 MNPT x 1 FNPT, 303 55

#### ETC™ Electronic Temperature Control



	Model	Voltage	Flow
2	9238	120VAC	1/4 NPT
٩		50/60HZ	40 SCFM (1,133 SLPM)
	9258	120VAC	1/2 NPT
		50/60Hz	100 SCFM (2,832 SLPM)
	9239	240VAC	1/4 NPT
		50/60Hz	40 SCFM (1,133 SLPM)
	9259	240VAC	1/2 NPT
		50/60Hz	100 SCFM (2,832 SLPM)
	FTC ando	sure	Polycarbonate NEMA 4Y

IP 66, ULS08, UL94-5V CE and ROHS Compliant

For more about the ETC, see page 217 of this catalog.

precise temperature control for your electrical enclosure. The LED readout of the ETC displays the internal temperature

EXAIR's digital ETC™ (Electronic Temperature Control) provides

of the electrical enclosure (°F or °C) that is constantly being monitored by a quick response thermocouple.

#### Thermostat



The adjustable thermostat is factory set at 95°F (35°C). It will normally hold ±2°F (1°C) of the desired temperature setting. It is rated 24V-240V AC or DC, 50/60Hz and is UL Recognized, CSA Certified.





## EXAIR





#### Accessories

#### **Magnetic Bases**

Model 9043 Model 9042









Magnetic bases are suited to applications where frequent movement of the air product is required. The powerful magnet permits horizontal or vertical mounting. A valve is provided that can be used to vary the force and flow.

Model#	Description	
9042	One Outlet Magnetic Base with Shutoff Valve (1/4 NPT)	
9043	Two Outlet Magnetic Base with Shutoff Valve (1/4 NPT)	
9029	One Outlet Swivel Magnetic Base with Shutoff Valve (1/4 NPT)	

#### **Stay Set Hoses**

For applications where frequent repositioning of the air product is required, the Flexible Stay Set Hoses are ideal. Simply mount the hose in close proximity to the application and bend it. Since the hose has "memory", it will not creep or bend. It will always keep the aim until physically moved to the next position and will withstand temperatures of up to 158°F (70°C).

(1/4 male NPT fitting on one end, 1/8 female NPT on the other)


Model #	Description			
9256	6" (152mm) 1/4 MNPT x 1/8 FNPT	AND DESCRIPTION OF THE PARTY OF		
9262	12" (305mm) 1/4 MNPT x 1/8 FNPT	CONTRACTOR DESCRIPTION OF THE PARTY OF THE P		
9268	18" (457mm) 1/4 MNPT x 1/8 FNPT	COMMON CONTRACTOR OF THE CONTR	San Constitution of the	
9274	24" (610mm) 1/4 MNPT x 1/8 FNPT		THE DESIGN SERVICE SERVICES	
9280	30" (762mm) 1/4 MNPT x 1/8 FNPT		and the second second second	# ( S   M ) ( )
9286	36" (914mm) 1/4 MNPT x 1/8 FNPT	CONTRACTOR OF THE PARTY OF THE	THE PERSON SERVICES	mad (moreon terms)

#### (1/4 male NPT fitting on each end)

(	the state of the control			
Model #	Description			
9206	6" (152mm) 1/4 MNPT x 1/4 MNPT	Control of the last of the las		
9212	12" (305mm) 1/4 MNPT x 1/4 MNPT	and the second s		
9218	18" (457mm) 1/4 MNPT x 1/4 MNPT		Pla CONTROL OF THE PARTY OF THE	
9224	24" (610mm) 1/4 MNPT x 1/4 MNPT	The second second second	tion the desired Section (1988)	
9230	30" (762mm) 1/4 MNPT x 1/4 MNPT		THE CONTRACTOR OF THE PARTY OF THE	The College of the Co
9236	36" (914mm) 1/4 MNPT x 1/4 MNPT		TOWNSHIP OF THE REAL PRINT	ALIE CONTRACTO DATES AND ADDRESS.










	s are 10', 20', 30', 40' Example: A Model 6	and 50'. Select t	he hose model numb ose x 20' long.	er (diameter) ar	nd indicate the le
Model #	Description	Model #	Description	Model #	Description
6928-	Hose 3/8" ID	6931-	Hose 1* ID	6934-	Hose 2" ID
6929-	Hose 1/2" ID	6932-	Hose 1-1/4" ID	6935-	Hose 2-1/2" ID
6930-	Hose 3/4* ID	6933-	Hose 1-1/2" ID	6936-	Hose 3" ID



Compressed Air Hose	
Compressed air hose is made of reinforced synthetic rubber to assure lon weathering, and temperatures up to 158°F (70°C). Hose lengths are 10′, 15 length with a dash. Example: A Model 900061-30 is 3/8° ID Hose x 30′ long	, 20', 30', 40' and 50'. Indicate the
weathering, and temperatures up to 158°F (70°C). Hose lengths are 10', 15	, 20', 30', 40' and 50'. Indicate the

Model #	Description	
900061	Compressed Air Hose, 1/4 MNPT x 1/4 MNPT (3/8" ID Hose)	
901179	Compressed Air Hose, 1/2 MNPT x 1/2 MNPT (1/2" ID Hose)	











#### Compressed Air Fittings







Model #	Material	Thread Size	
Model #	Material	Inread Size	
900405	Brass	1/4 MNPT x 1/8 FNPT	
900105	Brass	1/4 FNPT x 1/8 MNPT	
9553	Brass	3/8 MNPT x 1/4 MNPT	
9897	Brass	1/2 MNPT x 3/8 MNPT	
900736	Brass	1/2 MNPT x 1/4 MNPT	
900622	Brass	1/2 MNPT x 1/4 FNPT	
900985	Brass	1/2 FNPT x 3/8 MNPT	

Thread Size

1/4 FNPT x 1/4 FNPT x 1/4 MNPT

3/8 ENDT v 3/8 ENDT v 3/8 ENDT

1/2 FNPT x 1/2 FNPT x 1/2 FNPT

1/2 FNPT x 1/4 FNPT x 1/2 FNPT

1/4 MNPT x 1/4 MNPT x 1/4 MNPT 3/8 ENDT v 1/4 ENDT v 3/8 MNDT

Model # Material

Brass


900005 Brass

9971 Brass

900621 Brass

900734 Brass





Thread Size

1/4 FNPT x 1/4 FNPT

900453 NP Brass 1/8 FNPT x 1/8 FNPT













-

Elbow				
Model #	Material	Thread Size		
7674	Brass	1/8 MNPT x 1/8 FNPT 45"		
9555	Brass	1/4 MNPT x 1/4 FNPT 90"		
9895	Brass	3/8 MNPT x 3/8 FNPT 90"		
900073	Brass	1/4 MNPT x 3/8 Tube 90°		

-6	L				
	۱	h	**	h	
	ı			i	
ш	n	н		у	

900735	Brass	1/2 FNPT			
	E	Bulkhead Fitting			
Model#	Material	Thread Size			
900069	900069 Brass 3/4-16 UNF x 1/4 FNPT x 1/4 FN				

50.38"

Model # Material Thread Size 900735 Brass

#### 60 Gallon Receiver Tank

9871 Brass



Some applications require an intermittent demand for a high volume of compressed air. This can cause fluctuations in pressure and volume throughout the compressed air system with some points being "starved" for compressed air. EXAIR's Model 9500-60 60 Gallon Receiver Tank can be installed near the point of high demand so there is an additional supply of compressed air available for a short duration. The time between the high volume demand occurrences should be long enough so the compressor has enough time to replenish the EXAIR 60 Gallon Receiver Tank.


The 60 gallon (227 liter) vertical steel tank with mounting feet saves floor space and meets the American Society of Mechanical Engineers (ASME) pressure vessel code. (It is not ASME rated for vacuum.) A drain valve is provided for placement at the bottom of the tank to discharge liquid and contaminants.

A user supplied check valve installed upstream of the receiver tank will maintain the tank at maximum pressure so upstream uses of compressed air do not deplete the tank. A user supplied needle valve can regulate the refilling of the Receiver Tank, effectively reducing the large intermittent air requirement into a smaller average demand.

- · Pressure tank has a primer finish
- Temperature rating is -20° to 450°F (-29° to 232°C)
- Tank maximum pressure is 200 PSIG (13.8 BAR)
- No plugs are included for open ports. User must
- supply pressure rated plugs and pressure Weight is 165 lbs. (75 kg)
- to installation.







Model # Description

2 NPT Inspect Ports

1/2 NPT - Drain















EXAIR

Standards

As the leader in standards compliance, EXAIR's products come with more than engineered performance, peak efficiency, the best technical knowledge and unmatched customer service...

EXAIR is dedicated to providing products that have been manufactured to meet the strict requirements of the following standards. These standards provide confidence that you are receiving reliable, high quality products which will perform as stated within the performance charts provided.

Our products meet or exceed the strict safety standards of OSHA and the European Union to ensure the safety of your personnel. Many of these standards will allow your products a smoother transaction when selling your products into international markets.





#### **OSHA and CE Compliance:**

EXAIR compressed air products comply with OSHA's Safety Requirements (29 CFR 1910.242(b) ), the EU General Product Safety Directive (2001/95/EC) and meet the noise limitation requirements (29 CFR-1910.95(a) ), of the EU Machinery Directive (2006/42/EC), EXAIR's Electronic Flow Control and Electronic Temperature Control meet the low voltage standards of the EU Low Voltage Directive (2006/95/EC), Some EXAIR products display the CE mark where there are applicable directives. All sound level measurements are taken at 3 feet from product.



Electrical portions of EXAIR's Static Eliminators, EFC, ETC, Digital Flowmeter solenoid valves, and thermostats comply with the RoHS (Restriction of Hazardous Substances) Directive 2011/65/EU, including the amendment outlined in the European Commission decision L 214/65.



#### **Conflict Mineral Free:**

Look for this symbol to designate conflict mineral free products throughout our catalog. EXAIR supports Section 1502 of the Dodd-Frank Wall Street Reform and Consumer Protection Act. We are committed to compliance with the conflict minerals rule in order to curb the illicit trade of tin, tantalum, tungsten and gold in the DRC region. EXAIR is using the CMRT 4.20 template to document our supply chain and commitment to conflict free products.



#### Reach:

Per Regulation (EC) No 1907/2006 Title I, Article 3, paragraph 3, the European Union has recently enacted legislation to register chemicals and substances imported into the EU to ensure a high level of protection of human health and the environment.

Per Title II, Article 7, paragraph 1, articles (products) must be registered when a substance is intended to be released under normal or reasonably foreseeable conditions of use and it is present in those articles in quantities totaling over 1 metric ton per producer or importer per year. Registration of EXAIR products is not required since they do not contain substances that are intentionally released.

**Best Practices** for Using Intelligent Compressed Air<sup>™</sup> Products

In order to achieve the best performance of your EXAIR Intelligent Compressed Air Product, a steady flow of compressed air must be supplied at the optimal pressure. Compressor output pressure, air flow rate, piping ID (inner diameter), the smoothness of the inside of the pipe, and connector type all contribute to the performance.

#### **Air Compressor Capability**

Especially for manufacturing uses, it is important to consider both the air pressure and air flow being produced by the air compressor providing the supply for all tooling. It is possible for an air compressor to produce sufficient supply pressure for an EXAIR product while not having adequate air flow to use the product for very long!

#### Air Pressure

The optimal operating pressure for most EXAIR products is 80 PSIG, with the exception of Vortex Tube based products, which are rated at 100 PSIG. Operating EXAIR products at air pressures less than 80 PSIG may lead to lower performance, but EXAIR encourages operating any blowoff product at as low a pressure as possible to achieve your desired result. A simple pressure regulator can lower your pressure and save energy. As a general rule near the 100 PSIG level, lowering air pressure by 2 PSIG will save 1% of energy used by an air compressor. Operating the product at pressures greater than 80 PSIG may produce slightly higher performance, but will require more energy to produce only a small gain.

#### **Connectors and Fittings**

Make sure that connectors and fittings do not restrict compressed air flow in any manner. Quick connectors can be especially problematic in this area. Because of their construction, quick connections that are rated at the same size as the incoming pipe or hose may actually have a much smaller inner diameter than that associated pipe or hose. This will significantly restrict the amount of air that is being supplied to the tool, starving it of the air flow it needs for best performance. In some cases, if the fitting is too small, the tool may not work at all!

## 6 1/8" tube 0 0 0 0 0 9/32" I.D. 9/32" I.D. 13/64" I.D. 11/32" I.D. Not Recommended

**Best Practices** for Using Intelligent Compressed Air<sup>™</sup> Products

#### **Proper Air Pipe Sizing**

In addition to all of the items above, it is also important to select the proper compressed air pipe size from the compressor to the point of use. Because the inside of a pipe is not perfectly smooth, the volume of air will become more restricted as it passes through a greater distance, thus reducing the available pressure at the point of use. To compensate for this loss, a larger diameter pipe is needed for a longer run. The table below shows the typical pressure loss in pounds per square inch for 100 feet of 1" Schedule 40 pipe. For lengths other than 100 feet, the pressure drop is proportional to the ratio of difference in lengths. For instance, the pressure drop in 50 feet of pipe will be approximately one-half the value on the table.

Free Air	Line Pressure (PSIG)								
(SCFM)	40	50	60	70	80	90	100	110	
50	1.66	1.33	1.11	0.95	0.83	0.75	0.66	0.60	
60	2.33	1.86	1.55	1.33	1.16	1.03	0.93	0.85	
70	3.09	2.47	2.06	1.77	1.55	1.37	1.24	1.12	
80	3.96	3.17	2.64	2.26	1.98	1.76	1.58	1.44	
90	4.92	3.94	3.28	2.81	2.46	2.19	1.97	1,79	
100	5.98	4.79	3.99	3.42	2.99	2.66	2.39	2.18	
125	9.04	7.23	6.03	5.17	4.52	4.02	3.62	3.29	
150	•	10.13	8.44	7.24	6.33	5.63	5.07	4.61	
175	-	-	-	9.63	8.42	7.49	6.74	6.13	
200	*				10.78	9.59	8.63	7.84	
225			*	*			10.73	9.75	

#### How to Calculate Compressed Air Consumption

	Met	hod 1	Method 2			
Air consump	tion is directly prop	ortional to absolute inlet pressure		flow by the ratio of the onverted to absolute		
	iCFM <sub>2</sub>	= P <sub>2</sub> + 1 atmosphere P <sub>1</sub> + 1 atmosphere	Step 1: Calculate the ratio of ab	solute inlet pressures.		
Example: A Model 3215 Vortex Tube consumes 15 SCFM at 100 PSIG (425 SLPM @ 6.9 BAR). To calculate the airflow with an inlet pressure of 80 PSIG (5.5 BAR), the calculation is as follows:			English Units: 80 PSIG + 14.7	Metric Units: 5.516 BAR + 1.014 = 0.8256		
			100 PSIG + 14.7 = 0.8256	6.895 BAR + 1.014		
English Units: Metric Units:		Step 2: Multiply known flow by the above ratio you just calculate				
SCFM <sub>2</sub> =	80 PSIG = + 14.7 100 PSIG + 14.7	SLPM <sub>2</sub> = 5.156 BAR 424.752 = +1.014 6.895 BAR +1.014	English Units: 15 SCFM = 12.384 × 0.8256 SCFM	Metric Units: 424.752 SLPM × 0.8256 = 350.693 SLPM		
		1	The	refore		

For more information on pipe sizing, pipe selection, conversion, and consumption, please visit our website at https://exair.co/04-airda or scan this qr code provided.

















Model 3215 consumes 15 SCFM @ 100 PSIG (425 SLPM @ 6.9 BAR) and will consume 12.4 SCFM @ 80 PSIG (351 SLPM @ 5.5 BAR).

Note: To convert SCFM to SLPM, multiply by the factor 28.3168 To convert PSIG to BAR multiply by the factor 0.0689